

Exercise 1

The screenshot shows the Oracle FreeSQL web interface. The SQL Worksheet contains the following query:

```
1 EXPLAIN PLAN FOR
2 SELECT * FROM patient_visits WHERE site_id = 3;
3
4 SELECT * FROM TABLE(DBMS_XPLAN.DISPLAY);
```

The Query result tab is selected, showing the execution plan. The execution time is 0.02 seconds. The plan is titled "PLAN_TABLE_OUTPUT".

Operation	Cost	Cardinality	Bytes	Temp	IO	Time
0 SELECT STATEMENT	1	20000	957K	205	(1)	00:00:01
1 TABLE ACCESS FULL	1	PATIENT_VISITS	20000	957K	205	(1) 00:00:01

Predicate Information (identified by operation id):

26.1.2 - Copyright © 2015, 2026 Oracle and/or its affiliates All rights reserved

Exercise 2

The screenshot shows the Oracle FreeSQL web interface. The SQL Worksheet contains the following query:

```
18 WHERE visit_date BETWEEN SYSDATE - 700 AND SYSDATE;
19
20 SELECT * FROM TABLE(DBMS_XPLAN.DISPLAY);
21
22 /*
```

The Query result tab is selected, showing the execution plan. The execution time is 00:00:00.012, and 15 rows were selected. The plan is titled "PLAN_TABLE_OUTPUT".

Operation	Cost	Cardinality	Bytes	Temp	IO	Time
0 SELECT STATEMENT	1	15	96159	4601K	207	(2) 00:00:01
1 FILTER	1	15	96159	4601K	207	(2) 00:00:01
2 TABLE ACCESS FULL	2	PATIENT_VISITS	96159	4601K	207	(2) 00:00:01

Predicate Information (identified by operation id):

```
1 - filter(SYSDATE@!>=SYSDATE@!-700)
2 - filter("VISIT_DATE">=SYSDATE@!-700 AND "VISIT_DATE"<=SYSDATE@!)
```

Elapsed: 00:00:00.012
15 rows selected.

26.1.2 - Copyright © 2015, 2026 Oracle and/or its affiliates All rights reserved

Exercise 3

The screenshot shows the FreeSQL web interface. The SQL query entered is:

```
-- Trailing column only -- index CANNOT be used from the middle
EXPLAIN PLAN FOR
SELECT * FROM patient_visits WHERE visit_date > SYSDATE - 90;
SELECT * FROM TABLE(DBMS_XPLAN.DISPLAY);
```

The query result shows the execution plan:

Id	Operation	Name	Rows	Bytes	Cost (%CPU)	Time
0	SELECT STATEMENT		12345	590K	206 (1)	00:00:01
* 1	TABLE ACCESS FULL	PATIENT_VISITS	12345	590K	206 (1)	00:00:01

Predicate Information (identified by operation id):

```
1 - filter("VISIT_DATE">SYSDATE@!-90)
```

Elapsed: 00:00:00.014
13 rows selected.

At the bottom, there is a footer with links: About Oracle, Contact Us, Legal Notices, Terms and Conditions, Your Privacy Rights, Delete Your FreeSQL Account, and Preferencias sobre cookies. Below this is a copyright notice: 261.2 - Copyright © 2015, 2026 Oracle and/or its affiliates All rights reserved.

Exercise 4

The screenshot shows the FreeSQL web interface. The SQL query entered is:

```
SELECT * FROM TABLE(DBMS_XPLAN.DISPLAY);
```

The query result shows the execution plan:

Id	Operation	Name	Rows	Bytes	Cost (%CPU)	Time
0	SELECT STATEMENT		10	490	205 (1)	00:00:01
* 1	TABLE ACCESS FULL	PATIENT_VISITS	10	490	205 (1)	00:00:01

Predicate Information (identified by operation id):

```
1 - filter(TO_CHAR("PATIENT_ID")='5432')
```

Elapsed: 00:00:00.013
13 rows selected.

At the bottom, there is a footer with links: About Oracle, Contact Us, Legal Notices, Terms and Conditions, Your Privacy Rights, Delete Your FreeSQL Account, and Preferencias sobre cookies. Below this is a copyright notice: 261.2 - Copyright © 2015, 2026 Oracle and/or its affiliates All rights reserved.