

D607 – Cloud Databases (Task 2)

Morrell J. Parrish

Western Governors University

Table of Contents

A. GOOGLE CLOUD PLATFORM SCHEMA	4
A.1. SCHEMA OBJECTS.....	4
A.2. SQL CODE TO CREATE SCHEMA	5
<i>A.2.1. Customers Table.....</i>	<i>5</i>
<i>A.2.2. Transactions Table</i>	<i>5</i>
<i>A.2.3. ShoppingCart Table</i>	<i>6</i>
B. POPULATING THE TABLES WITH DATA.....	8
B.1. RECORD IMPORT	8
B.2. DATA PREPROCESSING	8
<i>B.2.1. Python Script – JSON to NDJSON.....</i>	<i>9</i>
<i>B.2.2. Python Script to Split File</i>	<i>9</i>
C. WRITING QUERIES AND RUNNING IN GCP	10
C.1. QUERY TO LIST UNIQUE CUSTOMERS.....	10
C.2. QUERY TO LIST ALL ITEMS IN A CUSTOMER’S SHOPPING CART	11
C.3. QUERY TO LIST TOTAL PURCHASE AMOUNTS FOR CUSTOMERS (DESC).....	12
C.4. PANOPTO VIDEO	13
CONCLUSION.....	13
REFERENCES	14

D607 – Cloud Databases (Task 2)

INTRODUCTION

After successfully convincing **Alliah Company** to transition from an **on-premises data storage solution** to a **cloud-based solution** in **Task 1**, your next responsibility is to set up a **sandbox environment** to validate that the **proposed cloud storage solution functions as expected**.

To achieve this, you will complete the following tasks using the provided **Alliah Company Scenario, Data Dictionary for Transaction Data, and Transaction Data** documents:

1. **Create the necessary database schema in Google Cloud Platform (GCP)** based on the optimal data store identified in Task 1.
2. **Populate the schema** with records from the **sample transaction dataset** to ensure data integrity.
3. **Execute and demonstrate queries** that validate the database functionality, proving that the data store performs as intended.

This process ensures that Alliah Company's **cloud migration is successful**, supporting **scalability, efficiency, and reliability** in their new cloud environment (Western Governors University, n.d.).

A. Google Cloud Platform Schema

A.1. Schema Objects

Customers

QUERY

OPEN IN

SHARE

COPY

<

SCHEMA

DETAILS

PREVIEW

TABLE EXPLORER

PREVIEW

INSIGHTS

LINEAGE

>

Filter

Enter property name or value

<input type="checkbox"/>	Field name	Type	Mode	Key	Collation	Default Value	Policy Tags	
<input type="checkbox"/>	address	STRING	NULLABLE	-	-	-	-	-
<input type="checkbox"/>	phone	STRING	NULLABLE	-	-	-	-	-
<input type="checkbox"/>	email	STRING	NULLABLE	-	-	-	-	-
<input type="checkbox"/>	name	STRING	NULLABLE	-	-	-	-	-
<input type="checkbox"/>	customer_id	STRING	NULLABLE	-	-	-	-	-

ShoppingCart

QUERY

OPEN IN

SHARE

<

SCHEMA

DETAILS

PREVIEW

TABLE EXPLORER

PREVIEW

INSIGHTS

LINEAGE

>

Filter

Enter property name or value

<input type="checkbox"/>	Field name	Type	Mode	Key	Collation	Default Value	Policy Tags
<input type="checkbox"/>	product_name	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	price	FLOAT	NULLABLE	-	-	-	-
<input type="checkbox"/>	quantity	INTEGER	NULLABLE	-	-	-	-
<input type="checkbox"/>	cart_id	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	product_category	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	vendor	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	transaction_id	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	product_id	STRING	NULLABLE	-	-	-	-

Transactions

QUERY

OPEN IN

SHARE

<

SCHEMA

DETAILS

PREVIEW

TABLE EXPLORER

PREVIEW

INSIGHTS

LINEAGE

Filter

Enter property name or value

<input type="checkbox"/>	<div>Field name</div>	Type	Mode	Key	Collation	Default Value	Policy Tag
<input type="checkbox"/>	email	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	name	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	customer_id	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	transaction_date	TIMESTAMP	NULLABLE	-	-	-	-
<input type="checkbox"/>	total_amount	FLOAT	NULLABLE	-	-	-	-
<input type="checkbox"/>	address	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	shipping_method	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	<div>shopping_cart</div>	RECORD	REPEATED	-	-	-	-
<input type="checkbox"/>	<div>customer</div>	RECORD	NULLABLE	-	-	-	-
<input type="checkbox"/>	phone	STRING	NULLABLE	-	-	-	-
<input type="checkbox"/>	transaction_id	STRING	NULLABLE	-	-	-	-

A.2. SQL Code to Create Schema

A.2.1. Customers Table

The **customers table** stores information about customers, including their unique ID, name, email, phone number, and address. This table helps manage customer-related data, such as personal details and contact information. It serves as the main reference table for identifying customers in other tables.

-- Customers Table Schema

```
CREATE TABLE `ca1-2870-c81ef5710c2c.wgu_d607_25e398a3cfed3dbe.Customers` (  
  
  customer_id STRING NOT NULL,  
  name STRING,  
  email STRING,  
  phone STRING,  
  address STRING  
);
```

Variables and Data Types:

- **customer_id (STRING, NOT NULL):** Unique identifier for each customer. This serves as the primary key.
- **name (STRING):** Customer's full name.
- **email (STRING):** Customer's email address for communication purposes.
- **phone (STRING):** Customer's phone number.
- **address (STRING):** Customer's physical address.

A.2.2. Transactions Table

The **transactions table** records transaction details for each purchase made by a customer. This table includes the transaction ID, customer ID (foreign key), transaction date, shipping method, and total amount. It tracks the overall activity of a transaction and helps in analyzing sales trends and customer purchasing behavior.

-- Transactions Table Schema

```
CREATE TABLE `ca1-2870-c81ef5710c2c.wgu_d607_25e398a3cfed3dbe.Transactions` (  
  transaction_id STRING NOT NULL,  
  customer_id STRING NOT NULL,  
  transaction_date TIMESTAMP,  
  shipping_method STRING,  
  total_amount FLOAT64  
);
```

Variables and Data Types:

- **transaction_id** (STRING, **NOT NULL**): Unique identifier for each transaction. This serves as the primary key.
- **customer_id** (STRING, **NOT NULL**): Foreign key referencing **customer_id** in the Customers table, linking each transaction to a customer.
- **transaction_date** (TIMESTAMP): Date and time when the transaction occurred.
- **shipping_method** (STRING): Method of shipping chosen for the transaction (e.g., Standard, Express).
- **total_amount** (FLOAT64): Total amount for the transaction.

A.2.3. ShoppingCart Table

The **shoppingcart** table stores details about items in a customer's shopping cart during a transaction. This table includes the cart ID, transaction ID (foreign key), product ID (foreign key), vendor, product category, product name, quantity, and price. It provides item-level tracking for each transaction, enabling inventory analysis and reporting.

-- ShoppingCart Table Schema

```
CREATE TABLE `ca1-2870-c81ef5710c2c.wgu_d607_25e398a3cfed3dbe.ShoppingCart` (  
  cart_id STRING NOT NULL,  
  transaction_id STRING NOT NULL,  
  product_id STRING,  
  vendor STRING,  
  product_category STRING,  
  product_name STRING,
```

```
    quantity INT64,  
    price FLOAT64  
);
```

Variables and Data Types:

- **cart_id** (STRING, **NOT NULL**): Unique identifier for each shopping cart. This serves as the primary key.
- **transaction_id** (STRING, **NOT NULL**): Foreign key referencing **transaction_id** in the Transactions table, linking each cart item to a transaction.
- **product_id** (STRING): Foreign key that references a product in the products catalog, identifying the specific item purchased.
- **vendor** (STRING): Vendor selling the product.
- **product_category** (STRING): Category of the product (e.g., Electronics, Clothing, Home Appliances).
- **product_name** (STRING): Name of the product.
- **quantity** (INT64): Number of units purchased for this product.
- **price** (FLOAT64): Price per unit of the product.

B. Populating the Tables with Data

B.1. Record Import

Customers									
					QUERY	OPEN IN	SHARE	COPY	SNAPSHOT
					SCHEMA	DETAILS	PREVIEW	TABLE EXPLORER	PREVIEW
								INSIGHTS	LINEAGE
									DATA PROF
Row	address	phone	email	name					
1	12278 Wood Run Suite 976 New Joseph, NH 29976	(933)745-1993	william58@example.org	Aaron Adams					
2	02617 James Cape Apt. 183 Smallchester, NY 43437	429.490.1112x53344	vparsons@example.org	Aaron Alvarez					
3	57446 Briggs Wells Suite 655 Bryanchester, MS 40420	(554)215-0075	sara54@example.org	Aaron Armstrong DDS					
4	73602 Cassandra Trafficway Rayburgh, MS 63105	609.763.9041x99888	ryan66@example.org	Aaron Brooks					
5	688 David Rest Apt. 655 Stephanieport, WI 52227	884-683-1872	christinaholmes@example.net	Aaron Crane					
6	8579 Garcia Mill North Donna, AK 22222	001-700-800-1477x4055	roachaaron@example.com	Aaron Fernandez					
7	379 Angela Burgs Suite 814 Davilahaven, TN 44241	(343)749-4069x25748	qgrimes@example.org	Aaron Garcia					
8	65924 Henderson Port Mcdanieltown, IL 45028	(447)649-0319	kevinwilliams@example.com	Aaron Garcia					
9	USNV Anderson FPO AP 74002	001-751-926-1638x6436	baileyashley@example.com	Aaron Garner					
10	Unit 6312 Box 8272	514.224.4784x53905	todd67@example.net	Aaron Guerra					
					Results per page: 50 1 – 50 of 10000				

B.2. Data Preprocessing

Data can be added manually or via upload. The “*TransactionData.json*” file contains customer’s demographics, transactions, and shopping cart info. The current transaction file is not compatible with BigQuery. **BigQuery** does NOT support array-wrapped JSON files; we need to modify the JSON file slightly. The first python code was used to convert the original JSON file to Newline-Delimited JSON (NDJON), move the Customer’s ID to the root level, correct incorrect vendor key names, and then save the file as “*TransactionData_fixed.json*”

The second code was used to separate the *TransactionData_fixed.json* file into three different files – customers, shoppingcart, and transactions. The new json files are uploaded via BigQuery’s upload feature; this option will create the database schema and insert the data into the appropriate tables.

B.2.1. Python Script – JSON to NDJSON

```

===== Convert JSON to Newline-Delimited JSON (NDJSON) =====
import json

# Load the JSON file
with open("TransactionData.json", "r") as f:
    data = json.load(f)

# Fix JSON structure
for record in data:
    # Move customer_id to root level
    record["customer_id"] = record["customer"]["customer_id"]
    record["name"] = record["customer"]["name"]
    record["email"] = record["customer"]["email"]
    record["phone"] = record["customer"]["phone"]
    record["address"] = record["customer"]["address"]

    # Fix incorrect vendor key names
    for item in record["shopping_cart"]:
        if "vendor: " in item:
            item["vendor"] = item.pop("vendor: ") # Rename the incorrect key

# Save the fixed JSON file
with open("TransactionData_fixed.json", "w") as f:
    for entry in data:
        f.write(json.dumps(entry) + "\n")

print("✅ JSON structure fixed! Saved as TransactionData_fixed.json")

```

B.2.2. Python Script to Split File

```

===== Python Script to Split and Save Data into Separate JSON Files =====

import json

# Load JSON file
with open("TransactionData_fixed.json", "r") as f:
    data = [json.loads(line) for line in f]

# Prepare lists for separate tables
customers = []
transactions = []
shopping_cart = []

# Extract data into separate tables
for record in data:
    # Extract customer details (avoid duplicates)
    customer = {
        "customer_id": record["customer_id"],
        "name": record["name"],
        "email": record["email"],
        "phone": record["phone"],
        "address": record["address"]
    }
    if customer not in customers:
        customers.append(customer)

```

```

# Extract transaction details
transactions.append({
    "transaction_id": record["transaction_id"],
    "customer_id": record["customer"]["customer_id"],
    "transaction_date": record["transaction_date"],
    "shipping_method": record["shipping_method"],
    "total_amount": record["total_amount"]
})

# Extract shopping cart items
for item in record["shopping_cart"]:
    shopping_cart.append({
        "cart_id": record["transaction_id"], # Each shopping cart is linked to a transaction
        "transaction_id": record["transaction_id"],
        "product_id": item["product_id"],
        "vendor": item.get("vendor", "Unknown Vendor"), # Fix vendor key issue
        "product_category": item["product_category"],
        "product_name": item["product_name"],
        "quantity": item["quantity"],
        "price": item["price"]
    })

# Save extracted data as separate JSON files
customer_file = "Customers.json"
transactions_file = "Transactions.json"
shopping_cart_file = "ShoppingCart.json"

with open(customer_file, "w") as f:
    for entry in customers:
        f.write(json.dumps(entry) + "\n")

with open(transactions_file, "w") as f:
    for entry in transactions:
        f.write(json.dumps(entry) + "\n")

with open(shopping_cart_file, "w") as f:
    for entry in shopping_cart:
        f.write(json.dumps(entry) + "\n")

print(f"✅ Extracted and saved Customers data to: {customer_file}")
print(f"✅ Extracted and saved Transactions data to: {transactions_file}")
print(f"✅ Extracted and saved ShoppingCart data to: {shopping_cart_file}")

```

C. Writing Queries and Running in GCP

C.1. Query to List Unique Customers

```

SELECT DISTINCT customer_id, name, email, phone, address
FROM `wgu-d607-d644e25097898fed.Customers`
LIMIT 10;

```

Query results							SAVE RESULTS	OPEN IN	
JOB INFORMATION		RESULTS	CHART	JSON	EXECUTION DETAILS		EXECUTION GRAPH		
Row	customer_id	name	email	phone	address		Expand		
1	754613f4-66ca-4ea3-9652-ccf...	Aaron Adams	william58@example.org	(933)745-1993	12278 Wood Run Suite 976 New Joseph, NH 29976				
2	697b408e-68c6-493e-bbf2-720...	Aaron Alvarez	vparsons@example.org	429.490.1112x53344	02617 James Cape Apt. 183 Smallchester, NY 43437				
3	dbc339ea-0aaf-4011-9145-957...	Aaron Armstrong DDS	sara54@example.org	(554)215-0075	57446 Briggs Wells Suite 655 Bryanchester, MS 40420				
4	c903962a-1146-4f22-8e8c-a01...	Aaron Brooks	ryan66@example.org	609.763.9041x99888	73602 Cassandra Trafficway Rayburgh, MS 63105				
5	c05124c8-518b-42ef-ae95-15d...	Aaron Crane	christinaholmes@example.net	884-683-1872	688 David Rest Apt. 655 Stephanieport, WI 52227				
6	f072cbe5-5a63-40e4-9213-8c4...	Aaron Fernandez	roachaaron@example.com	001-700-800-1477x4055	8579 Garcia Mill North Donna, AK 22222				
7	592afa8b-9ec4-4771-b97b-849...	Aaron Garcia	qgrimes@example.org	(343)749-4069x25748	379 Angela Burgs Suite 814 Davilahaven, TN 44241				
8	09297b1f-f435-45d3-9c75-29b...	Aaron Garcia	kevinwilliams@example.com	(447)649-0319	65924 Henderson Port Mcdanieltown, IL 45028				
9	4449b387-0221-4b70-8ac7-9e...	Aaron Garner	baileyashley@example.com	001-751-926-1638x6436	USNV Anderson FPO AP 74002				
10	7dcadce4-f194-484a-bf20-55b...	Aaron Guerra	todd67@example.net	514.224.4784x53905	Unit 6312 Box 8272				

C.2. Query to List All Items in a Customer's Shopping Cart

SELECT

```

    c.customer_id,
    c.name,
    sc.product_name,
    sc.quantity,
    sc.price,
    (sc.quantity * sc.price) AS total_price
FROM `wgu_d607_d644e25097898fed.ShoppingCart` AS sc
JOIN `wgu_d607_d644e25097898fed.Transactions` AS t
ON sc.transaction_id = t.transaction_id
JOIN `wgu_d607_d644e25097898fed.Customers` AS c
ON t.customer_id = c.customer_id
WHERE c.customer_id = (
    SELECT customer_id
    FROM `wgu_d607_d644e25097898fed.Customers`
    LIMIT 1
); -- Dynamically selects one customer

```

Additionally, you can use the below script to select a specific customer

SELECT

```

    c.customer_id,
    c.name,
    sc.product_name,
    sc.quantity,

```

```

    sc.price,
    (sc.quantity * sc.price) AS total_price
FROM `wgu_d607_d644e25097898fed.ShoppingCart` AS sc
JOIN `wgu_d607_d644e25097898fed.Transactions` AS t
ON sc.transaction_id = t.transaction_id
JOIN `wgu_d607_d644e25097898fed.Customers` AS c
ON t.customer_id = c.customer_id
WHERE c.customer_id = 'cb4ef4b2-9114-461c-97cf-2d8452bab9ae'; -- Replace with specific
customer_id

```

Query results							
JOB INFORMATION		RESULTS	CHART	JSON	EXECUTION DETAILS		EXECUTION GRAPH
Row	customer_id	name	product_name	quantity	price	total_price	
1	754613f4-66ca-4ea3-9652-ccf...	Aaron Adams	Camera	1	944.99	944.99	
2	754613f4-66ca-4ea3-9652-ccf...	Aaron Adams	Office Desk	1	249.99	249.99	
3	754613f4-66ca-4ea3-9652-ccf...	Aaron Adams	Hair Dryer	2	56.99	113.98	
4	754613f4-66ca-4ea3-9652-ccf...	Aaron Adams	Desk Chair	3	149.99	449.97	
5	754613f4-66ca-4ea3-9652-ccf...	Aaron Adams	Inkjet Printer	3	209.99	629.97	

C.3. Query to List Total Purchase Amounts for Customers (Desc)

```

SELECT
    c.customer_id,
    c.name,
    SUM(t.total_amount) AS total_spent
FROM `wgu_d607_d644e25097898fed.Transactions` AS t
JOIN `wgu_d607_d644e25097898fed.Customers` AS c
ON t.customer_id = c.customer_id
GROUP BY c.customer_id, c.name
ORDER BY total_spent DESC;

```

Query results			
JOB INFORMATION		RESULTS	CHART
Row	customer_id	name	total_spent
1	21c24535-0a0d-4090-a298-aa7...	Kayla Jones	11959.89
2	fb4d59d0-609a-4102-89cc-d8b...	Daniel Meyer	11129.9
3	abece1e8-be9e-49ca-a6ec-c24...	Ashley Taylor	10319.89
4	2f370215-ee90-43e3-a54f-863...	Cynthia George	10293.88
5	4a611071-9d1d-4476-ace4-5c3...	Rebecca Ford	10264.91
6	c82883e3-9c26-4ee4-9f90-2bf...	Emily Walker	10153.87
7	e825de81-74af-42b0-9d0f-c1c...	Juan Clark	10139.91
8	e434b95b-400a-43ff-b01a-d6c...	Daniel Glenn	10055.89
9	38f1a0e4-8c5c-4b9e-a838-d54...	Amber Anderson	9574.91
10	df37dd35-b5be-4e4f-9205-5b1...	Danielle Simon	9479.9

C.4. Panopto Video

[Link](#)

Conclusion

In conclusion, transitioning to a cloud-based data storage solution provides Alliah Company with enhanced scalability, reliability, and efficiency. The successful creation of the database schema in Google Cloud Platform, coupled with the accurate population of tables and execution of queries, demonstrates the robustness of the proposed solution. This process ensures that Alliah Company is well-equipped to handle increasing data volumes while maintaining data integrity and accessibility. By validating the functionality of the database and the accuracy of data processing, the migration to the cloud is proven to be a strategic move, supporting the company's long-term success.

References

Western Governors University. (n.d.). *DPN2 Task 2: Cloud Data Solution Implementation*.

Retrieved February 8, 2025, from <https://apps.cgpoex.wgu.edu/wgulearning/course/course-v1:WGUx+OEX0419+v01>