

Formalizing Typing Rules for Natural Languages using Effects

Matthieu Boyer

17th April 2025


Plan

Introduction

Mathematical Background

Effects, Semantics

What the hell am I doing?



Defining definites and indefinites

Plan

Introduction

Mathematical Background

Effects, Semantics

Plan

Introduction

Mathematical Background

Category Theory

Type Theory

Effects, Semantics

Slide 42

Definition 2.1 — Category. A (small) *category* is described by the following data:

- 0 A class of objects (nodes of a graph).

Slide 42

Definition 2.2 — Category. A (small) *category* is described by the following data:

- 0 A class of objects (nodes of a graph).
- 1 For a pair A, B of objects, a set $\text{Hom}(A, B)$ of functions from A to B called *morphisms*, *maps* or *arrows*. We denote it by $f : A \rightarrow B$ or $A \xrightarrow{f} B$.

Slide 42

Definition 2.3 — Category. A (small) *category* is described by the following data:

- 0 A class of objects (nodes of a graph).
- 1 For a pair A, B of objects, a set $\text{Hom}(A, B)$ of functions from A to B called *morphisms*, *maps* or *arrows*. We denote it by $f : A \rightarrow B$ or $A \xrightarrow{f} B$.
- 2 For all triplets A, B, C , a composition law $\circ_{A,B,C}$:

$$\begin{aligned} \text{Hom}(B, C) \times \text{Hom}(A, B) &\rightarrow \text{Hom}(A, C) \\ (g, f) &\mapsto g \circ f \end{aligned}$$

Slide 42

Definition 2.4 — Category. A (small) *category* is described by the following data:

- 0 A class of objects (nodes of a graph).
- 1 For a pair A, B of objects, a set $\text{Hom}(A, B)$ of functions from A to B called *morphisms*, *maps* or *arrows*. We denote it by $f : A \rightarrow B$ or $A \xrightarrow{f} B$.
- 2 For all triplets A, B, C , a composition law $\circ_{A,B,C}$:

$$\begin{aligned} \text{Hom}(B, C) \times \text{Hom}(A, B) &\rightarrow \text{Hom}(A, C) \\ (g, f) &\mapsto g \circ f \end{aligned}$$

- 2 For all objects A , an identity map $\text{id}_A \in \text{Hom}(A, A)$.

Slide 42

Definition 2.5 — Category. A (small) *category* is described by the following data:

3 Associativity: $f \circ (g \circ h) = (f \circ g) \circ h = f \circ g \circ h$

Slide 42

Definition 2.6 — Category. A (small) *category* is described by the following data:

- 3 Associativity: $f \circ (g \circ h) = (f \circ g) \circ h = f \circ g \circ h$
- 3 Unitarity: $f \circ \text{id}_A = f = \text{id}_B \circ f$.

Slide 42

A few examples of categories are:

Set whose objects are Sets and arrows are functions between sets.

Slide 42

A few examples of categories are:

Set whose objects are Sets and arrows are functions between sets.

Top whose objects are Topological Spaces and arrows are continuous maps between those.

Slide 42

A few examples of categories are:

Set whose objects are Sets and arrows are functions between sets.

Top whose objects are Topological Spaces and arrows are continuous maps between those.

Grp whose objects are Groups and arrows are Group Homomorphisms.

Slide 42

A few examples of categories are:

Set whose objects are Sets and arrows are functions between sets.


Top whose objects are Topological Spaces and arrows are continuous maps between those.

Grp whose objects are Groups and arrows are Group Homomorphisms.

Vec whose objects are Vector Spaces on a field k and arrows are Linear Maps.

Commuter Rail, basically

The right language for categories is the commutative diagram one.
The associativity rewrites as:



Commuter Rail, basically

In *Set* we have the following commutative diagram:

$$\begin{array}{ccc}
 \mathbb{R} & \xrightarrow{\times 2} & \mathbb{R} \\
 \downarrow .2 & & \downarrow .2 \\
 \mathbb{R}^+ & \xrightarrow{\times 4} & \mathbb{R}^+
 \end{array}$$

Commuter Rail, basically

In *Set* we have the following commutative diagram:

$$\begin{array}{ccc}
 \mathbb{R} & \xrightarrow{\times 2} & \mathbb{R} \\
 \downarrow .2 & & \downarrow .2 \\
 \mathbb{R}^+ & \xrightarrow{\times 4} & \mathbb{R}^+
 \end{array}$$

It simply states that:

$$\forall x \in \mathbb{R}, (2x^2) = 4x^2$$

Of wolf, and man.

Definition 2.7 Let \mathcal{A}, \mathcal{B} be two categories. A functor $\mathcal{F} : \mathcal{A} \rightarrow \mathcal{B}$ is:

- 0 An object $F(A) \in \mathcal{B}$ for each object A of \mathcal{A} .
- 1 For each pair $A_1, A_2 \in \mathcal{A}$, a function:

$$\begin{aligned} F_{A_1, A_2} : \operatorname{Hom}_{\mathcal{A}}(A_1, A_2) &\rightarrow \operatorname{Hom}_{\mathcal{B}}(F A_1, F A_2) \\ f &\mapsto F(f) \end{aligned}$$

Of wolf, and man.

We ask the following equations to be satisfied:

$F(g \circ f) = F(g) \circ F(f)$, that is

$$\begin{array}{ccccc}
 A & \xrightarrow{g} & B & \xrightarrow{f} & C \\
 \downarrow F & & \downarrow F & & \downarrow F \\
 FA & \xrightarrow{Fg} & FB & \xrightarrow{Ff} & FC
 \end{array}$$

and $F(\text{id}_A) = \text{id}_{F(A)}$



O.K. Corral

Definition 2.8 A natural transformation is a functor in the category of small categories and functors. If $F, G : \mathcal{A} \Rightarrow \mathcal{B}$ are functors, a natural transformation θ from F to G is, for each object of \mathcal{A} a function θ_A such that the following diagram commutes for all $f : A \rightarrow B$.

$$\begin{array}{ccc} FA & \xrightarrow{Ff} & FB \\ \theta_A \downarrow & & \downarrow \theta_B \\ GA & \xrightarrow{Gf} & GB \end{array}$$

O.K. Corral

Definition 2.9 An adjunction $L \dashv R$ between two functors $L : \mathcal{A} \rightarrow \mathcal{B}$ and $R : \mathcal{B} \rightarrow \mathcal{A}$ is a pair of natural transformations $\eta : \text{Id}_{\mathcal{A}} \Rightarrow R \circ L$ and $\varepsilon : L \circ R \Rightarrow \text{Id}_{\mathcal{B}}$ verifying the zigzag equations:



Plan

Introduction

Mathematical Background

Category Theory


Type Theory

Effects, Semantics

Yu-Gi-Oh

Definition 2.10 A product of two objects A and B in a category φ is a triplet

$$(A \times B, \pi_1 : A \times B \rightarrow A, \pi_2 : A \times B \rightarrow B)$$



such that for all pair of arrows $X \xrightarrow{f} A$ et $X \xrightarrow{g} B$, there is a unique $h : X \rightarrow A \times B$ such that $f = \pi_1 \circ h, g = \pi_2 \circ h$.

Yu-Gi-Oh 2

Definition 2.11 A terminal object $\mathbb{1}$ in a category $\Gamma \vdash$ is an object such that for all A in $\Gamma \vdash$ there is one and only one arrow $A \rightarrow \mathbb{1}$.

An initial object is the same thing with the arrows reversed.

Definition 2.12 A category is cartesian if all products exist and it has a terminal object $\mathbb{1}$.

Cartesian products and terminal objects are unique, up to isomorphism.

Yu-Gi-Oh 3

Definition 2.13 A cartesian closed category is a cartesian category where we define for each object A a functor $A \Rightarrow \Gamma \vdash \rightarrow \Gamma \vdash$ right adjunct to $A \times \Gamma \vdash \rightarrow \Gamma \vdash$. This means we have bijections $\Phi_{X,Y} : \text{Hom}(A \times X, Y) \rightarrow \text{Hom}(X, A \Rightarrow Y)$ called curriffication bijections..

Yu-Gi-Oh 3

Definition 2.14 A cartesian closed category is a cartesian category where we define for each object A a functor $A \Rightarrow \Gamma \vdash \rightarrow \Gamma \vdash$ right adjunct to $A \times \Gamma \vdash \rightarrow \Gamma \vdash$. This means we have bijections $\Phi_{X,Y} : \text{Hom}(A \times X, Y) \rightarrow \text{Hom}(X, A \Rightarrow Y)$ called currrification bijections..

Set is a cartesian closed category, where currrification is defined by the partial application of high arity functions to a subset of their arguments.

Use the Types, Luke

Definition 2.15 The λ -calculus is defined by the following basic

grammar:

$E ::=$	$x \in Var$	<i>(Variables)</i>
	$ App(E, E)$	<i>(Application)</i>
	$ \lambda x. E$	<i>(Evaluation)</i>

Use the Types, Luke

Definition 2.16 We give ourselves a set of type variables $TyVar$ and define types by:

$$\begin{array}{l} A, B ::= \alpha \in TyVar \\ \quad | A \times B \\ \quad | \mathbf{1} \\ \quad | A \Rightarrow B \end{array}$$

A context $M = x_1 : A_1, \dots, x_n : A_n$ is a list of pairs $x_i : A_i$ with a variable x_i and a type A_i , all the variables being different.

Fudge Supreme

Definition 2.17 A typing $\Gamma \vdash M : A$ is a triplet composed of a context Γ , a λ -term M and a type A , such that all free variables of M are in Γ . A proof tree for a typing judgement is constructed inductively from a set of rules of the form:

$$\begin{array}{c}
 \frac{}{x : A \vdash x : A} \text{Var} \\
 \frac{\Gamma, x : A \vdash M : B}{\Gamma \vdash \lambda x.M : A \Rightarrow B} \text{Lam} \\
 \frac{\Gamma \vdash M : A \Rightarrow B \quad \Delta \vdash N : A}{\Gamma, \Delta \vdash App(M, N) : B} \text{App}
 \end{array}$$

Plan

Introduction

Mathematical Background

Effects, Semantics

Bibliography I