

CS 101: Computer Programming and Utilization

19-Programming with Classes

Instructor: Sridhar Iyer
IIT Bombay

What does this program do?

```
class poly {  
    private:  
        float coefs[10]; int degree;  
    public:  
        void read();  
        void print();  
};  
  
int main() {  
    poly p; double point;  
    p.read();  
    p.print();  
}
```

```
void poly::read() {  
    cin >> degree;  
    for (int i=0;i<=degree;i++)  
        cin >> coefs[i];  
}  
  
void poly::print() {  
    cout << coefs[0];  
    for (int i=1;i<=degree;i++)  
        cout << " + " << coefs[i] <<  
        " x^" << i ;  
    cout << endl;  
}
```

Recall: Class = Struct + ?

- Constructor(s)
 - How to set up the initial configuration
 - Perhaps allocate memory
- Destructors
 - Release resources and clean up state
- Methods (functions)
 - Change the state of the struct members in clean, controlled ways
 - Methods are like functions except they have access to the invisible variable “this” (more on this later)
- Access control: public, protected, private
- Inheritance (extending classes)

Activity: Adding a method to a class

Add a function 'eval' to the class poly that will evaluate the value of the polynomial at a given point and output that value.

Think: Write the pseudo-code for eval().

Pair: Write the C++ function for eval(). Modify main().

Share: Compare with demo18-poly.cpp.

Further Discussion: demo18-poly-constructor.cpp

- What is the need for constructors?

Newton-Raphson: Finding root of poly

Recall the Newton-Raphson method for finding root of a polynomial in one variable.

- Given a function f defined over real x , and its derivative f' , begin with a guess x_0 for a root of f .
- Get a better approximation x_1 :
$$x_1 = x_0 - f(x_0) / f'(x_0)$$
- Repeat the process until a sufficiently accurate values is reached.

Activity

Think: Add a function 'diff' to the class poly that will return its derivative as \rightarrow poly 'q'.

Pair: Modify the main() program to find the root of the given polynomial, using Newton-Raphson method.

Share: Compare with demo18-poly-NR-1.cpp.

Use of 'this' pointer: (Not discussed in class; see lab12)

- What is need for 'this' pointer?
 - this \rightarrow eval(x)
- demo18-poly-NR-2.cpp

Notes

Newton-Raphson Method:

- en.wikipedia.org/wiki/Newton's_method
- www.mathresource.iitb.ac.in/applet/NewtonRaphson/

Classes

- www.cplusplus.com/doc/tutorial/classes/

'this' pointer

- www.tutorialspoint.com/cplusplus/cpp_this_pointer.htm