

# GUIDE TO USING SIAM'S L<sup>A</sup>T<sub>E</sub>X STYLE\*

DIANNE DOE<sup>†</sup>, PAUL T. FRANK<sup>‡</sup>, AND JANE E. SMITH<sup>‡</sup>

April 17, 2015

**Abstract.** Documentation is given for use of the SIAM L<sup>A</sup>T<sub>E</sub>X macros. Instructions and suggestions for compliance with SIAM style standards are also included. Familiarity with standard L<sup>A</sup>T<sub>E</sub>X commands is assumed.

**Key words.** L<sup>A</sup>T<sub>E</sub>X, B<sub>I</sub>B<sub>T</sub>E<sub>X</sub>, SIAM Journals

**AMS subject classifications.**

**1. Introduction.** This file is documentation for the SIAM L<sup>A</sup>T<sub>E</sub>X style, including how to typeset the main document, the B<sub>I</sub>B<sub>T</sub>E<sub>X</sub> file, and any supplementary material. More information about SIAM's editorial style can be found in the style manual, available at <http://www.siam.org/journals/pdf/stylemanual.pdf>. The SIAM latex files can be found at <http://www.siam.org/journals/auth-info.php>. The files that are distributed are given below. **To do: Fix file names.**

- `siamart.cls` (required): Main L<sup>A</sup>T<sub>E</sub>X class file.
- `siamplain.bst` (required): Bibliographic style file for B<sub>I</sub>B<sub>T</sub>E<sub>X</sub>.
- `docsiamart.tex`: Produces this documentation.
- `docsiambib.bib`: Example B<sub>I</sub>B<sub>T</sub>E<sub>X</sub> database.
- `docsiamsupp.tex`: Supplemental file example and documentation.

The outline of a SIAM L<sup>A</sup>T<sub>E</sub>X article is shown in [Example 1](#).

## Example 1: Document outline

```
\documentclass{siamart}

% Packages and macros definitions go here.

\begin{document}

% Front matter goes here: title, authors, abstract, etc.
% Main body goes here.
% Appendices goes here (optional).
% Acknowledgements go here (optional).
% Bibliography goes here.

\end{document}
```

Class options can be included in the bracketed argument of the command, separated by commas. By default, lines which extend past the margin will have black boxes next to them to help authors identify lines that they need to fix, by rewriting or inserting breaks. Enabling the **final** option turns these boxes off, so that very small margin breaks which are not noticeable will not cause boxes to be generated. Use the **review** option to create line numbers before submitting your manuscript to a SIAM

---

\*Acknowledgments such as funding go here.

<sup>†</sup>Imagination Corp., Chicago, IL ([ddoe@imag.com](mailto:ddoe@imag.com)).

<sup>‡</sup>Department of Applied Mathematics, Fictional University, Boise, ID ([ptfrank@fictional.edu](mailto:ptfrank@fictional.edu), [jessmith@fictional.edu](mailto:jessmith@fictional.edu)).

journal.

**2. Front matter. To do:** We should change this to set `pdftitle` and `pdfauthor`, and then also use these in setting the page headers with `markboth`. The title and author parts are formatted using the standard `\title`, `\author`, and `\maketitle` commands as described in Lamport [4]. If there is more than one author, the authors should be separated by the `\and` command. The addresses and support acknowledgments are added via `\thanks`. Each author's thanks should specify their address. The support acknowledgment should be put in a thanks for the title, unless specific support needs to be specified for individual authors, in which case it should follow the author address. The header for this file was produced by the code in Example 2, including an example of a shared footnote.

#### Example 2: Title and authors

```
\title{Guide to Using SIAM's \LaTeX\ Style%
\thanks{Acknowledgments such as funding go here.}}

\subtitle{\today}

\author{Dianne Doe%
\thanks{Imagination Corp., Chicago, IL (\email{ddoe@imag.com}).}%
\and
Paul T. Frank%
\thanks{Department of Applied Mathematics, Fictional University, Boise,
ID
(\email{ptfrank@fictional.edu}, \email{jesmith@fictional.edu}).}
\and
Jane E. Smith%
\footnotemark[3]
}

\maketitle
```

Example 3 shows how to specify the page headings, with the authors' names and the title (possibly shortened to fit).

#### Example 3: Page headers

```
\pagestyle{myheadings}
\thispagestyle{plain}
\markboth{Dianne Doe, Paul T. Frank, and Jane E. Smith}%
{Guide to Using SIAM'S \LaTeX\ Style}
```

Following the author and title is the abstract, key words listing, and AMS subject classifications, designated using the `abstract`, `keywords`, and `AMS` environments. Authors are responsible for providing AMS numbers which can be found on the AMS web site [1]. The abstract, keywords, and AMS subject classifications for this document were specified in Example 4.

**Example 4: Abstract, keywords, and AMS classifications**

```

\newcommand{\BibTeX}{\scshape Bib}\TeX\xspace} % <- Preamble
\begin{abstract}
  Documentation is given for use of the SIAM \LaTeX macros.
  Instructions and suggestions for compliance with SIAM style
  standards are also included. Familiarity with standard \LaTeX
  commands is assumed.
\end{abstract}

\begin{keywords}
  \LaTeX, \BibTeX, SIAM Journals
\end{keywords}

\begin{AMS}
\end{AMS}

```

**3. Cross-references and hyperlinks.** SIAM now supports cross-references and hyperlinks via the `cleveref` and `hyperef` packages. To create a cross reference, use the commands `\cref` (inside sentence) and `\Cref` (beginning of a sentence) in place of the object name and `\ref`; examples are shown in the sections below for equations, tables, figures, sections, etc.. Hyperlinks are created with the `\href` and `\url` commands, as shown in [Example 5](#). SIAM has also defined the `\email` command, as shown in [Example 2](#).

**Example 5: Creating hyperlinks**

Click `\href{http://www.siam.org}{here}` to go to the SIAM homepage;  
the url is `\url{http://www.siam.org}`.

Click [here](http://www.siam.org) to go to the SIAM homepage; the url is <http://www.siam.org>.

**4. Math and equations.** Here we show some example equations, with numbering, and examples of referencing the equations. SIAM now includes the package `amsmath` by default. The SIAM L<sup>A</sup>T<sub>E</sub>X class adds the following macros by default: `\const`, `\diag`, `\grad`, `\Range`, `\rank`, `\supp`. This have the effect of rendering the item as a mathop. [Examples 6 to 13](#) use many of the features of the package `amsmath` and examples from [5].

**Example 6: Blackboard math**

```

\usepackage{amsfonts} % <- Preamble
Blackboard bold characters, such as  $\mathbb{C}$  and  $\mathbb{R}$ ,
should be created with the \texttt{amsfonts} package, although this
is not included by default.

```

Blackboard bold characters, such as  $\mathbb{C}$  and  $\mathbb{R}$ , should be created with the `amsfonts` package, although this is not included by default.

**Example 7: In-line math**

The following shows normal setup of math in text:

Let  $S=[s_{ij}]$  ( $1 \leq i,j \leq n$ ) be a  $(0,1,-1)$ -matrix of order  $n$ .

The following shows normal setup of math in text: Let  $S = [s_{ij}]$  ( $1 \leq i, j \leq n$ ) be a  $(0, 1, -1)$ -matrix of order  $n$ .

**Example 8: In-line matrix**

Matrices of no more than two rows appearing in text can be created as shown in the next example:

$B = \begin{bmatrix} B_{11} & B_{12} \\ B_{21} & B_{22} \end{bmatrix}$ .

Matrices of no more than two rows appearing in text can be created as shown in the next example:  $B = \begin{bmatrix} B_{11} & B_{12} \\ B_{21} & B_{22} \end{bmatrix}$ .

**Example 9: Creating matrices**

Display matrices can be rendered using environments from `\texttt{amsmath}`:

```
\begin{equation}\label{eq:matrices}
  S=\begin{bmatrix}1&0\\0&0\end{bmatrix}
  \quad\text{and}\quad
  C=\begin{pmatrix}1&1&0\\1&1&0\\0&0&0\end{pmatrix}.
\end{equation}
```

Equation `\cref{eq:matrices}` shows some example matrices.

Display matrices can be rendered using environments from `amsmath`:

$$(1) \quad S = \begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix} \quad \text{and} \quad C = \begin{pmatrix} 1 & 1 & 0 \\ 1 & 1 & 0 \\ 0 & 0 & 0 \end{pmatrix}.$$

Equation (1) shows some example matrices.

**Example 10: Using SIAM-defined macros**

```
\usepackage{braket,amsfonts} % <- Preamble
```

An example of a SIAM macro:

```
\begin{equation}\label{eq:range}
  \Range(A) = \set{ y \in \mathbb{R}^n \mid y = Ax }
\end{equation}
```

An example of a SIAM macro:

$$(2) \quad \text{Range}(A) = \{ y \in \mathbb{R}^n \mid y = Ax \}$$

**Example 11: Equation split across lines**

We claim that the projection  $g(U, V)$  is given by the pair of matrices:

```
\begin{multline} \label{eq:ml}
g(U, V) = \biggl( \frac{R(U, V)V\Sigma^T U^T -
U\Sigma V^T R(U, V)^T}{2} U, \\\
\frac{R(U, V)^T U\Sigma V^T - V
\Sigma^T U^T R(U, V)}{2} V \biggr).
\end{multline}
```

We claim that the projection  $g(U, V)$  is given by the pair of matrices:

$$(3) \quad g(U, V) = \left( \frac{R(U, V)V\Sigma^T U^T - U\Sigma V^T R(U, V)^T}{2} U, \right. \\ \left. \frac{R(U, V)^T U\Sigma V^T - V\Sigma^T U^T R(U, V)}{2} V \right).$$

**Example 12: Subequations**

We calculate the Fréchet derivative of  $F$  as follows:

```
\begin{subequations}
\begin{align}
F'(U, V)(H, K)
&= \langle R(U, V), H\Sigma V^T + U\Sigma K^T \rangle - \\
&P(H\Sigma V^T + U\Sigma K^T) \rangle \label{eq:aa} \\\
&= \langle R(U, V), H\Sigma V^T + U\Sigma K^T \rangle \\\
&= \langle R(U, V)V\Sigma^T, H \rangle + \\
&\langle \Sigma^T U^T R(U, V), K^T \rangle. \label{eq:bb}
\end{align}
\end{subequations}
\Cref{eq:aa} is the first line, and \cref{eq:bb} is the last line.
```

We calculate the Fréchet derivative of  $F$  as follows:

$$(4a) \quad F'(U, V)(H, K) = \langle R(U, V), H\Sigma V^T + U\Sigma K^T \rangle - P(H\Sigma V^T + U\Sigma K^T) \\ = \langle R(U, V), H\Sigma V^T + U\Sigma K^T \rangle$$

$$(4b) \quad = \langle R(U, V)V\Sigma^T, H \rangle + \langle \Sigma^T U^T R(U, V), K^T \rangle.$$

Equation (4a) is the first line, and (4b) is the last line.

**Example 13: Aligned equations**

```
\Cref{eq:a,eq:b,eq:c} show three aligned equations.
\begin{align}
f &= g \label{eq:a}, \\
f' &= g' \label{eq:b}, \quad \text{and} \\
\mathcal{L}f &= \mathcal{L}g \label{eq:c}.
\end{align}
```

Equations (5–7) show three aligned equations.

$$\begin{array}{ll} (5) & f = g, \\ (6) & f' = g', \quad \text{and} \\ (7) & \mathcal{L}f = \mathcal{L}g. \end{array}$$

**5. Theorem-like environments.** SIAM uses the `ntheorem` package. Several theorem-like environments are predefined:

- `theorem`
- `lemma`
- `corollary`
- `definition`
- `proposition`

SIAM also defines a `proof` environment that automatically inserts a  $\square$  at the end of any proof, even if it ends in an equation environment. *Note that the document may need to be compiled twice for the mark to appear.* Some of the calculus examples were adapted from <http://tutorial.math.lamar.edu/Classes/CalcI/MeanValueTheorem.aspx>. ■

**Example 14: Theorem**

```
\begin{theorem}[Mean Value Theorem]\label{thm:mvt}
Suppose  $f$  is a function that is continuous on the closed interval
 $[a,b]$ . and differentiable on the open interval  $(a,b)$ .
Then there exists a number  $c$  such that  $a < c < b$  and
\begin{displaymath}
f'(c) = \frac{f(b)-f(a)}{b-a}.
\end{displaymath}
In other words,
\begin{displaymath}
f(b)-f(a) = f'(c)(b-a).
\end{displaymath}
\end{theorem}
```

**THEOREM 1 (Mean Value Theorem).** *Suppose  $f$  is a function that is continuous on the closed interval  $[a, b]$ . and differentiable on the open interval  $(a, b)$ . Then there exists a number  $c$  such that  $a < c < b$  and*

$$f'(c) = \frac{f(b) - f(a)}{b - a}.$$

*In other words,*

$$f(b) - f(a) = f'(c)(b - a).$$

## Example 15: Corollary and proof

```

\begin{corollary}
  Let  $f(x)$  be continuous and differentiable everywhere. If  $f(x)$ 
  has at least two roots, then  $f'(x)$  must have at least one root.
\end{corollary}
\begin{proof}
  Let  $a$  and  $b$  be two distinct roots of  $f$ .
  By \cref{thm:mvt}, there exists a number  $c$  such that
  \begin{displaymath}
    f'(c) = \frac{f(b)-f(a)}{b-a} = \frac{0-0}{b-a} = 0.
  \end{displaymath}
\end{proof}

```

COROLLARY 2. *Let  $f(x)$  be continuous and differentiable everywhere. If  $f(x)$  has at least two roots, then  $f'(x)$  must have at least one root.*

*Proof.* Let  $a$  and  $b$  be two distinct roots of  $f$ . By [Theorem 1](#), there exists a number  $c$  such that

$$f'(c) = \frac{f(b) - f(a)}{b - a} = \frac{0 - 0}{b - a} = 0. \quad \square$$

SIAM provides commands to create your own theorem-, definition-, and remark-like environments:

- `newsiamthm` - Small caps header, italicized body.
- `newsiamdefn` - Small caps header, normal body.
- `newsiamremark` - Italics header, normal body.

## Example 16: New theorem-like environment

```

\newsiamthm{claim}{Claim} % <- Preamble
\begin{claim}\label{cl:constant}
  If  $f'(x) = 0$  for all  $x$  \in  $(a,b)$  then  $f(x)$  is constant on  $(a,b)$ .
\end{claim}
\begin{proof}
  Left to reader.
\end{proof}

```

CLAIM 3. *If  $f'(x) = 0$  for all  $x \in (a,b)$  then  $f(x)$  is constant on  $(a,b)$ .*  
*Proof.* Left to reader.  $\square$

## Example 17: New definition-like environment

```

\newsiamdefn{defn}{Definition} % <- Preamble
\begin{defn}\label{defn:sym}
  We say a matrix  $A$  is \emph{symmetric} if  $a_{ij} = a_{ji}$  for all
   $i, j$ .
\end{defn}

```

DEFINITION 4. We say a matrix  $A$  is *symmetric* if  $a_{ij} = a_{ji}$  for all  $i, j$ .

**Example 18: New remark-like environment**

```
\newsiamremark{ex}{Example} % <- Preamble
\begin{ex}[Trivial note]\label{ex:a}
  Let  $f(x) = 2$ . Since  $f'(x) = 0$  for all  $x$ ,  $f$  is constant
  everywhere.
\end{ex}
```

*Example 5* (Trivial note). Let  $f(x) = 2$ . Since  $f'(x) = 0$  for all  $x$ ,  $f$  is constant everywhere.

**Example 19: References**

We can reference multiple types of objects with a single reference:

```
\cref{ex:a,cl:constant,thm:mvt}.
```

We can reference multiple types of objects with a single reference: [Example 5](#), [Claim 3](#), and [Theorem 1](#).

**6. Tables.** [Example 20](#) shows the code to generate [Table 1](#). This example uses subfloats via the `subfig` package, as well as special column options from the `array` package.

**Example 20: Example table with subtables**

```
\usepackage{array,subfig} % <- Preamble
\newcolumntype{R}{>{\$}r<{\$}} %
\newcolumntype{V}[1]{>{[\;]*\#{1}{R@{\;};}R<{\;}} %
\begin{table}[htbp]
  \caption{Example table adapted from Kolda and Mayo \cite{KoMa14}.}
  \label{tab:KoMa14}
  \centering
  \subfloat[ $\beta=1$ ]{
    \begin{tabular}{|c|R|V{3}|c|R@{\;,\;}\pm$\;,\;1|} \hline
      occ. & \multicolumn{1}{c|}{ $\lambda$ } & \multicolumn{4}{c|}{ $\mathbf{x}$ } & \\
      fevals & \multicolumn{2}{c|}{time (sec.)} \\\hline
      718 & 11.3476 & 0.5544 & 0.3155 & 1.2018 & 0.0977 & 45 & 0.17 & 0.06 \\\hline
      134 & 3.7394 & 0.2642 & -1.1056 & 0.2657 & -0.3160 & 31 & 0.12 & 0.05 \\\hline
      144 & 2.9979 & 1.0008 & 0.4969 & -0.0212 & -0.4817 & 31 & 0.12 & 0.05 \\\hline
      4 & \multicolumn{6}{c|}{\emph{--- Failed to converge ---}} & 0.21 & 0.10 \\\hline
    \end{tabular}
  }

  \subfloat[ $\beta=-1$ ]{
    \begin{tabular}{|c|R|V{3}|c|R@{\;,\;}\pm$\;,\;1|} \hline
      occ. & \multicolumn{1}{c|}{ $\lambda$ } & \multicolumn{4}{c|}{ $\mathbf{x}$ } & \\
      fevals & \multicolumn{2}{c|}{time (sec.)} \\\hline
      72 & -1.1507 & 0.2291 & 0.6444 & 0.3540 & -0.8990 & 34 & 0.14 & 0.06 \\\hline
      150 & -3.2777 & 0.8349 & -0.7603 & -0.3532 & -0.2635 & 33 & 0.14 & 0.07 \\\hline
      148 & -3.5998 & 1.0486 & 0.6046 & 0.3736 & 0.3971 & 41 & 0.16 & 0.08 \\\hline
      624 & -6.3985 & 0.1003 & 0.1840 & 0.5305 & 1.2438 & 48 & 0.19 & 0.08 \\\hline
      4 & \multicolumn{6}{c|}{\emph{--- Converged to wrong solution ---}} & 0.10 & 0.11 \\\hline
      2 & \multicolumn{6}{c|}{\emph{--- Failed to converge ---}} & 0.23 & 0.02 \\\hline
    \end{tabular}
  }
\end{table}
```

**7. Figures.** **To do:** Need to add Tikz and epstopdf examples in this section.

**8. Algorithms.** **To do:** SIAM wants the algorithm caption to be small caps (which I have copied here), although I'm not sure why because this does not match the table and figures.



Table 1: Example table adapted from Kolda and Mayo [3].

(a)  $\beta = 1$ 

occ.	$\lambda$	$\mathbf{x}$	fevals	time (sec.)
718	11.3476	[ 0.5544 0.3155 1.2018 0.0977 ]	45	$0.17 \pm 0.06$
134	3.7394	[ 0.2642 -1.1056 0.2657 -0.3160 ]	31	$0.12 \pm 0.05$
144	2.9979	[ 1.0008 0.4969 -0.0212 -0.4817 ]	31	$0.12 \pm 0.05$
4	— <i>Failed to converge</i> —			$0.21 \pm 0.10$

(b)  $\beta = -1$ 

occ.	$\lambda$	$\mathbf{x}$	fevals	time (sec.)
72	-1.1507	[ 0.2291 0.6444 0.3540 -0.8990 ]	34	$0.14 \pm 0.06$
150	-3.2777	[ 0.8349 -0.7603 -0.3532 -0.2635 ]	33	$0.14 \pm 0.07$
148	-3.5998	[ 1.0486 0.6046 0.3736 0.3971 ]	41	$0.16 \pm 0.08$
624	-6.3985	[ 0.1003 0.1840 0.5305 1.2438 ]	48	$0.19 \pm 0.08$
4	— <i>Converged to wrong solution</i> —			$0.10 \pm 0.11$
2	— <i>Failed to converge</i> —			$0.23 \pm 0.02$

**To do:** I prefer `algpseudocode` to `algorihmic`. Should we include neither in the header and let the user choose?

Algorithm 1 is produced by the code in Example 21.

#### Example 21: Example algorithm

```
\usepackage{algorihmic} % <- Preamble
\begin{algorithm}
\caption{Build tree}
\label{alg:buildtree}
\begin{algorihmic}
\STATE{Define  $\mathcal{P} := \{ \{1\}, \ldots, \{d\} \}$ }
\WHILE{ $\#\mathcal{P} > 1$ }
\STATE{Choose  $C^{\text{prime}} \in \mathcal{C}_p(P)$  with  $C^{\text{prime}} :=$ 
 $\operatorname{argmin}_{C \in \mathcal{C}_p(P)} \varrho(C)$ }
\STATE{Find an optimal partition tree  $T_{C^{\text{prime}}}$ }
\STATE{Update  $\mathcal{P} := (\mathcal{P} \setminus C^{\text{prime}}) \cup \{ \bigcup_{t \in C^{\text{prime}}} t \}$ }
\STATE{Update  $\mathcal{T} := \mathcal{T} \cup \{ \bigcup_{t \in \tau} t : \tau \in T_{C^{\text{prime}}} \setminus \{C^{\text{prime}}\} \}$ }
\ENDWHILE
\RETURN  $\mathcal{T}$ 
\end{algorihmic}
\end{algorithm}
```

**9. Sections and cross-referencing.** Sections are denoted using standard L<sup>A</sup>T<sub>E</sub>X section commands, i.e., `\section`, `\subsection`, etc. The appendices are defined the same way except that the first one is preceded by the `\appendix` command. The acknowledgment section is preceded by `\section*{Acknowledgments}`; it comes after any appendices and before the bibliography.

SIAM uses the `cleveref` package for cross-referencing, including customizations to adhere to SIAM's style guidelines. The macros automatically determine the proper way to format standard references, including the name of the reference and the hyper-link. Use `\Cref` for a reference at the beginning of a sentence and `\cref` otherwise. A label for a section should always begin with `sec`. Example 22 shows how to reference

## ALGORITHM 1 Build tree

---

```

Define  $P := T := \{\{1\}, \dots, \{d\}\}$ 
while  $\#P > 1$  do
  Choose  $C' \in \mathcal{C}_p(P)$  with  $C' := \operatorname{argmin}_{C \in \mathcal{C}_p(P)} \varrho(C)$ 
  Find an optimal partition tree  $T_{C'}$ 
  Update  $P := (P \setminus C') \cup \{\bigcup_{t \in C'} t\}$ 
  Update  $T := T \cup \{\bigcup_{t \in \tau} t : \tau \in T_{C'} \setminus \mathcal{L}(T_{C'})\}$ 
end while
return  $T$ 

```

---

sections.

**To do:** Hyperlinks are currently black, even though they are enabled. We may want to turn on some colors for testing purposes and/or to try different options.

**To do:** For some reason, the SIAM style does not have PDF bookmarks. Let's fix that.

**To do:** Explain how to automatically reference sections in the supplement.

## Example 22: Right and wrong ways to reference a section

```

Inside a sentence\dots\\
Single: \cref{sec:intro}\\
Range: \cref{sec:intro,sec:front,%
sec:sec}\\
Multiple: \cref{sec:intro,sec:sec,%
sec:tab,sec:math,sec:thm}\\
Appendix: \cref{sec:changes}\\

```

```

Beginning of a sentence\dots\\
Single: \Cref{sec:intro}\\
Range: \Cref{sec:intro,sec:front,%
sec:sec}\\
Multiple: \Cref{sec:intro,sec:sec,%
sec:tab,sec:math,sec:thm}\\
Appendix: \Cref{sec:changes}\\

```

```

Just don't do it this way\dots\\
Section~\ref{sec:intro}

```

Inside a sentence...

Single: §1

Range: §§1, 2, and 9

Multiple: §§1, 4–6, and 9

Appendix: Appendix A

Beginning of a sentence...

Single: Section 1

Range: Sections 1, 2, and 9

Multiple: Sections 1, 4–6, and 9

Appendix: Appendix A

Just don't do it this way...

Section 1

**10. Supplemental material.** **To do:** Explain how to do supplementary material, including L<sup>A</sup>T<sub>E</sub>X files as well as multimedia.

**11. Bibliography.** The SIAM B<sup>I</sup>B<sup>T</sup>E<sup>X</sup> style file, now called `siamplain.bst`, has been updated to include the new keys listed below:

- **doi**: Digital object identifier, a unique alphanumeric string
- **url**: Web address, usually impermanent
- **urldate**: Date that the web address was last accessed
- **eprint**: Archive identifier, a unique alphanumeric string
- **eprintclass**: Archive class
- **archive**: Archive URL, defaults to `http://arXiv.org/abs`
- **archivepreprint**: Archive name, defaults to “arXiv”.
- **eid**: Article ID, if there are no page numbers
- **pagetotal**: Total number of pages, for use with article ID

Every entry type has been modified to include an optional link to a DOI, a URL, and/or an archive preprint reference. Additionally, the **article** entry now supports

an Article ID, `eid`, and number of pages, `pagetotal`. To use this, include the following code in your L<sup>A</sup>T<sub>E</sub>X source code: `\bibliographystyle{siamplain}`.

**11.1. DOI.** A digital object identifier (DOI) is a unique alphanumeric string that provides a persistent link to its location on the Internet. The publisher assigns a DOI when your article is published and made available electronically. Using the `doi` field in BIB<sub>T</sub>E<sub>X</sub> to specify it, as shown for [3] in Example 23; observe the new `doi` field which produces a hyperlink in the citation. Do not include the full URL, i.e., `http://dx.doi.org/` preceding the DOI.

Example 23: Example article in BIB<sub>T</sub>E<sub>X</sub>

```
@Article{KoMa14,
  title =      {An Adaptive Shifted Power Method for Computing
                Generalized Tensor Eigenpairs},
  author =     {Tamara G. Kolda and Jackson R. Mayo},
  doi =        {10.1137/140951758},
  journal =    {SIAM Journal on Matrix Analysis and Applications},
  number =     {4},
  volume =     {35},
  year =       {2014},
  month =      dec,
  pages =      {1563--1581},
}
```

**11.2. URL.** There is also now support for the `url` field. Generally, the DOI is preferred to the URL, since the DOIs should be a permanent references. For that reason, it is good practice to specify the last date that the URL was accessed, which is specified by the optional `urldate` field. Reference [2] produced by Example 24 shows an example of using these fields.

Example 24: Example with the URL field in BIB<sub>T</sub>E<sub>X</sub>

```
@Misc{Hi14,
  author =     {Nick Higham},
  title =      {A Call for Better Indexes},
  howpublished = {SIAM Blogs},
  year =       2014,
  month =      nov,
  url =        {http://blogs.siam.org/a-call-for-better-indexes/},
  urldate =     {2015-04-05}
}
```

**11.3. Preprint servers such as arXiv.** More and more manuscripts are available on preprint servers. In fact, SIAM's publication policy explicitly allows the final accepted version of any article to be posted on a preprint server such as arXiv.

For an arXiv paper, the `eprint` field is used to specify identifier. The optional `eprintclass` field specifies the class. Example 25 shows the BIB<sub>T</sub>E<sub>X</sub> for [7].

**Example 25: Example arXiv reference in  $\text{BIB}\text{T}_{\text{E}}\text{X}$** 

```

@Misc{PeKoPi14,
  title = {Accelerating Community Detection by Using {K}-core Subgraphs},
  author = {Chengbin Peng and Tamara G. Kolda and Ali Pinar},
  eprint = {1403.2226},
  year = 2014,
  month = mar,
  eprintclass = {math.NA}
}

```

Other preprint servers are supported as well, but these require specification of the `archive` and `archiveprefix`. In this case, the target URL is formed by concatenating the `archive`, a forward slash (/), and the `eprint`; and the text for the hyperlink is formed by concatenating the `archiveprefix`, a color (:), and the `eprint`. [Example 26](#) shows the code to generate [8], including the preprint from PubMed. Note that this example has both the journal citation as well as the link for the preprint.

**Example 26: Example PubMed reference in  $\text{BIB}\text{T}_{\text{E}}\text{X}$** 

```

@Article{WoZhMeSh05,
  author = {Woessner, Donald E. and Zhang, Shanrong and
    Merritt, Matthew E. and Sherry, A. Dean},
  title = {Numerical Solution of the {Bloch} Equations Provides Insights
    into the Optimum Design of {PARACEST} Agents for {MRI}},
  journal = {Magnetic Resonance in Medicine},
  doi = {10.1002/mrm.20408},
  volume = 53,
  number = 4,
  month = apr,
  year = 2005,
  pages = {790--799},
  archiveprefix = {PubMed},
  archive = {http://www.ncbi.nlm.nih.gov/pubmed},
  eprint = {15799055}
}

```

**11.4. Article ID.** Some journals use an article ID rather than page numbers. The field `eid` specifies the article ID. The optional field `pagetotal` can say the number of pages in the document. An example of an article using these fields is shown in [Example 27](#) for citation [6].

Example 27: Example article ID reference in BibT<sub>E</sub>X

```
@Article{Ne03,
  title =      {Properties of Highly Clustered Networks},
  author =     {Newman, M. E. J.},
  doi =        {10.1103/PhysRevE.68.026121},
  journal =    {Phys. Rev. E},
  volume =     {68},
  year =       {2003},
  eid =        {026121},
  pagetotal =  {6},
  month =      aug,
}
```

**To do:** The new siam bib file is called `siamplain.bst`. There could also be a `siamalpha.bst` for alphabetic style references per the request of David Gleich.

**Appendix A. Changes.** The new SIAM styles includes the following significant changes as compared to older versions:

- Removed uppercase on title.

**Appendix B.** Acknowledgements go here. **To do:** Something is broken. There should not be an “Appendix” starting this, and the title is missing.

## REFERENCES

- [1] AMERICAN MATHEMATICAL SOCIETY, *Mathematics Subject Classification*, 2010, <http://www.ams.org/mathscinet/msc/msc2010.html> (accessed 2015/03/29).
- [2] NICK HIGHAM, *A call for better indexes*. SIAM Blogs, Nov. 2014, <http://blogs.siam.org/a-call-for-better-indexes/> (accessed 2015-04-05).
- [3] TAMARA G. KOLDA AND JACKSON R. MAYO, *An adaptive shifted power method for computing generalized tensor eigenpairs*, SIAM Journal on Matrix Analysis and Applications, 35 (2014), pp. 1563–1581, doi:10.1137/140951758.
- [4] LESLIE LAMPORT, *L<sup>A</sup>T<sub>E</sub>X: A Document Preparation System*, Addison–Wesley, Reading, MA, 1986.
- [5] FRANK MITTELBACH AND MICHEL GOOSSENS, *The L<sup>A</sup>T<sub>E</sub>X Companion*, Addison–Wesley, 2nd ed., 2004.
- [6] M. E. J. NEWMAN, *Properties of highly clustered networks*, Phys. Rev. E, 68 (2003), 026121 (6 pages), doi:10.1103/PhysRevE.68.026121.
- [7] CHENGBIN PENG, TAMARA G. KOLDA, AND ALI PINAR, *Accelerating community detection by using K-core subgraphs*, Mar. 2014, [arXiv:1403.2226 \[math.NA\]](https://arxiv.org/abs/1403.2226).
- [8] DONALD E. WOESSNER, SHANRONG ZHANG, MATTHEW E. MERRITT, AND A. DEAN SHERRY, *Numerical solution of the Bloch equations provides insights into the optimum design of PARACEST agents for MRI*, Magnetic Resonance in Medicine, 53 (2005), pp. 790–799, doi:10.1002/mrm.20408, PubMed:15799055.

**To do:** This files creates a bunch of extra files as it compiles. Not sure how to remove them.