

For [Issue #493](#) “Issue N - Progress-Section in terms-2.tex - for RC-4-June”

(The blue text are only title lines for the review process. They are not planned being included into the MPI standard)

The goal of this text is to describe the reality of MPI-4.0 (and older) more understandable, accurately and precisely, i.e. not to change anything.

It should be placed in MPI-4.1 as a new Section 2.9 Progress (after error handling, before implementation issues).

## 2.9 Progress

Definition of a “progress chunk”:

For a stage of an MPI operation (or parts of it) to be completed, it is often necessary for one or more other MPI processes to perform some activities. These activities may occur during the starting or completing MPI procedures for the operation or they may be separated from the operation-related MPI procedures. We name an activity separated in this way a *progress chunk*. An example of a progress chunk is the transfer of message data from a buffered mode send operation that completed before the matching receive operation was started.

Definition of a “blocked MPI procedure call”:

An MPI procedure is *blocked* if it delays its return until some specific activity or state-change has occurred in another MPI process.

A blocked MPI procedure call can be

- a non-local MPI procedure call that delays its return until a specific semantically-related MPI call on another MPI process, or
- a local MPI procedure call that delays its return until some unspecific MPI call in another MPI process causes a specific state-change in that MPI process, or
- an MPI finalization procedure (MPI\_FINALIZE or MPI\_SESSION\_FINALIZE) that delays its return or exit because the MPI finalization must guarantee that all remaining progress chunks will be executed before the MPI finalization is finished.

Some examples of a non-local blocked MPI procedure call:

- MPI\_SSEND delays its return until the matching receive operation is started at the destination MPI process (for example, by a call to MPI\_RECV or to MPI\_IRecv).
- MPI\_RECV delays its return until the matching send operation is started at the source MPI process (for example, by a call to MPI\_SEND or to MPI\_ISEND).

Some examples of a local blocked MPI procedure call:

- MPI\_RSEND, when the message data cannot be entirely buffered, delays its return until the destination MPI process has received the portion of message data that cannot be buffered, which may require one or more unspecific MPI procedure call(s) at the destination MPI process.
- MPI\_RECV, in the use case when the message was buffered at the source MPI process (e.g. with MPI\_BSEND), delays its return until the message is received, which may require one or more unspecific MPI procedure calls at the source MPI process to send the buffered data.

Definition of “progress”:

All MPI processes are required to “guarantee progress”, i.e., all progress chunks will eventually be executed. This guarantee is required to be provided by

- blocked MPI procedures, and

**Kommentiert [RR1]:** Wording: chunk is used, e.g., in OpenMP schedules and often, the default chunk size is 1. Chunk is rarely used in MPI-4.0 and none of these uses would be conflicting with this usage because it is always a chunk of xxx and xxx is different. Only here it is progress.

**Kommentiert [RR2]:** Example would be sending out the buffered message of a Bsend, i.e., doing a progress chunk

- repeatedly called MPI test procedures (see below) that return flag=false.

The progress must be provided independently of whether a progress chunk belongs to a specific session or to the world model (see Sections 11.2 and 11.3). Other ways of fulfilling this guarantee are possible and permitted (for example, a dedicated progress thread, or off-loading to a network interface controller (NIC)).

MPI test procedures are MPI\_TEST, MPI\_TESTANY, MPI\_TESTALL, MPI\_TESTSOME MPI\_IPROBE, MPI\_IMPROBE, MPI\_REQUEST\_GET\_STATUS, MPI\_WIN\_TEST, and MPI\_PARRIVED.

#### Definition of “strong progress”:

*Strong progress* is provided by an MPI implementation if all local procedures return independently of MPI procedure calls in other MPI processes (operation-related or not).

#### Definition of “weak progress”:

An MPI implementation provides *weak progress* if it does not provide strong progress.

#### Correctness of applications when using MPI implementations with different quality of progress.

*Advice to users.* The type of progress may influence the performance of MPI operations. A correct MPI application must be written under the assumption that only weak progress is provided. Every MPI application that is correct under weak progress will be correctly executed if strong progress is provided. The other way around, i.e. that correctness under the assumption of strong progress implies also correctness if only weak progress is provided, is not proven, but the MPI standard is designed such that it should be true. (*End of advice to users.*)

*Rationale.* The design of MPI restricts any use of synchronization methods that are not based on MPI communication procedures, which would likely result in deadlock without guaranteed strong progress in MPI, see for example Section 2.7 and Example 12.x in Section 12.7.3. (*End of rationale.*)

#### Further reading

For further rules, see Sect 2.4.2 the definition on local MPI procedures, Sect. 3.5 on point-to-point communication, and especially Sect. 3.7.4, paragraphs “Progress” on page 75, especially the paragraph on MPI\_TEST, Sect. 3.8.1 and 3.8.2 on MPI\_I(M)PROBE, Sect. 3.8.4 the advice to implementors for MPI\_TEST\_CANCELLED, Sect. 4.2.2 on MPI\_PARRIVED, especially the paragraph on repeated calls to MPI\_PARRIVED, Sect. 5.12 on collective procedure, Sect. 11.2.2 Example 11.6 on MPI\_FINALIZE and especially the related advice to implementors, Sect. 11.3.1. on MPI\_SESSION\_FINALIZE, especially the paragraph on “MPI\_SESSION\_FINALIZE may be synchronizing” together with the related rationale, the first advice to implementors and Example 11.8, Sect. 11.6 on MPI and threads, Sect. 12.7.3 on progress with one-sided communication, especially the rationale at the end, and Sect. 14.6.3 on MPI parallel file I/O.

Limits of minimal progress / special rule for shared memory RMA (this restriction would be new in MPI-4.1, but it was always reality since the MPI shared memory was introduced in MPI-3.0):

(To be added in the RMA chapter, e.g. at the end of RMA Section 12.7.3 Progress)

**Kommentiert [RR3]:** Comment from RMA WG meeting Oct. 27, 2022: one may add an additional environmental inquiry (like MPI\_TAG\_UB or MPI\_IO) in MPI\_4.0 Section 9.1.2.

In principle, there are many options (by Dan):  
The potential future enquiry mechanism for strong progress could be:

- a global attribute
- a global info key-value pair
- an object-specific attribute/info
- an operation-specific attribute/info
- a combination of some/all of the above
- an assertion "user does not need strong progress" -- scoped global/per-object/per-operation
- a requested/provided "request strong progress; provided?" -- scoped global/per-object/per-operation

This question is outside of the scope of this issue.  
This issue is of course the basis for such an additionally possible issue.

**Kommentiert [RR4]:** MPI\_4.0, page 24, lines 19-27:  
“This document specifies the behavior of a parallel program assuming that only MPI calls are used. The interaction of an MPI program with other possible means of communication, I/O, and process management is not specified. Unless otherwise stated in the specification of the standard, MPI places no requirements on the result of its interaction with external mechanisms that provide similar or equivalent functionality. This includes, but is not limited to, interactions with external mechanisms for process control, shared and remote memory access, file system access and control, interprocess communication, process signaling, and terminal I/O.”  
(Highlighting by the author of this comment)



**Other activities outside of the scope of this issue:**

**Progress rule for `MPI_WIN_SYNC`**

---

History of changes

- Rolf Rabenseifner, Oct. 4, 2022
- Dan Holmes, Oct. 5, 2022
- Rolf Rabenseifner, Oct. 18, 2022
- Joseph Schuchart, Oct. 18, 2022
- Dan Holmes, Oct. 18, 2022
- Rolf Rabenseifner, Oct. 19, 2022
- Dan Holmes, Oct. 21, 2022
- Rolf Rabenseifner, Oct. 25, 2022
- Dan Holmes, Oct. 25, 2022
- Rolf Rabenseifner, Oct. 25, 2022
- Rolf Rabenseifner, Oct.26, 2022
- Claudia Blaas-Schenner, Oct. 27, 2022
- Rolf Rabenseifner, Oct. 31, 2022
- Dan Holmes, Oct. 31, 2022
- Rolf Rabenseifner, Nov. 1, 2022

**Kommentiert [RR7]:** (by Dan)

IMHO, clarification of the relationship between `MPI_WIN_SYNC` and progress should be done by the RMA WG; there are two reasonable options for them to consider but both are outwith the remit of our issue/PR:

- 1) Add a sentence like "Repeated calls to `MPI_WIN_SYNC` do not, by themselves, guarantee progress for any MPI operations."
- 2) Add a sentence like "Repeated calls to `MPI_WIN_SYNC` must guarantee progress for all enabled MPI operations."

Whichever is chosen, I would like to see the example we discussed in the joint WG meeting included and elucidated.

**See Issue #636** "add example showing impact of progress"

<https://github.com/mpi-forum/mpi-issues/issues/636>