

Proofs are Programs

Induction

Short Recap

Inductive Datatypes

```
Inductive nat : Type :=  
  | 0  
  | S (n : nat).
```

Recursive Functions

```
Fixpoint plus (n : nat) (m : nat) : nat :=  
  match n with  
  | 0 => m  
  | S n' => S (plus n' m)  
end.
```

Proofs by

```
Theorem plus_0_n : ... .  
Proof. ... Qed.
```

Simplification

```
simpl. reflexivity.
```

Rewriting

```
rewrite -> H.
```

Case Analysis

```
destruct n as [| n'] eqn:E.
```

Quizzes

Introduction Patterns

```
Inductive rgb : Type :=  
  | red  
  | green  
  | blue.
```

```
Inductive color : Type :=  
  | black  
  | white  
  | primary (p : rgb).
```

c: color

Introduction Patterns

```
Inductive rgb : Type :=  
  | red  
  | green  
  | blue.
```

```
Inductive color : Type :=  
  | black  
  | white  
  | primary (p : rgb).
```

`c: color`

`destruct c.`

opens three subgoals
(for all constructors of color)

Introduction Patterns

```
Inductive rgb : Type :=  
  | red  
  | green  
  | blue.
```

```
Inductive color : Type :=  
  | black  
  | white  
  | primary (p : rgb).
```

$c : \text{color}$

`destruct c.`

opens three subgoals
(for all constructors of color)

`destruct c as [].`

opens three subgoals

Introduction Patterns

```
Inductive rgb : Type :=  
  | red  
  | green  
  | blue.
```

```
Inductive color : Type :=  
  | black  
  | white  
  | primary (p : rgb).
```

c: color

destruct c.

opens three subgoals
(for all constructors of color)

destruct c as [].

opens three subgoals

destruct c as [| |].

opens three subgoals

Introduction Patterns

```
Inductive rgb : Type :=  
  | red  
  | green  
  | blue.
```

```
Inductive color : Type :=  
  | black  
  | white  
  | primary (p : rgb).
```

c: color

destruct c.

opens three subgoals
(for all constructors of color)

destruct c as [].

opens three subgoals

destruct c as [| |].

opens three subgoals

destruct c as [| | p].

opens three subgoals
+ names argument of
primary (p)

Introduction Patterns

```
Inductive rgb : Type :=  
  | red  
  | green  
  | blue.
```

```
Inductive color : Type :=  
  | black  
  | white  
  | primary (p : rgb).
```

c: color

destruct c.

opens three subgoals
(for all constructors of color)

destruct c as [].

opens three subgoals

destruct c as [| |].

opens three subgoals

destruct c as [| | p].

opens three subgoals
+ names argument of
primary (p)

destruct c as [| | []].

opens 5 subgoals:
- black
- white
- primary red
- primary green
- primary blue

We reach limits easily...

Theorem `plus_0_n` : forall n:nat,
0 + n = n.




Theorem `plus_0_r` : forall n:nat,
n + 0 = n.




```
Fixpoint plus (n : nat) (m : nat) : nat :=  
  match n with  
  | 0 => m  
  | S n' => S (plus n' m)  
  end.
```


Building upon old files




Building upon old files



Building upon old files



Building upon old files



Induction

- General principle to show that $\forall n \in \mathbb{N}. P(n)$
 - show $P(0)$
 - show that for any $n > 0$ if $P(n - 1)$ holds, then so does $P(n)$
 - Alternatively show that for any n' if $P(n')$ holds, then so does $P(S\ n')$

- Typical example $P(n) := \sum_{i=0}^n i = \frac{n(n+1)}{2}$

Proof by Induction

Proof by Induction

Theorem `add_0_r` : `forall n:nat,`
`n + 0 = n.`

Theorem: For any n , $n + 0 = n$.

Proof by Induction

Theorem `add_0_r` : `forall n:nat,`
 `n + 0 = n.`

Theorem: For any n , $n + 0 = n$.

Proof.

`intros n.`
 `induction n as [| n' IHn'].`

Proof: by induction on n .

Proof by Induction

Theorem `add_0_r` : `forall n:nat,`
`n + 0 = n.`

Theorem: For any n , $n + 0 = n$.

Proof.

`intros n.`

Proof: by induction on n .

`induction n as [| n' IHn'].`

`- (* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + 0 = 0$.

Proof by Induction

Theorem `add_0_r` : `forall n:nat,`
 `n + 0 = n.`

Theorem: For any n , $n + 0 = n$.

Proof.

`intros n.`

Proof: by induction on n .

`induction n as [| n' IHn'].`

– `(* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + 0 = 0$.

`reflexivity.`

This follows directly from the definition of $+$.

Proof by Induction

Theorem `add_0_r` : `forall n:nat,`
`n + 0 = n.`

Theorem: For any n , $n + 0 = n$.

Proof.

`intros n.`

Proof: by induction on n .

`induction n as [| n' IHn'].`

– `(* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + 0 = 0$.

`reflexivity.`

This follows directly from the definition of $+$.

– `(* n = S n' *)`

Next, suppose $n = S\ n'$, where $n' + 0 = n'$ (IHn'). We must show that $(S\ n') + 0 = S\ n'$

Proof by Induction

Theorem `add_0_r` : `forall n:nat,`
`n + 0 = n.`

Theorem: For any n , $n + 0 = n$.

Proof.

`intros n.`

Proof: by induction on n .

`induction n as [| n' IHn'].`

– `(* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + 0 = 0$.

`reflexivity.`

This follows directly from the definition of $+$.

– `(* n = S n' *)`

Next, suppose $n = S\ n'$, where $n' + 0 = n'$ (IHn'). We must show that $(S\ n') + 0 = S\ n'$.

`simpl.`

By the definition of $+$ this follows from $S\ (n' + 0) = S\ n'$.

Proof by Induction

Theorem `add_0_r` : `forall n:nat,`
`n + 0 = n.`

Theorem: For any n , $n + 0 = n$.

Proof.

`intros n.`

Proof: by induction on n .

`induction n as [| n' IHn'].`

– `(* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + 0 = 0$.

`reflexivity.`

This follows directly from the definition of $+$.

– `(* n = S n' *)`

Next, suppose $n = S\ n'$, where $n' + 0 = n'$ (IHn'). We must show that $(S\ n') + 0 = S\ n'$.

`simpl.`

By the definition of $+$ this follows from $S\ (n' + 0) = S\ n'$.

`rewrite -> IHn'.`

By the inductive hypothesis (IHn') this is equivalent to $S\ n' = S\ n'$.

Proof by Induction

Theorem `add_0_r` : `forall n:nat,`
`n + 0 = n.`

Theorem: For any n , $n + 0 = n$.

Proof.

`intros n.`

Proof: by induction on n .

`induction n as [| n' IHn'].`

– `(* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + 0 = 0$.

`reflexivity.`

This follows directly from the definition of $+$.

– `(* n = S n' *)`

Next, suppose $n = S\ n'$, where $n' + 0 = n'$ (IHn'). We must show that $(S\ n') + 0 = S\ n'$.

`simpl.`

By the definition of $+$ this follows from $S\ (n' + 0) = S\ n'$.

`rewrite -> IHn'.`

By the inductive hypothesis (IHn') this is equivalent to $S\ n' = S\ n'$.

`reflexivity.`

This concludes the proof.

Proof by Induction

Theorem `add_0_r` : `forall n:nat,`
`n + 0 = n.`

Theorem: For any n , $n + 0 = n$.

Proof.

`intros n.`

Proof: by induction on n .

`induction n as [| n' IHn'].`

– `(* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + 0 = 0$.

`reflexivity.`

This follows directly from the definition of $+$.

– `(* n = S n' *)`

Next, suppose $n = S\ n'$, where $n' + 0 = n'$ (IHn'). We must show that $(S\ n') + 0 = S\ n'$.

`simpl.`

By the definition of $+$ this follows from $S\ (n' + 0) = S\ n'$.

`rewrite -> IHn'.`

By the inductive hypothesis (IHn') this is equivalent to $S\ n' = S\ n'$.

`reflexivity.`

This concludes the proof.

Qed.

Paper Proofs (Informal Proofs)

Paper Proofs (Informal Proofs)

Theorem `add_assoc''` : `forall n m p : nat,`
`n + (m + p) = (n + m) + p.`

Theorem: For any $n\ m\ p$,
 $n + (m + p) = (n + m) + p$

Paper Proofs (Informal Proofs)

Theorem `add_assoc''` : `forall n m p : nat,`
`n + (m + p) = (n + m) + p.`

Theorem: For any $n\ m\ p$,
 $n + (m + p) = (n + m) + p$

Proof.

`intros n m p.`
`induction n as [| n' IHn'].`

Proof: By induction on n .

Paper Proofs (Informal Proofs)

Theorem `add_assoc''` : `forall n m p : nat,`
`n + (m + p) = (n + m) + p.`

Theorem: For any $n\ m\ p$,
 $n + (m + p) = (n + m) + p$

Proof.

`intros n m p.`

`induction n as [| n' IHn'].`

Proof: By induction on n .

`- (* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + (m + p) = (0 + m) + p$.

Paper Proofs (Informal Proofs)

Theorem `add_assoc''` : `forall n m p : nat,`
`n + (m + p) = (n + m) + p.`

Theorem: For any $n\ m\ p$,
 $n + (m + p) = (n + m) + p$

Proof.

`intros n m p.`

`induction n as [| n' IHn'].`

Proof: By induction on n .

`- (* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + (m + p) = (0 + m) + p$.

`reflexivity.`

This follows directly from the definition of $+$.

Paper Proofs (Informal Proofs)

Theorem `add_assoc''` : `forall n m p : nat,`
`n + (m + p) = (n + m) + p.`

Theorem: For any $n\ m\ p$,
 $n + (m + p) = (n + m) + p$

Proof.

`intros n m p.`

Proof: By induction on n .

`induction n as [| n' IHn'].`

`- (* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + (m + p) = (0 + m) + p$.

`reflexivity.`

This follows directly from the definition of $+$.

`- (* n = S n' *)`

Next, suppose $n = S\ n'$, where $n' + (m + p) = (n' + m) + p$ (IHn').
We must show that $(S\ n') + (m + p) = ((S\ n') + m) + p$

Paper Proofs (Informal Proofs)

Theorem `add_assoc''` : `forall n m p : nat,`
`n + (m + p) = (n + m) + p.`

Theorem: For any $n\ m\ p$,
 $n + (m + p) = (n + m) + p$

Proof.

Proof: By induction on n .

`intros n m p.`

`induction n as [| n' IHn'].`

`- (* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + (m + p) = (0 + m) + p$.

`reflexivity.`

This follows directly from the definition of $+$.

`- (* n = S n' *)`

Next, suppose $n = S\ n'$, where $n' + (m + p) = (n' + m) + p$ (IHn').
We must show that $(S\ n') + (m + p) = ((S\ n') + m) + p$

`simpl.`

By the definition of $+$ this follows from $S\ (n' + (m + p)) = S\ ((n' + m) + p)$

Paper Proofs (Informal Proofs)

Theorem `add_assoc''` : `forall n m p : nat,`
`n + (m + p) = (n + m) + p.`

Theorem: For any $n\ m\ p$,
 $n + (m + p) = (n + m) + p$

Proof.

Proof: By induction on n .

`intros n m p.`

`induction n as [| n' IHn'].`

`- (* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + (m + p) = (0 + m) + p$.

`reflexivity.`

This follows directly from the definition of $+$.

`- (* n = S n' *)`

Next, suppose $n = S\ n'$, where $n' + (m + p) = (n' + m) + p$ (IHn').
We must show that $(S\ n') + (m + p) = ((S\ n') + m) + p$

`simpl.`

By the definition of $+$ this follows from $S\ (n' + (m + p)) = S\ ((n' + m) + p)$

`rewrite IHn'.`

which is immediate from the inductive hypothesis (IHn')

`reflexivity.`

Paper Proofs (Informal Proofs)

Theorem `add_assoc''` : `forall n m p : nat,`
`n + (m + p) = (n + m) + p.`

Theorem: For any $n\ m\ p$,
 $n + (m + p) = (n + m) + p$

Proof.

Proof: By induction on n .

`intros n m p.`

`induction n as [| n' IHn'].`

`- (* n = 0 *)`

First, suppose $n = 0$. We must show that $0 + (m + p) = (0 + m) + p$.

`reflexivity.`

This follows directly from the definition of $+$.

`- (* n = S n' *)`

Next, suppose $n = S\ n'$, where $n' + (m + p) = (n' + m) + p$ (IHn').
We must show that $(S\ n') + (m + p) = ((S\ n') + m) + p$

`simpl.`

By the definition of $+$ this follows from $S\ (n' + (m + p)) = S\ ((n' + m) + p)$

`rewrite IHn'.`

which is immediate from the inductive hypothesis (IHn')

`reflexivity.`

Qed.

Summary

Proofs by

Case Analysis

```
destruct n as [ | n'] eqn:E.
```

Induction

```
induction n as [ | [n' H]].
```

Introduction Patterns

```
destruct c as [ | | p ].
```

```
intros [ | | [] ].
```

“Informal Proofs”



Proof: by induction on n.

Proofs within Proofs

```
assert (H:..).  
{ ... }
```