

Messina E2B: MessinaSurv vs Others

March 30, 2015

1 Preparation

```
library(plyr)
library(messina)
library(maxstat)
library(doMC)

deltaForMargin = function(margin, sigma_epsilon = 1, alpha = 0.05) margin - 2*sigma_epsilon*qnorm(alpha)
marginForDelta = function(delta, sigma_epsilon = 1, alpha = 0.05) delta + 2*sigma_epsilon*qnorm(alpha)

messina_objectives = list("cox.log2" = messinaSurvObj.CoxCoef(log(2)))

e2b.design = expand.grid(
  Delta = seq(0, 5, 0.5),
  R1 = c(1, 2, 4, 8, 16),
  sigma_epsilon = 1,
  p1 = c(0.2, 0.5, 0.8),
  pc = c(0, 0.2, 0.5),
  alpha = 0.2,
  stat.alpha = 0.05,
  messina.objective = "cox.log2",
  messina.minmarg = 1,
  n = c(25, 50, 100),
  reps = 5e1)

e2b.design$margin = marginForDelta(e2b.design$Delta, e2b.design$sigma_epsilon, alpha = e2b.design$alpha)

detector_multicut = function(x, y, ncuts = 10, correct = "none")
{
  if (ncuts == 1)      { correct = "none" }
  if (is.vector(x))    { x = matrix(x, nrow = 1) }

  aapply(x, 1, function(x1) {
    cutpoints = quantile(x1, probs = (1:ncuts)/(ncuts + 1))
    pvals = sapply(cutpoints, function(c) {
      x1c = x1 > c
      test = survdiff(y ~ x1c)
      pval = pchisq(test$chisq, df = 1, lower.tail = FALSE)
      pval
    })
    pvals = p.adjust(pvals, correct)
    pvals[is.na(pvals)] = 1
  })
}
```



```

}

registerDoMC(32)

e2b.design$jobindex = 1:nrow(e2b.design)
set.seed(20150320)
e2b.det = mply(e2b.design, e2b.expfun, .parallel = TRUE)

e2b.design = rbind(
  cbind(e2b.design, method = "maxstat", detrates = simplify2array(e2b.det)[1,]),
  cbind(e2b.design, method = "c1", detrates = simplify2array(e2b.det)[2,]),
  cbind(e2b.design, method = "c10", detrates = simplify2array(e2b.det)[3,]),
  cbind(e2b.design, method = "cH10", detrates = simplify2array(e2b.det)[4,]),
  cbind(e2b.design, method = "messina", detrates = simplify2array(e2b.det)[5,]),
  cbind(e2b.design, method = "messina_0m", detrates = simplify2array(e2b.det)[6,])
)

```

```

e2b.design2 = expand.grid(
  Delta = seq(0, 5, 0.5),
  R1 = c(1, 4, 16),
  sigma_epsilon = 1,
  p1 = c(0.2, 0.5),
  pc = c(0.2, 0.5),
  alpha = 0.2,
  stat.alpha = 0.05,
  messina.objective = "cox.log2",
  messina.minmarg = 1,
  n = c(25, 50, 100),
  reps = 5e2)

e2b.design2$margin = marginForDelta(e2b.design2$Delta, e2b.design2$sigma_epsilon, alpha = e2b.design2$alpha)

registerDoMC(32)
e2b.design2$jobindex = 1:nrow(e2b.design2)
set.seed(20150321)
e2b.det2 = mply(e2b.design2, e2b.expfun, .parallel = TRUE)

e2b.design2 = rbind(
  cbind(e2b.design2, method = "maxstat", detrates = simplify2array(e2b.det2)[1,]),
  cbind(e2b.design2, method = "c1", detrates = simplify2array(e2b.det2)[2,]),
  cbind(e2b.design2, method = "c10", detrates = simplify2array(e2b.det2)[3,]),
  cbind(e2b.design2, method = "cH10", detrates = simplify2array(e2b.det2)[4,]),
  cbind(e2b.design2, method = "messina", detrates = simplify2array(e2b.det2)[5,]),
  cbind(e2b.design2, method = "messina_0m", detrates = simplify2array(e2b.det2)[6,])
)

```

```

e2b.design3 = expand.grid(
  Delta = 100,
  R1 = 4,
  sigma_epsilon = 1,
  p1 = seq(0, 1, 0.05),
  pc = 0.2,

```

```

    alpha = 0.2,
    stat.alpha = 0.05,
    messina.objective = "cox.log2",
    messina.minmarg = 1,
    n = 50,
    reps = 5e3)

registerDoMC(32)
e2b.design3$jobindex = 1:nrow(e2b.design3)
set.seed(20150321)
e2b.det3 = mply(e2b.design3, e2b.expfun, .parallel = TRUE)

e2b.design3 = rbind(
  cbind(e2b.design3, method = "maxstat", detraterate = simplify2array(e2b.det3)[1,]),
  cbind(e2b.design3, method = "c1", detraterate = simplify2array(e2b.det3)[2,]),
  cbind(e2b.design3, method = "c10", detraterate = simplify2array(e2b.det3)[3,]),
  cbind(e2b.design3, method = "cH10", detraterate = simplify2array(e2b.det3)[4,]),
  cbind(e2b.design3, method = "messina", detraterate = simplify2array(e2b.det3)[5,]),
  cbind(e2b.design3, method = "messina_0m", detraterate = simplify2array(e2b.det3)[6,])
)

```

```

e2b.design4 = expand.grid(
  Delta = 100,
  R1 = 1,
  sigma_epsilon = 1,
  p1 = 0.5,
  pc = 0.2,
  alpha = 0.2,
  stat.alpha = 0.05,
  multicut.n = 1:25,
  n = 50,
  reps = 5e3)

e2b.detfun4 = function(x, y, multicut.n, stat.alpha, ...)
{
  det.multicut = detector_multicut(x, y, multicut.n) < stat.alpha
  det.multicutHolm = detector_multicut(x, y, multicut.n, "holm") < stat.alpha

  c(mc = det.multicut, mcH = det.multicutHolm)
}

e2b.repfun4 = function(i, Delta, R1, sigma_epsilon, pc, p1, multicut.n, stat.alpha, n, ...)
{
  data = e2b.datafun(n, p1, pc, Delta, R1, sigma_epsilon)
  dets = try(e2b.detfun4(data$x, data$y, multicut.n, stat.alpha))
  if(class(dets) == "try-error") { return(c(NA, NA)) }
  return(dets)
}

e2b.expfun4 = function(Delta, R1, sigma_epsilon, pc, p1, multicut.n, stat.alpha, n, reps, ...)
{
  detections = sapply(1:reps, e2b.repfun4, Delta = Delta, R1 = R1, sigma_epsilon = sigma_epsilon,
    detraterate = rowMeans(detections, na.rm = TRUE))
}

```

```

    detraterate
  }

registerDoMC(32)
set.seed(20150321)
e2b.det4 = mply(e2b.design4, e2b.expfun4, .parallel = TRUE)

e2b.design4 = rbind(
  cbind(e2b.design4, method = "mc", detraterate = simplify2array(e2b.det4)[1,]),
  cbind(e2b.design4, method = "mcH", detraterate = simplify2array(e2b.det4)[2,])
)

```

```

library(ggplot2)


e2b.design$method = as.character(e2b.design$method)
e2b.design$method[e2b.design$method == "messina_0m"] = "messina0m"
e2b.design$method = as.factor(e2b.design$method)
e2b.design2$method = as.character(e2b.design2$method)
e2b.design2$method[e2b.design2$method == "messina_0m"] = "messina0m"
e2b.design2$method = as.factor(e2b.design2$method)
e2b.design3$method = as.character(e2b.design3$method)
e2b.design3$method[e2b.design3$method == "messina_0m"] = "messina0m"
e2b.design3$method = as.factor(e2b.design3$method)
e2b.design4$method = as.character(e2b.design4$method)
e2b.design4$method[e2b.design4$method == "mc"] = "'Optimal'"
e2b.design4$method[e2b.design4$method == "mcH"] = "'Optimal' + MTC"
e2b.design4$method = as.factor(e2b.design4$method)

# ggplot(e2b.design[e2b.design$ln == 25,], aes(x = margin, y = detraterate, colour = factor(method))) + geom
# ggplot(e2b.design[e2b.design$ln == 50,], aes(x = margin, y = detraterate, colour = factor(method))) + geom
# ggplot(e2b.design[e2b.design$ln == 100,], aes(x = margin, y = detraterate, colour = factor(method))) + geom


# ggplot(e2b.design2[e2b.design2$ln == 25,], aes(x = margin, y = detraterate, colour = factor(method))) + geom
# ggplot(e2b.design2[e2b.design2$ln == 50,], aes(x = margin, y = detraterate, colour = factor(method))) + geom
# ggplot(e2b.design2[e2b.design2$ln == 100,], aes(x = margin, y = detraterate, colour = factor(method))) + geom

e2b.design2$method = as.character(e2b.design2$method)
e2b.design2$method[e2b.design2$method == "c1"] = "Median cut"
e2b.design2$method[e2b.design2$method == "messina"] = "Messina2"
ggplot(e2b.design2[e2b.design2$margin >= 0 & e2b.design2$R1 == 4 & e2b.design2$pc == 0.2 & e2b.design2$ln == 100,], aes(x = margin, y = detraterate, colour = factor(method))) + geom

```



```
ggplot(e2b.design3[e2b.design3$method %in% c("c1", "maxstat", "messina"),], aes(x = p1, y = detrare, col = method))
```



```
ggplot(e2b.design4, aes(x = multicut.n, y = detrare, colour = factor(method))) + geom_line(lwd = 1) + xlab("Class balance")
```

