



d Webpack

- a React Router
- b Custom hooks
- c More about styles
- d Webpack

Bundling

- Configuration file
- Bundling React
- Loaders
- Transpilers
- CSS
- Webpack-dev-server
- Source maps
- Minifying the code
- Development and production configuration
- Polyfill

- e Class components, Miscellaneous
- f Exercises: extending the bloglist

In the early days, React was somewhat famous for being very difficult to configure the tools required for application development. To make the situation easier, Create React App was developed, which eliminated configuration-related problems. Vite, which is also used in the course, has recently replaced Create React App in new applications.

Both Vite and Create React App use *bundlers* to do the actual work. We will now familiarize ourselves with the bundler called Webpack used by Create React App. Webpack was by far the most popular bundler for years. Recently, however, there have been several new generation bundlers such as esbuild used by Vite, which are significantly faster and easier to use than Webpack. However, e.g. esbuild still lacks some useful features (such as hot reload of the code in the browser), so next we will get to know the old ruler of bundlers, Webpack.

Bundling

We have implemented our applications by dividing our code into separate modules that have been *imported* to places that require them. Even though ES6 modules are defined in the ECMAScript standard, the older browsers do not know how to handle code that is divided into modules.

For this reason, code that is divided into modules must be *bundle*d for browsers, meaning that all of the source code files are transformed into a single file that contains all of the application code. When we deployed our React frontend to production in part 3, we performed the bundling of our application with the `npm run build` command. Under the hood, the npm script bundles the source, and this produces the following collection of files in the `dist` directory:



The `index.html` file located at the root of the `dist` directory is the "main file" of the application which loads the bundled JavaScript file with a `script` tag:



As we can see from the example application that was created with Vite, the build script also bundles the application's CSS files into a single `assets/index-d526a0c5.css` file.

In practice, bundling is done so that we define an entry point for the application, which typically is the `index.js` file. When webpack bundles the code, it includes not only the code from the entry point but also the code that is imported by the entry point, as well as the code imported by its import statements, and so on.

Since part of the imported files are packages like React, Redux, and Axios, the bundled JavaScript file will also contain the contents of each of these libraries.

The old way of dividing the application's code into multiple files was based on the fact that the `index.html` file loaded all of the separate JavaScript files of the application with the help of `script` tags. This resulted in decreased performance, since the loading of each separate file results in some overhead. For this reason, these days the preferred method is to bundle the code into a single file.

Next, we will create a suitable webpack configuration for a React application by hand from scratch.

Let's create a new directory for the project with the following subdirectories (`build` and `src`) and files:



The contents of the `package.json` file can e.g. be the following:



Let's install webpack with the command:



We define the functionality of webpack in the `webpack.config.js` file, which we initialize with

the following content:

```
const path = require('path')
const config = () => {
  return {
    entry: './src/index.js',
    output: {
      path: path.resolve(__dirname, 'build'),
      filename: 'main.js'
    }
  }
}
module.exports = config
```

copy

Note: it would be possible to make the definition directly as an object instead of a function:

```
const path = require('path')
const config = {
  entry: './src/index.js',
  output: {
    path: path.resolve(__dirname, 'build'),
    filename: 'main.js'
  }
}
module.exports = config
```

copy

An object will suffice in many situations, but we will later need certain features that require the definition to be done as a function.

We will then define a new npm script called *build* that will execute the bundling with webpack:

```
// ...
"scripts": {
  "build": "webpack --mode=development"
},
// ...
```

copy

Let's add some more code to the *src/index.js* file:

```
const hello = name => {
  console.log(`Hello ${name}`)
}
```

copy

When we execute the `npm run build` command, our application code will be bundled by webpack. The operation will produce a new *main.js* file that is added under the *build* directory:

```
+ webpack npm run build
> webpack-osa7@0.0.1 build
> webpack --mode=development
asset main.js 1.24 KiB [compared for emit] (name: main)
./src/index.js 56 bytes [built] [code generated]
webpack 5.68.0 compiled successfully in 110 ms
+ webpack cat build/main.js
/*
 * ATTENTION: The "eval" devtool has been used (maybe by default in mode: "development").
 * This devtool is neither made for production nor for readable output files.
 * It uses "eval()" calls to create a separate source file in the browser devtools.
 * If you are trying to read the output file, select a different devtool (https://webpack.js.org/configuration/devtool/)
 * or disable the default devtool with "devtool: false".
 * If you are looking for production-ready output files, see mode: "production" (https://webpack.js.org/configuration/mode/).
 */
/***** (C) => { // webpackBootstrap
```

The file contains a lot of stuff that looks quite interesting. We can also see the code we wrote earlier at the end of the file:

```
eval("const hello = name => {\n  console.log(`Hello ${name}`)\n}\n\n//\nsourceURL=webpack://webpack-osa7//src/index.js?");
```

copy

Let's add an *App.js* file under the *src* directory with the following content:

```
const App = () => {
  return null
}

export default App
```

copy

Let's import and use the *App* module in the *index.js* file:

```
import App from './App';
const hello = name => {
  console.log(`Hello ${name}`)
}
App()
```

copy

When we bundle the application again with the `npm run build` command, we notice that webpack has acknowledged both files:

```
+ webpack npm run build
> webpack-osa7@0.0.1 build
> webpack --mode=development
asset main.js 4.21 KiB [emitted] (name: main)
  runtime modules 670 bytes 3 modules
  cacheable modules 144 bytes
  ./src/index.js 89 bytes [built] [code generated]
  ./src/App.js 55 bytes [built] [code generated]
webpack 5.68.0 compiled successfully in 114 ms
```

copy

Our application code can be found at the end of the bundle file in a rather obscure format:

```
eval("__webpack_require__,__webpack_exports__);\n/* harmony import */ var _App_\n__WEBPACK_IMPORTED_MODULE_0__ = __webpack_require__(/*! ./App */ "./src/App.js\n");\n\nconst hello = name => (\n  console.log(`Hello ${name}`)\n);\n\n(_App_\n__WEBPACK_IMPORTED_MODULE_0__[/* default */])()\n\n// sourceURL=webpack://webpack-osa7//src/index.js?");
```

copy

Configuration file

Let's take a closer look at the contents of our current `webpack.config.js` file:

```
const path = require('path')

const config = () => {
  return {
    entry: './src/index.js',
    output: {
      path: path.resolve(__dirname, 'build'),
      filename: 'main.js'
    }
  }
}

module.exports = config
```

copy

The configuration file has been written in JavaScript and the function returning the configuration object is exported using Node's module syntax.

Our minimal configuration definition almost explains itself. The `entry` property of the configuration object specifies the file that will serve as the entry point for bundling the application.

The `output` property defines the location where the bundled code will be stored. The target directory must be defined as an *absolute path*, which is easy to create with the `path.resolve` method. We also use `__dirname` which is a variable in Node that stores the path to the current directory.

Bundling React

Next, let's transform our application into a minimal React application. Let's install the required libraries:

```
npm install react react-dom
```

copy

And let's turn our application into a React application by adding the familiar definitions in the `index.js` file:

```
import React from 'react'
import ReactDOM from 'react-dom/client'
import App from './App'

ReactDOM.createRoot(document.getElementById('root')).render(<App />)
```

copy

We will also make the following changes to the `App.js` file:

```
import React from 'react' // we need this now also in component files
const App = () => {
  return (
    <div>
      hello webpack
    </div>
  )
}

export default App
```

copy

We still need the `build/index.html` file that will serve as the "main page" of our application that will load our bundled JavaScript code with a `script` tag:

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8" />
    <title>React App</title>
  </head>
  <body>
    <div id="root"></div>
    <script type="text/javascript" src="./main.js"></script>
  </body>
</html>
```

copy

When we bundle our application, we run into the following problem:

```
ERROR in ./src/App.js 2:2
Module parse failed: Unexpected token (2:2)
You may need an appropriate loader to handle this file type, currently no loaders are configured to process this file. See https://webpack.js.org/concepts#loaders
rs
I const App = () => (
>   <div>hello webpack</div>
I )
I
@ ./src/index.js 1:0-24 7:0-3
webpack 5.68.0 compiled with 1 error in 121 ms
```

copy

Loaders

The error message from webpack states that we may need an appropriate *loader* to bundle the `App.js` file correctly. By default, webpack only knows how to deal with plain JavaScript. Although we may have become unaware of it, we are using `JSX` for rendering our views in React. To illustrate this, the following code is not regular JavaScript:

```
const App = () => {
  return (
    <div>
      hello webpack
    </div>
  )
}
```

copy

The syntax used above comes from JSX and it provides us with an alternative way of defining a React element for an HTML `div` tag.

We can use `loaders` to inform webpack of the files that need to be processed before they are bundled.

Let's configure a loader to our application that transforms the JSX code into regular JavaScript:

```
const path = require('path')

const config = () => {
  return {
    entry: './src/index.js',
    output: {
      path: path.resolve(__dirname, 'build'),
      filename: 'main.js'
    }
  }
}

module.exports = config
```

copy

```

    output: {
      path: path.resolve(__dirname, 'build'),
      filename: 'main.js'
    },
    module: {
      rules: [
        {
          test: /\.js$/,
          loader: 'babel-loader',
          options: {
            presets: ['@babel/preset-react'],
          }
        },
      ],
    },
  }
}

module.exports = config

```

Loaders are defined under the `module` property in the `rules` array.

The definition of a single loader consists of three parts:

```
{
  test: /\.js$/,
  loader: 'babel-loader',
  options: {
    presets: ['@babel/preset-react']
  }
}
```

The `test` property specifies that the loader is for files that have names ending with `.js`. The `loader` property specifies that the processing for those files will be done with `babel-loader`. The `options` property is used for specifying parameters for the loader, which configure its functionality.

Let's install the loader and its required packages as a *development dependency*:

```
npm install @babel/core babel-loader @babel/preset-react --save-dev
```

[copy](#)

Bundling the application will now succeed.

If we make some changes to the `App` component and take a look at the bundled code, we notice that the bundled version of the component looks like this:

```
const App = () =>
  react__WEBPACK_IMPORTED_MODULE_0___default.a.createElement(
    'div',
    null,
    'hello webpack'
)
```

[copy](#)

As we can see from the example above, the React elements that were written in JSX are now created with regular JavaScript by using React's `createElement` function.

You can test the bundled application by opening the `build/index.html` file with the *open file* functionality of your browser:

It's worth noting that if the bundled application's source code uses `async/await`, the browser will not render anything on some browsers. Googling the error message in the console will shed some light on the issue. With the previous solution being deprecated we now have to install two more missing dependencies, that is `core-js` and `regenerator-runtime`:

```
npm install core-js regenerator-runtime
```

[copy](#)

You need to import those dependencies at the top of the `index.js` file:

```
import 'core-js/stable/index.js'
import 'regenerator-runtime/runtime.js'
```

[copy](#)

Our configuration contains nearly everything that we need for React development.

Transpilers

The process of transforming code from one form of JavaScript to another is called *transpiling*. The general definition of the term is to compile source code by transforming it from one language to another.

By using the configuration from the previous section, we are *transpiling* the code containing JSX into regular JavaScript with the help of `babel`, which is currently the most popular tool for the job.

As mentioned in part 1, most browsers do not support the latest features that were introduced in ES6 and ES7, and for this reason, the code is usually transpiled to a version of JavaScript that implements the ES5 standard.

The transpilation process that is executed by Babel is defined with *plugins*. In practice, most developers use ready-made presets that are groups of pre-configured plugins.

Currently, we are using the `@babel/preset-react` preset for transpiling the source code of our application:

```
{
  test: /\.js$/,
  loader: 'babel-loader',
  options: {
    presets: ['@babel/preset-react']
  }
}
```

[copy](#)

Let's add the `@babel/preset-env` plugin that contains everything needed to take code using all of the latest features and transpile it to code that is compatible with the ES5 standard:

```
{
  test: /\.js$/,
  loader: 'babel-loader',
  options: {
    presets: ['@babel/preset-env', '@babel/preset-react']
  }
}
```

[copy](#)

Let's install the preset with the command:

```
npm install @babel/preset-env --save-dev
```

copy

When we transpile the code, it gets transformed into old-school JavaScript. The definition of the transformed `App` component looks like this:

```
var App = function App() {
  return /*#__PURE__*/React.createElement("div", null, "hello webpack");
};
```

copy

As we can see, variables are declared with the `var` keyword as ES5 JavaScript does not understand the `const` keyword. Arrow functions are also not used, which is why the function definition used the `function` keyword.

CSS

Let's add some CSS to our application. Let's create a new `src/index.css` file:

```
.container {
  margin: 10px;
  background-color: #dee8e4;
}
```

copy

Then let's use the style in the `App` component:

```
const App = () => {
  return (
    <div className="container">
      hello webpack
    </div>
  )
}
```

copy

And we import the style in the `index.js` file:

```
import './index.css'
```

copy

This will cause the transpilation process to break:

```
ERROR in ./src/index.css 1:0
Module parse failed: Unexpected token (1:0)
You may need an appropriate loader to handle this file type, currently no loaders
are configured to process this file. See https://webpack.js.org/concepts#loaders
rs
> .container {
|   margin: 10px;
|   background-color: #dee8e4;
@ ./src/index.js 4:0-21
```

When using CSS, we have to use `css` and `style` loaders:

```
{
  rules: [
    {
      test: /\.js$/,
      loader: 'babel-loader',
      options: {
        presets: ['@babel/preset-react', '@babel/preset-env'],
      },
    },
    {
      test: /\.css$/,
      use: ['style-loader', 'css-loader'],
    },
  ],
}
```

copy

The job of the `css` loader is to load the `CSS` files and the job of the `style` loader is to generate and inject a `style` element that contains all of the styles of the application.

With this configuration, the CSS definitions are included in the `main.js` file of the application. For this reason, there is no need to separately import the `CSS` styles in the main `index.html` file of the application.

If needed, the application's CSS can also be generated into its own separate file by using the `mini-css-extract-plugin`.

When we install the loaders:

```
npm install style-loader css-loader --save-dev
```

copy

The bundling will succeed once again and the application gets new styles.

Webpack-dev-server

The current configuration makes it possible to develop our application but the workflow is awful (to the point where it resembles the development workflow with Java). Every time we make a change to the code, we have to bundle it and refresh the browser to test the code.

The `webpack-dev-server` offers a solution to our problems. Let's install it with the command:

```
npm install --save-dev webpack-dev-server
```

copy

Let's define an npm script for starting the dev server:

```
{
  // ...
  "scripts": {
    "build": "webpack --mode=development",
    "start": "webpack serve --mode=development"
  },
  // ...
}
```

copy

Let's also add a new `devServer` property to the configuration object in the `webpack.config.js` file:

```
const config = {
  entry: './src/index.js',
  output: {
    path: path.resolve(__dirname, 'build'),
    filename: 'main.js',
  },
  devServer: {
```

copy

```

    static: path.resolve(__dirname, 'build'),
    compress: true,
    port: 3000,
  },
  // ...
};

```

The `npm start` command will now start the dev-server at port 3000, meaning that our application will be available by visiting `http://localhost:3000` in the browser. When we make changes to the code, the browser will automatically refresh the page.

The process for updating the code is fast. When we use the dev-server, the code is not bundled the usual way into the `main.js` file. The result of the bundling exists only in memory.

Let's extend the code by changing the definition of the `App` component as shown below:

```

import React, { useState } from 'react'
import './index.css'

const App = () => {
  const [counter, setCounter] = useState(0)

  return (
    <div className="container">
      hello webpack {counter} clicks
      <button onClick={() => setCounter(counter + 1)}>
        press
      </button>
    </div>
  )
}

export default App

```

The application works nicely and the development workflow is quite smooth.

Source maps

Let's extract the click handler into its own function and store the previous value of the counter in its own `values` state:

```


const App = () => {
  const [counter, setCounter] = useState(0)
  const [values, setValues] = useState([])

  const handleClick = () => {
    setCounter(counter + 1)
    setValues(values.concat(counter))
  }

  return (
    <div className="container">
      hello webpack {counter} clicks
      <button onClick={handleClick}>
        press
      </button>
    </div>
  )
}

```

The application no longer works and the console will display the following error:



We know that the error is in the `onClick` method, but if the application was any larger the error message would be quite difficult to track down:

```

App.js:27 Uncaught TypeError: Cannot read property 'concat' of undefined
at handleClick (App.js:27)

```

The location of the error indicated in the message does not match the actual location of the error in our source code. If we click the error message, we notice that the displayed source code does not resemble our application code:

A screenshot of a browser's developer tools source editor. It shows the `handleClick` function from `App.js`. The code is identical to the one in the previous screenshot, but the context is different, showing the original source code rather than the bundled version.

Of course, we want to see our actual source code in the error message.

Luckily, fixing the error message in this respect is quite easy. We will ask webpack to generate a so-called source map for the bundle, which makes it possible to *map errors* that occur during the execution of the bundle to the corresponding part in the original source code.

The source map can be generated by adding a new `devtool` property to the configuration object with the value 'source-map':

```

const config = {
  entry: './src/index.js',
  output: {
    // ...
  },
  devServer: {
    // ...
  },
  devtool: 'source-map',
  // ...
};

```

Webpack has to be restarted when we make changes to its configuration. It is also possible to make webpack watch for changes made to itself but we will not do that this time.

The error message is now a lot better

```

    1 > Uncaught TypeError: Cannot read property 'concat' of undefined
      at handleClick (App.js:9)
      at Object.invokeGuardedCallbackDev (react-dom.development.js:148)
      at Object.invokeGuardedCallback (react-dom.development.js:139)
      at invokeGuardedCallbackAndCatchFirstError (react-dom.development.js:279)
      at invokeGuardedCallbackWithPriority (react-dom.development.js:270)
      at executeDispatchesInOrder (react-dom.development.js:158)
      at executeDispatches (react-dom.development.js:158)
      at executeDispatchesAndLeave (react-dom.development.js:168)

```

since it refers to the code we wrote:

```

1 import React, {useState} from 'react'
2
3 const App = () => {
4   const [values, setValues] = useState([])
5   const [values, setValues] = useState()
6
7   const handleClick = () => {
8     setValues(values.concat(counter))
9   }
10
11   return (
12     <div className="container">
13       <h1>Hello webpack!</h1>
14       <button onClick={handleClick}>Press me</button>
15     </div>
16   )
17 }
18
19 export default App
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
279
280
281
282
283
284
285
286
287
288
289
289
290
291
292
293
294
295
296
297
298
299
299
300
301
302
303
304
305
306
307
308
309
309
310
311
312
313
314
315
316
317
318
319
319
320
321
322
323
324
325
326
327
328
329
329
330
331
332
333
334
335
336
337
338
339
339
340
341
342
343
344
345
346
347
348
349
349
350
351
352
353
354
355
356
357
358
359
359
360
361
362
363
364
365
366
367
368
369
369
370
371
372
373
374
375
376
377
378
379
379
380
381
382
383
384
385
386
387
388
389
389
390
391
392
393
394
395
396
397
398
399
399
400
401
402
403
404
405
406
407
408
409
409
410
411
412
413
414
415
416
417
418
419
419
420
421
422
423
424
425
426
427
428
429
429
430
431
432
433
434
435
436
437
438
439
439
440
441
442
443
444
445
446
447
448
449
449
450
451
452
453
454
455
456
457
458
459
459
460
461
462
463
464
465
466
467
468
469
469
470
471
472
473
474
475
476
477
478
479
479
480
481
482
483
484
485
486
487
488
489
489
490
491
492
493
494
495
496
497
498
499
499
500
501
502
503
504
505
506
507
508
509
509
510
511
512
513
514
515
516
517
518
519
519
520
521
522
523
524
525
526
527
528
529
529
530
531
532
533
534
535
536
537
538
539
539
540
541
542
543
544
545
546
547
548
549
549
550
551
552
553
554
555
556
557
558
559
559
560
561
562
563
564
565
566
567
568
569
569
570
571
572
573
574
575
576
577
578
579
579
580
581
582
583
584
585
586
587
588
589
589
590
591
592
593
594
595
596
597
598
599
599
600
601
602
603
604
605
606
607
608
609
609
610
611
612
613
614
615
616
617
618
619
619
620
621
622
623
624
625
626
627
628
629
629
630
631
632
633
634
635
636
637
638
639
639
640
641
642
643
644
645
646
647
648
649
649
650
651
652
653
654
655
656
657
658
659
659
660
661
662
663
664
665
666
667
668
669
669
670
671
672
673
674
675
676
677
678
679
679
680
681
682
683
684
685
686
687
688
689
689
690
691
692
693
694
695
696
697
697
698
699
699
700
701
702
703
704
705
706
707
708
709
709
710
711
712
713
714
715
716
717
718
719
719
720
721
722
723
724
725
726
727
728
729
729
730
731
732
733
734
735
736
737
738
739
739
740
741
742
743
744
745
746
747
748
749
749
750
751
752
753
754
755
756
757
758
759
759
760
761
762
763
764
765
766
767
768
769
769
770
771
772
773
774
775
776
777
778
779
779
780
781
782
783
784
785
786
787
788
788
789
789
790
791
792
793
794
795
796
797
797
798
799
799
800
801
802
803
804
805
806
807
808
809
809
810
811
812
813
814
815
816
817
818
819
819
820
821
822
823
824
825
826
827
828
829
829
830
831
832
833
834
835
836
837
838
839
839
840
841
842
843
844
845
846
847
848
849
849
850
851
852
853
854
855
856
857
858
859
859
860
861
862
863
864
865
866
867
868
869
869
870
871
872
873
874
875
876
877
878
879
879
880
881
882
883
884
885
886
887
888
888
889
889
890
891
892
893
894
895
896
897
897
898
899
899
900
901
902
903
904
905
906
907
908
909
909
910
911
912
913
914
915
916
917
918
919
919
920
921
922
923
924
925
926
927
928
929
929
930
931
932
933
934
935
936
937
938
939
939
940
941
942
943
944
945
946
947
948
949
949
950
951
952
953
954
955
956
957
958
958
959
960
961
962
963
964
965
966
967
968
969
969
970
971
972
973
974
975
976
977
978
979
979
980
981
982
983
984
985
986
987
987
988
989
989
990
991
992
993
994
995
996
997
997
998
999
999
1000
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1087
1088
1089
1089
1090
1091
1092
1093
1094
1095
1095
1096
1097
1097
1098
1099
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1169
1170
1171
1172
1173
1174
1175
1176
1177
1177
1178
1179
1179
1180
1181
1182
1183
1184
1185
1186
1187
1187
1188
1189
1189
1190
1191
1192
1193
1194
1195
1195
1196
1197
1197
1198
1199
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1277
1278
1279
1279
1280
1281
1282
1283
1284
1285
1286
1287
1287
1288
1289
1289
1290
1291
1292
1293
1294
1295
1295
1296
1297
1297
1298
1299
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1377
1378
1379
1379
1380
1381
1382
1383
1384
1385
1386
1387
1387
1388
1389
1389
1390
1391
1392
1393
1394
1395
1395
1396
1397
1397
1398
1399
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1477
1478
1479
1479
1480
1481
1482
1483
1484
1485
1486
1487
1487
1488
1489
1489
1490
1491
1492
1493
1494
1495
1495
1496
1497
1497
1498
1499
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1577
1578
1579
1579
1580
1581
1582
1583
1584
1585
1586
1587
1587
1588
1589
1589
1590
1591
1592
1593
1594
1595
1595
1596
1597
1597
1598
1599
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1677
1678
1679
1679
1680
1681
1682
1683
1684
1685
1686
1687
1687
1688
1689
1689
1690
1691
1692
1693
1694
1695
1695
1696
1697
1697
1698
1699
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1787
1788
1789
1789
1790
1791
1792
1793
1794
1795
1795
1796
1797
1797
1798
1799
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1877
1878
1879
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1888
1889
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1977
1978
1979
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1988
1989
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2088
2089
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2188
2189
2189
2190
2191
2192
2193
21
```

```
}
```

Our goal is to configure the application with webpack in such a way that, when used locally, the application uses the json-server available in port 3001 as its backend.

The bundled file will then be configured to use the backend available at the <https://notes2023.fly.dev/api/notes> URL.

We will install axios, start the json-server, and then make the necessary changes to the application. For the sake of changing things up, we will fetch the notes from the backend with our custom hook called `useNotes`:

```
import React, { useState, useEffect } from 'react'
import axios from 'axios'
const useNotes = (url) => {
  const [notes, setNotes] = useState([])
  useEffect(() => {
    axios.get(url).then(response => {
      setNotes(response.data)
    })
  }, [url])
  return notes
}

const App = () => {
  const [counter, setCounter] = useState(0)
  const [values, setValues] = useState([])
  const url = 'https://notes2023.fly.dev/api/notes'
  const notes = useNotes(url)

  const handleClick = () => {
    setCounter(counter + 1)
    setValues(values.concat(counter))
  }

  return (
    <div className="container">
      hello webpack {counter} clicks
      <button onClick={handleClick}>press</button>
      <div>{notes.length} notes on server {url}</div>
    </div>
  )
}

export default App
```

The address of the backend server is currently hardcoded in the application code. How can we change the address in a controlled fashion to point to the production backend server when the code is bundled for production?

Webpack's configuration function has two parameters, `env` and `argv`. We can use the latter to find out the `mode` defined in the npm script:

```
const path = require('path')
const config = (env, argv) => {
  console.log(`argv.mode: ${argv.mode}`)
  return {
    // ...
  }
}
module.exports = config
```

Now, if we want, we can set Webpack to work differently depending on whether the application's operating environment, or `mode`, is set to production or development.

We can also use webpack's `DefinePlugin` for defining *global default constants* that can be used in the bundled code. Let's define a new global constant `BACKEND_URL` that gets a different value depending on the environment that the code is being bundled for:

```
const path = require('path')
const webpack = require('webpack')

const config = (env, argv) => {
  console.log(`argv`, argv.mode)

  const backend_url = argv.mode === 'production'
    ? 'https://notes2023.fly.dev/api/notes'
    : 'http://localhost:3001/notes'

  return {
    entry: './src/index.js',
    output: {
      path: path.resolve(__dirname, 'build'),
      filename: 'main.js'
    },
    devServer: {
      static: path.resolve(__dirname, 'build'),
      compress: true,
      port: 3000,
    },
    devtool: 'source-map',
    module: {
      // ...
    },
    plugins: [
      new webpack.DefinePlugin({
        BACKEND_URL: JSON.stringify(backend_url)
      })
    ]
  }
}

module.exports = config
```

The global constant is used in the following way in the code:

```
const App = () => {
  const [counter, setCounter] = useState(0)
  const [values, setValues] = useState([])
  const notes = useNotes(BACKEND_URL)

  // ...
  return (
    <div className="container">
      hello webpack {counter} clicks
      <button onClick={handleClick}>press</button>
      <div>{notes.length} notes on server {BACKEND_URL}</div>
    </div>
  )
}
```

If the configuration for development and production differs a lot, it may be a good idea to separate the configuration of the two into their own files.

Now, if the application is started with the command `npm start` in development mode, it fetches the notes from the address <http://localhost:3001/notes>. The version bundled with the command `npm run build` uses the address <https://notes2023.fly.dev/api/notes> to get the list of notes.

We can increment the bundled production version of the application locally by executing the

If you inspect the browser compatibility section of the application locally by executing the following command in the `build` directory:

```
npx static-server
```

copy

By default, the bundled application will be available at <http://localhost:9080>.

Polyfill

Our application is finished and works with all relatively recent versions of modern browsers, except for Internet Explorer. The reason for this is that, because of `axios`, our code uses Promises, and no existing version of IE supports them:

Browser compatibility													
Update compatibility data on GitHub													
Chrome	Edge	Firefox	Internet Explorer	Opera	Safari	Android webview	Chrome for Android	Edge Mobile	Firefox for Android	Opera for Android	Safari on iOS	Samsung Internet	Node.js
Basic support													
32	Yes	29	No	19	8	4.4.3	32	Yes	29	Yes	8	Yes	0.12
Promise(<code>)</code> constructor													
32	Yes	29 *	No	19	8 *	4.4.3	32	Yes	29 *	Yes	8 *	Yes	0.12 *
all													
32	Yes	29	No	19	8	4.4.3	32	Yes	29	Yes	8	Yes	0.12
prototype													
32	Yes	29	No	19	8	4.4.3	32	Yes	29	Yes	8	Yes	0.12

There are many other things in the standard that IE does not support. Something as harmless as the `find` method of JavaScript arrays exceeds the capabilities of IE:

Browser compatibility													
Update compatibility data on GitHub													
Chrome	Edge	Firefox	Internet Explorer	Opera	Safari	Android webview	Chrome for Android	Edge Mobile	Firefox for Android	Opera for Android	Safari on iOS	Samsung Internet	Node.js
Basic support													
45	Yes	25	No	32	8	Yes	Yes	Yes	4	Yes	8	Yes	4.0.0

In these situations, it is not enough to transpile the code, as transpilation simply transforms the code from a newer version of JavaScript to an older one with wider browser support. IE understands Promises syntactically but it simply has not implemented their functionality. The `find` property of arrays in IE is simply `undefined`.

If we want the application to be IE-compatible, we need to add a `polyfill`, which is code that adds the missing functionality to older browsers.

Polyfills can be added with the help of `webpack` and `Babel` or by installing one of many existing polyfill libraries.

The polyfill provided by the `promise-polyfill` library is easy to use. We simply have to add the following to our existing application code:

```
import PromisePolyfill from 'promise-polyfill'  
if (!window.Promise) {  
  window.Promise = PromisePolyfill  
}
```

copy

If the global `Promise` object does not exist, meaning that the browser does not support Promises, the polyfilled `Promise` is stored in the global variable. If the polyfilled `Promise` is implemented well enough, the rest of the code should work without issues.

One exhaustive list of existing polyfills can be found [here](#).

The browser compatibility of different APIs can be checked by visiting <https://caniuse.com> or Mozilla's website.

[Propose changes to material](#)

Part 7c
[Previous part](#)

Part 7e
[Next part](#)



Houston

