

Data with Http



John Papa

PRINCIPAL ARCHITECT

@john_papa www.johnpapa.net



Overview




Http

RxJS, Observables, and Subscriptions

Async Pipe

Promises





Http



Http

We use Http to get and save data with Promises or Observables. We isolate the http calls in a shared Service.



Http Then and Now

Angular 1

```
this.getVehicles = function() {  
  return $http.get('api/vehicles')  
    .then(function(response) {  
      return response.data.data;  
    })  
    .catch(handleError);  
}
```

Angular 2

```
getVehicles() {  
  return this.http.get('api/vehicles')  
    .map((response: Response) =>  
      <Vehicle[]>response.json().data)  
    .catch(this.handleError);  
}
```



Providers

```
import { NgModule } from '@angular/core';
import { BrowserModule } from '@angular/platform-browser';
import { HttpClientModule } from '@angular/http';
import './rxjs-extensions';
import { AppComponent } from './app.component';
import { VehicleListComponent } from './vehicle-list.component';
```

Located in module @angular/http

```
@NgModule({
  imports: [BrowserModule, HttpClientModule],
  declarations: [AppComponent, VehicleListComponent],
  bootstrap: [AppComponent]
})
export class AppModule { }
```

Import the Http module

Http Requirements

We need the **HttpModule** to make Http calls



vehicle.service.ts

```
@Injectable()
```

```
export class VehicleService {  
  constructor(private http: Http) { }
```

Make and return the async
GET call

```
  getVehicles() {  
    return this.http.get('api/vehicles')  
      .map((response: Response) => <Vehicle[]>response.json().data)  
      .catch(this.handleError);  
  }
```

Map the response

```
  private handleError(error: Response) {  
    console.error(error);  
    return Observable.throw(error.json().error || 'Server error');  
  }  
}
```

Handle any exception



vehicle-list.component.ts

```
constructor(private vehicleService: VehicleService) { }  
getHeroes() {  
  this.vehicleService.getVehicles()  
    .subscribe(  
      vehicles => this.vehicles = vehicles,  
      error => this.errorMessage = <any>error  
    );  
}  
ngOnInit() { this.getHeroes(); }
```

Subscribe to the
observable

Success and failure cases

Subscribing to the Observable

Component is handed an **Observable**

We **Subscribe** to it



1

2

3

Http Step by Step



Http Step by Step

1

2

3

1

Import
HttpModule



Http Step by Step

1

1

Import
HttpModule

2

2

Call Http.get in a
Service and
return the
mapped result

3



Http Step by Step

1

1

Import
HttpModule

2

2

Call Http.get in a
Service and
return the
mapped result

3

3


Subscribe to the
Service's
function in the
Component



Demo



Http





RxJs



RxJs

RxJs (Reactive Js) implements the asynchronous observable pattern and is widely used in Angular 2



app.module.ts

```
import 'rxjs/Rx';
```

Imports all of RxJs

Importing RxJs

RxJs is a large library

For production, only import the modules you require




app.module.ts

```
import './rxjs-extensions';
```

rxjs-extensions.ts

```
import 'rxjs/add/operator/catch';  
import 'rxjs/add/operator/do';  
import 'rxjs/add/operator/map';  
import 'rxjs/add/operator/toPromise';
```

Prefer importing only what we use from RxJs



vehicle.service.ts

```
return this.http.get('api/vehicles')  
  .map((response: Response) =>  
    <Vehicle[]>response.json().data  
  )  
  .catch(this.handleError);
```

Retrieve the JSON

data is what we
defined on the server

Returning from **Http**

We don't return the response

Service does the work

The consumers simply get the data



Catching Errors

```
getVehicles() {  
    return this.http.get('api/vehicles')  
        .map((response: Response) => <Vehicle[]>response.json().data)  
        .catch(this.handleError);  
}  
  
private handleError(error: Response) {  
    console.error(error);  
    let msg = `Error status code ${error.status} at ${error.url}`;  
    return Observable.throw(msg);  
}
```

Catch

Exception Handling

We catch errors in the Service

We pass some error messages to the consumer for presentation



```
getHeroes() {  
  this.vehicleService.getVehicles()  
    .subscribe(  
    vehicles => this.vehicles = vehicles,  
    error => this.errorMessage = <any>error  
  );  
}
```

Subscribe to the
observable

Success and failure cases

Subscribing to the Observable


Component is handed an **Observable**

We **Subscribe** to it

We can handle errors here, for presenting to the user if we wish



RxJs



1 1 0 1 0 1 0
0 1 0 1 1 0 0



Async Pipe



Async Pipe

The Async Pipe receives a Promise or Observable as input and subscribes to the input, eventually emitting the value(s) as changes arrive.



vehicle-list.component.ts

```
export class VehicleListComponent {  
  vehicles: Observable<Vehicle[]>;  
  constructor(private vehicleService: VehicleService) { }  
  getVehicles() {  
    this.vehicles = this.vehicleService.getVehicles();  
  }  
}
```

Property becomes Observable

Set the observable from the Service

Observable Properties

Component is simplified

Grab the **Observable** and set it to the property



```
<ul>
  <li *ngFor="let vehicle of vehicles | async">
    {{ vehicle.name }}
  </li>
</ul>
```

Subscribes to the
Vehicles

Async Pipe in the Template


Apply the **async** Pipe



Demo



Async



Demo




Promises



Demo



Putting It All Together



Http



Http

Observables and Subscriptions

Async Pipe

Promises

