

Height over
orography field

Changing default
project

Changing default
data request

Allow multiple
variables in a
single file

Change in the
behaviour of
"max_split_freq"
key

Training dr2xml: news in version 3.0

May 19, 2022



Table des matières

Height over
orography field

Changing default
project

Changing default
data request

Allow multiple
variables in a
single file

Change in the
behaviour of
"max_split_freq"
key

- ① Output a field at a designated height level over orography
 - Method 1 (perso or dev variables)
 - Method 2 (extra variables)
- ② Use of a specific project to define the characteristics of output files
- ③ Use of a specific Data Request
- ④ Allow multiple variables in a single file
- ⑤ Change in the behaviour of "max_split_freq" key

Output a field at a designated height level over orography (1)

Height over
orography field

Changing default
project

Changing default
data request

Allow multiple
variables in a
single file

Change in the
behaviour of
"max_split_freq"
key

Method 1 (perso or dev variables):

- Home data request

```
perso; zg50!zg; atmos; day; CNRM_day; time-mean; XY-HG;
      ANY; ANY
```

- Simulation settings

```
'perso_sdims_description':{
  'zg50':{
    'HG50':{
      'value':'50',
      'axis':"Z",
      'positive':'true',
      'out_name':'HG50'
    }
  }
}
```

Output a field at a designated height level over orography (2)

Height over
orography field

Changing default
project

Changing default
data request

Allow multiple
variables in a
single file

Change in the
behaviour of
"max_split_freq"
key

Method 2 (extra variables):

- Home data request

```
extra; ua50m!ua; atmos; 6hr; CNRM_HOMZ6hr; time-point;
XY-HG; ANY; ANY
```

- Extra table CNRM_HOMZ6hr.json

```
"ua50m": {
  "frequency": "6hr",
  "modeling_realm": "atmos",
  "standard_name": "eastward_wind",
  "units": "m s-1",
  "cell_methods": "area: time: point",
  "cell_measures": "area: areacella",
  "long_name": "Eastward Wind at 50m",
  "comment": "Zonal wind at 50m height",
  "dimensions": "longitude latitude time height50m",
  "out_name": "ua50m",
  "type": "real",
  "positive": "",
  "valid_min": "",
  "valid_max": "",
  "ok_min_mean_abs": "",
  "ok_max_mean_abs": "",
  "cnrm_priority": "1"
}
```

Output a field at a designated height level over orography (2)

Height over
orography field

Changing default
project

Changing default
data request

Allow multiple
variables in a
single file

Change in the
behaviour of
"max_split_freq"
key

Method 2 (extra variables):

- Extra table coordinates.json

```
"height50m": {
  "standard_name": "height",
  "units": "m",
  "axis": "Z",
  "long_name": "height",
  "climatology": "",
  "formula": "",
  "must_have_bounds": "no",
  "out_name": "height",
  "positive": "up",
  "requested": "",
  "requested_bounds": "",
  "stored_direction": "increasing",
  "tolerance": "",
  "type": "double",
  "valid_max": "120.0",
  "valid_min": "80.0",
  "value": "50.",
  "z_bounds_factors": "",
  "z_factors": "",
  "bounds_values": "",
  "generic_level_name": ""
}
```

Use of a specific project to define the characteristics of output files (1)

Height over
orography field

Changing default
project

Changing default
data request

Allow multiple
variables in a
single file

Change in the
behaviour of
"max_split_freq"
key

The following keys can be specified in the `lab_and_model` settings:

- *project_settings*:
 - description: name of the project used to define output characteristics
 - allowed values:
 - name of a standard project defined in dr2xml (see repository dr2xml/projects, except dr2xml.py and basics.py), without ".py" suffix
 - path to a file defining a project setting
 - default value: value of the key *project*
- *project*:
 - description: name of the project
 - allowed values: name of the project
 - default value: "CMIP6"
- *save_project_settings* (not yet implemented):
 - description: file where an aggregate version of the settings will be saved if specified
 - allowed values: path to the file
 - default value: None

Use of a specific project to define the characteristics of output files (2)

Height over
orography field

**Changing default
project**

Changing default
data request

Allow multiple
variables in a
single file

Change in the
behaviour of
"max_split_freq"
key

Additional information:

- The file `dr2xml/projects/dr2xml.py` contains all the variables required to run `dr2xml`.
- The file `dr2xml/projects/basics.py` is built other the former and add the main variables used in standard projects (non specific variables). It also defined a basic list of attributes, variables and comments that will be added to the different xios objects.
- All the configuration files must derive from `dr2xml/projects/dr2xml.py` and it is advisable to make them derive from `dr2xml/projects/basics.py`.

Use of a specific Data Request

Height over
orography field

Changing default
project

Changing default
data request

Allow multiple
variables in a
single file

Change in the
behaviour of
"max_split_freq"
key

The following key can be specified in the lab_and_model settings:

- *data_request_used*:
 - description: name of the Data Request to be used
 - allowed values:
 - "CMIP6": default CMIP6 Data Request
 - "no": no data request
 - default value: "CMIP6"

Additional information:

- If no data request is used:
 - cmor variables can not be used
 - additional coordinates must be added in the extra table coordinates.json (for instance "latitude" and "longitude")
- not yet tested with perso variables but should work provided that they are well defined in xml files
- some elements linked to the data request still remain in the code for now...

Allow multiple variables in a single file

Height over
orography field

Changing default
project

Changing default
data request

**Allow multiple
variables in a
single file**

Change in the
behaviour of
"max_split_freq"
key

The following key can be specified in the lab_and_model settings:

- *grouped_vars_per_file*:
 - description: list of list of variables that should be grouped together
 - allowed values: list of list of strings
 - default value: void list

Additional information:

- To be putted together in a single file, the following characteristics of the variables must be the same : frequency, table, grid_label, split_freq, split_freq_format, split_last_date, split_start_offset, split_end_offset, grid_descriptin, grid_resolution, target_hgrid_id, zgrid_id, source_grid
- Only a few tests have been made with this functionality, bugfixes are likely to be needed

Height over
orography field

Changing default
project

Changing default
data request

Allow multiple
variables in a
single file

Change in the
behaviour of
"max_split_freq"
key

Change in the behaviour of "max_split_freq" key

The "max_split_freq" key (defined in simulation or lab_and_model settings) is used as the upper limit for split frequency of output files if provided.

Up to version 2.2*, it was used only for files which split frequencies was expressed in year.

From version 3.0, it will be used in all cases.

Height over
orography field

Changing default
project

Changing default
data request

Allow multiple
variables in a
single file

Change in the
behaviour of
"max_split_freq"
key

Any question?