

# Probabilistic Programming Languages

*Reactive Probabilistic Programming*

Guillaume Baudart

*MPRI 2023-2024*

# Uncertainty in embedded systems



# Uncertainty in embedded systems

## Synchronous languages

- High-level specification language
- Generate correct-by-construction embedded code
- Industrial tool: ANSYS Scade

## Challenges

- Noisy environment, perceived through noisy sensors
- Interaction with other autonomous entities



# Uncertainty in embedded systems

## Synchronous languages

- High-level specification language
- Generate correct-by-construction embedded code
- Industrial tool: ANSYS Scade

## Challenges

- Noisy environment, perceived through noisy sensors
- Interaction with other autonomous entities



# Uncertainty in embedded systems

## Synchronous languages

- High-level specification language
- Generate correct-by-construction embedded code
- Industrial tool: ANSYS Scade

## Challenges

- Noisy environment, perceived through noisy sensors
- Interaction with other autonomous entities





# Uncertainty in embedded systems

## Synchronous languages


- High-level specification language
- Generate correct-by-construction embedded code
- Industrial tool: ANSYS Scade

## Challenges

- Noisy environment, perceived through noisy sensors
- Interaction with other autonomous entities

## Existing approaches

- Manually implement stochastic controller: *Can be error prone*
- Offline statistical tests: *Requires up-to-date offline data*



# Uncertainty in embedded systems

## Synchronous languages

- High-level specification language
- Generate correct-by-construction embedded code
- Industrial tool: ANSYS Scade

## Challenges


- Noisy environment, perceived through noisy sensors
- Interaction with other autonomous entities

## Existing approaches

- Manually implement stochastic controller: *Can be error prone*
- Offline statistical tests: *Requires up-to-date offline data*

## Reactive Probabilistic Programming



- Synchronous languages with probabilistic constructs
- Make the probabilistic model explicit
- Automatically learn posterior distributions from observations



# Reactive Probabilistic Programming (Demo)

## Simultaneous **L**ocalization **A**nd **M**apping

- Environment: slippery wheels and noisy color sensor
- System: infer current position and map, output command (left/right/up/down)



At each step:

- Move to the next position
- Observe the color of the ground
- Use inferred position to compute next command


- exact position + color sensor
- estimated color of a map cell
- estimated position



# Reactive systems

Synchronous data-flow languages and block diagrams

- Signal: stream of values
- System: stream processor



```
let node robot (gps) = u where
  rec u = controller (x0 → pre x)
  and x = tracker (u, gps)
```


# Reactive probabilistic systems

Synchronous data-flow languages and block diagrams

- Signal: stream of values
- System: stream processor

**ProbZelus**: add support to deal with uncertainty

- Extend a synchronous language
- Parallel composition: deterministic/probabilistic
- Inference-in-the-loop
- Streaming inference



```
let proba robot (gps) = u where
  rec u = controller (x0_dist → pre x_dist)
  and x_dist = infer tracker (u, gps)
```

# Synchronous programming

---

## Reactive Probabilistic Programming

# Lustre $\rightarrow$ Lucid Synchrone $\rightarrow$ Zelus $\rightarrow$ ProbZelus

## Dataflow synchronous programming

- Set of stream equations
- Discrete logical time steps
- At each step, compute the current value given inputs and previous values

## Stream operations

- Constant are lifted to stream:  $1 = 1, 1, 1, \dots$
- Temporal operators:  $\rightarrow$ , `pre`, `fby`
- Control structures: `reset/every`, `present`, `automaton`

# Lustre $\rightarrow$ Lucid Synchrone $\rightarrow$ Zelus $\rightarrow$ ProbZelus

Dataflow synchronous programming

- Set of stream equations
- Discrete logical time steps
- At each step, compute the current value given inputs and previous values

```
node nat v = cpt where  
  rec cpt = v  $\rightarrow$  pre cpt + 1
```

$$cpt_n = \text{if } (n = 0) \text{ then } v_0 \text{ else } cpt_{n-1} + 1$$



# Lustre $\rightarrow$ Lucid Synchrone $\rightarrow$ Zelus $\rightarrow$ ProbZelus

Dataflow synchronous programming

- Set of stream equations
- Discrete logical time steps
- At each step, compute the current value given inputs and previous values

```
node nat v = cpt where  
  rec cpt = v  $\rightarrow$  pre cpt + 1
```

$$cpt_n = \text{if } (n = 0) \text{ then } v_0 \text{ else } cpt_{n-1} + 1$$



$t = 0$


# Lustre $\rightarrow$ Lucid Synchrone $\rightarrow$ Zelus $\rightarrow$ ProbZelus

Dataflow synchronous programming

- Set of stream equations
- Discrete logical time steps
- At each step, compute the current value given inputs and previous values

```
node nat v = cpt where  
  rec cpt = v  $\rightarrow$  pre cpt + 1
```

$$cpt_n = \text{if } (n = 0) \text{ then } v_0 \text{ else } cpt_{n-1} + 1$$



$t = 0$


# Lustre $\rightarrow$ Lucid Synchrone $\rightarrow$ Zelus $\rightarrow$ ProbZelus

Dataflow synchronous programming

- Set of stream equations
- Discrete logical time steps
- At each step, compute the current value given inputs and previous values

```
node nat v = cpt where  
  rec cpt = v  $\rightarrow$  pre cpt + 1
```

$$cpt_n = \text{if } (n = 0) \text{ then } v_0 \text{ else } cpt_{n-1} + 1$$




# Lustre $\rightarrow$ Lucid Synchrone $\rightarrow$ Zelus $\rightarrow$ ProbZelus

Dataflow synchronous programming

- Set of stream equations
- Discrete logical time steps
- At each step, compute the current value given inputs and previous values

```
node nat v = cpt where  
  rec cpt = v  $\rightarrow$  pre cpt + 1
```

$$cpt_n = \text{if } (n = 0) \text{ then } v_0 \text{ else } cpt_{n-1} + 1$$




# Lustre $\rightarrow$ Lucid Synchrone $\rightarrow$ Zelus $\rightarrow$ ProbZelus

Dataflow synchronous programming

- Set of stream equations
- Discrete logical time steps
- At each step, compute the current value given inputs and previous values

```
node nat v = cpt where  
  rec cpt = v  $\rightarrow$  pre cpt + 1
```

$$cpt_n = \text{if } (n = 0) \text{ then } v_0 \text{ else } cpt_{n-1} + 1$$






# Lustre $\rightarrow$ Lucid Sychrone $\rightarrow$ Zelus $\rightarrow$ ProbZelus

## Dataflow synchronous programming

- Set of stream equations
- Discrete logical time steps
- At each step, compute the current value given inputs and previous values

```
node nat v = cpt where  
  rec cpt = v  $\rightarrow$  pre cpt + 1
```

$$cpt_n = \text{if } (n = 0) \text{ then } v_0 \text{ else } cpt_{n-1} + 1$$




# Lustre $\rightarrow$ Lucid Sychrone $\rightarrow$ Zelus $\rightarrow$ ProbZelus

## Dataflow synchronous programming

- Set of stream equations
- Discrete logical time steps
- At each step, compute the current value given inputs and previous values

```
node nat v = cpt where  
  rec cpt = v  $\rightarrow$  pre cpt + 1
```

$$cpt_n = \text{if } (n = 0) \text{ then } v_0 \text{ else } cpt_{n-1} + 1$$



# Examples

```
let node n1 () = (o1, o2) where  
  rec reset o1 = nat 0 every (0 fby o2 = 3)  
  and reset o2 = nat 0 every (0 fby o1 = 2)
```

# Examples

```
let node n1 () = (o1, o2) where
  rec reset o1 = nat 0 every (0 fby o2 = 3)
  and reset o2 = nat 0 every (0 fby o1 = 2)
```

o1		0	1	2	3	4	5	6	0	1	2	...
o2		0	1	2	0	1	2	3	4	5	6	...

# Examples

```
let node n1 () = (o1, o2) where
  rec reset o1 = nat 0 every (0 fby o2 = 3)
  and reset o2 = nat 0 every (0 fby o1 = 2)
```

```
let node n2 () = o where
  rec o1, o2 = n1 ()
  and o = present (o2 = 0) → o1 else 1
```

o1		0	1	2	3	4	5	6	0	1	2	...
o2		0	1	2	0	1	2	3	4	5	6	...



# Examples

```
let node n1 () = (o1, o2) where
  rec reset o1 = nat 0 every (0 fby o2 = 3)
  and reset o2 = nat 0 every (0 fby o1 = 2)
```

o1		0	1	2	3	4	5	6	0	1	2	...
o2		0	1	2	0	1	2	3	4	5	6	...

```
let node n2 () = o where
  rec o1, o2 = n1 ()
  and o = present (o2 = 0) → o1 else 1
```

o1		0	1	2	3	4	5	6	0	1	2	...
o2		0	1	2	0	1	2	3	4	5	6	...
o		1	1	1	3	1	1	1	1	1	1	...

# Examples

```
let node n1 () = (o1, o2) where
  rec reset o1 = nat 0 every (0 fby o2 = 3)
  and reset o2 = nat 0 every (0 fby o1 = 2)
```

o1		0	1	2	3	4	5	6	0	1	2	...
o2		0	1	2	0	1	2	3	4	5	6	...

```
let node n2 () = o where
  rec o1, o2 = n1 ()
  and o = present (o2 = 0) → o1 else 1
```

o1		0	1	2	3	4	5	6	0	1	2	...
o2		0	1	2	0	1	2	3	4	5	6	...
o		1	1	1	3	1	1	1	1	1	1	...

```
let node n3 () = o where
  rec o1, o2 = n1 ()
  and o = present (o2 = 0) → last o + o1 init 1
```

# Examples

```
let node n1 () = (o1, o2) where
  rec reset o1 = nat 0 every (0 fby o2 = 3)
  and reset o2 = nat 0 every (0 fby o1 = 2)
```

o1		0	1	2	3	4	5	6	0	1	2	...
o2		0	1	2	0	1	2	3	4	5	6	...

```
let node n2 () = o where
  rec o1, o2 = n1 ()
  and o = present (o2 = 0) → o1 else 1
```

o1		0	1	2	3	4	5	6	0	1	2	...
o2		0	1	2	0	1	2	3	4	5	6	...
o		1	1	1	3	1	1	1	1	1	1	...

```
let node n3 () = o where
  rec o1, o2 = n1 ()
  and o = present (o2 = 0) → last o + o1 init 1
```

o1		0	1	2	3	4	5	6	0	1	2	...
o2		0	1	2	0	1	2	3	4	5	6	...
o		1	1	1	4	4	4	4	4	4	4	...

# Exercises

*pid.zls*


```
let node integr (y, dt) = o where  
  rec ???
```

```
let node deriv (y, dt) = o where  
  rec ???
```

```
let node pid ((p, i, d), r, y, dt) = o where  
  rec ???
```

# Hierarchical automata

```
let node stopwatch (toggle, restart) = t where
  rec automaton
    | Main →
      do automaton
        | Idle      → do t = 0                until toggle then Run(0)
        | Run(ti)   → do t = ti fby (t + 1) until toggle then Stop(t)
        | Stop(ti) → do t = ti                until toggle then Run(t)
      end
    until restart then Main
```





# Demo

# ProbZelus


---

## Reactive Probabilistic Programming

# Reactive probabilistic programming

## Probabilistic constructs

- $x = \text{sample}(d)$ : introduce a random variable  $x$  of distribution  $d$
- $\text{observe}(d, y)$ : condition on the fact that  $y$  was sampled from  $d$
- $\text{infer } m \ y$ : compute posterior distribution of  $m$  given  $y$




```
let proba tracker (y) = x where
  rec x = x0 → sample(mv_gaussian(f *@ (pre x), q))
  and () = observe(mv_gaussian(h *@ x, r), y)
```

# Reactive probabilistic programming

## Probabilistic constructs

- $x = \text{sample}(d)$ : introduce a random variable  $x$  of distribution  $d$
- $\text{observe}(d, y)$ : condition on the fact that  $y$  was sampled from  $d$
- $\text{infer } m \ y$ : compute posterior distribution of  $m$  given  $y$




```
let proba tracker (y) = x where
  rec x = x0 → sample(mv_gaussian(f *@ (pre x), q))
  and () = observe(mv_gaussian(h *@ x, r), y)
```

# Reactive probabilistic programming


## Probabilistic constructs

- $x = \text{sample}(d)$ : introduce a random variable  $x$  of distribution  $d$
- $\text{observe}(d, y)$ : condition on the fact that  $y$  was sampled from  $d$
- $\text{infer } m \ y$ : compute posterior distribution of  $m$  given  $y$




```
let proba tracker (y) = x where
  rec x = x0 → sample(mv_gaussian(f *@ (pre x), q))
  and () = observe(mv_gaussian(h *@ x, r), y)
```

# Reactive probabilistic programming




$t = 0$

# Reactive probabilistic programming




$t = 0$

# Reactive probabilistic programming







# Reactive probabilistic programming



# Reactive probabilistic programming



# Reactive probabilistic programming





# Demo

Co-iterative semantics

---

Schedule agnostic semantics

# Deterministic semantics





$$\begin{aligned} [[c]]_{\gamma}^{\text{init}} &= () \\ [[c]]_{\gamma}^{\text{step}} (( )) &= (), c \end{aligned}$$

$$\begin{aligned} [[x]]_{\gamma}^{\text{init}} &= () \\ [[x]]_{\gamma}^{\text{step}} (( )) &= (), \gamma(x) \end{aligned}$$

$$\begin{aligned} [[i \rightarrow \text{pre } e]]_{\gamma}^{\text{init}} &= (i, [[e]]_{\gamma}^{\text{init}}) \\ [[i \rightarrow \text{pre } e]]_{\gamma}^{\text{step}} (p, s) &= \text{let } s', v = [[e]]_{\gamma}^{\text{step}} (s) \text{ in } (v, s'), p \end{aligned}$$


# Deterministic semantics



$[[c]]_{\gamma}^{\text{init}}$   
 $[[c]]_{\gamma}^{\text{step}} (( ))$

$[[x]]_{\gamma}^{\text{init}}$   
 $[[x]]_{\gamma}^{\text{step}} (( ))$

$[[i \rightarrow \text{pre } e]]$   
 $[[i \rightarrow \text{pre } e]]$



# Deterministic equations

$$\left[ \begin{array}{l} e \text{ where rec init } x = c \\ \quad \text{and } x = e_x \\ \quad \text{and } y = e_y \end{array} \right]_{\gamma}^{\text{init}} = c, \left( \llbracket e \rrbracket_{\gamma}^{\text{init}}, \llbracket e_x \rrbracket_{\gamma}^{\text{init}}, \llbracket e_y \rrbracket_{\gamma}^{\text{init}} \right)$$

$$\left[ \begin{array}{l} e \text{ where rec init } x = c \\ \quad \text{and } x = e_x \\ \quad \text{and } y = e_y \end{array} \right]_{\gamma}^{\text{step}} (p_x, (s, s_x, s_y)) = \begin{array}{l} \text{let } s'_x, v_x = \llbracket e_x \rrbracket_{\gamma + [x.\text{last} \leftarrow p_x]}^{\text{step}} (s_x) \text{ in} \\ \text{let } s'_y, v_y = \llbracket e_y \rrbracket_{\gamma + [x.\text{last} \leftarrow p_x, x \leftarrow v_x]}^{\text{step}} (s_y) \text{ in} \\ \text{let } s', v = \llbracket e \rrbracket_{\gamma + [x.\text{last} \leftarrow p_x, x \leftarrow v_x, y \leftarrow v_y]}^{\text{step}} (s) \text{ in} \\ (v_x, (s', s'_x, s'_y)) \end{array}$$



# Deterministic equations

$$\left[ \begin{array}{l} e \text{ where } \text{rec init } x = c \\ \text{and } x = e_x \\ \text{and } y = e_y \end{array} \right]_{\gamma}^{\text{init}} = c, \left( \llbracket e \rrbracket_{\gamma}^{\text{init}}, \llbracket e_x \rrbracket_{\gamma}^{\text{init}}, \right.$$

$$\left. \left[ \begin{array}{l} e \text{ where } \text{rec init } x = c \\ \text{and } x = e_x \\ \text{and } y = e_y \end{array} \right]_{\gamma}^{\text{step}} (p_x, (s, s_x, s_y)) = \text{let } s'_x, v_x = \llbracket e_x \rrbracket_{\gamma+}^{\text{step}} \right.$$

$$\text{let } s'_y, v_y = \llbracket e_y \rrbracket_{\gamma+}^{\text{step}} \text{let } s', v = \llbracket e \rrbracket_{\gamma+}^{\text{step}} [x.$$

$$(v_x, (s', s'_x, s'_y))$$

## Reactive Probabilistic Programming

Guillaume Baudart  
MIT-IBM Watson AI Lab,  
IBM Research  
USA

Louis Mandel  
MIT-IBM Watson AI Lab,  
IBM Research  
USA

Eric Atkinson  
MIT  
USA

Benjamin Sherman  
MIT  
USA

Marc Pouzet  
École Normale Supérieure,  
PSL Research University  
France

Michael Carbin  
MIT  
USA

### Abstract

Synchronous modeling is at the heart of programming languages like Lustre, Esterel, or SCADE used routinely for implementing safety critical control software, e.g., fly-by-wire and engine control in planes. However, to date these languages have had limited modern support for modeling uncertainty — probabilistic aspects of the software's environment or behavior — even though modeling uncertainty is a primary activity when designing a control system.

In this paper we present ProbZelus the first *synchronous probabilistic programming language*. ProbZelus conservatively provides the facilities of a synchronous language to write control software, with probabilistic constructs to model uncertainties and perform *inference-in-the-loop*.

We present the design and implementation of the language. We propose a measure-theoretic semantics of probabilistic stream functions and a simple type discipline to separate deterministic and probabilistic expressions. We demonstrate a semantics-preserving compilation into a first-order functional language that lends itself to a simple presentation of inference algorithms for streaming models. We also redesign the delayed sampling inference algorithm to provide efficient *streaming* inference. Together with an evaluation on several reactive applications, our results demonstrate that ProbZelus enables the design of reactive probabilistic applications and efficient, bounded memory inference.

**CCS Concepts:** • **Theory of computation** → **Streaming models**; • **Software and its engineering** → **Data flow languages**.

**Keywords:** Probabilistic programming, Reactive programming, Streaming inference, Semantics, Compilation

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

PLDI '20, June 15–20, 2020, London, UK

© 2020 Copyright held by the owner/author(s).

ACM ISBN 978-1-4503-7613-6/20/06.

<https://doi.org/10.1145/3385412.3386009>

### ACM Reference Format:

Guillaume Baudart, Louis Mandel, Eric Atkinson, Benjamin Sherman, Marc Pouzet, and Michael Carbin. 2020. Reactive Probabilistic Programming. In *Proceedings of the 41st ACM SIGPLAN International Conference on Programming Language Design and Implementation (PLDI '20)*, June 15–20, 2020, London, UK. ACM, New York, NY, USA, 15 pages. <https://doi.org/10.1145/3385412.3386009>

### 1 Introduction

Synchronous languages [2] were introduced thirty years ago for designing and implementing real-time control software. They are founded on the synchronous abstraction [4] where a system is modeled ideally, as if communications and computations were instantaneous and paced on a global clock. This abstraction is simple but powerful: input, output and local signals are streams that advance synchronously and a system is a stream function. It is at the heart of the data-flow languages Lustre [20] and SCADE [13]; it is also the underlying model behind the discrete-time subset of Simulink.

The data-flow programming style is very well adapted to the direct expression of the classic control blocks of control engineering (e.g., relays, filters, PID controllers, control logic), and a discrete time model of the environment, with the feedback between the two. For example, consider a backward Euler integration method defined by the following stream equations and its corresponding implementation in Zelus [7], a language reminiscent of Lustre:

$$x_0 = x0_0 \quad x_n = x_{n-1} + x'_n \times h \quad \forall n \in \mathbb{N}, n > 0$$

```
let node integr (x0, x') = x where
  rec x = x0 -> (pre x + x' * h)
```

The *node integr* is a function from input streams *x0* and *x'* to output stream *x*. The *initialization* operator *->* returns its left-hand side value at the first time step and its right-hand side expression on every time step thereafter. The *unit-delay* operator *pre* returns the value of its expression at the previous time step. The following table presents a sample *timeline* showing the sequences of values taken by the streams defined in the program (where *h* is set to 0.1).

# Deterministic equations

$$\left[ \begin{array}{l} e \text{ where } \text{rec init } x = c \\ \text{and } x = e_x \\ \text{and } y = e_y \end{array} \right]_{\gamma}^{\text{init}} = c, \left( \llbracket e \rrbracket_{\gamma}^{\text{init}}, \llbracket e_x \rrbracket_{\gamma}^{\text{init}}, \right.$$


$$\left[ \begin{array}{l} e \text{ where } \text{rec init } x = c \\ \text{and } x = e_x \\ \text{and } y = e_y \end{array} \right]_{\gamma}^{\text{step}} (p_x, (s, s_x, s_y)) = \text{let } s'_x, v_x = \dots$$

$$\text{let } s'_y, v_y = \dots \\ \text{let } s', v = \dots \\ (v_x, (s', s'_x, s'_y))$$

**Scheduling.** In the expression  $e \text{ where } \text{rec } E$ ,  $E$  is a set of mutually recursive equations. In practice, a scheduler re-orders the equations according to their dependencies. Initializations  $\text{init } x_j = c_j$  are grouped at the beginning, and an equation  $x_j = e_j$  must be scheduled after the equation  $x_i = e_i$  if the expression  $e_j$  uses  $x_i$  outside a **last** construct. A program satisfying this partial order is said to be *scheduled*. The compiler can also introduce additional equations to relax the scheduling constraints and rejects programs that cannot be statically scheduled [5]. After scheduling, the expression  $e \text{ where } \text{rec } E$  has the following form.

$e \text{ where } \text{rec init } x_1 = c_1 \dots \text{and init } x_k = c_k \\ \text{and } y_1 = e_1 \dots \text{and } y_n = e_n$

For simplicity, we also assume that every initialized variable is defined in a subsequent equation, i.e.,  $\{x_i\}_{1..k} \cap \{y_j\}_{1..n} = \{x_i\}_{1..k}$ . If it is not the case, in this kernel we can always add additional equations of the form  $x_i = \text{last } x_i$ .




# Example

`rec`  $x = 1 + \text{pre } x$

■ Initial state:  $()$ ,  $0$

■ Output:  $1, 2, 3, 4, \dots$




# Example

`rec x = 1 + pre x`

■ Initial state:  $()$ ,  $0$

■ Output:  $1, 2, 3, 4, \dots$




# Example

`rec x = 1 + pre x`

■ Initial state:  $()$ ,  $0$

■ Output:  $1, 2, 3, 4, \dots$




# Example

`rec`  $x = 1 + \text{pre } x$

■ Initial state:  $() , 0$

■ Output:  $1, 2, 3, 4, \dots$




# Example

`rec x = 1 + pre x`

■ Initial state: `()`, `0`

■ Output: `1`, `2`, `3`, `4`, `....`




# Example

`rec x = 1 + pre x`

■ Initial state:  $()$ ,  $0$

■ Output:  $1, 2, 3, 4, \dots$






# Example

`rec`  $x = 1 + \text{pre } x$

■ Initial state:  $()$ ,  $0$

■ Output:  $1, 2, 3, 4, \dots$




# Example

`rec x = 1 + pre x`

■ Initial state:  $()$ ,  $0$

■ Output:  $1, 2, 3, 4, \dots$




# Example

`rec x = 1 + pre x`

■ Initial state:  $()$ ,  $0$

■ Output:  $1, 2, 3, 4, \dots$




# Example

`rec`  $x = 1 + \text{pre } x$

■ Initial state:  $() , 0$


■ Output:  $1, 2, 3, 4, \dots$



# Example

`rec x = 1 + pre x`

- Initial state: `()`, `0`
- Output: `1`, `2`, `3`, `4`, `....`




# Example

`rec x = 1 + pre x`

■ Initial state:  $()$ ,  $0$

■ Output:  $1, 2, 3, 4, \dots$




# Example

`rec x = 1 + pre x`

■ Initial state:  $()$ ,  $0$

■ Output:  $1, 2, 3, 4, \dots$




# Example

`rec x = 1 + pre x`

■ Initial state:  $()$ ,  $0$

■ Output:  $1, 2, 3, 4, \dots$






# Deterministic vs. probabilistic

## Deterministic streams

Transition function returns a pair of state and value


$$\text{CoStream}(T, S) = S \times (S \rightarrow S \times T)$$





## Probabilistic streams

Transition function returns a **measure** over (state, value)



$$\text{CoPStream}(T, S) = S \times (S \rightarrow \Sigma_{S \times T} \rightarrow [0, \infty])$$



# Probabilistic semantics



# Probabilistic semantics



*if  $e$  is deterministic*

$$\{e\}_{\gamma}^{\text{init}} \\ \{e\}_{\gamma}^{\text{step}}(s)$$

$$\{\text{sample}(e)\}_{\gamma}^{\text{init}} \\ \{\text{sample}(e)\}_{\gamma}^{\text{step}}(s)$$

$$\{\text{observe}(e_1, e_2)\}_{\gamma}^{\text{init}} \\ \{\text{observe}(e_1, e_2)\}_{\gamma}^{\text{step}}(s_1, s_2)$$

$$\begin{aligned} &= \llbracket e \rrbracket_{\gamma}^{\text{init}} \\ &= \text{let } s', v = \llbracket e \rrbracket_{\gamma}^{\text{step}}(s) \text{ in } \delta_{s', v} \\ &= \llbracket e \rrbracket_{\gamma}^{\text{init}} \\ &= \text{let } s', \mu = \llbracket e \rrbracket_{\gamma}^{\text{step}}(s) \text{ in } \int \mu(dv) \delta_{s', v} \\ &= \llbracket e_1 \rrbracket_{\gamma}^{\text{init}}, \llbracket e_2 \rrbracket_{\gamma}^{\text{init}} \\ &= \text{let } s'_1, \mu = \llbracket e_1 \rrbracket_{\gamma}^{\text{step}}(s_1) \text{ in} \\ &\quad \text{let } s'_2, v = \llbracket e_2 \rrbracket_{\gamma}^{\text{step}}(s_2) \text{ in} \\ &\quad \mu_{\text{pdf}}(v) * \delta_{(s'_1, s'_2), ()} \end{aligned}$$

# Probabilistic equations

$$\left\{ \begin{array}{l} e \text{ where rec init } x = c \\ \text{and } x = e_x \\ \text{and } y = e_y \end{array} \right\}_{\gamma}^{\text{init}} = c, \left( \llbracket e \rrbracket_{\gamma}^{\text{init}}, \llbracket e_x \rrbracket_{\gamma}^{\text{init}}, \llbracket e_y \rrbracket_{\gamma}^{\text{init}} \right)$$


$$\left\{ \begin{array}{l} e \text{ where rec init } x = c \\ \text{and } x = e_x \\ \text{and } y = e_y \end{array} \right\}_{\gamma}^{\text{step}} (p_x, (m, m_x, m_y)) = \int \llbracket e_x \rrbracket_{\gamma+[x.\text{last} \leftarrow p_x]}^{\text{step}} (m_x) (dm'_x, dv_x) \\ \int \llbracket e_y \rrbracket_{\gamma+[x.\text{last} \leftarrow p_x, x \leftarrow v_x]}^{\text{step}} (m_y) (dm'_y, dv_y) \\ \int \llbracket e \rrbracket_{\gamma+[x.\text{last} \leftarrow p_x, x \leftarrow v_x, y \leftarrow v_y]}^{\text{step}} (m) (dm', dv) \\ \delta_{(v_x, (m', m'_x, m'_y)), v}$$

# Probabilistic equations

$$\begin{aligned}
 \left\{ \begin{array}{l} e \text{ where rec init } x = c \\ \text{and } x = e_x \\ \text{and } y = e_y \end{array} \right\}_{\gamma}^{\text{init}} &= c, \left( \llbracket e \rrbracket_{\gamma}^{\text{init}}, \llbracket e_x \rrbracket_{\gamma}^{\text{init}}, \llbracket e_y \rrbracket_{\gamma}^{\text{init}} \right) \\
 \left\{ \begin{array}{l} e \text{ where rec init } x = c \\ \text{and } x = e_x \\ \text{and } y = e_y \end{array} \right\}_{\gamma}^{\text{step}} (p_x, (m, m_x, m_y)) &= \int \llbracket e_x \rrbracket_{\gamma+[x.\text{last} \leftarrow p_x]}^{\text{step}} (m_x) (dm'_x, dv_x) \\
 &\quad \int \llbracket e_y \rrbracket_{\gamma+[x.\text{last} \leftarrow p_x, x \leftarrow v_x]}^{\text{step}} (m_y) (dm'_y, dv_y) \\
 &\quad \int \llbracket e \rrbracket_{\gamma+[x.\text{last} \leftarrow p_x, x \leftarrow v_x, y \leftarrow v_y]}^{\text{step}} (m) (dm', dv) \\
 &\quad \delta_{(v_x, (m', m'_x, m'_y)), v}
 \end{aligned}$$

Nested integrals require a fixed schedule

# Semantics of infer



$$\begin{aligned}
 \llbracket \text{infer}(e) \rrbracket_{\gamma}^{\text{init}} &= \delta_{\llbracket e \rrbracket_{\gamma}^{\text{init}}} \\
 \llbracket \text{infer}(e) \rrbracket_{\gamma}^{\text{step}}(\sigma) &= \text{let } \nu = \int \sigma(dm) \llbracket e \rrbracket_{\gamma}^{\text{step}}(m) \text{ in let } \bar{\nu} = \nu / \nu(\top) \text{ in} \\
 &\quad (\pi_{1*}(\bar{\nu}), \pi_{2*}(\bar{\nu}))
 \end{aligned}$$

# Compilation

---

Reactive Probabilistic Programming

# Target

Simplified syntax

$x ::= \text{variables}$

$c ::= \text{constants}$

$d ::= \text{let } p = e \mid \text{let } f = \text{fun } p \rightarrow e \mid d \ d$

$p ::= x \mid (p, p)$

$e ::= c \mid x \mid (e, e) \mid \text{op } (e) \mid f (e)$

$\mid \text{if } e \text{ then } e \text{ else } e \mid \text{let } p = e \text{ in } e$

$\mid \text{sample } (e) \mid \text{factor } (e) \mid \text{observe } (e, e)$

$\mid \text{infer } (e)$



# Target

Simplified syntax

$x ::= \text{variables}$

$c ::= \text{constants}$

$d ::= \text{let } p = e \mid \text{let } f =$

$p ::= x \mid (p, p)$

$e ::= c \mid x \mid (e, e) \mid \text{op}$

$\mid \text{if } e \text{ then } e \text{ else } e$

$\mid \text{sample } (e) \mid \text{factor}$

$\mid \text{infer } (e)$

## Probabilistic semantics

$$\llbracket \text{let } f = \text{fun } p \rightarrow e \rrbracket^\phi = \phi + \left[ f \leftarrow \lambda v. \llbracket e \rrbracket^\phi_{[p \leftarrow v]} \right] \text{ if } \text{kindOf}(e) = P$$

$$\llbracket e \rrbracket^\phi_\gamma = \lambda U. \delta_{\llbracket e \rrbracket^\phi_\gamma}(U) \text{ if } \text{kindOf}(e) = D$$

$$\llbracket f(e) \rrbracket^\phi_\gamma = \lambda U. \phi(f)(\llbracket e \rrbracket^\phi_\gamma)(U)$$

$$\llbracket \text{if } e_1 \text{ then } e_2 \text{ else } e_3 \rrbracket^\phi_\gamma = \lambda U. \text{if } \llbracket e_1 \rrbracket^\phi_\gamma \text{ then } \llbracket e_2 \rrbracket^\phi_\gamma(U) \text{ else } \llbracket e_3 \rrbracket^\phi_\gamma(U)$$

$$\llbracket \text{let } p = e_1 \text{ in } e_2 \rrbracket^\phi_\gamma = \lambda U. \int_{\llbracket \text{typeOf}(e_1) \rrbracket} \llbracket e_1 \rrbracket^\phi_\gamma(dv) \llbracket e_2 \rrbracket^\phi_{\gamma+[p \leftarrow v]}$$

$$\llbracket \text{sample}(e) \rrbracket^\phi_\gamma = \lambda U. \llbracket e \rrbracket^\phi_\gamma(U)$$

$$\llbracket \text{factor}(e) \rrbracket^\phi_\gamma = \lambda U. \llbracket e \rrbracket^\phi_\gamma \cdot \delta_{()}(U)$$

$$\llbracket \text{observe}(e_1, e_2) \rrbracket^\phi_\gamma = \lambda U. \text{pdf}(\llbracket e_1 \rrbracket^\phi_\gamma)(\llbracket e_2 \rrbracket^\phi_\gamma) \cdot \delta_{()}(U)$$

$$\llbracket \text{infer}(e) \rrbracket^\phi_\gamma = \begin{cases} \frac{\lambda U. \llbracket e \rrbracket^\phi_\gamma(U)}{\llbracket e \rrbracket^\phi_\gamma(\llbracket \text{typeOf}(e) \rrbracket)} & \text{if } 0 < \llbracket e \rrbracket^\phi_\gamma(\llbracket \text{typeOf}(e) \rrbracket) < \infty \\ \text{Error} & \text{otherwise} \end{cases}$$


Careful with 0, and  $\infty$ ...

# Compilation = Allocation + Transition

## Synchronous languages

- Static analyses (typing, causality, initialization)
- Normalization, scheduling (**rec**  $x = y + 1$  **and**  $y = 0 \rightarrow$  **pre**  $x$ )
- Compilation

Memory can be statically allocated



# Allocation

$$\mathcal{A}(x) = ()$$

$$\mathcal{A}((e_1, e_2)) = (\mathcal{A}(e_1), \mathcal{A}(e_2))$$

$$\mathcal{A}(\text{present } e \rightarrow e_1 \text{ else } e_2) = (\mathcal{A}(e), \mathcal{A}(e_1), \mathcal{A}(e_2))$$

$$\mathcal{A}(\text{op}(e)) = \mathcal{A}(e)$$

$$\mathcal{A}(f(e)) = (f\_init, \mathcal{A}(e))$$

$$\mathcal{A}(\text{sample}(e)) = \mathcal{A}(e)$$

$$\mathcal{A}(\text{factor}(e)) = \mathcal{A}(e)$$

$$\mathcal{A}(\text{observe}(e_1, e_2)) = (\mathcal{A}(e_1), \mathcal{A}(e_2))$$

$$\mathcal{A}(\text{infer}(e)) = \mathcal{A}(e)$$

# Allocation

$$\mathcal{A}(x) = ()$$

$$\mathcal{A}((e_1, e_2)) = (\mathcal{A}(e_1), \mathcal{A}(e_2))$$

$$\mathcal{A}(\text{present } e \rightarrow e_1 \text{ else } e_2) = (\mathcal{A}(e), \mathcal{A}(e_1), \mathcal{A}(e_2))$$

$$\mathcal{A}(\text{op}(e)) = \mathcal{A}(e)$$

$$\mathcal{A}(f(e)) = (f\_init, \mathcal{A}(e))$$

$$\mathcal{A}(\text{sample}(e)) = \mathcal{A}(e)$$

$$\mathcal{A}(\text{factor}(e)) = \mathcal{A}(e)$$

$$\mathcal{A}(\text{observe}(e_1, e_2)) = (\mathcal{A}(e_1), \mathcal{A}(e_2))$$

$$\mathcal{A}(\text{infer}(e)) = \mathcal{A}(e)$$

$$\mathcal{A} \left( \begin{array}{l} e \text{ where} \\ \text{rec init } x = c_x \\ \text{and init } y = c_y \\ \text{and } x = e_x \\ \text{and } y = e_y \end{array} \right) = \left( \begin{array}{l} (c_x, c_y), \\ (\mathcal{A}(e_1), \mathcal{A}(e_2)), \\ \mathcal{A}(e) \end{array} \right)$$

# Transition

```
C(c) = fun s -> (c, s)
C(x) = fun s -> (x, s)
C(last x) = fun s -> (x_last, s)
```

```
C((e1, e2)) = fun (s1,s2) ->
  let v1,s1' = C(e1)(s1) in
  let v2,s2' = C(e2)(s2) in
  ((v1,v2), (s1',s2'))
```

```
C(op(e)) = fun s ->
  let v,s' = C(e)(s) in
  (op(v), s')
```

```
C(f(e)) = fun (s1,s2) ->
  let v1,s1' = C(e)(s1) in
  let v2,s2' = f_step(s2,v) in
  (v2, (s1',s2'))
```

```
C(present e -> e1 else e2) =
fun (s,s1,s2) ->
  let v, s' = C(e)(s) in
  if v then let v1,s1' = C(e1)(s1) in
    (v1, (s',s1',s2))
  else let v2,s2' = C(e2)(s2) in
    (v2, (s',s1,s2'))
```

```
C(sample(e)) = fun s ->
  let mu,s' = C(e)(s) in
  let v = sample(mu) in (v, s')
```

```
C(observe(e1, e2)) = fun (s1,s2) ->
  let v1,s1' = C(e1)(s1) in
  let v2,s2' = C(e2)(s2) in
  let _ = observe(v1,v2) in
  (( ), (s1',s2'))
```

```
C(factor(e)) = fun s ->
  let v,s' = C(e)(s) in
  let _ = factor(v) in (( ), s')
```

```
C(infer(e)) = fun sigma ->
  let mu,sigma' = infer(C(e), sigma) in
  (mu, sigma')
```

# Transition

```
C(c) = fun s -> (c, s)
C(x) = fun s -> (x, s)
C(last x) = fun s -> (x_last, s)
```

```
C((e1, e2)) = fun (s1,s2) ->
  let v1,s1' = C(e1)(s1) in
```

```
  let v = C(present e -> e1 else e2) =
    fun (s,s1,s2) ->
      let v, s' = C(e)(s) in
      if v then let v1,s1' = C(e1)(s1) in
        (v1, (s',s1',s2))
      else let v2,s2' = C(e2)(s2) in
        (v2, (s',s1,s2'))
```

```
C(present e -> e1 else e2) =
fun (s,s1,s2) ->
  let v, s' = C(e)(s) in
  if v then let v1,s1' = C(e1)(s1) in
    (v1, (s',s1',s2))
  else let v2,s2' = C(e2)(s2) in
    (v2, (s',s1,s2'))
```

```
C(sample(e)) = fun s ->
  let mu,s' = C(e)(s) in
  let v = sample(mu) in (v, s')
```

```
C(observe(e1, e2)) = fun (s1,s2) ->
  let v1,s1' = C(e1)(s1) in
  let v2,s2' = C(e2)(s2) in
  let _ = observe(v1,v2) in
  ((), (s1',s2'))
```

```
factor(e) = fun s ->
  let v,s' = C(e)(s) in
  let _ = factor(v) in ((), s')
```

```
infer(e) = fun sigma ->
  let mu,sigma' = infer(C(e), sigma) in
  (mu, sigma')
```

# Transition

```
C(c) = fun s -> (c, s)
C(x) = fun s -> (x, s)
C(last x) = fun s -> (x_last, s)
```

```
C((e1, e2)) = fun (s1, s2) ->
  let v1, s1' = C(e1)(s1) in
```

```
  let v2, s2' = C(e2)(s2) in
  ((v1, v2), (s1', s2'))

C(present e -> e1 else e2) =
  fun (s, s1, s2) ->
    let v, s' = C(e)(s) in
    if v then let v1, s1' = C(e1)(s1) in
      (v1, (s', s1', s2'))
    else let v2, s2' = C(e2)(s2) in
      (v2, (s', s1, s2'))
```

```
C(present e -> e1 else e2) =
  fun (s, s1, s2) ->
    let v, s' = C(e)(s) in
    if v then let v1, s1' = C(e1)(s1) in
      (v1, (s', s1', s2'))
    else let v2, s2' = C(e2)(s2) in
      (v2, (s', s1, s2'))
```

```
C(sample(e)) = fun s ->
  let mu, s' = C(e)(s) in
  let v = sample(mu) in (v, s')
```

```
C(observe(e1, e2)) = fun (s1, s2) ->
  let v1, s1' = C(e1)(s1) in
  let v2, s2' = C(e2)(s2) in
  let _ = observe(v1, v2) in
  (((), (s1', s2')))
```

```
C(factor(e)) = fun s ->
  let v, s' = C(e)(s) in
  let _ = factor(v) in (((), s'))
```

```
C(infer(e)) = fun sigma ->
  let mu, sigma' = infer(C(e), sigma) in
  (mu, sigma')
```


```
C(sample(e)) = fun s ->
  let mu, s' = C(e)(s) in
  let v = sample(mu) in (v, s')
```

```
C(observe(e1, e2)) = fun (s1, s2) ->
  let v1, s1' = C(e1)(s1) in
  let v2, s2' = C(e2)(s2) in
  let _ = observe(v1, v2) in
  (((), (s1', s2')))
```

```
C(factor(e)) = fun s ->
  let v, s' = C(e)(s) in
  let _ = factor(v) in (((), s'))
```

```
C(infer(e)) = fun sigma ->
  let mu, sigma' = infer(C(e), sigma) in
  (mu, sigma')
```

# The Zelus compiler





# Generated code

```
(* a synchronous stream function with type 'a -D→ 'b *)
(* is represented by an OCaml value of type ('a, 'b) node *)
type ('a, 'b) node =
  Node:
    { alloc : unit → 's; (* allocate the state *)
      step : 's → 'a → 'b; (* compute a step *)
      reset : 's → unit; (* reset/initialize the state *)
    } → ('a, 'b) cnode

(*
  let m = alloc () in
  reset m;
  while true do
    let o = step m i in ...
  done
*)
```

# Streaming inference

---

Reactive Probabilistic Programming

# Particle filter

Approximate inference algorithm : importance sampling, but...

- Add a resampling step at each **observe**
- Compute the score of the particles to compute a distribution
- Re-sample a new set of particles from this distribution

How can we duplicate a particle during execution?

- Continuation Passing Style (CPS)?
- Clone the memory state?

# Particle filter

Approximate inference algorithm : importance sampling, but...

- Add a resampling step at each **observe**
- Compute the score of the particles to compute a distribution
- Re-sample a new set of particles from this distribution

How can we duplicate a particle during execution?

- Continuation Passing Style (CPS)?
- Clone the memory state?


(\* the same with a method copy \*)

**type** ('a, 'b) cnode =

Cnode:

```
{ alloc : unit → 's; (* allocate the state *)  
  copy : 's → 's → unit; (* copy the source into the destination *)  
  step : 's → 'a → 'b; (* compute a step *)  
  reset : 's → unit; (* reset/initialize the state *)  
} → ('a, 'b) cnode
```


# Particle filter



# Particle filter

Intractable integrals

Approximation: weighted sum from multiple particles



# Particle filter

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

# Particle filter

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$



# Particle filter

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10)) → gaussian (pre x, 1)  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$


```
sample (gaussian (0, 10))
```

# Particle filter

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10)) → gaussian (pre x, 1)  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

sample (gaussian (0, 10))




# Particle filter

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```




# Particle filter

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```



$t = 1$

# Particle filter


```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))
```



# Particle filter


```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))
```



# Particle filter


```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))  
observe (gaussian (x, 1), 5)
```



# Particle filter

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$


```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))  
observe (gaussian (x, 1), 5)
```

$t = 2$

```
sample (gaussian (pre x, 1))  
observe (gaussian (x, 1), ...)
```



...



# Delayed sampling

Simple Particles Filters can be impractical

- Require lot of computing power
- Poor approximation

Exact inference is often possible

Semi-Symbolic inference

- Perform as much exact computation as possible
- Fall back to a Particle Filter when symbolic computation fails

Main idea

- Keep track of conjugacy relationships
- Incorporate observations analytically
- Sample only when necessary

# Delayed sampling

Simple Particles Filters can be impractical

- Require lot of computing power
- Poor approximation

Exact inference is often possible

Semi-Symbolic inference

- Perform as much exact computation as possible
- Fall back to a Particle Filter when symbolic computation fails

Main idea

- Keep track of conjugacy relationships
- Incorporate observations analytically
- Sample only when necessary

## Example: Conjugate Gaussians

$$x \sim \mathcal{N}(\mu_0, \sigma_0)$$

$$y \sim \mathcal{N}(x, \sigma)$$

$$x \mid (y = v) \sim \mathcal{N}(\mu_1, \sigma_1)$$

$$\mu_1 = \left( \frac{1}{\sigma_0^2} + \frac{1}{\sigma^2} \right)^{-1} \left( \frac{\mu_0}{\sigma_0^2} + \frac{v}{\sigma^2} \right)$$

$$\sigma_1 = \left( \frac{1}{\sigma_0^2} + \frac{1}{\sigma^2} \right)^{-2}$$

# Delayed sampling

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

# Delayed sampling

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

# Delayed sampling

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10)) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$


```
sample (gaussian (0, 10))
```

# Delayed sampling

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10)) → gaussian (pre x, 1)  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

sample (gaussian (0, 10))




# Delayed sampling

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```




# Delayed sampling

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```






# Delayed sampling

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```




# Delayed sampling

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```



## Example: 2 Gaussians

$$x \sim \mathcal{N}(\mu_0, \sigma_0)$$

$$y \sim \mathcal{N}(x, \sigma)$$

$$x | (y = v) \sim \mathcal{N}(\mu_1, \sigma_1)$$

$$\mu_1 = \left( \frac{1}{\sigma_0^2} + \frac{1}{\sigma^2} \right)^{-1} \left( \frac{\mu_0}{\sigma_0^2} + \frac{v}{\sigma^2} \right)$$


$$\sigma_1 = \left( \frac{1}{\sigma_0^2} + \frac{1}{\sigma^2} \right)^{-2}$$

# Delayed sampling

```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))
observe (gaussian (x, 1), 3)
```



## Example: 2 Gaussians

$$x \sim \mathcal{N}(\mu_0, \sigma_0)$$

$$y \sim \mathcal{N}(x, \sigma)$$

$$x | (y = v) \sim \mathcal{N}(\mu_1, \sigma_1)$$

$$\mu_1 = \left( \frac{1}{\sigma_0^2} + \frac{1}{\sigma^2} \right)^{-1} \left( \frac{\mu_0}{\sigma_0^2} + \frac{v}{\sigma^2} \right)$$


$$\sigma_1 = \left( \frac{1}{\sigma_0^2} + \frac{1}{\sigma^2} \right)^{-2}$$

# Delayed sampling

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```



$t = 1$

```
sample (gaussian (pre x, 1))
```

# Delayed sampling


```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))
```



# Delayed sampling


```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))
```



# Delayed sampling


```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))  
observe (gaussian (x, 1), 5)
```



# Delayed sampling


```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))  
observe (gaussian (x, 1), 5)
```





# Delayed sampling


```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))  
observe (gaussian (x, 1), 5)
```



# Delayed sampling

```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

$t = 0$


```
sample (gaussian (0, 10))
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), 5)
```

$t = 2$

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), ...)
```



# Delayed sampling

```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

$t = 0$


```
sample (gaussian (0, 10))
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), 5)
```

$t = 2$

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), ...)
```




# Delayed sampling

```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```


$t = 0$

```
sample (gaussian (0, 10))
observe (gaussian (x, 1), 3)
```

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), 3)
```



Unbounded resources



# Delayed sampling

```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

$t = 0$


```
sample (gaussian (0, 10))
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), 5)
```

$t = 2$

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), ...)
```



# Streaming Delayed sampling

```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

$t = 0$


```
sample (gaussian (0, 10))
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), 5)
```

$t = 2$

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), ...)
```



# Streaming Delayed sampling

```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

$t = 0$


```
sample (gaussian (0, 10))
observe (gaussian (x, 1), 3)
```

$t = 1$

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), 5)
```

$t = 2$

```
sample (gaussian (pre x, 1))
observe (gaussian (x, 1), ...)
```



# Streaming Delayed sampling

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```

$t = 0$

```
sample (gaussian (0, 10))  
observe (gaussian (x, 1), 3)
```

x

$t = 1$

```
sample (gaussian (pre x, 1))  
observe (gaussian (x, 1), 5)
```

pre x


x

$t = 2$


```
sample (gaussian (pre x, 1))  
observe (gaussian (x, 1), ...)
```

pre x

x



$\mathcal{N}(4.32, 0.816)$





# Delayed Sampling semantics

$$\llbracket op(e) \rrbracket_{\gamma, g, w} = \\ \text{let } (e', g_e, w_e) = \llbracket e \rrbracket_{\gamma, g, w} \text{ in } (\text{app}(op, e'), g_e, w_e)$$

$$\llbracket \text{if } e \text{ then } e_1 \text{ else } e_2 \rrbracket_{\gamma, g, w} = \\ \text{let } e', g_e, w_e = \llbracket e \rrbracket_{\gamma, g, w} \text{ in} \\ \text{let } v, g_v = \text{value}(e', g_e) \text{ in} \\ \text{if } v \text{ then } \llbracket e_1 \rrbracket_{\gamma, g_v, w_e} \text{ else } \llbracket e_2 \rrbracket_{\gamma, g_v, w_e}$$

$$\llbracket \text{sample}(e) \rrbracket_{\gamma, g, w} = \\ \text{let } \mu, g_e, w' = \llbracket e \rrbracket_{\gamma, g, w} \text{ in} \\ \text{let } X, g' = \text{assume}(\mu, g_e) \text{ in } (X, g', w')$$

$$\llbracket \text{observe}(e_1, e_2) \rrbracket_{\gamma, g, w} = \\ \text{let } \mu, g_1, w_1 = \llbracket e_1 \rrbracket_{\gamma, g, w} \text{ in let } X, g_x = \text{assume}(\mu, g_1) \text{ in} \\ \text{let } e'_2, g_2, w_2 = \llbracket e_2 \rrbracket_{\gamma, g_x, w_1} \text{ in let } v, g_v = \text{value}(e'_2, g_2) \text{ in} \\ \text{let } g' = \text{observe}(X, v, g_v) \text{ in } (( ), g', w_2 * \mu_{\text{pdf}}(v))$$

$$\llbracket \text{infer}(\text{fun } s \rightarrow e, \sigma) \rrbracket_{\gamma} = \\ \text{let } \mu = \lambda U. \sum_{i=1}^N \text{let } s_i, g_i = \text{draw}(\llbracket \sigma \rrbracket_{\gamma}) \text{ in} \\ \text{let } (e_i, s'_i), w_i, g'_i = \llbracket \text{fun } s \rightarrow e \rrbracket_{\gamma, 1, g_i}(s_i) \text{ in} \\ \text{let } d_i = \text{distribution}(e_i, g'_i) \text{ in} \\ \overline{w}_i * d_i(\pi_1(U)) * \delta_{s'_i, g'_i}(\pi_2(U)) \\ \text{in } (\pi_{1*}(\mu), \pi_{2*}(\mu))$$

---


$$\overline{w}_i = w_i / \sum_{i=1}^N w_i$$

# Delayed Sampling semantics

$$\llbracket op(e) \rrbracket_{\gamma, g, w} = \\ \text{let } (e', g_e, w_e) = \llbracket e \rrbracket_{\gamma, g, w} \text{ in } (\text{app}(op, e'), g_e, w_e)$$

$$\llbracket \text{if } e \text{ then } e_1 \text{ else } e_2 \rrbracket_{\gamma, g, w} = \\ \text{let } e', g_e, w_e = \llbracket e \rrbracket_{\gamma, g, w} \text{ in} \\ \text{let } v, g_v = \text{value}(e', g_e) \text{ in} \\ \text{if } v \text{ then } \llbracket e_1 \rrbracket_{\gamma, g_v, w_e} \text{ else } \llbracket e_2 \rrbracket_{\gamma, g_v, w_e}$$

$$\llbracket \text{sample}(e) \rrbracket_{\gamma, g, w} = \\ \text{let } \mu, g_e, w' = \llbracket e \rrbracket_{\gamma, g, w} \text{ in} \\ \text{let } X, g' = \text{assume}(\mu, g_e) \text{ in } (X, g', w')$$

$$\llbracket \text{observe}(e_1, e_2) \rrbracket_{\gamma, g, w} = \\ \text{let } \mu, g_1, w_1 = \llbracket e_1 \rrbracket_{\gamma, g, w} \text{ in let } X, g_x = \text{assume}(\mu, g_1) \text{ in} \\ \text{let } e'_2, g_2, w_2 = \llbracket e_2 \rrbracket_{\gamma, g_x, w_1} \text{ in let } v, g_v = \text{value}(e'_2, g_2) \text{ in} \\ \text{let } g' = \text{observe}(X, v, g_v) \text{ in } (( ), g', w_2 * \mu_{\text{pdf}}(v))$$

$$\llbracket \text{infer}(\text{fun } s \rightarrow e, \sigma) \rrbracket_{\gamma} = \\ \text{let } \mu = \lambda U. \sum_{i=1}^N \text{let } s_i, g_i = \text{draw}(\llbracket \sigma \rrbracket_{\gamma}) \text{ in} \\ \text{let } (e_i, s'_i), w_i, g'_i = \llbracket \text{fun } s \rightarrow e \rrbracket_{\gamma, 1, g_i}(s_i) \text{ in} \\ \text{let } d_i = \text{distribution}(e_i, g'_i) \text{ in} \\ \overline{w}_i * d_i(\pi_1(U)) * \delta_{s'_i, g'_i}(\pi_2(U)) \\ \text{in } (\pi_{1*}(\mu), \pi_{2*}(\mu))$$

Manipulate symbolic terms (e.g.,  $\text{app}(+, \dots)$ )

---


$$\overline{w}_i = w_i / \sum_{i=1}^N w_i$$

# Delayed Sampling semantics

$$\llbracket op(e) \rrbracket_{\gamma, g, w} =$$

$$\text{let } (e', g_e, w_e) = \llbracket e \rrbracket_{\gamma, g, w} \text{ in } (\text{app}(op, e'), g_e, w_e)$$

$$\llbracket \text{if } e \text{ then } e_1 \text{ else } e_2 \rrbracket_{\gamma, g, w} =$$

$$\text{let } e', g_e, w_e = \llbracket e \rrbracket_{\gamma, g, w} \text{ in}$$

$$\text{let } v, g_v = \text{value}(e', g_e) \text{ in}$$

$$\text{if } v \text{ then } \llbracket e_1 \rrbracket_{\gamma, g_v, w_e} \text{ else } \llbracket e_2 \rrbracket_{\gamma, g_v, w_e}$$

$$\llbracket \text{sample}(e) \rrbracket_{\gamma, g, w} =$$

$$\text{let } \mu, g_e, w' = \llbracket e \rrbracket_{\gamma, g, w} \text{ in}$$

$$\text{let } X, g' = \text{assume}(\mu, g_e) \text{ in } (X, g', w')$$

$$\llbracket \text{observe}(e_1, e_2) \rrbracket_{\gamma, g, w} =$$

$$\text{let } \mu, g_1, w_1 = \llbracket e_1 \rrbracket_{\gamma, g, w} \text{ in let } X, g_x = \text{assume}(\mu, g_1) \text{ in}$$

$$\text{let } e'_2, g_2, w_2 = \llbracket e_2 \rrbracket_{\gamma, g_x, w_1} \text{ in let } v, g_v = \text{value}(e'_2, g_2) \text{ in}$$

$$\text{let } g' = \text{observe}(X, v, g_v) \text{ in } ((), g', w_2 * \mu_{\text{pdf}}(v))$$

$$\llbracket \text{infer}(\text{fun } s \rightarrow e, \sigma) \rrbracket_{\gamma} =$$

$$\text{let } \mu = \lambda U. \sum_{i=1}^N \text{let } s_i, g_i = \text{draw}(\llbracket \sigma \rrbracket_{\gamma}) \text{ in}$$

$$\text{let } (e_i, s'_i), w_i, g'_i = \llbracket \text{fun } s \rightarrow e \rrbracket_{\gamma, 1, g_i}(s_i) \text{ in}$$

$$\text{let } d_i = \text{distribution}(e_i, g'_i) \text{ in}$$

$$\overline{w}_i * d_i(\pi_1(U)) * \delta_{s'_i, g'_i}(\pi_2(U))$$

$$\text{in } (\pi_{1*}(\mu), \pi_{2*}(\mu))$$

Manipulate symbolic terms (e.g.,  $\text{app}(+, \dots)$ )

High-level API: graph manipulations  
assume, observe, value



---


$$\overline{w}_i = w_i / \sum_{i=1}^N w_i$$

# Evaluation


## Algorithms comparison

- PF Particle Filtering
- ▼ SDS Streaming Delayed Sampling



# Benchmarks

Baseline: SDS with 1,000 particles



## Conclusions

- SDS is always faster to match accuracy
- Reduction in particle count outweighs symbolic overhead
- SDS can be exact (1 particle)
- PF is impractical for advanced examples


# Static analysis

---

Reactive Probabilistic Programming


# Bounded memory delayed sampling?

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```



# Bounded memory delayed sampling?


```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```






# Bounded memory delayed sampling?

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```




# Bounded memory delayed sampling?

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```




# Bounded memory delayed sampling?

```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```



# Bounded memory delayed sampling?


```
let proba tracker (y) = x where  
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))  
  and () = observe (gaussian (x, 1), y)
```



Yes!


# Bounded memory delayed sampling?

```
let proba tracker (y) = x, x0 where
  rec init x0 = sample (gaussian (0, 10))
  and x = x0 → sample (gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```




# Bounded memory delayed sampling?

```
let proba tracker (y) = x, x0 where
  rec init x0 = sample (gaussian (0, 10))
  and x = x0 → sample (gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```




# Bounded memory delayed sampling?

```
let proba tracker (y) = x, x0 where
  rec init x0 = sample (gaussian (0, 10))
  and x = x0 → sample (gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```



# Bounded memory delayed sampling?


```
let proba tracker (y) = x, x0 where
  rec init x0 = sample (gaussian (0, 10))
  and x = x0 → sample (gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```






# Bounded memory delayed sampling?

```
let proba tracker (y) = x, x0 where
  rec init x0 = sample (gaussian (0, 10))
  and x = x0 → sample (gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```



# Bounded memory delayed sampling?

```
let proba tracker (y) = x, x0 where
  rec init x0 = sample (gaussian (0, 10))
  and x = x0 → sample (gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```




No!

# Bounded memory delayed sampling?

```
let proba tracker (y) = x, x0 where
  rec init x0 = sample (gaussian (0, 10))
  and x = x0 → sample (gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

Can we determine if a given program will run in bounded memory?



No!

# Trace: abstract execution

```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

trace	state	time
$x_0 \leftarrow \perp ::$	$X = x_0$	$t = 0$
$y_0 \leftarrow x_0 ::$		
observe $y_0 ::$		
$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$y_1 \leftarrow x_1 ::$		
observe $y_1 ::$		
$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
$y_2 \leftarrow x_2 ::$		
...		

# Trace: abstract execution

```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

	trace	state	time
random variable →	$x_0 \leftarrow \perp ::$	$X = x_0$	$t = 0$
	$y_0 \leftarrow x_0 ::$		
	observe $y_0 ::$		
	<hr/>		
	$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
	$y_1 \leftarrow x_1 ::$		
	observe $y_1 ::$		
	<hr/>		
	$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
	$y_2 \leftarrow x_2 ::$		
	...		

# Trace: abstract execution

```
let proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

	trace	state	time
random variable →	$x_0 \leftarrow \perp ::$ $y_0 \leftarrow x_0 ::$	$X = x_0$	$t = 0$
observation →	$\text{observe } y_0 ::$		
	$x_1 \leftarrow x_0 ::$ $y_1 \leftarrow x_1 ::$ $\text{observe } y_1 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
	$x_2 \leftarrow x_1 ::$ $y_2 \leftarrow x_2 ::$ ...	$x = x_2, \text{ pre } x = x_1$	$t = 2$

# Static analysis for delayed sampling

## Semantic properties

### m-consumed property

Chains of variables before an observe are bounded

### unseparated paths property

Chains of variables referenced in the state are bounded

Theorem: *The program satisfies these two properties iff it executes in bounded memory*

# Static analysis for delayed sampling

## Semantic properties

### **m-consumed property**

Chains of variables before an observe are bounded

### **unseparated paths property**

Chains of variables referenced in the state are bounded

Theorem: *The program satisfies these two properties iff it executes in bounded memory*

---

## Static analysis

Track variables introduced but not used yet

Track maximal path between pairs of variable in the state

Theorem: *Any program that passes the analysis executes in bounded memory*



# *m*-consumed property

```
proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

trace	state	time
$x_0 \leftarrow \perp ::$	$X = x_0$	$t = 0$
$y_0 \leftarrow x_0 ::$		
observe $y_0 ::$		
$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$y_1 \leftarrow x_1 ::$		
observe $y_1 ::$		
$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
$y_2 \leftarrow x_2 ::$		
...		

# *m*-consumed property

```
proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gauss
  and () = observe (gaussian (x, 1), y)
```

Chains of variables before an observe are bounded

trace	state	time
$x_0 \leftarrow \perp ::$	$x = x_0$	$t = 0$
$y_0 \leftarrow x_0 ::$		
observe $y_0 ::$		
$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$y_1 \leftarrow x_1 ::$		
observe $y_1 ::$		
$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
$y_2 \leftarrow x_2 ::$		
...		

# *m*-consumed property

```
proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gauss
  and () = observe (gaussian (x, 1), y)
```

Chains of variables before an observe are bounded

$y_0$  is 0-consumed →

trace	state	time
$x_0 \leftarrow \perp ::$	$x = x_0$	$t = 0$
$y_0 \leftarrow x_0 ::$		
observe $y_0 ::$		
$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$y_1 \leftarrow x_1 ::$		
observe $y_1 ::$		
$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
$y_2 \leftarrow x_2 ::$		
...		

# *m*-consumed property

```
proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gauss
  and () = observe (gaussian (x, 1), y)
```

Chains of variables before an observe are bounded

	trace	state	time
	$x_0 \leftarrow \perp ::$	$x = x_0$	$t = 0$
$x_0$ is 1-consumed →	$y_0 \leftarrow x_0 ::$		
$y_0$ is 0-consumed →	observe $y_0 ::$		
	$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
	$y_1 \leftarrow x_1 ::$		
	observe $y_1 ::$		
	$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
	$y_2 \leftarrow x_2 ::$		
	...		

# *m*-consumed property

```
proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gauss
  and () = observe (gaussian (x, 1), y)
```

Chains of variables before an observe are bounded

	trace	state	time
	$x_0 \leftarrow \perp ::$	$x = x_0$	$t = 0$
$x_0$ is 1-consumed →	$y_0 \leftarrow x_0 ::$		
$y_0$ is 0-consumed →	observe $y_0 ::$		
	$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$x_1$ is 1-consumed →	$y_1 \leftarrow x_1 ::$		
$y_1$ is 0-consumed →	observe $y_1 ::$		
	$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
	$y_2 \leftarrow x_2 ::$		
	...		

# *m*-consumed property

```
proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gauss
  and () = observe (gaussian (x, 1), y)
```

Chains of variables before an observe are bounded

	trace	state	time
	$x_0 \leftarrow \perp ::$	$x = x_0$	$t = 0$
$x_0$ is 1-consumed	→ $y_0 \leftarrow x_0 ::$		
$y_0$ is 0-consumed	→ observe $y_0 ::$		
	$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$x_1$ is 1-consumed	→ $y_1 \leftarrow x_1 ::$		
$y_1$ is 0-consumed	→ observe $y_1 ::$		
	$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
	$y_2 \leftarrow x_2 ::$		
	...		

Yes!

# Unseparated paths property

```
proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

trace	state	time
$x_0 \leftarrow \perp ::$	$X = x_0$	$t = 0$
$y_0 \leftarrow x_0 ::$		
observe $y_0 ::$		
$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$y_1 \leftarrow x_1 ::$		
observe $y_1 ::$		
$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
$y_2 \leftarrow x_2 ::$		
...		

# Unseparated paths property

```
proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gauss
  and () = observe (gaussian (x, 1), y)
```

Chains of variables referenced in the state are bounded

trace	state	time
$x_0 \leftarrow \perp ::$ $y_0 \leftarrow x_0 ::$ observe $y_0 ::$	$X = x_0$	$t = 0$
$x_1 \leftarrow x_0 ::$ $y_1 \leftarrow x_1 ::$ observe $y_1 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$x_2 \leftarrow x_1 ::$ $y_2 \leftarrow x_2 ::$ ...	$x = x_2, \text{ pre } x = x_1$	$t = 2$



# Unseparated paths property

```
proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gauss
  and () = observe (gaussian (x, 1), y)
```

Chains of variables referenced in the state are bounded

trace	state	time
$x_0 \leftarrow \perp ::$ $y_0 \leftarrow x_0 ::$ observe $y_0 ::$	$x = x_0$	$t = 0$
$x_1 \leftarrow x_0 ::$ $y_1 \leftarrow x_1 ::$ observe $y_1 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$x_2 \leftarrow x_1 ::$ $y_2 \leftarrow x_2 ::$ ...	$x = x_2, \text{ pre } x = x_1$	$t = 2$

# Unseparated paths property

```
proba tracker (y) = x where
  rec x = sample (gaussian (0, 10) → gauss
  and () = observe (gaussian (x, 1), y)
```

Chains of variables referenced in the state are bounded

trace	state	time
$x_0 \leftarrow \perp ::$ $y_0 \leftarrow x_0 ::$ observe $y_0 ::$	$x = x_0$	$t = 0$
$x_1 \leftarrow x_0 ::$ $y_1 \leftarrow x_1 ::$ observe $y_1 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$x_2 \leftarrow x_1 ::$ $y_2 \leftarrow x_2 ::$ ...	$x = x_2, \text{ pre } x = x_1$	$t = 2$

Yes!

# Unseparated paths property

```
proba tracker (y) = x where
  rec init x0 = sample (gaussian (0, 10))
  and x = x0 → sample (gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

Chains of variables referenced in the state are bounded

trace	state	time
$x_0 \leftarrow \perp ::$	$x = x_0$	$t = 0$
$y_0 \leftarrow x_0 ::$	$x0 = x_0$	
$observe\ y_0 ::$		
$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$y_1 \leftarrow x_1 ::$	$x0 = x_0$	
$observe\ y_1 ::$		
$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
$y_2 \leftarrow x_2 ::$	$x0 = x_0$	
...		

# Unseparated paths property

```
proba tracker (y) = x where
  rec init x0 = sample (gaussian (0, 10))
  and x = x0 → sample (gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

Chains of variables referenced in the state are bounded

trace	state	time
$x_0 \leftarrow \perp ::$	$x = x_0$	$t = 0$
$y_0 \leftarrow x_0 ::$	$x_0 = x_0$	
$\text{observe } y_0 ::$		
$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$y_1 \leftarrow x_1 ::$	$x_0 = x_0$	
$\text{observe } y_1 ::$		
$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
$y_2 \leftarrow x_2 ::$	$x_0 = x_0$	
...		

# Unseparated paths property

```
proba tracker (y) = x where
  rec init x0 = sample (gaussian (0, 10))
  and x = x0 → sample (gaussian (pre x, 1))
  and () = observe (gaussian (x, 1), y)
```

Chains of variables referenced in the state are bounded

trace	state	time
$x_0 \leftarrow \perp ::$	$x = x_0$	$t = 0$
$y_0 \leftarrow x_0 ::$	$x_0 = x_0$	
$\text{observe } y_0 ::$		
$x_1 \leftarrow x_0 ::$	$x = x_1, \text{ pre } x = x_0$	$t = 1$
$y_1 \leftarrow x_1 ::$	$x_0 = x_0$	
$\text{observe } y_1 ::$		
$x_2 \leftarrow x_1 ::$	$x = x_2, \text{ pre } x = x_1$	$t = 2$
$y_2 \leftarrow x_2 ::$	$x_0 = x_0$	
...		


No!

# Evaluation

	<i>m</i> -consumed		unsep. paths		bounded mem.	
	output	actual	output	actual	output	actual
Kalman	✓	✓	✓	✓	✓	✓
Kalman Hold-First	✓	✓	✗	✗	✗	✗
Gaussian Random Walk	✗	✗	✓	✓	✗	✗
Robot	✓	✓	✓	✓	✓	✓
Coin	✓	✓	✓	✓	✓	✓
Gaussian-Gaussian	✓	✓	✓	✓	✓	✓
Outlier	✗	✗	✓	✓	✗	✗
MTT	✗	✗	✓	✓	✗	✗
SLAM	✗	✓	✓	✓	✗	✓

# Evaluation

memory is  
probabilistically  
bounded




	<i>m</i> -consumed		unsep. paths		bounded mem.	
	output	actual	output	actual	output	actual
Kalman	✓	✓	✓	✓	✓	✓
Kalman Hold-First	✓	✓	✗	✗	✗	✗
Gaussian Random Walk	✗	✗	✓	✓	✗	✗
Robot	✓	✓	✓	✓	✓	✓
Coin	✓	✓	✓	✓	✓	✓
Gaussian-Gaussian	✓	✓	✓	✓	✓	✓
Outlier	✗	✗	✓	✓	✗	✗
MTT	✗	✗	✓	✓	✗	✗
SLAM	✗	✓	✓	✓	✗	✓




# Evaluation

memory is  
probabilistically  
bounded



memory is  
always bounded



	<i>m</i> -consumed		unsep. paths		bounded mem.	
	output	actual	output	actual	output	actual
Kalman	✓	✓	✓	✓	✓	✓
Kalman Hold-First	✓	✓	✗	✗	✗	✗
Gaussian Random Walk	✗	✗	✓	✓	✗	✗
Robot	✓	✓	✓	✓	✓	✓
Coin	✓	✓	✓	✓	✓	✓
Gaussian-Gaussian	✓	✓	✓	✓	✓	✓
Outlier	✗	✗	✓	✓	✗	✗
MTT	✗	✗	✓	✓	✗	✗
SLAM	✗	✓	✓	✓	✗	✓



# Applications: Control

---

## Reactive Probabilistic Programming


# Cartpole PID

*exec\_simple\_pid*

```
let node controller (angle, (p,i,d)) = action where
  rec e = angle -. (0.0 → pre theta)
  and theta = p *. e +. i *. integr(0., e) +. d *. deriv(e)
  and action = if theta > 0. then Right else Left

let p = 0.0403884114239
let i = 0.041460471604
let d = 0.0705417538223

let node main () = () where
  rec obs, _, stop = cart_pole_gym true (Right → pre action)
  and reset action = controller (obs.pole_angle, (p, i, d))
  every stop
```




# Cartpole learn from angle

*exec\_smart\_pid*

(\* Learn the coefficients that minimize the angle \*)

```
let proba model obs_init = p, (i, d) where
  rec init p = sample (gaussian 0. 0.1)
  and init i = sample (gaussian 0. 0.1)
  and init d = sample (gaussian 0. 0.1)
  and action = controller (obs.pole_angle, (p,i,d))
  and obs = simple_pendulum (obs_init, Right → pre action)
  and () = factor (-10. *. abs_float (obs.pole_angle))

let node main () = () where
  rec obs, _, stop = cart_pole_gym true (Right → pre action)
  and reset action = controller (obs.pole_angle, (p, i, d))
    every stop
  and pid_dist = infer 1000 model obs
  and p, (i, d) = draw pid_dist
```




# Cartpole learn from example

*exec\_smart\_pid*

```
(* Favor action similar to example *)
let proba model (obs, ctrl_action) = p, (i, d) where
  rec init p = sample (gaussian 0. 0.1)
  and init i = sample (gaussian 0. 0.1)
  and init d = sample (gaussian 0. 0.1)
  and action = controller (obs.pole_angle, (p,i,d))
  and () = factor (if action = ctrl_action then 0. else -0.2)


let node main () = () where
  rec obs, _, stop = cart_pole_gym true (Right → pre action)
  and reset action = controller (obs.pole_angle, (p, i, d))
  every stop
  and pid_dist = infer 1000 model obs
  and p, (i, d) = draw pid_dist
```



# Cartpole learn from example

*exec\_smart\_pid*

```
(* Favor action similar to example *)  
let proba model (obs, ctrl_action) = p, (i, d) where  
  rec init p = sample (gaussian 0. 0.1)  
  and init i = sample (gaussian 0. 0.1)  
  and init d = sample (gaussian 0. 0.1)  
  and action = controller (obs.pole_angle, (p,i,d))  
  and () = factor (if action = ctrl_action then 0. else -0.2)  
  
let node main fix = () where  
  rec obs, _, stop = cart_pole_gym true (Right → pre action)  
  and reset action = controller (obs.pole_angle, (p, i, d))  
  every stop  
  and automaton  
    | Learn → do pid_dist = infer 1000 model obs  
              and p, (i, d) = draw pid_dist  
              until fix then Fix  
    | Fix → do until (not fix) then Learn  
end
```



# References

## Reactive probabilistic programming

Guillaume Baudart, Louis Mandel, Eric Atkinson, Benjamin Sherman, Marc Pouzet, Michael Carbin  
PLDI 2020

## Delayed Sampling and Automatic Rao-Blackwellization of Probabilistic Programs.

Lawrence Murray, Daniel Lundén, Jan Kudlicka, David Broman, Thomas B. Schön  
AISTATS 2017

## A Co-iterative Characterization of Synchronous Stream Functions

Paul Caspi and Marc Pouzet  
CMCS 1998

## Statically Bounded-Memory Delayed Sampling for Probabilistic Streams

Eric Atkinson, Guillaume Baudart, Louis Mandel, Charles Yuan, Michael Carbin  
OOPLSA 2021