

MySQL 8.0 Command Line Client

mysql> show tables;

Tables_in_vfl
auth
authd
crop
dist1
farmer
taluka

6 rows in set (0.00 sec)

mysql> desc auth;

Field	Type	Null	Key	Default	Extra
username	varchar(20)	NO	PRI	NULL	
password	varchar(20)	YES		NULL	
talukno	int	YES	MUL	NULL	
email	varchar(30)	YES		NULL	

4 rows in set (0.00 sec)

mysql> select * from auth;

username	password	talukno	email
sharanu	sharanu@123	1	NULL
shivakumar	shivakumar@123	2	akshathamshetty2@gmail.com
syed	syed@123	3	NULL

3 rows in set (0.00 sec)

mysql>

MySQL 8.0 Command Line Client

mysql> show tables;

Tables_in_vfl
auth
authd
crop
dist1
farmer
taluka

6 rows in set (0.00 sec)

mysql> desc authd;

Field	Type	Null	Key	Default	Extra
username	varchar(20)	NO	PRI	NULL	
password	varchar(20)	YES		NULL	
email	varchar(30)	YES		NULL	

3 rows in set (0.00 sec)

mysql> select * from authd;

username	password	email
suhas	vvvv	mpshetty12@gmail.com

1 row in set (0.03 sec)

mysql>

MySQL 8.0 Command Line Client

```
mysql> show tables;
```

Tables_in_vfl
auth
authd
crop
dist1
farmer
taluka

6 rows in set (0.00 sec)

```
mysql> desc crop;
```

Field	Type	Null	Key	Default	Extra
produce	int	YES		NULL	
requirement	int	YES		NULL	
cropno	int	YES	MUL	NULL	
talukno	int	YES	MUL	NULL	

4 rows in set (0.00 sec)

```
mysql> select * from crop;
```

produce	requirement	cropno	talukno
1000	200	1	1
100	40	2	1
100	60	3	1
40	60	3	2
200	100	4	2
250	100	5	3
0	60	6	3

7 rows in set (0.03 sec)

```
mysql>
```

MySQL 8.0 Command Line Client

mysql> show tables;

Tables_in_vfl
auth
authd
crop
dist1
farmer
taluka

6 rows in set (0.00 sec)

mysql> desc dist1;

Field	Type	Null	Key	Default	Extra
cropid	int	NO	PRI	NULL	
cropname	varchar(20)	YES		NULL	
cropcost	int	YES		NULL	

3 rows in set (0.00 sec)

mysql> select * from dist1;

cropid	cropname	cropcost
1	tomato	20
2	potato	40
3	chilli	30
4	onion	100
5	kottumbari	85
6	raddish	80

6 rows in set (0.02 sec)

mysql> █


```
mysql> show tables;
```

Tables_in_vfl
auth
authd
crop
dist1
farmer
taluka

6 rows in set (0.00 sec)

```
mysql> desc farmer;
```

Field	Type	Null	Key	Default	Extra
aadharno	int	NO	PRI	NULL	
farmername	varchar(20)	YES		NULL	
balance	int	YES		NULL	
paid	int	YES		NULL	
talukno	int	YES	MUL	NULL	
accountno	int	YES		NULL	

6 rows in set (0.00 sec)

```
mysql> select * from farmer;
```

aadharno	farmername	balance	paid	talukno	accountno
1	vighneeee	125	540	1	1000777
2	veeresh	90	2170	1	10001233
3	vighnesh	240	1500	2	10001234
4	raja	200	500	3	10001235

4 rows in set (0.04 sec)

```
mysql>
```


mysql> show tables;

mysql> show tables;

Tables_in_vfl
auth
authd
crop
dist1
farmer
taluka

6 rows in set (0.00 sec)

mysql> desc taluka;

Field	Type	Null	Key	Default	Extra
talukid	int	NO	PRI	NULL	
talukname	varchar(20)	YES		NULL	
talukfund	int	YES		NULL	

3 rows in set (0.00 sec)

mysql> select * from taluka;

talukid	talukname	talukfund
1	Hunsur	15000
2	piriyapattan	20000
3	saragur	24000

3 rows in set (0.03 sec)

mysql> ■