

Mismeasure For Measure


PART 1 OF N

Mateusz Pusz
June 28, 2023




The Mars Climate Orbiter

- **Robotic space probe** launched by NASA on December 11, 1998




The Mars Climate Orbiter


- **Robotic space probe** launched by NASA on December 11, 1998
- Project costs: **\$327.6 million**
 - spacecraft development: \$193.1 million
 - launching it: \$91.7 million
 - mission operations: \$42.8 million




The Mars Climate Orbiter

- **Robotic space probe** launched by NASA on December 11, 1998
- Project costs: **\$327.6 million**
 - spacecraft development: \$193.1 million
 - launching it: \$91.7 million
 - mission operations: \$42.8 million
- Mars Climate Orbiter began the planned *orbital insertion maneuver* on September 23, 1999 at 09:00:46 UTC







The Mars Climate Orbiter

- Space probe went **out of radio contact** when it passed behind Mars at 09:04:52 UTC
 - *49 seconds* earlier than expected
- Communication was never reestablished
- The **spacecraft disintegrated** due to atmospheric stresses or **re-entered heliocentric space** after leaving Mars' atmosphere

What went wrong?

What went wrong?

- The **primary cause** of this discrepancy was that
 - one piece of ground software supplied by Lockheed Martin produced results in a *United States customary unit*, **contrary to its Software Interface Specification** (SIS)
 - second system, supplied by NASA, expected those results to be in *SI units*, **in accordance** with the SIS

What went wrong?

- The **primary cause** of this discrepancy was that
 - one piece of ground software supplied by Lockheed Martin produced results in a *United States customary unit*, **contrary to its Software Interface Specification** (SIS)
 - second system, supplied by NASA, expected those results to be in *SI units*, **in accordance** with the SIS
- Specifically
 - software that calculated the *total impulse produced by thruster firings* calculated results in **pound-force seconds**
 - the trajectory calculation software then used these results to *update the predicted position* of the spacecraft and expected it to be in **newton seconds**
 - the quantities of those two units should use a **conversion factor of 4.45** if done properly



Taking the Responsibility

- NASA does not place the responsibility on Lockheed for the mission loss
- Various officials at NASA have stated that NASA itself was at fault for failing to make the appropriate checks and tests that would have caught the discrepancy

Taking the Responsibility

- **NASA does not place the responsibility on Lockheed** for the mission loss
- Various officials at NASA have stated that **NASA itself was at fault for failing to make the appropriate checks and tests** that would have caught the discrepancy
- The **discrepancy between calculated and measured position**, resulting in the discrepancy between desired and actual orbit insertion altitude, **had been noticed earlier by at least two navigators**
 - their **concerns were dismissed because** they *"did not follow the rules about filling out form to document their concerns"*

mp-units

- A Physical Quantities and Units library for C++
- MIT License
- Hosted on Github at [mpusz/mp-units](https://github.com/mpusz/mp-units)
- Extensive documentation at mpusz.github.io/mp-units
- Available in the Compiler Explorer (Thank You Matt Godbolt!!!)

How to prevent such errors with `mp-units`? (<https://godbolt.org/z/TnjbjPsYa>)

```
namespace lockheed_martin {
    struct thruster {
        static quantity<usc::pound_force * si::second> get_firing_total_impulse()
        {
            auto q = 42 * (lbf * s);
            std::cout << "Sending total impulse of: " << q << '\n';
            return q;
        }
    };
} // namespace lockheed_martin
```

How to prevent such errors with `mp-units`? (<https://godbolt.org/z/TnjbjPsYa>)

```
namespace lockheed_martin {
    struct thruster {
        static quantity<usc::pound_force * si::second> get_firing_total_impulse()
        {
            auto q = 42 * (lbf * s);
            std::cout << "Sending total impulse of: " << q << '\n';
            return q;
        }
    };
} // namespace lockheed_martin
```

```
namespace nasa {
    struct trajectory {
        static void update_position(quantity<si::newton * si::second> q)
        {
            std::cout << "Received total impulse of: " << q << '\n';
        }
    };
} // namespace nasa
```


How to prevent such errors with `mp-units`? (<https://godbolt.org/z/TnjbjPsYa>)

```
namespace lockheed_martin {
    struct thruster {
        static quantity<usc::pound_force * si::second> get_firing_total_impulse()
        {
            auto q = 42 * (lbf * s);
            std::cout << "Sending total impulse of: " << q << '\n';
            return q;
        }
    };
} // namespace lockheed_martin
```

```
namespace nasa {
    struct trajectory {
        static void update_position(quantity<si::newton * si::second> q)
        {
            std::cout << "Received total impulse of: " << q << '\n';
        }
    };
} // namespace nasa
```

```
auto q = lockheed_martin::thruster::get_firing_total_impulse();
nasa::trajectory::update_position(q);
```

How to prevent such errors with `mp-units`? (<https://godbolt.org/z/TnjbjPsYa>)

```
namespace lockheed_martin {
    struct thruster {
        static quantity<usc::pound_force * si::second> get_firing_total_impulse()
        {
            auto q = 42 * (lbf * s);
            std::cout << "Sending total impulse of: " << q << '\n';
            return q;
        }
    };
} // namespace lockheed_martin
```

```
namespace nasa {
    struct trajectory {
        static void update_position(quantity<si::newton * si::second> q)
        {
            std::cout << "Received total impulse of: " << q << '\n';
        }
    };
} // namespace nasa
```

```
auto q = lockheed_martin::thruster::get_firing_total_impulse();
nasa::trajectory::update_position(q);
```

Sending total impulse of: 42 lbf s
Received total impulse of: 186.825 N s


How to prevent such errors with `mp-units`? (<https://godbolt.org/z/xzYfEdrTK>)

```
namespace lockheed_martin {
    struct thruster {
        static quantity<si::newton * si::second> get_firing_total_impulse()
        {
            auto q = 42 * (lbf * s);
            std::cout << "Sending total impulse of: " << q << '\n';
            return q;
        }
    };
} // namespace lockheed_martin
```

```
namespace nasa {
    struct trajectory {
        static void update_position(quantity<si::newton * si::second> q)
        {
            std::cout << "Received total impulse of: " << q << '\n';
        }
    };
} // namespace nasa
```

```
auto q = lockheed_martin::thruster::get_firing_total_impulse();
nasa::trajectory::update_position(q);
```

Sending total impulse of: 42 lbf s
Received total impulse of: 186.825 N s

The background is a solid yellow color. It is decorated with several black geometric shapes, primarily parallelograms and triangles, arranged in a pattern that suggests a 3D perspective or a stylized architectural design. These shapes are positioned around the edges and corners of the frame.

CAUTION
Programming
is addictive
(and too much fun)