

产品名称: *


图纸编号: *









Size: *

Rev: *

Date: *

Sheet: *





产品名称: *

图纸编号: *

Size: *

Rev: *

Date: *

Sheet: *

Comment	Description	Designator	Footprint	LibRef	Quantity
NC	无极性电容	C1, C3, C31, C32, C33, C34	CAPC_0603_2	C	6
20pF	无极性电容	C13, C14	CAPC_0603_2	C	2
100nF	无极性电容	C14, C15, C17, C17, C18, C19, C20, C21, C22, C23, C24, C24, C25, C25, C27, C28, C29, C30	CAPC_0603_2	C	18
10uF/6.3v	无极性电容	C15, C18, C23, C26, C26, C28, C29	CAPC_0603_2	C	7
47uF/25V		C27	CAPE_D	C	1
LED绿	Typical RED, GREEN, YELLOW, AMBER GaAs LED	D1, D2, D3, D4, D5, D6, D7, D8, D9, D10	LED_0805_G	LED2	10
SMA-KE	SMB Straight Connector	J1, J2, J3	SMARA	SMB	3
K2-1102SP-E4SC-04		K1, K2, K3, K4	SW_PB_SMD_6X6	KEY_M	4
BUTTON		K5	KFT DIP-8X8	BUTTON	1
MPL2012S1ROMHT	Inductor footprint4026	L1, L2, L3	Inductor_0805	Inductor	3
DEBUG	Header, 5-Pin	P1	Header 2.54X5	Header 5	1
WJ128V-5.0-2P	Header, 2-Pin, Right Angle	P2, P5	KF128_2P	Header 2H	2
USB-B		P3	USB_Micro_DIP41	USB5	1
2.54*3	Header, 3-Pin, Right Angle	P4	Header 2.54X3	Header 3H	1
Header 2H	Header, 2-Pin, Right Angle	P6, P7, P8, P9	Header 2.54X2	Header 2H	4
Header 6	Header, 6-Pin	P10	Header 2.54X6	Header 6	1
0R	Resistor	R1, R56, R57	RESC_0603_2	R	3
22R	Resistor, Resistor, Resistor, Resistor, [NoValue], Resistor, [NoValue], Resistor, Resistor, Resistor, Resistor, [NoValue], Resistor, Resistor, Resistor, Resistor, Resistor, Resistor, Resistor, Resistor, Resistor, Resistor, Resistor	R2, R3, R4, R5, R19, R20, R20, R21, R22, R23, R24, R32, R34, R35, R35, R36, R36, R37, R37, R38, R39, R40, R41, R42, R43, R44, R52, R53, R54, R55	RESC_0603_2	R	30
10k	Resistor, Resistor, Resistor, [NoValue], [NoValue], [NoValue], Resistor	R19, R21, R23, R26, R30, R31, R45	RESC_0603_2	R	7
120R	Resistor	R22	RESC_0603_2	R	1
4K7	Resistor	R24, R27, R29	RESC_0603_2	R	3
1M		R25	RESC_0603_2	R	1
100R	Resistor	R33, R34	RESC_0603_2	R	2
1k		R38, R39, R40, R52, R53, R54, R55, R56, R59, R61	RESC_0603_2	R	10
ET001、ET003		U2, U7	ET001	SX_1278/1268/1280	2
STM32F103R8T6	ARM Cortex-M3 32-bit MCU, 64 KB Flash, 20 KB Internal RAM, 51 I/Os, 64-pin LQFP, -40 to 85 degC, Tray	U3	STM-LQFP64_N	STM32F103R8T6	1
TP8485E-SR		U4	SOIC_8	SP485	1
AMS1117-3.3		U5	SOT223_3	AMS1117	1
ET003_SX1268/1280MCU		U6	ET001/3_MCU	ET001/3_MCU	1
tmp75AIDR		U6	SOIC_8	tmp75AIDR	1
12MHz		Y1	xt3225	XTAL-WY	1