



My Basic Network Scan

Report generated by Tenable Nessus™

Thu, 07 Aug 2025 13:19:20 IST

TABLE OF CONTENTS

Vulnerabilities by Host

- 192.168.220.6.....4

Nessus Essentials

Vulnerabilities by Host

192.168.220.6

2

CRITICAL

3

HIGH

6

MEDIUM

0

LOW

72

INFO

Host Information

IP: 192.168.220.6
MAC Address: 08:00:27:36:62:0B 02:42:E0:C3:1C:57
OS: Linux Kernel 6.12.33+kali-amd64

Vulnerabilities

190856 - Node.js 18.x < 18.19.1 / 20.x < 20.11.1 / 21.x < 21.6.2 Multiple Vulnerabilities (Wednesday February 14 2024 Security Releases).

Synopsis

Node.js - JavaScript run-time environment is affected by multiple vulnerabilities.

Description

The version of Node.js installed on the remote host is prior to 18.19.1, 20.11.1, 21.6.2. It is, therefore, affected by multiple vulnerabilities as referenced in the Wednesday February 14 2024 Security Releases advisory.

- On Linux, Node.js ignores certain environment variables if those may have been set by an unprivileged user while the process is running with elevated privileges with the only exception of CAP_NET_BIND_SERVICE. Due to a bug in the implementation of this exception, Node.js incorrectly applies this exception even when certain other capabilities have been set. This allows unprivileged users to inject code that inherits the process's elevated privileges. Impacts: Thank you, to Tobias Niesen for reporting this vulnerability and for fixing it. (CVE-2024-21892)
- A vulnerability in Node.js HTTP servers allows an attacker to send a specially crafted HTTP request with chunked encoding, leading to resource exhaustion and denial of service (DoS). The server reads an unbounded number of bytes from a single connection, exploiting the lack of limitations on chunk extension bytes. The issue can cause CPU and network bandwidth exhaustion, bypassing standard safeguards like timeouts and body size limits. Impacts: Thank you, to Bartek Nowotarski for reporting this vulnerability and thank you Paolo Insogna for fixing it. (CVE-2024-22019)
- The permission model protects itself against path traversal attacks by calling path.resolve() on any paths given by the user. If the path is to be treated as a Buffer, the implementation uses Buffer.from() to obtain a Buffer from the result of path.resolve(). By monkey-patching Buffer internals, namely, Buffer.prototype.utf8Write, the application can modify the result of path.resolve(), which leads to a path traversal vulnerability. Impacts: Please note that at the time this CVE was issued, the permission model is an experimental feature of Node.js. Thank you, to Tobias Niesen for reporting this vulnerability and for fixing it. (CVE-2024-21896)

- `setuid()` does not affect `libuv`'s internal `io_uring` operations if initialized before the call to `setuid()`.

This allows the process to perform privileged operations despite presumably having dropped such privileges through a call to `setuid()`. Impacts: Thank you, to valette for reporting this vulnerability and thank you Tobias Niesen for fixing it. (CVE-2024-22017)

- A vulnerability in the `privateDecrypt()` API of the `crypto` library, allowed a covert timing side-channel during PKCS#1 v1.5 padding error handling. The vulnerability revealed significant timing differences in decryption for valid and invalid ciphertexts. This poses a serious threat as attackers could remotely exploit the vulnerability to decrypt captured RSA ciphertexts or forge signatures, especially in scenarios involving API endpoints processing JSON Web Encryption messages. Impacts: Thank you, to hkario for reporting this vulnerability and thank you Michael Dawson for fixing it. (CVE-2023-46809)

- Node.js depends on multiple built-in utility functions to normalize paths provided to `node:fs` functions, which can be overwritten with user-defined implementations leading to filesystem permission model bypass through path traversal attack. Impacts: Please note that at the time this CVE was issued, the permission model is an experimental feature of Node.js. Thank you, to xion for reporting this vulnerability and thank you Rafael Gonzaga for fixing it. (CVE-2024-21891)

- The Node.js Permission Model does not clarify in the documentation that wildcards should be only used as the last character of a file path. For example: `--allow-fs-read=/home/node/.ssh/*.pub` will ignore `pub` and give access to everything after `.ssh/`. Impacts: Please note that at the time this CVE was issued, the permission model is an experimental feature of Node.js. Thank you, to Tobias Niesen for reporting this vulnerability and thank you Rafael Gonzaga for fixing it. (CVE-2024-21890)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<http://www.nessus.org/u?313add11>

Solution

Upgrade to Node.js version 18.19.1 / 20.11.1 / 21.6.2 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.1041

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.4 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

| | |
|------|--------------------|
| CVE | CVE-2023-46809 |
| CVE | CVE-2024-21890 |
| CVE | CVE-2024-21891 |
| CVE | CVE-2024-21892 |
| CVE | CVE-2024-21896 |
| CVE | CVE-2024-22017 |
| CVE | CVE-2024-22019 |
| XREF | IAVB:2024-B-0016-S |

Plugin Information

Published: 2024/02/21, Modified: 2025/04/03

Plugin Output

tcp/0

```
Path          : /usr/lib/python3/dist-packages/playwright/driver/node
Installed version : 20.11.0
Fixed version  : 20.11.1
```

242134 - Node.js 20.x < 20.19.4 / 22.x < 22.17.1 / 24.x < 24.4.1 Multiple Vulnerabilities (Tuesday, July 15, 2025 Security Releases).

Synopsis

Node.js - JavaScript run-time environment is affected by multiple vulnerabilities.

Description

The version of Node.js installed on the remote host is prior to 20.19.4, 22.17.1, 24.4.1. It is, therefore, affected by multiple vulnerabilities as referenced in the Tuesday, July 15, 2025 Security Releases advisory.

- The V8 release used in Node.js v24.0.0 has changed how string hashes are computed using rapidhash. This implementation re-introduces the HashDoS vulnerability as an attacker who can control the strings to be hashed can generate many hash collisions - an attacker can generate collisions even without knowing the hash-seed. While the V8 team does not classify this as a security vulnerability, the Node.js project considers it one due to its potential impact in real-world scenarios. Impact: Thank you, to sharp_edged for reporting this vulnerability and thank you targos for fixing it. (CVE-2025-27209)

- An incomplete fix has been identified for CVE-2025-23084 in Node.js, specifically affecting Windows device names like CON, PRN, and AUX. This vulnerability affects Windows users of path.join API. Impact: Thank you, to oblivionsage for reporting this vulnerability and thank you RafaelGSS for fixing it. (CVE-2025-27210)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://nodejs.org/en/blog/vulnerability/july-2025-security-releases/>

Solution

Upgrade to Node.js version 20.19.4 / 22.17.1 / 24.4.1 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.1 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N)

CVSS v3.0 Temporal Score

7.9 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.0041

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

| | |
|------|------------------|
| CVE | CVE-2025-27209 |
| CVE | CVE-2025-27210 |
| XREF | IAVB:2025-B-0120 |

Plugin Information

Published: 2025/07/15, Modified: 2025/07/18

Plugin Output

tcp/0

```
Path          : /usr/lib/python3/dist-packages/playwright/driver/node
Installed version : 20.11.0
Fixed version  : 20.19.4
```


192945 - Node.js 18.x < 18.20.1 / 20.x < 20.12.1 / 21.x < 21.7.2 Multiple Vulnerabilities (Wednesday, April 3, 2024 Security Releases).

Synopsis

Node.js - JavaScript run-time environment is affected by multiple vulnerabilities.

Description

The version of Node.js installed on the remote host is prior to 18.20.1, 20.12.1, 21.7.2. It is, therefore, affected by multiple vulnerabilities as referenced in the Wednesday, April 3, 2024 Security Releases advisory.

- An attacker can make the Node.js HTTP/2 server completely unavailable by sending a small amount of HTTP/2 frames packets with a few HTTP/2 frames inside. It is possible to leave some data in nhttp2 memory after reset when headers with HTTP/2 CONTINUATION frame are sent to the server and then a TCP connection is abruptly closed by the client triggering the Http2Session destructor while header frames are still being processed (and stored in memory) causing a race condition. Impacts: Thank you, to bart for reporting this vulnerability and Anna Henningsen for fixing it. (CVE-2024-27983)

- The team has identified a vulnerability in the http server of the most recent version of Node, where malformed headers can lead to HTTP request smuggling. Specifically, if a space is placed before a content-length header, it is not interpreted correctly, enabling attackers to smuggle in a second request within the body of the first. Impacts: Thank you, to bpingel for reporting this vulnerability and Paolo Insogna for fixing it. Summary The Node.js project will release new versions of the 18.x, 20.x, 21.x releases lines on or shortly after, Wednesday, April 3, 2024 in order to address: (CVE-2024-27982)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://nodejs.org/en/blog/vulnerability/april-2024-security-releases/>

Solution

Upgrade to Node.js version 18.20.1 / 20.12.1 / 21.7.2 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

8.2 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:H)

CVSS v3.0 Temporal Score

7.1 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.0

EPSS Score

0.6865

CVSS v2.0 Base Score

5.4 (CVSS2#AV:N/AC:H/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

4.0 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

| | |
|------|--------------------|
| CVE | CVE-2024-27982 |
| CVE | CVE-2024-27983 |
| XREF | IAVB:2024-B-0033-S |

Plugin Information

Published: 2024/04/05, Modified: 2024/04/19

Plugin Output

tcp/0

```
Path          : /usr/lib/python3/dist-packages/playwright/driver/node
Installed version : 20.11.0
Fixed version  : 20.12.1
```

201969 - Node.js 18.x < 18.20.4 / 20.x < 20.15.1 / 22.x < 22.4.1 Multiple Vulnerabilities (Monday, July 8, 2024 Security Releases).

Synopsis

Node.js - JavaScript run-time environment is affected by multiple vulnerabilities.

Description

The version of Node.js installed on the remote host is prior to 18.20.4, 20.15.1, 22.4.1. It is, therefore, affected by multiple vulnerabilities as referenced in the Monday, July 8, 2024 Security Releases advisory.

- The CVE-2024-27980 was identified as an incomplete fix for the BatBadBut vulnerability. This vulnerability arises from improper handling of batch files with all possible extensions on Windows via `child_process.spawn` / `child_process.spawnSync`. A malicious command line argument can inject arbitrary commands and achieve code execution even if the shell option is not enabled. This vulnerability affects all users of `child_process.spawn` and `child_process.spawnSync` on Windows in all active release lines.

Impact: Thank you, to tianst for reporting this vulnerability and thank you RafaelGSS for fixing it.

(CVE-2024-27980)

- A security flaw in Node.js allows a bypass of network import restrictions. By embedding non-network imports in data URLs, an attacker can execute arbitrary code, compromising system security. Verified on various platforms, the vulnerability is mitigated by forbidding data URLs in network imports. Exploiting this flaw can violate network import security, posing a risk to developers and servers. Impact: Thank you, to dittyroma for reporting this vulnerability and thank you RafaelGSS for fixing it. (CVE-2024-22020)

- A vulnerability has been identified in Node.js, affecting users of the experimental permission model when the `--allow-fs-write` flag is used. Node.js Permission Model do not operate on file descriptors, however, operations such as `fs.fchown` or `fs.fchmod` can use a read-only file descriptor to change the owner and permissions of a file. This vulnerability affects all users using the experimental permission model in Node.js 20 and Node.js 22. Please note that at the time this CVE was issued, the permission model is an experimental feature of Node.js. Impact: Thank you, to 4xpl0r3r for reporting this vulnerability and thank you RafaelGSS for fixing it. (CVE-2024-36137)

- A vulnerability has been identified in Node.js, affecting users of the experimental permission model when the `--allow-fs-read` flag is used. This flaw arises from an inadequate permission model that fails to restrict file stats through the `fs.lstat` API. As a result, malicious actors can retrieve stats from files that they do not have explicit read access to. This vulnerability affects all users using the experimental permission model in Node.js 20 and Node.js 22. Please note that at the time this CVE was issued, the permission model is an experimental feature of Node.js. Impact: Thank you, to haxatron1 for reporting this vulnerability and thank you RafaelGSS for fixing it. (CVE-2024-22018)

- The Permission Model assumes that any path starting with two backslashes `\\` has a four-character prefix that can be ignored, which is not always true. This subtle bug leads to vulnerable edge cases. This vulnerability affects Windows users of the Node.js Permission Model in version v22.x and v20.x Impact:

Thank you, to tniessen for reporting this vulnerability and thank you RafaelGSS for fixing it.

(CVE-2024-37372)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://nodejs.org/en/blog/vulnerability/july-2024-security-releases/>

Solution

Upgrade to Node.js version 18.20.4 / 20.15.1 / 22.4.1 or later.

Risk Factor

High

CVSS v3.0 Base Score

8.1 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.1 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.0074

CVSS v2.0 Base Score

9.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:C)

CVSS v2.0 Temporal Score

6.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

| | |
|------|--------------------|
| CVE | CVE-2024-22018 |
| CVE | CVE-2024-22020 |
| CVE | CVE-2024-27980 |
| CVE | CVE-2024-36137 |
| CVE | CVE-2024-37372 |
| XREF | IAVB:2024-B-0039-S |
| XREF | IAVB:2024-B-0083-S |

Plugin Information

Published: 2024/07/08, Modified: 2025/01/24

Plugin Output

tcp/0

```
Path          : /usr/lib/python3/dist-packages/playwright/driver/node
Installed version : 20.11.0
Fixed version  : 20.15.1
```

214404 - Node.js 18.x < 18.20.6 / 20.x < 20.18.2 / 22.x < 22.13.1 / 23.x < 23.6.1 Multiple Vulnerabilities (Tuesday, January 21, 2025 Security Releases).

Synopsis

Node.js - JavaScript run-time environment is affected by multiple vulnerabilities.

Description

The version of Node.js installed on the remote host is prior to 18.20.6, 20.18.2, 22.13.1, 23.6.1. It is, therefore, affected by multiple vulnerabilities as referenced in the Tuesday, January 21, 2025 Security Releases advisory.

- A memory leak could occur when a remote peer abruptly closes the socket without sending a GOAWAY notification. Additionally, if an invalid header was detected by nghttp2, causing the connection to be terminated by the peer, the same leak was triggered. This flaw could lead to increased memory consumption and potential denial of service under certain conditions. This vulnerability affects HTTP/2 Server users on Node.js v18.x, v20.x, v22.x and v23.x. Impact: Thank you, to newtmitch for reporting this vulnerability and thank you RafaelGSS for fixing it. (CVE-2025-23085)

- With the aid of the diagnostics_channel utility, an event can be hooked into whenever a worker thread is created. This is not limited only to workers but also exposes internal workers, where an instance of them can be fetched, and its constructor can be grabbed and reinstated for malicious usage. This vulnerability affects Permission Model users (--permission) on Node.js v20, v22, and v23. Impact: Thank you, to leodog896 for reporting this vulnerability and thank you RafaelGSS for fixing it. (CVE-2025-23083)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<http://www.nessus.org/u?68bc9901>

Solution

Upgrade to Node.js version 18.20.6 / 20.18.2 / 22.13.1 / 23.6.1 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.7 (CVSS:3.0/AV:L/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N)

CVSS v3.0 Temporal Score

6.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.0

EPSS Score

0.0006

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

| | |
|------|--------------------|
| CVE | CVE-2025-23083 |
| CVE | CVE-2025-23085 |
| XREF | IAVB:2025-B-0012-S |

Plugin Information

Published: 2025/01/21, Modified: 2025/08/05

Plugin Output

tcp/0

```
Path          : /usr/lib/python3/dist-packages/playwright/driver/node
Installed version : 20.11.0
Fixed version  : 20.18.2
```

**236766 - Node.js 20.x < 20.19.2 / 22.x < 22.15.1 / 22.x < 22.15.1 / 23.x < 23.11.1 / 24.x < 24.0.2
Multiple Vulnerabilities (Wednesday, May 14, 2025 Security Releases).**

Synopsis

Node.js - JavaScript run-time environment is affected by multiple vulnerabilities.

Description

The version of Node.js installed on the remote host is prior to 20.19.2, 22.15.1, 22.15.1, 23.11.1, 24.0.2. It is, therefore, affected by multiple vulnerabilities as referenced in the Wednesday, May 14, 2025 Security Releases advisory.

- In Node.js, the ReadFileUtf8 internal binding leaks memory due to a corrupted pointer in uv_fs_s.file: a UTF-16 path buffer is allocated but subsequently overwritten when the file descriptor is set. This results in an unrecoverable memory leak on every call. Repeated use can cause unbounded memory growth, leading to a denial of service. Impact: Thank you, to Justin Nietzel for reporting and fixing this vulnerability.

(CVE-2025-23165)

- The C++ method SignTraits::DeriveBits() may incorrectly call ThrowException() based on user-supplied inputs when executing in a background thread, crashing the Node.js process. Such cryptographic operations are commonly applied to untrusted inputs. Thus, this mechanism potentially allows an adversary to remotely crash a Node.js runtime. Impact: Thank you, @panva and @tniessen, for reporting and fixing this vulnerability. (CVE-2025-23166)

- A flaw in Node.js 20's HTTP parser allows improper termination of HTTP/1 headers using \r \rX instead of the required \r \r . This inconsistency enables request smuggling, allowing attackers to bypass proxy- based access controls and submit unauthorized requests. The issue was resolved by upgrading llhttp to version 9, which enforces correct header termination. Impact: Thank you, to kenballus for reporting this vulnerability and thank you RafaelGSS for fixing it. (CVE-2025-23167)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://nodejs.org/en/blog/vulnerability/may-2025-security-releases/>

Solution

Upgrade to Node.js version 20.19.2 / 22.15.1 / 22.15.1 / 23.11.1 / 24.0.2 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.2 (CVSS:3.0/AV:L/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

5.4 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.0004

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

| | |
|------|------------------|
| CVE | CVE-2025-23165 |
| CVE | CVE-2025-23166 |
| CVE | CVE-2025-23167 |
| XREF | IAVB:2025-B-0079 |

Plugin Information

Published: 2025/05/15, Modified: 2025/05/16

Plugin Output

tcp/0

```
Path          : /usr/lib/python3/dist-packages/playwright/driver/node
Installed version : 20.11.0
Fixed version  : 20.19.2
```

240237 - SQLite 3.44.0 < 3.49.1 Multiple Vulnerabilities

Synopsis

The remote host is missing multiple security updates.

Description

The version of SQLite installed on the remote host is 3.44.0 through 3.49.0 before 3.49.1. It is, therefore, affected by multiple vulnerabilities:

- In SQLite 3.44.0 through 3.49.0 before 3.49.1, the `concat_ws()` SQL function can cause memory to be written beyond the end of a malloc-allocated buffer. If the separator argument is attacker-controlled and has a large string (e.g., 2MB or more), an integer overflow occurs in calculating the size of the result buffer, and thus malloc may not allocate enough memory. (CVE-2025-29087)
- An integer overflow can be triggered in SQLite's ``concat_ws()`` function. The resulting, truncated integer is then used to allocate a buffer. When SQLite then writes the resulting string to the buffer, it uses the original, untruncated size and thus a wild Heap Buffer overflow of size ~4GB can be triggered. This can result in arbitrary code execution. (CVE-2025-3277)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://www.sqlite.org/cves.html>

Solution

Upgrade to SQLite 3.49.1 or later.

Risk Factor

High

CVSS v4.0 Base Score

6.9 (CVSS:4.0/AV:N/AC:L/AT:N/PR:N/UI:N/VC:L/VI:L/VA:L/SC:L/SI:L/SA:L)

VPR Score

6.7

EPSS Score

0.0006

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-2025-3277
CVE CVE-2025-29087

Plugin Information

Published: 2025/06/23, Modified: 2025/06/23

Plugin Output

tcp/0

```
Path          : /bin/sqlite3
Installed version : 3.46.1
Fixed version  : 3.49.1
```

tcp/0

```
Path          : /usr/bin/sqlite3
Installed version : 3.46.1
Fixed version  : 3.49.1
```

242325 - SQLite < 3.50.2 Memory Corruption

Synopsis

The remote host is missing multiple security updates.

Description

The version of SQLite installed on the remote host is prior to 3.50.2. It is, therefore, affected by a memory corruption issue. The vulnerability can occur where the number of aggregate terms could exceed the number of columns available, leading to memory corruption.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://www.sqlite.org/cves.html>

Solution

Upgrade to SQLite 3.50.2 or later.

Risk Factor

Medium

CVSS v4.0 Base Score

7.2 (CVSS:4.0/AV:N/AC:H/AT:P/PR:L/UI:N/VC:L/VI:H/VA:L/SC:L/SI:H/SA:L)

CVSS v3.0 Base Score

6.4 (CVSS:3.0/AV:N/AC:H/PR:L/UI:N/S:U/C:L/I:H/A:L)

VPR Score

9.4

EPSS Score

0.0004

CVSS v2.0 Base Score

6.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:C/A:P)

STIG Severity

I

References

CVE CVE-2025-6965
XREF IAVA:2025-A-0529

Plugin Information

Published: 2025/07/18, Modified: 2025/07/18

Plugin Output

tcp/0

```
Path          : /bin/sqlite3
Installed version : 3.46.1
Fixed version  : 3.50.2
```

tcp/0

```
Path          : /usr/bin/sqlite3
Installed version : 3.46.1
Fixed version  : 3.50.2
```

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/8834/www

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : O=Nessus Users United/OU=Nessus Server/L=New York/C=US/ST=NY/CN=kali  
| -Issuer  : O=Nessus Users United/OU=Nessus Certification Authority/L=New York/C=US/ST=NY/CN=Nessus  
            Certification Authority
```

141394 - Apache HTTP Server Installed (Linux)

Synopsis

The remote host has Apache HTTP Server software installed.

Description

Apache HTTP Server is installed on the remote Linux host.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0530

Plugin Information

Published: 2020/10/12, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path          : /usr/sbin/apache2
Version       : 2.4.65
Associated Package : apache2-bin: /usr/sbin/apache2
Managed by OS : True
Running       : no
```

```
Configs found :
- /etc/apache2/apache2.conf
```

```
Loaded modules :
- libphp8.4
- mod_access_compat
- mod_alias
- mod_auth_basic
- mod_authn_core
- mod_authn_file
- mod_authz_core
- mod_authz_host
```


- mod_authz_user
- mod_autoindex
- mod_deflate
- mod_dir
- mod_env
- mod_filter
- mod_mime
- mod_mpm_prefork
- mod_negotiation
- mod_reqtimeout
- mod_setenvif
- mod_status

142640 - Apache HTTP Server Site Enumeration

Synopsis

The remote host is hosting websites using Apache HTTP Server.

Description

Domain names and IP addresses from Apache HTTP Server configuration file were retrieved from the remote host. Apache HTTP Server is a webserver environment written in C. Note: Only Linux- and Unix-based hosts are currently supported by this plugin.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/11/09, Modified: 2025/07/14

Plugin Output

tcp/0

```
Sites and configs present in /usr/sbin/apache2 Apache installation:
- following sites are present in /etc/apache2/apache2.conf Apache config file:
+ - *:80
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2025/07/14

Plugin Output

tcp/0

The remote operating system matched the following CPE :

cpe:/o:linux:linux_kernel -> Linux Kernel

Following application CPE's matched on the remote system :

cpe:/a:apache:http_server:2.4.65 -> Apache Software Foundation Apache HTTP Server
cpe:/a:docker:docker:1 -> Docker
cpe:/a:exiv2:exiv2:0.28.5 -> Exiv2
cpe:/a:exiv2:libexiv2:0.28.5
cpe:/a:gnupg:libgpgcrypt:1.11.0 -> GnuPG Libgpgcrypt
cpe:/a:haxx:curl:8.14.1 -> Haxx Curl
cpe:/a:haxx:libcurl:8.14.1 -> Haxx libcurl
cpe:/a:jmcnamara:sheetextractor:0.6.6 -> John McNamara Spreadsheet::ParseExcel
cpe:/a:linuxfoundation:containerd:1.7.24 -> The Linux Foundation containerd
cpe:/a:nginx:nginx:1.26.3 -> Nginx
cpe:/a:nginx:nginx:1.26.3-3 -> Nginx
cpe:/a:nodejs:node.js:20.11.0 -> Nodejs Node.js

```
cpe:/a:nodejs:node.js:20.19.2 -> Nodejs Node.js
cpe:/a:numpy:numpy:2.2.4 -> NumPy
cpe:/a:openssl:openssl:3.0.16 -> OpenSSL Project OpenSSL
cpe:/a:openssl:openssl:3.5.0 -> OpenSSL Project OpenSSL
cpe:/a:openssl:openssl:3.5.1 -> OpenSSL Project OpenSSL
cpe:/a:openvpn:openvpn:2.6.14 -> OpenVPN
cpe:/a:oracle:openjdk:21.0.8 -> Oracle OpenJDK -
cpe:/a:php:php:8.4.10 -> PHP PHP
cpe:/a:postgresql:postgresql:17.5 -> PostgreSQL
cpe:/a:ruby-lang:ruby:3.3.8 -> Ruby-lang Ruby
cpe:/a:sqlite:sqlite:3.46.1 -> SQLite
cpe:/a:tenable:nessus -> Tenable Nessus
cpe:/a:tenable:nessus:10.9.2 -> Tenable Nessus
cpe:/a:tornadoweb:tornado:6.4.2 -> Tornado Web Server Tornado
cpe:/a:tukaani:xz:5.8.1 -> Tukaani XZ
cpe:/a:vim:vim:9.1 -> Vim
x-cpe:/a:java:jre:21.0.8
x-cpe:/a:libndp:libndp:1.9
```

237414 - Containerd Installed (Linux)

Synopsis

containerd was detected on the remote host.

Description

containerd, a container runtime which can manage the complete container lifecycle of its host system is installed on the target host.

See Also

<https://github.com/containerd/containerd/tree/main>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/05/28, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path          : /usr/bin/containerd
Version       : 1.7.24
Associated Package : containerd 1.7.24
Managed by OS : True
```

182774 - Curl Installed (Linux / Unix)

Synopsis

Curl is installed on the remote Linux / Unix host.

Description

Curl (also known as curl and cURL) is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.
- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.182774' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

See Also

<https://curl.se/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/10/09, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path          : /usr/bin/curl
Version       : 8.14.1
Associated Package : curl 8.14.1-2
Managed by OS : True
```

55472 - Device Hostname

Synopsis

It was possible to determine the remote system hostname.

Description

This plugin reports a device's hostname collected via SSH or WMI.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/06/30, Modified: 2025/07/28

Plugin Output

tcp/0

```
Hostname : kali
kali (hostname command)
```

54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 99
```


159488 - Docker Installed (Linux)

Synopsis

Docker was detected on the remote host.

Description

A container virtualization suite is installed on the remote host.

See Also

<https://www.docker.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/04/04, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path      : /usr/bin/docker
Version   : 1
Build     : 411e817
Managed by OS : True
```

93561 - Docker Service Detection

Synopsis

Docker was detected on the remote host.

Description

The Docker service is running on the remote host. Docker is an open-source project that automates the deployment of applications inside software containers.

See Also

<https://www.docker.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2016/09/16, Modified: 2025/07/28

Plugin Output

tcp/0

```
Client:
Server:
  Version: 0.19.0
```

```
There were no containers detected running on Docker.
```

Synopsis

Detected Dockerfiles on the host.

Description

The host contains Dockerfiles, text files containing instructions to build Docker images.

See Also

<https://docs.docker.com/engine/reference/builder/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/03/29, Modified: 2025/07/28

Plugin Output

tcp/0

```
Dockerfiles found: 3
- /usr/share/metasploit-framework/tools/payloads/ysoserial/Dockerfile
- /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/net-ssh-7.3.0/Dockerfile
- /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/puma-6.6.0/tools/Dockerfile
```

25203 - Enumerate IPv4 Interfaces via SSH

Synopsis

Nessus was able to enumerate the IPv4 interfaces on the remote host.

Description

Nessus was able to enumerate the network interfaces configured with IPv4 addresses by connecting to the remote host via SSH using the supplied credentials.

Solution

Disable any unused IPv4 interfaces.

Risk Factor

None

Plugin Information

Published: 2007/05/11, Modified: 2025/04/28

Plugin Output

tcp/0

The following IPv4 addresses are set on the remote host :

- 172.17.0.1 (on interface docker0)
- 192.168.220.6 (on interface eth0)
- 127.0.0.1 (on interface lo)

25202 - Enumerate IPv6 Interfaces via SSH

Synopsis

Nessus was able to enumerate the IPv6 interfaces on the remote host.

Description

Nessus was able to enumerate the network interfaces configured with IPv6 addresses by connecting to the remote host via SSH using the supplied credentials.

Solution

Disable IPv6 if you are not actually using it. Otherwise, disable any unused IPv6 interfaces.

Risk Factor

None

Plugin Information

Published: 2007/05/11, Modified: 2025/04/28

Plugin Output

tcp/0

The following IPv6 interfaces are set on the remote host :

- fe80::a00:27ff:fe36:620b (on interface eth0)
- ::1 (on interface lo)

33276 - Enumerate MAC Addresses via SSH

Synopsis

Nessus was able to enumerate MAC addresses on the remote host.

Description

Nessus was able to enumerate MAC addresses by connecting to the remote host via SSH with the supplied credentials.

Solution

Disable any unused interfaces.

Risk Factor

None

Plugin Information

Published: 2008/06/30, Modified: 2022/12/20

Plugin Output

tcp/0

The following MAC addresses exist on the remote host :

- 08:00:27:36:62:0b (interface eth0)
- 02:42:e0:c3:1c:57 (interface docker0)

170170 - Enumerate the Network Interface configuration via SSH

Synopsis

Nessus was able to parse the Network Interface data on the remote host.

Description

Nessus was able to parse the Network Interface data on the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/01/19, Modified: 2025/02/11

Plugin Output

tcp/0

```
lo:
  IPv4:
    - Address : 127.0.0.1
      Netmask : 255.0.0.0
  IPv6:
    - Address : ::1
      Prefixlen : 128
      Scope : host
      ScopeID : 0x10
docker0:
  MAC : 02:42:e0:c3:1c:57
  IPv4:
    - Address : 172.17.0.1
      Netmask : 255.255.0.0
      Broadcast : 172.17.255.255
eth0:
  MAC : 08:00:27:36:62:0b
  IPv4:
    - Address : 192.168.220.6
      Netmask : 255.255.255.0
      Broadcast : 192.168.220.255
  IPv6:
    - Address : fe80::a00:27ff:fe36:620b
      Prefixlen : 64
      Scope : link
      ScopeID : 0x20
```

179200 - Enumerate the Network Routing configuration via SSH

Synopsis

Nessus was able to retrieve network routing information from the remote host.

Description

Nessus was able to retrieve network routing information the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/08/02, Modified: 2023/08/02

Plugin Output

tcp/0

```
Gateway Routes:
  eth0:
    ipv4_gateways:
      192.168.220.1:
        subnets:
          - 0.0.0.0/0
Interface Routes:
  docker0:
    ipv4_subnets:
      - 172.17.0.0/16
  eth0:
    ipv4_subnets:
      - 192.168.220.0/24
    ipv6_subnets:
      - fe80::/64
```


168980 - Enumerate the PATH Variables

Synopsis

Enumerates the PATH variable of the current scan user.

Description

Enumerates the PATH variables of the current scan user.

Solution

Ensure that directories listed here are in line with corporate policy.

Risk Factor

None

Plugin Information

Published: 2022/12/21, Modified: 2025/07/28

Plugin Output

tcp/0

```
Nessus has enumerated the path of the current scan user :
```

```
/usr/local/sbin  
/usr/local/bin  
/usr/sbin  
/usr/bin
```

35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

<https://standards.ieee.org/faqs/regauth.html>

<http://www.nessus.org/u?794673b4>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

```
The following card manufacturers were identified :
```

```
08:00:27:36:62:0B : PCS Systemtechnik GmbH
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:  
- 08:00:27:36:62:0B  
- 02:42:E0:C3:1C:57
```

204827 - Exiv2 Installed (Linux / Unix)

Synopsis

Exiv2 is installed on the remote Linux / Unix host.

Description

Exiv2 is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.

- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.204827' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

See Also

<https://exiv2.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/07/29, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path          : /usr/bin/exiv2
Version       : 0.28.5
Associated Package : exiv2 0.28.5
Managed by OS : True
```

168982 - Filepaths contain Dangerous characters (Linux)

Synopsis

This Tenable product detected files or paths on the scanned Unix-like system which contain characters with command injection or privilege escalation potential.

Description

This Tenable product detected files or paths on the scanned Unix-like system which contain characters with command injection or privilege escalation potential. Although almost any character is valid for an entry in this kind of filesystem, such as semicolons, use of some of them may lead to problems or security compromise when used in further commands.

This product has chosen in certain plugins to avoid digging within those files and directories for security reasons.

These should be renamed to avoid security compromise.

Solution

Rename these files or folders to not include dangerous characters.

Risk Factor

None

Plugin Information

Published: 2022/12/21, Modified: 2024/07/24

Plugin Output

tcp/22

The following files and directories contain potentially dangerous characters such as brackets, ampersand, or semicolon.

This scanner avoided access to these files when possible for safety:

```
/usr/share/node_modules/@babel/core/lib/config
/usr/share/node_modules/@babel/eslint-shared-fixtures/config
/usr/share/node_modules/@babel/generator/lib/node
/usr/share/node_modules/@babel/helper-define-polyfill-provider/lib/node
/usr/share/node_modules/@babel/node
/usr/share/node_modules/@npmcli/config
/usr/share/node_modules/@types/node
/usr/share/nodejs/@babel/core/lib/config
/usr/share/nodejs/@babel/eslint-shared-fixtures/config
/usr/share/nodejs/@babel/generator/lib/node
/usr/share/nodejs/@babel/helper-define-polyfill-provider/lib/node
/usr/share/nodejs/@babel/node
/usr/share/nodejs/@npmcli/config
/usr/share/nodejs/@types/node
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/8834/www

```
The remote web server type is :  
NessusWWW
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/8834/www

Response Code : HTTP/1.1 200 OK

Protocol version : HTTP/1.1

HTTP/2 TLS Support: No

HTTP/2 Cleartext Support: No

SSL : yes

Keep-Alive : no

Options allowed : (Not implemented)

Headers :

Cache-Control: must-revalidate

X-Frame-Options: DENY

Content-Type: text/html

ETag: 862b32cacee1122de9c3c75a392c0d0d

Connection: close

X-XSS-Protection: 1; mode=block

Server: NessusWWW

Date: Thu, 07 Aug 2025 07:43:18 GMT

X-Content-Type-Options: nosniff

Content-Length: 1217

Content-Security-Policy: upgrade-insecure-requests; block-all-mixed-content; form-action 'self'; frame-ancestors 'none'; frame-src https://store.tenable.com; default-src 'self'; connect-src 'self' www.tenable.com; script-src 'self' www.tenable.com; img-src 'self' data:; style-src 'self' www.tenable.com; object-src 'none'; base-uri 'self';

Strict-Transport-Security: max-age=31536000; includeSubDomains

Expect-CT: max-age=0

Response Body :

```
<!doctype html>
<html lang="en">
  <head>
    <meta http-equiv="X-UA-Compatible" content="IE=edge,chrome=1" />
    <meta http-equiv="Content-Security-Policy" content="upgrade-insecure-requests; block-all-
mixed-content; form-action 'self'; frame-src https://store.tenable.com; default-src 'self'; connect-
src 'self' www.tenable.com; script-src 'self' www.tenable.com; img-src 'self' data;; style-src
'self' www.tenable.com; object-src 'none'; base-uri 'self';" />
    <meta name="viewport" content="width=device-width, initial-scale=1">
    <meta charset="utf-8" />
    <title>Nessus</title>
    <link rel="stylesheet" href="nessus6.css?v=1753222061535" id="theme-link" />
    <link rel="stylesheet" href="tenable_links.css?v=ac05d80f1e3731b79d12103cdf9367fc" />
    <link rel="stylesheet" href="wizard_templates.css?v=0e2ae10949ed6782467b3810ccce69c5" />
    <!--[if lt IE 11]>
      <script>
        window.location = '/unsupported6.html';
      </script>
    <![endif]-->
    <script src="nessus6.js?v=1753222061535"></script>
    <script src="p [...]
```


171410 - IP Assignment Method Detection

Synopsis

Enumerates the IP address assignment method(static/dynamic).

Description

Enumerates the IP address assignment method(static/dynamic).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/02/14, Modified: 2025/07/28

Plugin Output

tcp/0

```
+ lo
+ IPv4
  - Address      : 127.0.0.1
    Assign Method : static
+ IPv6
  - Address      : ::1
    Assign Method : static
+ eth0
+ IPv4
  - Address      : 192.168.220.6
    Assign Method : dynamic
+ IPv6
  - Address      : fe80::a00:27ff:fe36:620b
    Assign Method : static
+ docker0
+ IPv4
  - Address      : 172.17.0.1
    Assign Method : static
```

Synopsis

Java is installed on the remote Linux / Unix host.

Description

One or more instances of Java are installed on the remote Linux / Unix host. This may include private JREs bundled with the Java Development Kit (JDK).

Notes:

- This plugin attempts to detect Oracle and non-Oracle JRE instances such as Zulu Java, Amazon Corretto, AdoptOpenJDK, IBM Java, etc
- To discover instances of JRE that are not in PATH, or installed via a package manager, 'Perform thorough tests' setting must be enabled.

See Also

[https://en.wikipedia.org/wiki/Java_\(software_platform\)](https://en.wikipedia.org/wiki/Java_(software_platform))

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0690

Plugin Information

Published: 2021/03/16, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path          : /usr/lib/jvm/java-21-openjdk-amd64/
Version       : 21.0.8
Application    : OpenJDK Java
Binary Location : /usr/lib/jvm/java-21-openjdk-amd64/bin/java
Details        : This Java install appears to be OpenJDK due to the install directory
                  name (high confidence).
Detection Method : "find" utility
Managed by OS  : True
```


189990 - Jmcnamara Spreadsheet-ParseExcel Installed (Unix)

Synopsis

Jmcnamara Spreadsheet-ParseExcel is installed on the remote Unix host.

Description

Jmcnamara Spreadsheet-ParseExcel is installed on the remote Unix host.

See Also

<https://github.com/jmcnamara/spreadsheet-parseexcel>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/02/05, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path          : /usr/share/perl5/Spreadsheet/ParseExcel.pm
Version       : 0.66
Associated Package : libspreadsheet-parseexcel-perl: /usr/share/perl5/Spreadsheet/ParseExcel.pm
Managed by OS   : True
```

151883 - Libgcrypt Installed (Linux/UNIX)

Synopsis

Libgcrypt is installed on this host.

Description

Libgcrypt, a cryptography library, was found on the remote host.

See Also

<https://gnupg.org/download/index.html>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/07/21, Modified: 2025/07/28

Plugin Output

tcp/0

```
Nessus detected 4 installs of Libgcrypt:

Path      : /usr/lib/x86_64-linux-gnu/libgcrypt.so.20.5.0
Version   : 1.11.0

Path      : /usr/lib/x86_64-linux-gnu/libgcrypt.so.20
Version   : 1.11.0

Path      : /lib/x86_64-linux-gnu/libgcrypt.so.20.5.0
Version   : 1.11.0

Path      : /lib/x86_64-linux-gnu/libgcrypt.so.20
Version   : 1.11.0
```

200214 - Libndp Installed (Linux / Unix)

Synopsis

Libndp is installed on the remote Linux / Unix host.

Description

Libndp is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.

- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.200214' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

See Also

<https://github.com/jpirko/libndp>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/06/07, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path          : libndp0 1.9-1 (via package manager)
Version       : 1.9
Managed by OS : True
```

Synopsis

Use system commands to obtain the list of mounted devices on the target machine at scan time.

Description

Report the mounted devices information on the target machine at scan time using the following commands.

```
/bin/df -h /bin/lsblk /bin/mount -l
```

This plugin only reports on the tools available on the system and omits any tool that did not return information when the command was ran.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/02/03, Modified: 2023/11/27

Plugin Output

tcp/0

```
$ df -h
Filesystem      Size  Used Avail Use% Mounted on
udev            3.8G   0    3.8G   0% /dev
tmpfs           781M  1.1M  780M   1% /run
/dev/sda1       38G   32G   3.7G  90% /
tmpfs           3.9G  4.0K   3.9G   1% /dev/shm
tmpfs           5.0M   0    5.0M   0% /run/lock
tmpfs           1.0M   0    1.0M   0% /run/credentials/systemd-journald.service
tmpfs           3.9G   64K   3.9G   1% /tmp
tmpfs           1.0M   0    1.0M   0% /run/credentials/getty@tty1.service
tmpfs           781M  120K   781M   1% /run/user/1000

$ lsblk
NAME MAJ:MIN RM  SIZE RO TYPE MOUNTPOINTS
sda   8:0    0   40G  0 disk
##sda1 8:1    0  37.9G  0 part /
##sda2 8:2    0    1K  0 part
##sda5 8:5    0   2.1G  0 part [SWAP]
sr0   11:0   1  1024M  0 rom

$ mount -l
sysfs on /sys type sysfs (rw,nosuid,nodev,noexec,relatime)
proc on /proc type proc (rw,nosuid,nodev,noexec,relatime)
```

```
udev on /dev type devtmpfs (rw,nosuid,relatime,size=3928616k,nr_inodes=982154,mode=755,inode64)
devpts on /dev/pts type devpts (rw,nosuid,noexec,relatime,gid=5,mode=600,ptmxmode=000)
tmpfs on /run type tmpfs (rw,nosuid,nodev,noexec,relatime,size=799300k,mode=755,inode64)
/dev/sdal on / type ext4 (rw,relatime,errors=remount-ro)
securityfs on /sys/kernel/security type securityfs (rw,nosuid,nodev,noexec,relatime)
tmpfs on /dev/shm type tmpfs (rw,nosuid,nodev,inode64)
cgroup2 on /sys/fs/cgroup type cgroup2
(rw,nosuid,nodev,noexec,relatime,nsdelegate,memory_recursiveprot)
pstore on /sys/fs/pstore type pstore (rw,nosuid,nodev,noexec,relatime)
bpf on /sys/fs/bpf type bpf (rw,nosuid,nodev,noexec,relatime,mode=700)
systemd-1 on /proc/sys/fs/binfmt_misc type autofs
(rw,relatime,fd=40,pgrp=1,timeout=0,minproto=5,maxproto=5,direct,pipe_ino=4663)
mqueue on /dev/mqueue type mqueue (rw,nosuid,nodev,noexec,relatime)
tmpfs on /run/lock type tmpfs (rw,nosuid,nodev,noexec,relatime,size=5120k,inode64)
debugfs on /sys/kernel/debug type debugfs (rw,nosuid,nodev,noexec,relatime)
hugetlbfs on /dev/hugepages type hugetlbfs (rw,nosuid,nodev,relatime,pagesize=2M [...])
```


193143 - Linux Time Zone Information

Synopsis

Nessus was able to collect and report time zone information from the remote host.

Description

Nessus was able to collect time zone information from the remote Linux host.

Solution

None

Risk Factor

None

Plugin Information

Published: 2024/04/10, Modified: 2024/04/10

Plugin Output

tcp/0

```
Via date: IST +0530
Via timedatectl: Time zone: Asia/Kolkata (IST, +0530)
Via /etc/localtime: IST-5:30
```

95928 - Linux User List Enumeration

Synopsis

Nessus was able to enumerate local users and groups on the remote Linux host.

Description

Using the supplied credentials, Nessus was able to enumerate the local users and groups on the remote Linux host.

Solution

None

Risk Factor

None

Plugin Information

Published: 2016/12/19, Modified: 2025/03/26

Plugin Output

tcp/0

```
----- [ User Accounts ] -----
```

```
User       : kali
Home folder : /home/kali
Start script : /usr/bin/zsh
Groups      : kali
              dip
              scanner
              lpadmin
              netdev
              users
              dialout
              wireshark
              video
              vboxsf
              cdrom
              adm
              audio
              sudo
              kaboxer
              bluetooth
              plugdev
              floppy
```

```
----- [ System Accounts ] -----
```

```
User       : root
Home folder : /root
Start script : /usr/bin/zsh
```

```
Groups      : root

User        : daemon
Home folder : /usr/sbin
Start script : /usr/sbin/nologin
Groups      : daemon

User        : bin
Home folder : /bin
Start script : /usr/sbin/nologin
Groups      : bin

User        : sys
Home folder : /dev
Start script : /usr/sbin/nologin
Groups      : sys

User        : sync
Home folder : /bin
Start script : /bin/sync
Groups      : nogroup

User        : games
Home folder : /usr/games
Start script : /usr/sbin/nologin
Groups      : games

User        : man
Home folder : /var/cache/man
Start script : /usr/sbin/nologin
Groups      : man

User        : lp
Home folder : /var/spool/lpd
Start script : /usr/sbin/nologin
Groups      : lp

User        : mail
Home folder : /var/mail
Start script : /usr/sbin/nologin
Groups      : mail

User        : news
Home folder : /var/spool/news
Start script : /usr/sbin/nologin
Groups      : news

User        : uucp
Home folder : /var/spool/uucp
Start script : /usr/sbin/nologin
Groups      : uucp

User        : proxy
Home folder : /bin
Start script : /usr/sbin/nologin
Groups      : proxy

User        : www-data
Home folder : /var/www
Start script : /usr/sbin/nologin
Groups      : www-data

User        : backup
Home folder : /var/backups
Start script : /usr/sbin/nologin
Groups      : backup

User        : list
Home folder : /var/list
Start script : /usr/sbin/nologin
```

```
Groups      : list
User        [...]
```

19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2025/06/25

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.9.2
Nessus build : 20017
Plugin feed version : 202508061659
Scanner edition used : Nessus Home
Scanner OS : LINUX
Scanner distribution : ubuntu1604-x86-64
Scan type : Normal
Scan name : My Basic Network Scan
```

```
Scan policy used : Basic Network Scan
Scanner IP : 192.168.220.6
Ping RTT : Unavailable
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : yes (on the localhost)
Attempt Least Privilege : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2025/8/7 13:13 IST (UTC +05:30)
Scan duration : 375 sec
Scan for malware : no
```

10147 - Nessus Server Detection

Synopsis

A Nessus daemon is listening on the remote port.

Description

A Nessus daemon is listening on the remote port.

See Also

<https://www.tenable.com/products/nessus/nessus-professional>

Solution

Ensure that the remote Nessus installation has been authorized.

Risk Factor

None

References

XREF IAVT:0001-T-0673

Plugin Information

Published: 1999/10/12, Modified: 2023/02/08

Plugin Output

tcp/8834/www

```
URL      : https://192.168.220.6:8834/  
Version  : unknown
```

64582 - Netstat Connection Information

Synopsis

Nessus was able to parse the results of the 'netstat' command on the remote host.

Description

The remote host has listening ports or established connections that Nessus was able to extract from the results of the 'netstat' command.

Note: The output for this plugin can be very long, and is not shown by default. To display it, enable verbose reporting in scan settings.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/02/13, Modified: 2023/05/23

Plugin Output

tcp/0

14272 - Netstat Portscanner (SSH)

Synopsis

Remote open ports can be enumerated via SSH.

Description

Nessus was able to run 'netstat' on the remote host to enumerate the open ports. If 'netstat' is not available, the plugin will attempt to use 'ss'.

See the section 'plugins options' about configuring this plugin.

Note: This plugin will run on Windows (using netstat.exe) in the event that the target being scanned is localhost.

See Also

<https://en.wikipedia.org/wiki/Netstat>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2004/08/15, Modified: 2025/05/27

Plugin Output

tcp/8834/www

```
Port 8834/tcp was found to be open
```

178771 - Node.js Installed (Linux / UNIX)

Synopsis

Node.js is installed on the remote Linux / UNIX host.

Description

Node.js is installed on the remote Linux / UNIX host.

See Also

<https://nodejs.org>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/07/25, Modified: 2025/07/28

Plugin Output

tcp/0

```
Nessus detected 2 installs of Node.js:

Path      : /usr/lib/python3/dist-packages/playwright/driver/node
Version   : 20.11.0

Path       : /usr/bin/node
Version    : 20.19.2
Managed   : 1
Package    : nodejs
Package release : 1
Package version : 20.19.2+dfsg

aliases :
- /bin/node
- /bin/nodejs
- /usr/bin/nodejs
```

178772 - Node.js Modules Installed (Linux)

Synopsis

Nessus was able to enumerate one or more Node.js modules installed on the remote host.

Description

Nessus was able to enumerate one or more Node.js modules installed on the remote host.

Note that 'Perform thorough tests' may be required for an in-depth search of all Node.js modules.

See Also

<https://nodejs.org/api/modules.html>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/07/25, Modified: 2025/07/28

Plugin Output

tcp/0

```
Installed top-level Node.js modules :

name: smart-buffer
version: 4.2.0
path: /usr/share/npm/node_modules/smart-buffer/package.json

name: is-lambda
version: 1.0.1
path: /usr/share/npm/node_modules/is-lambda/package.json

name: cli-columns
version: 4.0.0
path: /usr/share/npm/node_modules/cli-columns/package.json

name: abort-controller
version: 3.0.0
path: /usr/share/npm/node_modules/abort-controller/package.json

name: npm-profile
version: 7.0.1
path: /usr/share/npm/node_modules/npm-profile/package.json

name: npm-audit-report
```

```
version: 4.0.0
path: /usr/share/npm/node_modules/npm-audit-report/package.json

name: env-paths
version: 2.2.1
path: /usr/share/npm/node_modules/env-paths/package.json

name: humanize-ms
version: 1.2.1
path: /usr/share/npm/node_modules/humanize-ms/package.json

name: tiny-relative-date
version: 1.3.0
path: /usr/share/npm/node_modules/tiny-relative-date/package.json

name: promise-all-reject-late
version: 1.0.1
path: /usr/share/npm/node_modules/promise-all-reject-late/package.json

name: parse-conflict-json
version: 3.0.0
path: /usr/share/npm/node_modules/parse-conflict-json/package.json

name: just-diff-apply
version: 5.4.1
path: /usr/share/npm/node_modules/just-diff-apply/package.json

name: json-stringify-nice
version: 1.1.4
path: /usr/share/npm/node_modules/json-stringify-nice/package.json

name: npm-install-checks
version: 6.0.0
path: /usr/share/npm/node_modules/npm-install-checks/package.json

name: read-cmd-shim
version: 4.0.0
path: /usr/share/npm/node_modules/read-cmd-shim/package.json

name: unique-slug
version: 4.0.0
path: /usr/share/npm/node_modules/unique-slug/package.json

name: ignore-walk
version: 6.0.0
path: /usr/share/npm/node_modules/ignore-walk/package.json

name: treeverse
version: 3.0.0
path: /usr/share/npm/node_modules/treeverse/package.json

name: npm-registry-fetch
version: 14.0.3
path: /usr/share/npm/node_modules/npm-registry-fetch/package.json

name: fastest-levenshtein
version: 1.0.16
path: /usr/share/npm/node_modules/fastest-levenshtein/package.json

name: proc [...]
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Linux Kernel 6.12.33+kali-amd64
Confidence level : 99
Method : uname
Type : general-purpose
Fingerprint : uname:Linux kali 6.12.33+kali-amd64 #1 SMP PREEMPT_DYNAMIC Kali 6.12.33-1kali1
(2025-06-25) x86_64 GNU/Linux

Following fingerprints could not be used to determine OS :

HTTP:!:Server: NessusWWW

SSLcert:!:i/CN:Nessus Certification Authorityi/O:Nessus Users Unitedi/OU:Nessus Certification
Authoritys/CN:kalis/O:Nessus Users Uniteds/OU:Nessus Server
177e9d64ad3ef3203f51f1c26fd73fea0da98477

11936 - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 6.12.33+kali-amd64
Confidence level : 99
Method : uname
```

```
The remote host is running Linux Kernel 6.12.33+kali-amd64
```

97993 - OS Identification and Installed Software Enumeration over SSH v2 (Using New SSH Library)

Synopsis

Information about the remote host can be disclosed via an authenticated session.

Description

Nessus was able to login to the remote host using SSH or local commands and extract the list of installed packages.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/05/30, Modified: 2025/02/11

Plugin Output

tcp/0

```
Nessus can run commands on localhost to check if patches are applied.
```

```
The output of "uname -a" is :
```

```
Linux kali 6.12.33+kali-amd64 #1 SMP PREEMPT_DYNAMIC Kali 6.12.33-1kali1 (2025-06-25) x86_64 GNU/Linux
```

```
Local checks have been enabled for this host.
```

```
The remote Debian system is :
```

```
kali-rolling
```

```
This is a Kali Linux system
```

```
OS Security Patch Assessment is available for this host.
```

```
Runtime : 1.290112 seconds
```

117887 - OS Security Patch Assessment Available

Synopsis

Nessus was able to log in to the remote host using the provided credentials and enumerate OS security patch levels.

Description

Nessus was able to determine OS security patch levels by logging into the remote host and running commands to determine the version of the operating system and its components. The remote host was identified as an operating system or device that Nessus supports for patch and update assessment. The necessary information was obtained to perform these checks.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0516

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

```
OS Security Patch Assessment is available.
```

```
Protocol : LOCAL
```


148373 - OpenJDK Java Detection (Linux / Unix)

Synopsis

A distribution of Java is installed on the remote Linux / Unix host.

Description

One or more instances of OpenJDK Java are installed on the remote host. This may include private JREs bundled with the Java Development Kit (JDK).

Notes:

- Addition information provided in plugin Java Detection and Identification (Unix)
- Additional instances of Java may be discovered by enabling thorough tests

See Also

<https://openjdk.java.net/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/04/07, Modified: 2025/07/14

Plugin Output

tcp/0

```
Path          : /usr/lib/jvm/java-21-openjdk-amd64/
Version       : 21.0.8
Binary Location : /usr/lib/jvm/java-21-openjdk-amd64/bin/java
Managed by OS  : True
```

168007 - OpenSSL Installed (Linux)

Synopsis

OpenSSL was detected on the remote Linux host.

Description

OpenSSL was detected on the remote Linux host.

The plugin timeout can be set to a custom value other than the plugin's default of 15 minutes via the 'timeout.168007' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

Note: This plugin leverages the '-maxdepth' find command option, which is a feature implemented by the GNU find binary. If the target does not support this option, such as HP-UX and AIX devices, users will need to enable 'thorough tests' in their scan policy to run the find command without using a '-maxdepth' argument.

See Also

<https://openssl.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/11/21, Modified: 2025/07/28

Plugin Output

tcp/0

Nessus detected 5 installs of OpenSSL:

| | |
|--------------------|--------------------|
| Path | : /usr/bin/openssl |
| Version | : 3.5.1 |
| Associated Package | : openssl 3.5.1-1 |
| Managed by OS | : True |

| | |
|--------------------|---------------------------|
| Path | : /opt/nessus/bin/openssl |
| Version | : 3.0.16 |
| Associated Package | : nessus |

```
Path      : /usr/lib/x86_64-linux-gnu/ruby/3.3.0/openssl.so
Version   : 3.5.0
Associated Package : libruby3.3
```

```
Path      : /usr/lib/x86_64-linux-gnu/libcrypto.so.3
Version   : 3.5.1
Associated Package : libssl3t64
```

```
Path      : /opt/nessus/lib/nessus/libcrypto.so.3
Version   : 3.0.16
Associated Package : nessus
```

We are unable to retrieve version info from the following list of OpenSSL files. However, these installs may include their version within the filename or the filename of the Associated Package.

e.g. libssl.so.3 (OpenSSL 3.x), libssl.so.1.1 (OpenSSL 1.1.x)

```
/opt/nessus/lib/nessus/libssl.so.3
/usr/lib/x86_64-linux-gnu/android/libcrypto.so.0
/usr/lib/x86_64-linux-gnu/libssl.so.3
/usr/lib/x86_64-linux-gnu/android/libssl.so.0
```

232856 - OpenVPN Installed (Linux)

Synopsis

OpenVPN is installed on the remote Linux host.

Description

OpenVPN is installed on the remote Linux host.

Note: Enabling the 'Perform thorough tests' setting will search the file system more broadly.

See Also

<https://openvpn.net/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/03/19, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path           : /usr/sbin/openvpn
Version        : 2.6.14
Associated Package : openvpn 2.6.14-1
Managed by OS  : True
```

216936 - PHP Scripting Language Installed (Unix)

Synopsis

The PHP scripting language is installed on the remote Unix host.

Description

The PHP scripting language is installed on the remote Unix host.

Note: Enabling the 'Perform thorough tests' setting will search the file system much more broadly. Thorough test is required to get results on hosts running MacOS.

See Also

<https://www.php.net>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/06/13, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path           : /usr/bin/php8.4
Version        : 8.4.10
Associated Package : php8.4-cli: /usr/bin/php8.4
INI file       : /etc/php/8.4/cli/php.ini
INI source     : PHP binary grep
Managed by OS : True
```

179139 - Package Manager Packages Report (nix)

Synopsis

Reports details about packages installed via package managers.

Description

Reports details about packages installed via package managers

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/08/01, Modified: 2025/05/07

Plugin Output

tcp/0

```
Successfully retrieved and stored package data.
```

66334 - Patch Report

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2025/07/14

Plugin Output

tcp/0

```
. You need to take the following 2 actions :
```

```
[ Node.js 20.x < 20.19.4 / 22.x < 22.17.1 / 24.x < 24.4.1 Multiple Vulnerabilities (Tuesday, July 15, 2025 Security Releases). (242134) ]
```

```
+ Action to take : Upgrade to Node.js version 20.19.4 / 22.17.1 / 24.4.1 or later.
```

```
+Impact : Taking this action will resolve 21 different vulnerabilities (CVEs).
```

```
[ SQLite < 3.50.2 Memory Corruption (242325) ]
```

```
+ Action to take : Upgrade to SQLite 3.50.2 or later.
```

```
+Impact : Taking this action will resolve 2 different vulnerabilities (CVEs).
```

130024 - PostgreSQL Client/Server Installed (Linux)

Synopsis

One or more PostgreSQL server or client versions are available on the remote Linux host.

Description

One or more PostgreSQL server or client versions have been detected on the remote Linux host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2019/10/18, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path      : /usr/lib/postgresql/17/bin/postgres (via package manager)
Version   : 17.5
```

tcp/0

```
Path      : /usr/lib/postgresql/17/bin/psql (via package manager)
Version   : 17.5
```


207584 - Ruby Gem Modules Installed (Linux)

Synopsis

Nessus was able to enumerate one or more Ruby Gem modules installed on the remote host.

Description

Nessus was able to enumerate one or more Ruby Gem modules installed on the remote host.

Note that 'Perform thorough tests' may be required for an in-depth search of all Ruby Gem modules.

See Also

<http://www.nessus.org/u?26bc7c8b>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/09/23, Modified: 2025/07/28

Plugin Output

tcp/0

```
330 Installed Ruby Gems :

name: Ascii85
version: 2.0.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//Ascii85-2.0.1

name: aarch64
version: 2.1.0
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//aarch64-2.1.0

name: abbrev
version: 0.1.2
path: /usr/lib/ruby/gems/3.3.0/gems//abbrev-0.1.2

name: actioncable
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//actioncable-7.1.5.1

name: actionmailbox
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//actionmailbox-7.1.5.1

name: actionmailer
```

```
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//actionmailer-7.1.5.1

name: actionpack
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//actionpack-7.1.5.1

name: actiontext
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//actiontext-7.1.5.1

name: actionview
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//actionview-7.1.5.1

name: activejob
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//activejob-7.1.5.1

name: activemodel
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//activemodel-7.1.5.1

name: activerecord
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//activerecord-7.1.5.1

name: activestorage
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//activestorage-7.1.5.1

name: activesupport
version: 7.1.5.1
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//activesupport-7.1.5.1

name: activesupport
version: 7.2.2.1
path: /usr/share/rubygems-integration/all/specifications//activesupport-7.2.2.1.gemspec

name: addressable
version: 2.8.7
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems//addressable-2.8.7

name: afm
version: 0.2.2
path: /usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0 [...]
```

202184 - Ruby Programming Language Installed (Linux)

Synopsis

The Ruby programming language is installed on the remote Linux host.

Description

The Ruby programming language is installed on the remote Linux host.

See Also

<https://ruby.org/en/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/07/11, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path      : package: ruby3.3  3.3.8-2
Version   : 3.3.8
Managed by OS : True
```

174788 - SQLite Local Detection (Linux)

Synopsis

The remote Linux host has SQLite Database software installed.

Description

Version information for SQLite was retrieved from the remote host. SQLite is an embedded database written in C.

- To discover instances of SQLite that are not in PATH, or installed via a package manager, 'Perform thorough tests' setting must be enabled.

See Also

<https://www.sqlite.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/04/26, Modified: 2025/07/28

Plugin Output

tcp/0

```
Nessus detected 2 installs of SQLite:

  Path    : /usr/bin/sqlite3
  Version : 3.46.1

  Path    : /bin/sqlite3
  Version : 3.46.1

Version reported by the package manager.
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/8834/www

```
This port supports TLSv1.3/TLSv1.2.
```

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/8834/www

```
Subject Name:

Organization: Nessus Users United
Organization Unit: Nessus Server
Locality: New York
Country: US
State/Province: NY
Common Name: kali

Issuer Name:

Organization: Nessus Users United
Organization Unit: Nessus Certification Authority
Locality: New York
Country: US
State/Province: NY
Common Name: Nessus Certification Authority

Serial Number: 00 B7 B5

Version: 3

Signature Algorithm: SHA-256 With RSA Encryption

Not Valid Before: Aug 07 07:28:04 2025 GMT
Not Valid After: Aug 06 07:28:04 2029 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 2048 bits
Public Key: 00 C5 5C 0D A2 61 C2 58 E7 2F 46 A4 27 36 03 AE EF BD 06 3D
```

```
21 FE 94 22 C8 58 B1 34 C4 58 F9 67 B4 03 01 A9 35 3B 17 F3
B0 8A B6 6C 2C C5 14 A5 0E 82 B0 6D 06 FE 74 E7 E2 93 58 27
96 BD 98 46 7E AD 1E 7F BA 66 71 84 D3 19 D0 7F 2D CF B7 55
DD FD 1F D6 CD FC 7C 98 05 BF 88 E7 D4 D5 D1 F4 CB AB D8 AF
9F 19 2A 13 74 DD E9 F6 44 47 34 7E 07 2E 40 43 E3 BF 39 A7
D2 EB 9C 68 DB 75 9C 97 50 93 25 B1 42 0F 36 ED 03 53 6C 40
64 BB 0B A7 50 4A 03 B8 B4 6A BF 51 CC C8 0E 05 C1 92 27 47
37 62 80 97 E8 7A 52 38 8F DF E9 13 1B CB 30 77 F4 03 00 1E
52 F9 2F 4F 18 5F 34 57 BA D3 E3 03 8E CA 25 81 36 B9 0B EE
6E BC F4 7A 49 B7 A5 4D 5E 2D BE 34 16 CC E4 55 68 67 10 9A
99 F6 C7 D5 B4 73 70 BA A6 44 C0 7C D8 1B 3A C1 30 85 AB D0
DD 71 C8 F6 76 B9 C3 97 3F 8A D6 FF D2 B7 87 11 AD
```

Exponent: 01 00 01

Signature Length: 256 bytes / 2048 bits

Signature: 00 7C 9B 09 BB D8 FD F9 37 22 B1 3C 0D 9D 64 BC D9 A2 39 F9
1A DA B6 08 1D 76 B7 37 A4 02 90 84 A3 88 ED 9B 7D 80 6B 38
FD 82 DF 12 1E B8 A1 ED 88 8B BE DA 57 DB 76 A0 03 4B 18 44
C1 64 19 6D 97 17 5D 88 C6 4B CA E6 56 03 A6 0E BA 56 FA 13
02 5E 94 7C 04 C0 E6 52 2B 79 46 68 39 64 AE 3B 07 15 13 4F
B2 58 DF 71 AA 16 FB D2 47 A1 96 4E 36 C9 22 87 76 6E 3E 56
09 AA 26 D0 43 D9 [...]

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffced>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2024/09/11

Plugin Output

tcp/8834/www

```
Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.
```

```
SSL Version : TLSv13
```

```
High Strength Ciphers (>= 112-bit key)
```

| Name | Code | KEX | Auth | Encryption | MAC |
|------------------------------|------------|-----|------|------------------------|-----|
| ----- | ----- | --- | --- | ----- | --- |
| TLS_AES_128_GCM_SHA256 | 0x13, 0x01 | - | - | AES-GCM(128) | |
| AEAD | | | | | |
| TLS_AES_256_GCM_SHA384 | 0x13, 0x02 | - | - | AES-GCM(256) | |
| AEAD | | | | | |
| TLS_CHACHA20_POLY1305_SHA256 | 0x13, 0x03 | - | - | ChaCha20-Poly1305(256) | |
| AEAD | | | | | |

```
SSL Version : TLSv12
```

```
High Strength Ciphers (>= 112-bit key)
```

| Name | Code | KEX | Auth | Encryption | MAC |
|-------------------------|------------|------|------|--------------|-----|
| ----- | ----- | --- | --- | ----- | --- |
| ECDHE-RSA-AES128-SHA256 | 0xC0, 0x2F | ECDH | RSA | AES-GCM(128) | |
| SHA256 | | | | | |

| | | | | |
|-------------------------|------------|------|-----|--------------|
| ECDHE-RSA-AES256-SHA384 | 0xC0, 0x30 | ECDH | RSA | AES-GCM(256) |
| SHA384 | | | | |

The fields above are :

```
{Tenable ciphertype}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/8834/www

Here is the list of SSL PFS ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

| Name | Code | KEX | Auth | Encryption | MAC |
|-------------------------|------------|------|------|--------------|-----|
| ----- | ----- | --- | ---- | ----- | --- |
| ECDHE-RSA-AES128-SHA256 | 0xC0, 0x2F | ECDH | RSA | AES-GCM(128) | |
| SHA256 | | | | | |
| ECDHE-RSA-AES256-SHA384 | 0xC0, 0x30 | ECDH | RSA | AES-GCM(256) | |
| SHA384 | | | | | |

The fields above are :

```
{Tenable ciphertype}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
```

```
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/8834/www

```
A TLSv1.2 server answered on this port.
```

tcp/8834/www

```
A web server is running on this port through TLSv1.2.
```

Synopsis

It was possible to enumerate installed software on the remote host via SSH.

Description

Nessus was able to list the software installed on the remote host by calling the appropriate command (e.g., 'rpm -qa' on RPM-based Linux distributions, dpkg, etc.).

Solution

Remove any software that is not in compliance with your organization's acceptable use and security policies.

Risk Factor

None

References

XREF IAVT:0001-T-0502

Plugin Information

Published: 2006/10/15, Modified: 2025/03/26

Plugin Output

tcp/0

Here is the list of packages installed on the remote Debian Linux system :

```
ii  7zip  24.09+dfsg-8  amd64  7-Zip file archiver with a high compression ratio
ii  accountsservice  23.13.9-7  amd64  query and manipulate user account information
ii  acl  2.3.2-2+b1  amd64  access control list - utilities
ii  adb  1:34.0.5-12  amd64  Android Debug Bridge
ii  adduser  3.152  all  add and remove users and groups
ii  adwaita-icon-theme  48.1-1  all  default icon theme of GNOME
ii  aircrack-ng  1:1.7+git20230807.4bf83f1a-2  amd64  wireless WEP/WPA cracking utilities
ii  alsa-topology-conf  1.2.5.1-3  all  ALSA topology configuration files
ii  alsa-ucm-conf  1.2.14-1  all  ALSA Use Case Manager configuration files
ii  amass  4.2.0-0kali1  amd64  In-depth DNS Enumeration and Network Mapping
ii  amass-common  4.2.0-0kali1  all  In-depth DNS Enumeration and Network Mapping
ii  amd64-microcode  3.20250311.1  amd64  Platform firmware and microcode for AMD CPUs and SoCs
ii  android-libbase  1:34.0.5-12  amd64  Android base library
ii  android-libboringssl  14.0.0+r45-2  amd64  Google's internal fork of OpenSSL for the Android
SDK
ii  android-libcutils  1:34.0.5-12  amd64  Android utils library for C
ii  android-liblog  1:34.0.5-12  amd64  Android NDK logger interfaces
ii  android-libziparchive  1:34.0.5-12  amd64  Library for ZIP archives
ii  android-udev-rules  0~20250314+ds-5  all  udev rules for Android tools
ii  apache2  2.4.65-2  amd64  Apache HTTP Server
```

```
ii  apache2-bin  2.4.65-2  amd64  Apache HTTP Server (modules and other binary files)
ii  apache2-data 2.4.65-2  all   Apache HTTP Server (common files)
ii  apache2-utils 2.4.65-2  amd64  Apache HTTP Server (utility programs for web servers)
ii  apparmor      4.1.0-1  amd64  user-space parser utility for AppArmor
ii  apt           3.0.3+kalil amd64  commandline package manager
ii  apt-file      3.3      all    search for files within Debian packages (command-line interface)
ii  apt-utils     3.0.3+kalil amd64  package [...]
```

42822 - Strict Transport Security (STS) Detection

Synopsis

The remote web server implements Strict Transport Security.

Description

The remote web server implements Strict Transport Security (STS).

The goal of STS is to make sure that a user does not accidentally downgrade the security of his or her browser.

All unencrypted HTTP connections are redirected to HTTPS. The browser is expected to treat all cookies as 'secure' and to close the connection in the event of potentially insecure situations.

See Also

<http://www.nessus.org/u?2fb3aca6>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/11/16, Modified: 2019/11/22

Plugin Output

tcp/8834/www

The STS header line is :

```
Strict-Transport-Security: max-age=31536000; includeSubDomains
```

136318 - TLS Version 1.2 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.2.

See Also

<https://tools.ietf.org/html/rfc5246>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/05/04, Modified: 2020/05/04

Plugin Output

tcp/8834/www

```
TLSv1.2 is enabled and the server supports at least one cipher.
```


138330 - TLS Version 1.3 Protocol Detection

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.3.

See Also

<https://tools.ietf.org/html/rfc8446>

Solution

N/A

Risk Factor

None

Plugin Information

Published: 2020/07/09, Modified: 2023/12/13

Plugin Output

tcp/8834/www

```
TLSv1.3 is enabled and the server supports at least one cipher.
```

110095 - Target Credential Issues by Authentication Protocol - No Issues Found

Synopsis

Nessus was able to log in to the remote host using the provided credentials. No issues were reported with access, privilege, or intermittent failure.

Description

Valid credentials were provided for an authentication protocol on the remote target and Nessus did not log any subsequent errors or failures for the authentication protocol.

When possible, Nessus tracks errors or failures related to otherwise valid credentials in order to highlight issues that may result in incomplete scan results or limited scan coverage. The types of issues that are tracked include errors that indicate that the account used for scanning did not have sufficient permissions for a particular check, intermittent protocol failures which are unexpected after the protocol has been negotiated successfully earlier in the scan, and intermittent authentication failures which are unexpected after a credential set has been accepted as valid earlier in the scan. This plugin reports when none of the above issues have been logged during the course of the scan for at least one authenticated protocol. See plugin output for details, including protocol, port, and account.

Please note the following :

- This plugin reports per protocol, so it is possible for issues to be encountered for one protocol and not another.

For example, authentication to the SSH service on the remote target may have consistently succeeded with no privilege errors encountered, while connections to the SMB service on the remote target may have failed intermittently.

- Resolving logged issues for all available authentication protocols may improve scan coverage, but the value of resolving each issue for a particular protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol and what particular check failed. For example, consistently successful checks via SSH are more critical for Linux targets than for Windows targets, and likewise consistently successful checks via SMB are more critical for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0520

Plugin Information

Published: 2018/05/24, Modified: 2024/03/25

Plugin Output

tcp/0

```
Nessus was able to execute commands locally with sufficient privileges  
for all planned checks.
```

141118 - Target Credential Status by Authentication Protocol - Valid Credentials Provided

Synopsis

Valid credentials were provided for an available authentication protocol.

Description

Nessus was able to determine that valid credentials were provided for an authentication protocol available on the remote target because it was able to successfully authenticate directly to the remote target using that authentication protocol at least once. Authentication was successful because the authentication protocol service was available remotely, the service was able to be identified, the authentication protocol was able to be negotiated successfully, and a set of credentials provided in the scan policy for that authentication protocol was accepted by the remote service. See plugin output for details, including protocol, port, and account.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/10/15, Modified: 2024/03/25

Plugin Output

tcp/0

```
Nessus was able to execute commands on localhost.
```

163326 - Tenable Nessus Installed (Linux)

Synopsis

Tenable Nessus is installed on the remote Linux host.

Description

Tenable Nessus is installed on the remote Linux host.

See Also

<https://www.tenable.com/products/nessus>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2022/07/21, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path      : /opt/nessus
Version   : 10.9.2
Build     : 20017
```

237200 - Tornado Detection

Synopsis

A Tornado Python library is installed on the remote host.

Description

A Tornado Python library is installed on the remote host.

Note that Nessus has relied upon on the application's self-reported version number.

See Also

https://python.Tornado.com/v0.1/docs/get_started/quickstart/

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/05/23, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path      : /usr/lib/python3/dist-packages/tornado-6.4.2.egg-info
Version   : 6.4.2
Managed by OS : True
```

192709 - Tukaani XZ Utils Installed (Linux / Unix)

Synopsis

Tukaani XZ Utils is installed on the remote Linux / Unix host.

Description

Tukaani XZ Utils is installed on the remote Linux / Unix host.

XZ Utils consists of several components, including:

- liblzma
- xz

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.
- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.192709' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

See Also

<https://xz.tukaani.org/xz-utils/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/03/29, Modified: 2025/07/28

Plugin Output

tcp/0

```
Nessus detected 2 installs of XZ Utils:

Path           : /usr/lib/x86_64-linux-gnu/liblzma.so.5.8.1
Version        : 5.8.1
Associated Package : liblzma5 5.8.1-1
Confidence      : High
```

```
Managed by OS      : True
Version Source     : Package

Path               : /usr/bin/xz
Version            : 5.8.1
Associated Package : xz-utils 5.8.1-1
Confidence         : High
Managed by OS     : True
Version Source     : Package
```


110483 - Unix / Linux Running Processes Information

Synopsis

Uses `/bin/ps auxww` command to obtain the list of running processes on the target machine at scan time.

Description

Generated report details the running processes on the target machine at scan time.

This plugin is informative only and could be used for forensic investigation, malware detection, and to confirm that your system processes conform to your system policies.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/06/12, Modified: 2023/11/27

Plugin Output

tcp/0

| USER | PID | %CPU | %MEM | VSZ | RSS | TTY | STAT | START | TIME | COMMAND |
|------|-----|------|------|-------|-------|-----|------|-------|------|-----------------------------------|
| root | 1 | 0.0 | 0.1 | 24440 | 15184 | ? | Ss | 12:40 | 0:01 | /sbin/init splash |
| root | 2 | 0.0 | 0.0 | 0 | 0 | ? | S | 12:40 | 0:00 | [kthreadd] |
| root | 3 | 0.0 | 0.0 | 0 | 0 | ? | S | 12:40 | 0:00 | [pool_workqueue_release] |
| root | 4 | 0.0 | 0.0 | 0 | 0 | ? | I< | 12:40 | 0:00 | [kworker/R-kvfree_rcu_reclaim] |
| root | 5 | 0.0 | 0.0 | 0 | 0 | ? | I< | 12:40 | 0:00 | [kworker/R-rcu_gp] |
| root | 6 | 0.0 | 0.0 | 0 | 0 | ? | I< | 12:40 | 0:00 | [kworker/R-sync_wq] |
| root | 7 | 0.0 | 0.0 | 0 | 0 | ? | I< | 12:40 | 0:00 | [kworker/R-slub_flushwq] |
| root | 8 | 0.0 | 0.0 | 0 | 0 | ? | I< | 12:40 | 0:00 | [kworker/R-netns] |
| root | 12 | 0.0 | 0.0 | 0 | 0 | ? | I | 12:40 | 0:00 | [kworker/u12:0-ipv6_addrconf] |
| root | 13 | 0.0 | 0.0 | 0 | 0 | ? | I< | 12:40 | 0:00 | [kworker/R-mm_percpu_wq] |
| root | 14 | 0.0 | 0.0 | 0 | 0 | ? | I | 12:40 | 0:00 | [rcu_tasks_kthread] |
| root | 15 | 0.0 | 0.0 | 0 | 0 | ? | I | 12:40 | 0:00 | [rcu_tasks_rude_kthread] |
| root | 16 | 0.0 | 0.0 | 0 | 0 | ? | I | 12:40 | 0:00 | [rcu_tasks_trace_kthread] |
| root | 17 | 0.0 | 0.0 | 0 | 0 | ? | S | 12:40 | 0:01 | [ksoftirqd/0] |
| root | 18 | 0.0 | 0.0 | 0 | 0 | ? | I | 12:40 | 0:00 | [rcu_preempt] |
| root | 19 | 0.0 | 0.0 | 0 | 0 | ? | S | 12:40 | 0:00 | [rcu_exp_par_gp_kthread_worker/0] |
| root | 20 | 0.0 | 0.0 | 0 | 0 | ? | S | 12:40 | 0:00 | [rcu_exp_gp_kthread_worker] |
| root | 21 | 0.0 | 0.0 | 0 | 0 | ? | S | 12:40 | 0:00 | [migration/0] |
| root | 22 | 0.0 | 0.0 | 0 | 0 | ? | S | 12:40 | 0:00 | [idle_inject/0] |
| root | 23 | 0.0 | 0.0 | 0 | 0 | ? | S | 12:40 | 0:00 | [cpuhp/0] |
| root | 24 | 0.0 | 0.0 | 0 | 0 | ? | S | 12:40 | 0:00 | [cpuhp/1] |
| root | 25 | 0.0 | 0.0 | 0 | 0 | ? | S | 12:40 | 0:00 | [idle_inject/1] |
| root | 26 | 0.0 | 0.0 | 0 | 0 | ? | S | [...] | | |

152742 - Unix Software Discovery Commands Available

Synopsis

Nessus was able to log in to the remote host using the provided credentials and is able to execute all commands used to find unmanaged software.

Description

Nessus was able to determine that it is possible for plugins to find and identify versions of software on the target host. Software that is not managed by the operating system is typically found and characterized using these commands. This was measured by running commands used by unmanaged software plugins and validating their output against expected results.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/08/23, Modified: 2021/08/23

Plugin Output

tcp/0

```
Unix software discovery checks are available.
```

```
Protocol : LOCAL
```

189731 - Vim Installed (Linux)

Synopsis

Vim is installed on the remote Linux host.

Description

Vim is installed on the remote Linux host.

See Also

<https://www.vim.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/01/29, Modified: 2025/07/28

Plugin Output

tcp/0

```
Nessus detected 2 installs of Vim:
```

```
Path      : /usr/bin/vim.tiny
Version   : 9.1
```

```
Path      : /usr/bin/vim.basic
Version   : 9.1
```

182848 - libcurl Installed (Linux / Unix)

Synopsis

libcurl is installed on the remote Linux / Unix host.

Description

libcurl is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.
- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.182848' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

See Also

<https://curl.se/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/10/10, Modified: 2025/07/28

Plugin Output

tcp/0

```
Nessus detected 2 installs of libcurl:
```

```
Path          : /usr/lib/x86_64-linux-gnu/libcurl.so.4.8.0
Version       : 8.14.1
Associated Package : libcurl4t64

Path          : /usr/lib/x86_64-linux-gnu/libcurl-gnutls.so.4.8.0
Version       : 8.14.1
Associated Package : libcurl3t64-gnutls
```

204828 - libexiv2 Installed (Linux / Unix)

Synopsis

libexiv2 is installed on the remote Linux / Unix host.

Description

libexiv2 is installed on the remote Linux / Unix host.

Additional information:

- More paths will be searched and the timeout for the search will be increased if 'Perform thorough tests' setting is enabled.
- The plugin timeout can be set to a custom value other than the plugin's default of 30 minutes via the 'timeout.204828' scanner setting in Nessus 8.15.1 or later.

Please see <https://docs.tenable.com/nessus/Content/SettingsAdvanced.htm#Custom> for more information.

See Also

<https://exiv2.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2024/07/29, Modified: 2025/07/28

Plugin Output

tcp/0

```
Path          : /usr/lib/x86_64-linux-gnu/libexiv2.so.0.28.5
Version       : 0.28.5
Associated Package : libexiv2-28 0.28.5
Managed by OS   : True
```

136340 - nginx Installed (Linux/UNIX)

Synopsis

NGINX is installed on the remote Linux / Unix host.

Description

NGINX, a web server with load balancing capabilities, is installed on the remote Linux / Unix host.

See Also

<https://www.nginx.com>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2020/05/05, Modified: 2025/07/28

Plugin Output

tcp/0

Nessus detected 2 installs of nginx:

```
Path      : nginx (via package manager)
Version   : 1.26.3-3

Path      : /usr/sbin/nginx
Version   : 1.26.3
Associated Package : nginx: /usr/sbin/nginx
Detection Method  : Binary in $PATH
Full Version     : 1.26.3
Managed by OS   : True
Nginx Plus      : False
```