

1. users

Purpose: The users table stores authentication and authorization details of all system users. It manages login credentials, user roles (Admin, Convener, Staff), account status, and profile information. This table controls access to the system.

Column Name	Data Type	Constraints
user_id	SERIAL	Primary Key
username	VARCHAR(100)	UNIQUE, NOT NULL
email	VARCHAR(150)	UNIQUE, NOT NULL
password_hash	VARCHAR(255)	NOT NULL
role	VARCHAR(20)	ADMIN , CONVENER , STAFF
profile_picture	VARCHAR(255)	Image path
is_active	BOOLEAN	Default TRUE
created_at	TIMESTAMP	Default CURRENT_TIMESTAMP
modified_at	TIMESTAMP	Auto updated

2. department

Purpose: The department table stores information about different departments in the organization. It helps in organizing staff members department-wise and supports department-based reporting.

Column Name	Data Type	Constraints
department_id	SERIAL	Primary Key
department_name	VARCHAR(100)	UNIQUE, NOT NULL
is_active	BOOLEAN	Default TRUE
created_at	TIMESTAMP	Default CURRENT_TIMESTAMP

3. staff

Purpose: The staff table stores profile and organizational details of staff members who participate in meetings. It is linked to the users table for login purposes and to the department table for organizational structure.

Column Name	Data Type	Constraints
staff_id	SERIAL	Primary Key
user_id	INT	FK → users(user_id), UNIQUE
staff_name	VARCHAR(150)	NOT NULL
designation	VARCHAR(100)	Optional
mobile_no	VARCHAR(15)	Numeric
email_address	VARCHAR(150)	UNIQUE
department_id	INT	FK → department(department_id)
profile_picture	VARCHAR(255)	Image path
is_active	BOOLEAN	Default TRUE
created_at	TIMESTAMP	Default CURRENT_TIMESTAMP

4. meeting_type

Purpose: The meeting_type table stores different categories of meetings such as team meetings, client meetings, and management meetings. It helps classify meetings and avoids hardcoding meeting types.

Column Name	Data Type	Constraints
meeting_type_id	SERIAL	Primary Key
meeting_type_name	VARCHAR(100)	UNIQUE, NOT NULL
is_active	BOOLEAN	Default TRUE
created_at	TIMESTAMP	Default CURRENT_TIMESTAMP

5. venue

Purpose: The venue table stores details of meeting locations, including physical rooms and virtual platforms. It helps manage where meetings are conducted.

Column Name	Data Type	Constraints
venue_id	SERIAL	Primary Key
venue_name	VARCHAR(150)	NOT NULL
venue_type	VARCHAR(50)	PHYSICAL , VIRTUAL
location	TEXT	Optional
is_active	BOOLEAN	Default TRUE
created_at	TIMESTAMP	Default CURRENT_TIMESTAMP

6. meeting_member

Purpose: The meeting_member table manages meeting participants and attendance. It resolves the many-to-many relationship between meetings and staff and records whether a staff member was present or absent.

Column Name	Data Type	Constraints
meeting_member_id	SERIAL	Primary Key
meeting_id	INT	FK → meetings
staff_id	INT	FK → staff
is_present	BOOLEAN	Default FALSE
attendance_marked_at	TIMESTAMP	Nullable
remarks	TEXT	Optional
created_at	TIMESTAMP	Default CURRENT_TIMESTAMP
UNIQUE(meeting_id, staff_id)	—	Prevent duplicates

7. meetings

Purpose: The meetings table is the core table of the system. It stores all meeting-related information such as meeting title, date, time, organizer, venue, meeting type, and cancellation details.

Column Name	Data Type	Constraints
meeting_id	SERIAL	Primary Key
meeting_title	VARCHAR(255)	NOT NULL
meeting_description	TEXT	Optional
meeting_date	DATE	NOT NULL
meeting_start_time	TIMESTAMP	NOT NULL
meeting_end_time	TIMESTAMP	End > Start
meeting_type_id	INT	FK → meeting_type
organizer_staff_id	INT	FK → staff
venue_id	INT	FK → venue
meeting_link	TEXT	Optional
is_cancelled	BOOLEAN	Default FALSE
cancellation_reason	TEXT	Nullable
cancelled_at	TIMESTAMP	Nullable
created_at	TIMESTAMP	Default CURRENT_TIMESTAMP
modified_at	TIMESTAMP	Auto updated

8. documents

Purpose: The documents table stores metadata of Minutes of Meeting (MOM) files and other meeting-related documents. The actual files are stored externally, and only file details and paths are saved in the database.

Column Name	Data Type	Constraints
document_id	SERIAL	Primary Key
meeting_id	INT	FK → meetings
document_title	VARCHAR(255)	NOT NULL
file_name	VARCHAR(255)	NOT NULL
file_path	TEXT	NOT NULL
uploaded_by	INT	FK → users
uploaded_at	TIMESTAMP	Default CURRENT_TIMESTAMP

9. reports

Purpose: The reports table stores generated reports such as meeting-wise and summary reports. It keeps track of report files generated by the system for analysis and record-keeping.

Column Name	Data Type	Constraints
report_id	SERIAL	Primary Key
report_name	VARCHAR(255)	NOT NULL
report_type	VARCHAR(50)	Summary / Meeting-wise
meeting_id	INT	FK → meetings (Nullable)
file_path	TEXT	NOT NULL
generated_by	INT	FK → users
generated_at	TIMESTAMP	Default CURRENT_TIMESTAMP