

Advanta Africa APIs

[SMS API](#) >

[RESELLER SMS CREDIT API](#)

[USSD GUIDE](#)

[SHORTCODE GUIDE](#)

[SMPP API](#)

[AIRTIME API](#)

[EMAIL API](#)

RESELLER CREDIT API

Important

You must be a reseller registered under Advanta Africa to use this API.

The **Reseller Credit API** allows you to transfer SMS credits to your sub-accounts or clients. You can use this in a payment integration to automate account top ups.

Important Notes

- The **apikey** and **partnerID** must belong to your reseller account.
- The **childID** is the client's **username**.
- The **amount** is in **Kenyan Shillings**, and the system will convert it into SMS units based on the configured SMS rate.
- If no SMS rate is set, the system defaults to an SMS rate of 1.
- You will receive a response indicating the status of the transaction.
- Once an account is credited, the transaction details will be recorded in the **Credit History** section, just like manual credit loading.

Advanta Africa APIs

[SMS API](#) >

[RESELLER SMS CREDIT API](#)

[USSD GUIDE](#)

[SHORTCODE GUIDE](#)

[SMPP API](#)

[AIRTIME API](#)

[EMAIL API](#)

POST Method

Endpoint: `https://{{url}}/api/services/credit`

Request Body:

```
1  {
2      "apikey": "{{apikey}}",
3      "partnerID": "
4      {{partnerID}}",
5      "childID": "{{childID}}",
6      "amount": "{{amount}}"
7  }
```

json

Sample Success Response:

```
1  {
2      "response-code": 200,
3      "response-description":
4      "Partner ID xxxx has been
5      credited with 5 units",
6      "prev-balance": "524.00",
7      "sms-units": "5",
8      "new-balance": "529.00"
9  }
```

json

Sample Error Response:

```
1  {
2      "response-code": 1005,
3      "response-description":
4      "The child account is
5      invalid. Kindly verify the
6      details"
7  }
```

json

Advanta Africa APIs

[SMS API >](#)

[RESELLER SMS CREDIT API](#)

[USSD GUIDE](#)

[SHORTCODE GUIDE](#)

[SMPP API](#)

[AIRTIME API](#)

[EMAIL API](#)

Code Examples (POST Request)

PHP

```
1      $ch = curl_init("https://{url}/api")
2      curl_setopt($ch, CURLOPT_RETURNTRANSFER,
3      true);
4      curl_setopt($ch, CURLOPT_POST,
5      true);
6      curl_setopt($ch, CURLOPT_HTTPHEADER,
7      ["Content-Type: application/json"]);
8      curl_setopt($ch, CURLOPT_POSTFIELDS,
9      json_encode([
10         "apikey" => "{{apikey}}",
11         "partnerID" => "{{partnerID}}",
12         "childID" => "{{childID}}",
13         "amount" => "{{amount}}"
14     ]));

$response = curl_exec($ch);
curl_close($ch);
echo $response;
```

Node.js

```
1      const axios = require('axios')
2
3      const data = {
4         apikey: "{{apikey}}",
5         partnerID: "{{partnerID}}",
6         childID: "{{childID}}",
7         amount: "{{amount}}"
8     };
9
10     axios.post("https://{url}/api",
11     data, {
12         headers: { "Content-Type": "application/json" }
13     });
```

Advanta Africa APIs

[SMS API](#) >

[RESELLER SMS CREDIT API](#)

[USSD GUIDE](#)

[SHORTCODE GUIDE](#)

[SMPP API](#)

[AIRTIME API](#)

[EMAIL API](#)

```
if (response) {
  console.log(response.data)
}.catch(error => console.error(error))
```

Python

```
1 import requests
2
3 url =
4 "https://{{url}}/api/endpoint"
5 headers = {"Content-Type":
6 "application/json"}
7 payload = {
8     "apikey": "{{apikey}}",
9     "partnerID": "
10 {{partnerID}}",
11     "childID": "{{childID}}",
12     "amount": "{{amount}}"
13 }

response = requests.post(url,
json=payload,
headers=headers)
print(response.json())
```

Last Updated: 3/14/2025, 12:29:27 PM

Contributors: harrykerry