



Microcontroller




File: microcontroller.kicad_sch

Sensors




File: sensors.kicad_sch

RF




File: rf.kicad_sch

Power



File: power.kicad_sch





Organization: Lapin Rocketry
Designer: Gianluca Gaiardi
Reviewer: Gianluca Gaiardi
License: CERN-OHL-S
URL:




Sheet: / File: flight_computer.kicad_sch		
Flight Computer		
Size: A4	Date: 19/04/2026	Revision: A
KiCad E.D.A. 10.0.3	Sheet 1 of 5	


Microcontroller bank A, B, C, D, E




Buzzer
PS1240P02BT



Microcontroller core



Memory



F = 25MHz
ESR = 40Ω
C_L = 8pF
C₀ = 7pF
C_S = 5pF
g_m = 5 mA/V
C_{tot} = C_L + (C_S / 2)

Safety factor (S _f)	Assurance level
S _f ≥ 0	Safe
3 ≤ S _f ≤ 5	Not safe
S _f > 3	Not safe

C_{L2} = 2 × (C_L - C_S) = 6pF
DL = (ESR × (π × F × C_{tot})² × (V_{DD})²) / 2 = 97.07μW
g_m critical = 4 × (ESR) × (2 × π × F)² × (C₀ + C_L)² = 0.89 mA/V
g_m margin = g_m margin / g_m critical = 5.63



Organization: Lapin Rocketry
Designer: Gianluca Gaiardi
Reviewer: Gianluca Gaiardi
License: CERN-OHL-S
URL:



Sheet: /Microcontroller/
File: microcontroller.kicad_sch






Size: A4


Date:

Revision:

KiCad E.D.A. 10.0.3

Sheet 3 of 5





Radio
CC1200
CC1201