Laboratory Exercise 3: Conditional Statements

Learning Outcomes:

- Cascade `if-else` and/or `switch-case` statements to form much complex decision path.

Exercise Details

The `if-else` is the most common conditional statement in C. This branching statement is composed of a Boolean expression to ensure that the condition is not ambiguous. Usually relational (`<,>,<=,>=, == !=`) and logical (`&&` and `||`) operators are used to accomplish the task regarding the formulation of the Boolean expression. `switch-case` statement on the other hand would perfectly match the `switch` variable with the case value. Cascading `if-else` and `switch-case` statements would then make for a more complex decision path. For the syntax details of the `if-else` statement, refer to your lecture guide.

Problem:

Waist-to-hip ratio is a way to calculate excess with you're carrying using the equation below:

$$\frac{Natural\ Waist\ Line}{Widest\ part\ of\ the\ hip}$$

This ratio can indicate susceptibility to a number of health issues including high blood pressure, heart disease and diabetes. The chart below represent the risk level and are based upon the guidelines of the World Health Organization (WHO) and other reputable sources.

Category	Male	Female
Low Risk	<0.95	<0.80
Moderate Risk	0.96-1.0	0.81-0.85
High Risk	≥1.0	≥0.86

Write a C code to implement this ratio categorization.

Example:

```
0-Male
1-Female
Choice: 1
Female Waist (inches): 24
Female Hip (inches): 34
Ratio: 0.70
Category: Low Risk
```