

Power Module Comparison

DroneCAN Power Module

Applicable to all Holybro Flight controllers and any Pixhawk standard controllers with CAN Bus

Model	PM08-CAN ↗
Input Voltage	7 to 60V (2S to 14S)
Current Rating	• Continuous current:200A • Burst current ◦ 400A @ 25°C 1 sec ◦ 1000A @ 25°C < 1 sec
Max Current Sensing	376A
Output Voltage	5.2V/3A Max
Ports	Molex CLIK-Mate 2mm 6Pin
Communication Protocol	DroneCAN
Dimensions	45 × 41 × 26mm (Not Include Cable)
Weight	185g (Include Cable)
Mounting Hole	Available ↗
Applicable Products	All Pixhawk standard flight controller with CAN Bus

Digital Power Modules


(Applicable for Pixhawk 5X & 6X and other FMUv6X FC)

Model	PM02D ↗	PM03D ↗
Input Voltage	• LV: 2~6S • HV: 2~12S	2~6S
PCB Cont./Burst Current Rating	60A/100A	60A/120A
Max Current Sensing	• LV: 164A • HV: 327A	164A
Output Voltage	5.2V/3A Max	• 5.2V/3A Max • 8V/12V 3A (Selectable)
Ports	• XT60 • 6Pin Molex 2.0mm	• XT60 • 6Pin Molex 2.0mm • XT30 *6 (optional) • B+ Pads *4
Built-in Power Distribution	No	Yes
PWM Header	No	No
Dimensions	25 × 25 × 10 mm	84 × 78 × 12 mm
Weight	20g	59g
Mounting Hole	N/A	45 × 45 mm
Applicable Products	Pixhawk 5X & 6X	Pixhawk 5X & 6X

Analog Power Module

(Applicable for Pixhawk 6C & 6C Mini, Pix32 V6, Cube Orange, etc)

Model	PM02 V3 ↗	PM06 V2 ↗
Input Voltage	2~12S	2~14S
PCB Cont./Burst Current Rating	60A/100A	70A/120A
Max Current Sensing	120A	120A
Output Voltage	5.2V/3A Max	5.2V/3A Max
Ports	• XT60 • 6Pin GHR 1.25mm	• XT60 • 6Pin GHR 1.25mm • B+ Pads *4
Built-in Power Distribution	No	Yes
PWM Header	No	No
Dimensions	25 × 25 ×10 mm	35 × 35 ×10 mm
Weight	20g	24g
Mounting Hole	N/A	30.5 × 30.5 mm
Applicable Products	• Pixhawk 6C/6C Mini • Pix32 V6 • etc	• Pixhawk 6C/6C Mini • Pix32 V6 • etc

◀  ▶


Previous
Download

Next

Power Distribution Board (PDB)

Last updated 10 months ago

Was this helpful?



© 2024 Holybro. All rights reserved.