

Essential Skills. Lab 2

Ali Abdulmadzhidov

09 September 2016

1 Debian packagins system

1. How does it work? Debian package system has various different level tools for user. The base of package system is dpkg - Debian package manager. In spite of man page says that the description of steps in installing or removing process is inadequate, i'll try.

***.deb - Debian package**

Debian package contains three sections:

Global header Contains version of debian-binary package. Current is 2.0

Control section Meta information about package. Confiles, preinst, postinst, prerm, postrm scripts, list of dependencies, md5 hashsumm, brief description.

Data section Includes installable files

Installation

dpkg -i

- 1 Extract of control files of the package
- 2 If another version of package is already installed, execute prerm script of the outdated package
- 3 If package has preinst script, execute it.
- 4 Run postrm script of old package
- 5 Unpack new, and at the same time backup old files.
- 6 Configure package

Configuration

dpkg -configure

- 1 Unpack conffiles, and backup old conffiles.
- 2 Run postinit script

Removing

dpkg -remove Removes an installed package, but lefts connfiles

- 1 Run prerm script
- 2 Remove isntalled files
- 3 Run posterm script

Purge

`dpkg -purge` Purges (removes) an installed or removed package with conffiles.

- 1 Remove package
- 2 Run postterm script

```
wget ftp://ftp.sendmail.org/pub/sendmail/sendmail.8.15.2.tar.gz
```

2. Cheking signature of file

```
wget ftp://ftp.sendmail.org/pub/sendmail/sendmail.8.15.2.tar.gz.sig
wget http://www.sendmail.com/sm/open_source/security/pgp_keys/sendmail2015.asc
gpg --import sendmail2015.asc
gpg --verify sendmail.8.15.2.tar.gz.sig
```

3. Extract souces

```
tar -xzf sendmail.8.15.2.tar.gz
```

4. Read readme file first... No, really for the first time I just builded it and can't start. Then remove all staff and read readme file.

```
cat README
```

5. Add

```
sudo apt install libapache2-mod-php
```

6. Restarting apache2.

```
sudo service apache2 restart
```

7. Go to <http://localhost/dokuwiki/doku.php> and add our first page about Federative Wiki

2 XML entities creating

1. XML + DDT

```
<!DOCTYPE root
[
<!ELEMENT root (animal)>
<!ELEMENT animal (name,skin,voice)>
<!ELEMENT name (#PCDATA)>
<!ELEMENT skin (#PCDATA)>
<!ELEMENT voice (#PCDATA)>
```

```

        <!ENTITY skin "have skin">
        <!ENTITY fur "have fur">
        <!ENTITY feathers "have feathers">
        <!ENTITY bark "bark">
        <!ENTITY mur "mur">
        <!ENTITY bee "bee">
        <!ENTITY brr "brr">
        <!ENTITY mooo "mooo">
        <!ENTITY oink "oink">
        <!ENTITY whistle "whistle">
        <!ENTITY no_voice "no_voice">
    ]>
    <root>
<animal>
    <name>cow</name>
    <skin>&skin;</skin>
    <voice>&mooo;</voice>
</animal>
<animal>
    <name>sheep</name>
    <skin>&fur;</skin>
    <voice>&bee;</voice>
</animal>
<animal>
    <name>horse</name>
    <skin>&skin;</skin>
    <voice>&brr;</voice>
</animal>
<animal>
    <name>pig</name>
    <skin>&skin;</skin>
    <voice>&oink;</voice>
</animal>
<animal>
    <name>mockingbird</name>
    <skin>&feathers;</skin>
    <voice>&whistle;</voice>
</animal>
<animal>
    <name>eal</name>
    <skin>&feathers;</skin>
    <voice>&whistle;</voice>
</animal>
</root>

```

2. XS SCHEME

```

<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:element name="root">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="animal" maxOccurs="unbounded">

```

```

        <xs:complexType>
        <xs:sequence>
            <xs:element name="name" type="xs:string"/>
            <xs:element name="voice" type="xs:string"/>
            <xs:element name="skin" type="xs:string"/>
        </xs:sequence>
        </xs:complexType>
    </xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
</xs:schema>

```

XSLT and CSS

1. XSLT

```

<?xml version='1.0' encoding='UTF-8'?>
<xsl:stylesheet version='1.0' xmlns:xsl='http://www.w3.org/1999/XSL/Transform'>
<xsl:template match='/'>
    <html>
    <body>
    <h2>Animals</h2>
    <table border='1'>
        <tr>
            <th style='text-align:left'>Name</th>
            <th style='text-align:left'>Skin</th>
            <th style='text-align:left'>Voice</th>
        </tr>
        <xsl:for-each select='root/animal'>
            <tr>
                <td class='name-v1'><xsl:value-of select='name'/></td>
                <td class='skin-v1'><xsl:value-of select='skin'/></td>
                <td class='voice-v1'><xsl:value-of select='voice'/></td>
            </tr>
        </xsl:for-each>
    </table>
    </body>
    </html>
</xsl:template>
</xsl:stylesheet>

```

2. CSS

```

td {
    background: #eecbb;
}
th {
    background: #ffff00;
}
.name-v1 {

```

```
        color: #0f0;
    }
    .name-vl:hover {
        color: #00f;
    }
    .voice-vl {
        color: #00f;
    }
    .voice-vl:hover {
        color: #0f0;
    }
    .skin-vl {
        color: #f00;
    }
    .skin-vl:hover {
        color: #f0f;
    }
}
```