



[Complete Guide](#)

Mardas MD2PDF Guide

Complete user manual and feature reference

A complete guide for installing, configuring, and using Mardas MD2PDF.

This document also acts as a live rendering sample for cover pages, tables of contents, mixed RTL/LTR text, formulas, code, images, tables, footnotes, page breaks, and safe HTML.

AUTHORS

Mardas MD2PDF Team
(Documentation)
Meraj Rastegar
(mrage@sars@gmail.com)

DATE

2026-05-20

INSTITUTION

Mardas Lab

COURSE

Markdown Publishing

VERSION

1.3.1

STATUS

Stable

KEYWORDS

Markdown
PDF
Persian
English
RTL/LTR
MathJax
Playwright

Table of Contents

- 1 Introduction
 - 1-1 Main capabilities
- 2 Installation
 - 2-1 Requirements
 - 2-2 Install from source
 - 2-3 Development installation
- 3 First PDF
- 4 Recommended Workflow
- 5 Front Matter
 - 5-1 Common fields
 - 5-2 Cover behavior
- 6 Language and Direction
 - 6-1 Direction priority
 - 6-2 Mixed text examples
- 7 Table of Contents
- 8 Markdown Feature Reference
 - 8-1 Paragraphs and emphasis
 - 8-2 Lists
 - 8-3 Task lists
 - 8-4 Tables
 - 8-5 Blockquotes
 - 8-6 Callouts
- 9 MathJax
 - 9-1 Math troubleshooting
- 10 Code Blocks
- 11 Images and Safe HTML
 - 11-1 Image rules
 - 11-2 Safe HTML
- 12 Page Flow and Layout

- [12-1](#) Manual page breaks
 - [12-2](#) Page size
 - [12-3](#) Margins
- [13](#) Watermarks
- [14](#) Themes
- [15](#) GUI Workflow
- [16](#) CLI Reference
- [17](#) Automation and CI
- [18](#) Troubleshooting
 - [18-1](#) Chromium is missing
 - [18-2](#) Persian text looks wrong
 - [18-3](#) Images do not appear
 - [18-4](#) Math appears as raw TeX
 - [18-5](#) Layout needs inspection
- [19](#) Footnotes
- [20](#) Final Publishing Checklist

Introduction

Mardas MD2PDF is a Markdown-to-PDF publishing tool designed for documents that mix Persian and English content. It keeps the writing workflow simple while giving the final PDF a professional printed layout.

The project is useful for reports, university documents, technical guides, educational notes, research drafts, project documentation, and any Markdown file that needs a clean PDF output.

TEXT

Markdown -> Structured HTML -> Chromium PDF

The renderer does not draw paragraphs manually on a PDF canvas. Instead, it converts Markdown into a structured HTML document, applies print-oriented CSS, renders formulas with MathJax, and asks Chromium to produce the final PDF. This gives the project better support for CSS print layout, mixed text direction, SVG formulas, syntax-highlighted code, local images, and complex tables.

Note

This guide is both documentation and a rendering sample. The PDF version of this file is available in the examples/ directory.

■ Main capabilities

Mardas MD2PDF focuses on the features that matter most for polished technical PDFs:

Capability	Description
Persian and English documents	<code>lang: fa</code> , <code>lang: en</code> , RTL/LTR shell direction, and mixed inline text.
Cover pages	Title, subtitle, authors, summary, logo, date, version, status, keywords, and academic metadata.

Capability	Description
Table of contents	Hierarchical TOC generated from Markdown headings.
MathJax	Inline and display formulas with browser-rendered output.
Code blocks	Pygments syntax highlighting for fenced and indented code blocks.
Local images	Markdown and safe HTML images can be embedded as data URIs.
Safe HTML	Raw HTML is sanitized by default.
Footnotes	Multiline Markdown footnotes are supported.
Themes	Modern, textbook-light, textbook-dark, and academic layouts.
Automation	CLI workflow suitable for local scripts and CI jobs.
GUI	Local browser-based editor, preview, option selector, and exporter.

Installation

Requirements

Before using the project, make sure you have:

- Python 3.10 or newer;
- a working virtual environment;
- Playwright Chromium installed;
- a Persian-capable font on the system, preferably Vazirmatn;
- Git, if you plan to clone the repository.

■ Install from source

BASH

```
git clone https://github.com/mragetsars/Mardas-MD2PDF.git
cd Mardas-MD2PDF
python -m venv .venv
source .venv/bin/activate
pip install -e .
python -m playwright install chromium
```

On Windows PowerShell:

POWERSHELL

```
python -m venv .venv
.venv\Scripts\Activate.ps1
pip install -e .
python -m playwright install chromium
```

■ Development installation

For development, install the optional test dependencies:

BASH

```
pip install -e .[dev]
pytest
```

The package exposes two console commands:

Command	Purpose
<code>mrs-md2pdf</code>	Convert Markdown files to PDF from the command line.
<code>mrs-md2pdf-gui</code>	Launch the local browser-based graphical interface.

First PDF

Create a simple PDF:

BASH

```
mrs-md2pdf input.md -o output.pdf
```

Create a PDF with a table of contents and the modern theme:

BASH

```
mrs-md2pdf input.md -o output.pdf --toc --theme modern
```

Create a long report with book-like page flow:

BASH

```
mrs-md2pdf input.md -o output.pdf \  
  --toc \  
  --toc-depth 4 \  
  --toc-page-break \  
  --h1-page-break \  
  --theme textbook-light
```

Save the intermediate HTML for debugging:

BASH

```
mrs-md2pdf input.md -o output.pdf --debug-html output.html
```

Recommended Workflow

A clean PDF workflow usually looks like this:

1. Write the content in Markdown.
2. Add YAML front matter for title, authors, language, direction, and cover metadata.

3. Render a first PDF with `--toc` and the desired theme.
4. Review the cover, table of contents, math pages, code pages, image pages, and footer numbering.
5. If layout debugging is needed, export `--debug-html` and inspect the generated HTML in a browser.
6. Finalize the Markdown and render again.

For important documents, always review the final PDF visually. Automated tests can catch many problems, but typography, spacing, and page breaks still need human review.

Front Matter

Front matter is optional YAML placed at the beginning of the Markdown file. It controls the cover page, PDF metadata, document language, document direction, and several report-specific fields.

YAML

```
---
title: "My Technical Report"
subtitle: "A Markdown-powered PDF document"
authors:
  - name: "Mardas"
    email: "mragetsars@gmail.com"
    affiliation: "Mardas Lab"
    role: "Author"
summary: |
  This text appears on the cover.
  Multiline summaries are supported.
institution: "University or Organization"
department: "Department name"
course: "Course or project title"
supervisor: "Supervisor name"
date: "2026-05-20"
version: "1.3.1"
status: "Draft"
keywords: [Markdown, PDF, RTL, MathJax]
cover_label: "Technical Report"
cover_logo: "src/assets/Mardas.png"
lang: en
dir: ltr
---
```


Common fields

Field	Purpose
<code>title</code>	Cover title and PDF metadata title.
<code>subtitle</code>	Optional text under the main title.
<code>author</code>	Simple single-author value.
<code>authors</code>	List of author objects with optional <code>name</code> , <code>email</code> , <code>affiliation</code> , and <code>role</code> .
<code>summary</code> / <code>description</code>	Cover summary and PDF metadata subject.
<code>institution</code> , <code>department</code> , <code>course</code>	Academic or organizational context.
<code>supervisor</code> , <code>group</code> , <code>student_id</code>	Optional report metadata fields.
<code>date</code> , <code>version</code> , <code>status</code>	Cover cards used for document state.
<code>keywords</code> / <code>tags</code>	Cover keywords and PDF metadata keywords.
<code>cover_label</code>	Small label above the cover title.
<code>cover_logo</code> / <code>logo</code>	Custom logo path relative to the Markdown file.
<code>lang</code>	Built-in UI language, usually <code>en</code> or <code>fa</code> .
<code>dir</code>	Document shell direction: <code>auto</code> , <code>ltr</code> , or <code>rtl</code> .

Cover behavior

The cover is rendered separately from the main document. This gives the output cleaner page numbering and better watermark behavior:

- the cover is not counted as a content page;
- footer page numbering starts after the cover;
- watermarks are applied to content pages only;
- the cover may use full-page theme backgrounds;

- the cover can be disabled when a plain document is needed.

Disable the cover:

BASH

```
mrs-md2pdf input.md -o output.pdf --no-cover
```

Use a custom logo:

BASH

```
mrs-md2pdf input.md -o output.pdf --cover-logo ./src/assets/Mardas.png
```

Keep the cover but hide the logo:

BASH

```
mrs-md2pdf input.md -o output.pdf --no-cover-logo
```

Language and Direction

Direction is one of the most important parts of Persian/English PDF generation. Mardas MD2PDF separates language selection from direction control.

`lang: en` creates an English/LTR document shell, English cover labels, English callout titles, and a `Table of Contents` heading.

`lang: fa` creates a Persian/RTL document shell, Persian cover labels, Persian callout titles, and a `فهرست مطالب` heading.

Direction priority

The document direction is resolved in this order:

1. CLI `--dir rtl|ltr|auto`
2. front matter fields such as `dir`, `direction`, `text_direction`, or `document_direction`

3. language-derived default from `lang`
4. automatic detection from the Markdown body

■ Mixed text examples

English writing can include Persian terms such as `راست به چپ`, `فونت فارسی`, and `گزارش فنی` without breaking the surrounding sentence.

Persian writing can include English identifiers such as `Playwright`, `MathJax`, `GitHub Actions`, `PDF`, and `RTL/LTR` inside the same paragraph.

Inline code remains stable: `mrs-md2pdf input.md -o output.pdf --toc`.

Table of Contents

Enable the table of contents:

BASH

```
mrs-md2pdf input.md -o output.pdf --toc
```

Control the depth:

BASH

```
mrs-md2pdf input.md -o output.pdf --toc --toc-depth 3
```

Start the body on a new page after the TOC:

BASH

```
mrs-md2pdf input.md -o output.pdf --toc --toc-page-break
```

Start each top-level heading on a new page:

BASH

```
mrs-md2pdf input.md -o output.pdf --h1-page-break
```

The TOC is generated from Markdown headings and preserves readable inline math in headings such as $E = mc^2$ and ϵ .

Markdown Feature Reference

■ Paragraphs and emphasis

Markdown paragraphs, **bold text**, *italic text*, `inline code`, links, ordered lists, unordered lists, task lists, and blockquotes are supported.

■ Lists

- Write content in Markdown.
- Add front matter for metadata.
- Render with the desired theme.
- Review the final PDF.

1. Install the package.
2. Install Chromium.
3. Run the CLI.
4. Inspect the output.

■ Task lists

- ☒ Markdown input
- ☒ Persian/English typography
- ☒ MathJax rendering
- ☒ Code highlighting
- ☐ Final human review

■ Tables

Feature	Status	Notes
Mixed RTL/LTR text	Yes	Paragraphs, headings, lists, and table cells receive direction-aware styling.
Local images	Yes	Markdown and safe HTML images are embedded when possible.
MathJax	Yes	Inline and display math use separate sizing rules.
Code highlighting	Yes	Pygments is used for fenced and indented code blocks.
Footnotes	Yes	Multiline Markdown footnotes are supported.
Raw HTML sanitizer	Yes	Unsafe tags and event handlers are removed by default.

■ Blockquotes

Good PDF publishing is more than text conversion. Typography, line height, contrast, page flow, images, formulas, and predictable rendering all matter.

■ Callouts

Callouts use GitHub-style markers and are translated according to the document language.

Note

Use callouts for explanatory notes that should stand out visually.

Tip

Use `--debug-html output.html` when you need to inspect the exact HTML sent to Chromium.

Warning

Use `--unsafe-html` only for trusted local Markdown because it disables the built-in sanitizer.

MathJax

Inline math should match the surrounding line height: $E = mc^2$, $T = 500$, and $\Sigma = I \cdot \epsilon$ should sit naturally inside a paragraph.

Display math receives more visual space:

$$\int_{-\infty}^{\infty} e^{-x^2} dx = \sqrt{\pi}$$

A matrix example:

$$A = \begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix}, \quad \det(A) = -2$$

An aligned equation block:

$$\begin{aligned} \text{precision} &= \frac{TP}{TP + FP} \\ \text{recall} &= \frac{TP}{TP + FN} \end{aligned}$$

■ Math troubleshooting

If math appears as raw TeX:

- make sure `--no-mathjax` was not used;
- check the terminal for MathJax warnings;
- increase the browser timeout for very large math-heavy documents;
- render a smaller test file to isolate the problematic formula.

Code Blocks

Fenced code blocks support syntax highlighting and language labels.

PYTHON

```
from dataclasses import dataclass

@dataclass
class Document:
    title: str
    lang: str = "en"

def render_message(doc: Document) -> str:
    return f"Rendering {doc.title} as PDF"

print(render_message(Document("Mardas Guide")))
```

JAVASCRIPT

```
const items = ["Markdown", "Persian", "English", "MathJax", "PDF"];
const message = items.map((item, index) => `${index + 1}. ${item}`).join("\n");
console.log(message);
```

Code fences without a language are also valid:

TEXT

```
This block has no explicit language.
It should still render safely.
```

Indented code blocks are supported:

```
SELECT title, lang, version
FROM documents
WHERE renderer = 'mardas-md2pdf';
```

Inline code is protected from math and footnote processing. For example, `$x$` and `[^note]` remain literal when they are inside backticks.

Images and Safe HTML

Images are resolved relative to the Markdown file. Local images are embedded into the generated HTML/PDF when they are small enough to embed safely.



Safe raw HTML images can also be used when explicit sizing is needed:



■ Image rules

- Prefer local images for stable PDF output.
- Keep images reasonably sized before embedding them.
- Use paths relative to the Markdown file.
- In the GUI, attach local image files or image folders before exporting.
- Very large images are left as links and a warning is printed to avoid excessive memory usage.

■ Safe HTML

Raw HTML is sanitized by default. The sanitizer keeps document-oriented elements such as `<div>`, `<span>`, `<table>`, `<figure>`, and `<img>`, while removing active or unsafe content such as scripts,

event handlers, iframes, forms, remote stylesheets, and unsafe URL schemes.

Use unsafe HTML only for trusted local files:

BASH

```
mrs-md2pdf input.md -o output.pdf --unsafe-html
```

Page Flow and Layout

■ Manual page breaks

A manual page break can be inserted with safe HTML:

HTML

```
<div class="md2pdf-page-break"></div>
```

■ Page size

Use a named page size:

BASH

```
mrs-md2pdf input.md -o output.pdf --page-size A4
```

Use landscape orientation:

BASH

```
mrs-md2pdf input.md -o output.pdf --page-size "A4 landscape"
```

Use explicit dimensions:

BASH

```
mrs-md2pdf input.md -o output.pdf --page-size "210mm 297mm"
```

Margins

BASH

```
mrs-md2pdf input.md -o output.pdf \  
  --margin-top 18mm \  
  --margin-bottom 18mm \  
  --margin-x 16mm
```

Watermarks

Text watermark:

BASH

```
mrs-md2pdf input.md -o output.pdf --watermark "DRAFT"
```

Image watermark:

BASH

```
mrs-md2pdf input.md -o output.pdf \  
  --watermark-image ./src/assets/Mardas.png \  
  --watermark-opacity 0.05 \  
  --watermark-width 95mm
```

Watermarks are applied to content pages only, not to the cover page.

Themes

Mardas MD2PDF includes four built-in themes.

Theme	Best for
	General documentation, proposals, software reports, and product-style guides.

Theme	Best for
<code>textbook-light</code>	Long educational documents, course notes, Persian/English learning material.
<code>textbook-dark</code>	Screen reading, low-light review, and presentation-like technical notes.
<code>academic</code>	Formal reports, university documents, thesis-like drafts, and structured papers.

Choose a theme with:

```
BASH
mrs-md2pdf input.md -o output.pdf --theme academic
```

GUI Workflow

Launch the GUI:

```
BASH
mrs-md2pdf-gui
```

The GUI is useful for users who prefer a visual workflow:

1. Paste or type Markdown.
2. Select theme, language, direction, page size, and export options.
3. Attach local image files or image folders.
4. Preview the document approximately.
5. Export the final PDF.

Important

The GUI preview is approximate. The final PDF is produced by the backend renderer, which applies the full Markdown processing, theme CSS, MathJax rendering, cover logic, and Chromium print layout.

CLI Reference

Option	Description
<code>input</code>	Input Markdown file.
<code>-o</code> , <code>--output</code>	Output PDF path.
<code>--title</code> , <code>--author</code> , <code>--description</code>	Override metadata from front matter.
<code>--toc</code> , <code>--toc-depth</code>	Enable and configure the table of contents.
<code>--toc-page-break</code> , <code>--h1-page-break</code>	Control printed page flow.
<code>--theme</code>	Choose <code>modern</code> , <code>textbook-light</code> , <code>textbook-dark</code> , or <code>academic</code> .
<code>--page-size</code>	Use <code>A4</code> , <code>Letter</code> , <code>Legal</code> , <code>A4 landscape</code> , or dimensions such as <code>210mm 297mm</code> .
<code>--dir</code>	Force <code>auto</code> , <code>ltr</code> , or <code>rtl</code> .
<code>--margin-top</code> , <code>--margin-bottom</code> , <code>--margin-x</code>	Control page margins.
<code>--font-dir</code>	Directory containing local Vazirmatn font files.
<code>--chromium-path</code>	Custom Chromium or Chrome executable path.
<code>--debug-html</code>	Save the intermediate HTML.
<code>--no-cover</code> , <code>--cover-logo</code> , <code>--no-cover-logo</code>	Configure the cover.
<code>--watermark</code> , <code>--watermark-image</code>	Add text or image watermarks.
<code>--no-header-footer</code>	Disable printed footer.
<code>--no-mathjax</code>	Do not load MathJax.
<code>--unsafe-html</code>	Disable raw HTML sanitization for trusted files.

Option	Description
<code>--timeout-ms</code>	Browser timeout in milliseconds.

Run the full help command when needed:

BASH

```
mrs-md2pdf --help
```

Automation and CI

A typical automation command can be as simple as:

BASH

```
mrs-md2pdf docs/report.md -o build/report.pdf --toc --theme modern
```

For CI workflows, prefer explicit options:

BASH

```
mrs-md2pdf docs/report.md -o build/report.pdf \  
  --toc \  
  --toc-depth 4 \  
  --theme modern \  
  --page-size A4 \  
  --dir auto \  
  --timeout-ms 60000
```

For debugging CI failures, save the intermediate HTML as an artifact:

BASH

```
mrs-md2pdf docs/report.md -o build/report.pdf --debug-html build/report.html
```

Troubleshooting

■ Chromium is missing

Run:

BASH

```
python -m playwright install chromium
```

or pass a custom browser path:

BASH

```
mrs-md2pdf input.md -o output.pdf --chromium-path /path/to/chrome
```

■ Persian text looks wrong

Install a Persian-capable font such as Vazirmatn, or pass a font directory:

BASH

```
mrs-md2pdf input.md -o output.pdf --font-dir ./fonts
```

If the directory is missing or does not contain recognized font files, the renderer prints a fallback warning and uses system fonts.

■ Images do not appear

Check that image paths are relative to the Markdown file. If you use the GUI, attach the local images or folders before export. Very large images are not embedded and produce a warning.

■ Math appears as raw TeX

Make sure MathJax is enabled and check for renderer warnings. For large documents, increase the timeout:

BASH

```
mrs-md2pdf input.md -o output.pdf --timeout-ms 90000
```

■ Layout needs inspection

Export debug HTML:

BASH

```
mrs-md2pdf input.md -o output.pdf --debug-html output.html
```

Open `output.html` in a browser and inspect the generated structure and CSS.

Footnotes

Footnotes are useful for references, technical notes, and extra explanations. [pipeline](#)

Final Publishing Checklist

Before publishing an important PDF, check the following items:

- ☒ Cover title, subtitle, author, date, and metadata.
- ☒ Language and document direction.
- ☒ Table of contents depth and labels.
- ☒ Pages containing formulas.
- ☒ Pages containing code blocks and inline code.
- ☒ Pages containing local images.
- ☒ Tables that span wide content.
- ☒ Footnotes and links.
- ☒ Footer numbering after the cover.
- ☐ Final visual review in a PDF viewer.

1. Mardas MD2PDF intentionally uses Chromium for layout instead of drawing every paragraph directly on a PDF canvas. This ↩ gives the project strong support for CSS print rules, mixed direction text, MathJax SVG output, tables, local images, and syntax-highlighted code.

- Multiline footnotes are supported.
- Markdown inside footnotes is preserved.
- Inline code like `@page`, `$x$`, and `[^id]` remains readable when it is written inside backticks.