Started on	Sunday, 7 September 2025, 10:00 AM
State	Finished
Completed on	Sunday, 7 September 2025, 11:33 AM
Time taken	1 hour 32 mins
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 2.00 out of 2.00

Write a C program to find simple interest. **Note:** Inputs are principle, year and rate.

For example:

Input	Result
1000 5 9	Simple Interest = 450.00

Answer: (penalty regime: 0 %)

Reset answer

```
#include<stdio.h>
int main()
{
 float p,t,r,si;
 scanf("%f %f %f",&p,&t,&r);
 si=(p*t*r)/100;
 printf("Simple Interest = %.2f\n",si);
return 0;
}
```

	Input	Expected	Got	
✔	1000 5 9	Simple Interest = 450.00	Simple Interest = 450.00	✔

Passed all tests! ✔

Correct

Marks for this submission: 2.00/2.00.

Question **2**

Correct

Mark 2.00 out of 2.00

Write a C program to find Minimum between two given integer values(a=-1000 b=-1500) using conditional operator(ternary operator).

For example:

Input	Result
-1000 -1500	Minimum between -1000 and -1500 is -1500

Answer: (penalty regime: 0 %)

Reset answer

```
#include <stdio.h>
int main()
{
    int a,b;
    scanf("%d %d", &a, &b);
    printf("Minimum between %d and %d is %d\n", a, b, (a<b) ? a : b);
    return 0;
}
```

	Input	Expected	Got	
✔	-1000 -1500	Minimum between -1000 and -1500 is -1500	Minimum between -1000 and -1500 is -1500	✔
✔	-3000 -1500	Minimum between -3000 and -1500 is -3000	Minimum between -3000 and -1500 is -3000	✔
✔	500 -500	Minimum between 500 and -500 is -500	Minimum between 500 and -500 is -500	✔

Passed all tests! ✔

Correct

Marks for this submission: 2.00/2.00.

Question **3**

Correct

Mark 2.00 out of 2.00

Write a C program to swap (For ex: a=-200,b=-300 into a=-300,b=-200) two values without using a third variable.

For example:

Input	Result
-200 -300	Numbers before swapping: -200 -300 Numbers after swapping: -300 -200

Answer: (penalty regime: 0 %)

Reset answer

```
#include <stdio.h>
int main()
{
    int a,b;
    scanf("%d %d", &a, &b);
    printf("Numbers before swapping: %d %d\n", a, b);
    a=a^b;
    b=a^b;
    a=a^b;
    printf("Numbers after swapping: %d %d\n", a, b);
    return 0;
}
```

	Input	Expected	Got	
✔	-200 -300	Numbers before swapping: -200 -300 Numbers after swapping: -300 -200	Numbers before swapping: -200 -300 Numbers after swapping: -300 -200	✔
✔	-20 -300	Numbers before swapping: -20 -300 Numbers after swapping: -300 -20	Numbers before swapping: -20 -300 Numbers after swapping: -300 -20	✔
✔	121 321	Numbers before swapping: 121 321 Numbers after swapping: 321 121	Numbers before swapping: 121 321 Numbers after swapping: 321 121	✔

Passed all tests! ✔

Correct

Marks for this submission: 2.00/2.00.

Question **4**

Correct

Mark 2.00 out of 2.00

Write a C program to check whether the given input (For ex:*) is an alphabet or digit using a conditional operator.

For example:

Input	Result
-	It is NOT AN ALPHABET
Z	It is AN ALPHABET

Answer: (penalty regime: 0 %)

Reset answer

```
#include<stdio.h>
int main()
{
    char ch;
    scanf("%c",&ch);

    ((ch >= 'A' && ch <= 'Z')|| (ch >= 'a' && ch <='z'))
    ? printf("It is AN ALPHABET")
    :printf("It is NOT AN ALPHABET");
       return 0;
}
```

	Input	Expected	Got	
✔	-	It is NOT AN ALPHABET	It is NOT AN ALPHABET	✔
✔	9	It is NOT AN ALPHABET	It is NOT AN ALPHABET	✔
✔	Z	It is AN ALPHABET	It is AN ALPHABET	✔

Passed all tests! ✔

Correct

Marks for this submission: 2.00/2.00.

Question **5**

Correct

Mark 2.00 out of 2.00

Write a C program to find the perimeter of the rectangle.

For example:

Input	Result
5 10	Perimeter of rectangle=30.00 units

Answer: (penalty regime: 0 %)

Reset answer

```
#include<stdio.h>
int main()
{
    float length,width,perimeter;
    scanf("%f %f %f",&length,&width,&perimeter);
    perimeter = 2*(length + width);
    printf("Perimeter of rectangle=%.2f units\n",perimeter);
}
```

	Input	Expected	Got	
✔	5 10	Perimeter of rectangle=30.00 units	Perimeter of rectangle=30.00 units	✔

Passed all tests! ✔

Correct

Marks for this submission: 2.00/2.00.