BODY

TORQUE SPECIFICATION

SS0FF-0

Part tightened	N·m	kgf⋅cm	ft·lbf
FRONT BUMPER (Wagon)	_	-	-
Front bumper cover x Body	5.4	55	48 in.·lbf
BACK DOOR	-	-	-
Back door lock x Body	12.5	128	9
Door hinge x Door panel	8.0	82	71 in.·lbf
Door hinge x Body	11.5	117	8
Door lock striler x Body	23	235	17
Back door outside handle x Back door outside garnish	4.0	40	35 in.·lbf
REAR WIPER AND WASHER (Wagon)	-	-	-
Wiper arm x Rear wiper motor	5.5	56	49 in.·lbf
Nut x Rear wiper motor	12	122	9
Rear wiper motor x Rear wiper motor	5.5	56	49 in.·lbf
BACK DOOR STAY	_	-	-
Back door stay x Door panel	22	224	16
Back door stay x Body	19.5	199	14
SLIDING ROOF	_	-	-
Drive rail x Bracket	5.5	56	49 in.·lbf
Sliding roof housing x Body	8.0	82	71 in.·lbf
Sliding roof glass x Sliding roof housing	5.5	56	49 in.·lbf
INSTRUMENT PANEL	_	-	-
Steering wheel nut	35	357	26
Front passenger airbag assembly x reinforcement For bolt:	20	205	15
For nut:	5.5	56	49
FRONT SEAT	-	-	-
Seat x Body	38	387	28
Seatback x Seat adjuster	43	440	32
Seat cushion x Seat adjuster	21	214	15
Side airbag cover x Seat back frame	4.7	48	42 in.·lbf
REAR SEAT (Wagon)	_	-	-
Seatback x Body	21	214	15
SEAT BELT	_	-	-
Front Seat Belt:	-	-	-
Adjustable anchor x Body	42	428	31
Shoulder anchor x Adjustable anchor	42	428	31
Retractor x Body Upper Bolt:	7.5	76	66 in.·lbf
Retractor x Body Lower Bolt:	42	428	31
Inner belt x Seat	42	428	31
Rear Seat Belt (Sedan):	-	-	-
Floor anchor x Body	42	428	31
Inner belt x Body	42	428	31
Retractor x Body	42	428	31
CRS anchor set bolt	21	214	15

SERVICE SPECIFICATIONS - BODY

Rear Seat Belt (Wagon):	-	-	-
Floor anchor x Body	42	428	31
Inner belt x Body	42	428	31
Retractor x Body Floor side: Roof Side:	42	428	31
CRS anchor set bolt	13.2	135	10