

Power Source

Headlight (w/ Daytime Running Light)

* 1 : Front Fog Light SW

The diagram illustrates the electrical system for the vehicle's lighting, including the Power Source, Headlight (w/ Daytime Running Light), and various components like relays, fuses, and switches. The diagram is divided into four main sections: 1. Power Source, 2. Headlight (w/ Daytime Running Light), 3. Headlight (w/ Daytime Running Light), and 4. Headlight (w/ Daytime Running Light).

Components and Connections:

- Power Source:** Includes the BATTERY, 120A ALT, 20A ECU-B1, 40A MAIN, 40A AM1, and 115 IGNITION SW.
- Headlight (w/ Daytime Running Light):** Includes the DIMMER RELAY, HEAD LP RELAY, 10A H-LP R LWR, 10A H-LP L LWR, 7.5A DRL, 10A H-LP R UPR, 10A H-LP L UPR, and 10A H-LP R LWR.
- Headlight (w/ Daytime Running Light):** Includes the DIMMER RELAY, HEAD LP RELAY, 10A H-LP R LWR, 10A H-LP L LWR, 7.5A DRL, 10A H-LP R UPR, 10A H-LP L UPR, and 10A H-LP R LWR.
- Headlight (w/ Daytime Running Light):** Includes the DIMMER RELAY, HEAD LP RELAY, 10A H-LP R LWR, 10A H-LP L LWR, 7.5A DRL, 10A H-LP R UPR, 10A H-LP L UPR, and 10A H-LP R LWR.
- Headlight (w/ Daytime Running Light):** Includes the DIMMER RELAY, HEAD LP RELAY, 10A H-LP R LWR, 10A H-LP L LWR, 7.5A DRL, 10A H-LP R UPR, 10A H-LP L UPR, and 10A H-LP R LWR.

Tables:

C14 COMBINATION SW

	H	T	EL	HL	HF	HU	BFG	LFG
OFF								
TAIL								
HEAD								
LOW								
HIGH								
FLASH								
OFF								
ON								

DIMMER SW

	H	T	EL	HL	HF	HU	BFG	LFG
OFF								
TAIL								
HEAD								
LOW								
HIGH								
FLASH								
OFF								
ON								