

Intergenerational evolution of attitudes towards integration

Jacopo Baldassarri, Andrea Blasco, Elisa Omodei

November 12th, 2009

The Model

N agents of two different types: $U = \{a, b\}$

The Model

N agents of two different types: $U = \{a, b\}$

Agents $1, \dots, M$ are of type a and agents $M + 1, \dots, N$ of type b

The Model

N agents of two different types: $U = \{a, b\}$

Agents $1, \dots, M$ are of type a and agents $M + 1, \dots, N$ of type b

Society evolves along $t = 0, 1, \dots, T$ interactions

The Model

Each agent i has individual preferences towards people types.
After t interactions, those are given by the couple of values (p_t^i, q_t^i) .

The Model

Each agent i has individual preferences towards people types.
After t interactions, those are given by the couple of values (p_t^i, q_t^i) .

The value p_t^i (q_t^i) is the probability that a given individual i of type a (b) has to meet every other individual of type a (b).

The Model

Each agent i has individual preferences towards people types.
After t interactions, those are given by the couple of values (p_t^i, q_t^i) .

The value p_t^i (q_t^i) is the probability that a given individual i of type a (b) has to meet every other individual of type a (b).

We say that a link between an individual i and another j is established when both agents have met during the time of one interaction.

This happens with a probability $p_t^i p_t^j$ ($q_t^i q_t^j$) when both are of type a (b), or with $p_t^i q_t^j$ ($q_t^i p_t^j$) when their types are different.

The Model

Agent connections have a life-span of one interaction only.

After a link has eventually been established, it is used to compute the new individual preferences and then it is removed.

This feature should capture the idea of intergenerational transmission of values.

So that an agent i at time t can be interpreted as the parent of the same agent i at the following interaction $t + 1$.

The Model

Agent connections have a life-span of one interaction only.

After a link has eventually been established, it is used to compute the new individual preferences and then it is removed.

This feature should capture the idea of intergenerational transmission of values.

So that an agent i at time t can be interpreted as the parent of the same agent i at the following interaction $t + 1$.

As a consequence of each interaction, individual preferences modify under the following deterministic rule:

p_{t+1}^i (q_{t+1}^i) equals the fraction of agents of type a (b) who are connected at distance d from an agent i at time t over the total number of agents connected at the same distance and time.

The Numerical Algorithm

We define:

```
double p[COLUMN];  
double q[COLUMN];  
double R[ROW][COLUMN];  
int A[ROW][COLUMN];  
int degree[ROW];  
int A_degree[ROW], B_degree[ROW];
```

The Numerical Algorithm

At $t = 0$ we use a random Adjacency Matrix and we compute

$$q[i] = A_degree[i] / degree[i]$$

$$p[i] = B_degree[i] / degree[i]$$

The Numerical Algorithm

We create a symmetric random matrix $N \times N$ with 0 on the diagonal (called R) and we compute the Adjacency Matrix at $t = 1$ in this way:

```
/* Adjacency Matrix */
    for(i=0; i<ROW; i++)
    {
for(j=i; j<COLUMN; j++)
{
    if(j < M && i < M )
    {
link = (double) *(R+(i*COLUMN)+j) - *(p+i) * *(p+j);
} else if (j >= M && i < M )
{
link = (double) *(R+(i*COLUMN)+j) - *(q+i)* *(p+j);

} else if (j >= M && i >= M)
{
link = (double) *(R+(i*COLUMN)+j) - *(q+i) * *(q+j);
}
if (link < 0)
{
*(A+(i*COLUMN)+j) = 1;
}
}
}
```

The first Simulation

We simulate a society composed of 100 individuals: 50 of type a and 50 of type b .

The first Simulation

We simulate a society composed of 100 individuals: 50 of type a and 50 of type b .

If in the computation of the probabilities we consider as friends only the agents at a distance $d = 1$, than after N interactions we'll have a situation of *Segregation*.


The first Simulation

We simulate a society composed of 100 individuals: 50 of type a and 50 of type b .

If in the computation of the probabilities we consider as friends only the agents at a distance $d = 1$, than after N interactions we'll have a situation of *Segregation*.


This happens because when the probability of meeting an agent of the other type becomes zero it will stay zero indefinitely.

The first Simulation



$t = 2$

The first Simulation



$t = 3$

The first Simulation



$t = 100$

The next step

The next step is to see what happens if we consider as friends also the agents linked at a distance $d = 2$.

The next step

The next step is to see what happens if we consider as friends also the agents linked at a distance $d = 2$.

This case shouldn't lead to segregation.
Infact when a probability becomes zero, it can become nonzero during the following steps.

An example

Let's consider the following random Adjacency Matrix at $t = 0$

$$A = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 1 & 0 \\ 0 & 1 & 1 & 1 \\ 0 & 0 & 1 & 1 \end{pmatrix}$$

The probabilities at $d = 2$ are:

$$\begin{array}{ll} p_1 = 1 & q_1 = 0 \\ p_2 = \frac{1}{3} & q_2 = \frac{2}{3} \\ p_3 = \frac{1}{3} & q_3 = \frac{2}{3} \\ p_4 = \frac{1}{3} & q_4 = \frac{2}{3} \end{array}$$

An example

At $t = 1$ we can get

$$A = \begin{pmatrix} 1 & 1 & 0 & 0 \\ 1 & 1 & 0 & 1 \\ 0 & 0 & 1 & 1 \\ 0 & 1 & 1 & 1 \end{pmatrix}$$

The probabilities at $d = 2$ are:

$$\begin{array}{ll} p_1 = \frac{2}{3} & q_1 = \frac{1}{3} \\ p_2 = \frac{1}{2} & q_2 = \frac{1}{2} \\ p_3 = \frac{1}{3} & q_3 = \frac{2}{3} \\ p_4 = \frac{1}{2} & q_4 = \frac{1}{2} \end{array}$$

q_1 isn't zero anymore!