



Laboratório
Nacional de
Computação
Científica

COMOD
Coordenação de Modelagem Computacional

Relatório de Atividades

Servidor: Marcio Borges

Petrópolis-RJ
September 9, 2023

1 Introduction

1 INTRODUCTION

Variational auto-encoder (VAE) model is a stochastic inference and learning algorithm based on variational Bayes (VB) inference proposed by [Kingma and Welling \(2014\)](#). This is a generative technique whose central idea is the development of representations in a low-dimensional latent space that can be mapped back into a realistic-looking image.

[Higgins et al. \(2016\)](#) introduced the β -VAE, a modification of the original VAE, that introduces an adjustable hyperparameter β to balance latent channel capacity and independence constraints with reconstruction accuracy. They demonstrate that with tuned values of β ($\beta > 1$) the β -VAE outperforms VAE ($\beta = 1$).


[Makhzani et al. \(2016\)](#); [Louizos et al. \(2017\)](#); [Burda et al. \(2016\)](#); [Zheng et al. \(2019\)](#); [Vahdat and Kautz \(2020\)](#)

2 ZHANG ET AL. (2022)

Variational auto-encoder (VAE) model is a generative network based on variational Bayes (VB) inference proposed by [Kingma and Welling \(2014\)](#).

[Zhang et al. \(2022\)](#) proposed a method to reconstruct porous media based on VAE and Fisher information with good quality and efficiency.

Consider the input data $\mathbb{X} = \{\mathbf{x}^{(i)}\}_{i=1}^N$ consisting of N independent and identically distributed (*i.i.d.*) samples of the continuous (or discrete) variable \mathbf{x} .



$$Z = \mu_Z + \sigma_Z \cdot \varepsilon, \quad \text{where } \varepsilon \sim \mathbb{N}(0, 1) \quad (1)$$

The Kullback–Leibler divergence (also called relative entropy and I-divergence) is a measure of divergence between two distributions ([Kullback and Leibler, 1951](#); [Csiszar, 1975](#)):

$$\mathcal{D}_{\text{KL}}(f_{\mathbb{P}} || f_{\mathbb{Q}}) = \int_{-\infty}^{\infty} \quad (2)$$

3 Fisher Information

Zheng et al. (2019) proposed a Fisher autoencoder

3 FISHER INFORMATION

Let $f(x; \theta)$ be the probability density function of the random variable \mathbb{X} conditioned on the parameter θ . The Fisher information measures the amount of information that an observation of \mathbb{X} carries about the unknown parameter θ . The partial derivative of the natural logarithm of the likelihood function is called **score** (\mathbf{S}):

$$\mathbf{S}(x, \theta) = \frac{\partial}{\partial \theta} \log [f(x; \theta)] . \quad (3)$$

Fisher information is defined as the variance of the score \mathbf{S} :

$$\begin{aligned} \mathcal{I}(\theta) = \mathbb{E}[\mathbf{S}^2 | \theta] &= \mathbb{E} \left[\left(\frac{\partial}{\partial \theta} \log [f(x; \theta)] \right)^2 \middle| \theta \right] \\ &= \int_{\mathbb{R}} \left(\frac{\partial}{\partial \theta} \log [f(x; \theta)] \right)^2 f(x; \theta) \mathrm{d}x \end{aligned} \quad (4)$$

If $\log [f(x; \theta)]$ is twice differentiable with respect to θ and under certain regularity conditions, Fisher information can be written as

$$\mathcal{I}(\theta) = \mathbb{E} \left[-\frac{\partial^2}{\partial \theta^2} \log [f(x; \theta)] \middle| \theta \right] . \quad (5)$$

Let \mathbb{X} be a scalar Gaussian random variable *i.e.* $\mathbb{X} \sim \mathbb{N}(\mu, \sigma^2)$. Then the probability density function is parameterized by the parameters μ and σ :

$$f(x; \mu, \sigma) = \frac{1}{\sigma \sqrt{2\pi}} \exp \left[-\frac{1}{2} \left(\frac{x - \mu}{\sigma} \right)^2 \right] . \quad (6)$$


Substituting Eq. (6) in Eq. (5) where $\theta = \mu$ or σ we can compute the Fisher information for a Gaussian variable as:

3 Fisher Information


$$\begin{aligned}\mathcal{I}(\mu) &= \mathbb{E} \left[-\frac{\partial^2}{\partial \mu^2} \left[\log \left(\frac{1}{\sigma \sqrt{2\pi}} \right) - \frac{1}{2} \left(\frac{\mathbb{X} - \mu}{\sigma} \right)^2 \right] \middle| \mu \right] \\ &= \mathbb{E} \left[-\frac{\partial}{\partial \mu} \left(-\frac{\mathbb{X} - \mu}{\sigma^2} \right) \middle| \mu \right] \\ &= \mathbb{E} \left[\frac{1}{\sigma^2} \right] = \frac{1}{\sigma^2}\end{aligned}\tag{7}$$

$$\begin{aligned}\mathcal{I}(\sigma) &= \mathbb{E} \left[-\frac{\partial}{\partial \sigma} \left[-\frac{1}{\sigma} + \frac{(\mathbb{X} - \mu)^2}{\sigma^3} \right] \middle| \sigma \right] \\ &= \mathbb{E} \left[-\frac{1}{\sigma^2} + \frac{3(\mathbb{X} - \mu)^2}{\sigma^4} \middle| \sigma \right] \\ &= -\frac{1}{\sigma^2} + \frac{3\sigma^2}{\sigma^4} = \frac{2}{\sigma^2}\end{aligned}\tag{8}$$

4 KLE



(a) Squared exponential covariance



(b) Exponential covariance

Table 1: Number of KL expansion terms needed to obtain an given energy level

Energy (%)	M	
	Exponential	Squared exp.
80	201	83
90	781	120
94	1928	148
96	3416	170
98	6111	208
100	$\sim 30,000$	\sim

REFERENCES

REFERENCES

- Yuri Burda, Roger Grosse, and Ruslan Salakhutdinov. Importance weighted autoencoders, 2016.
- I. Csiszar. *I-Divergence Geometry of Probability Distributions and Minimization Problems*. *The Annals of Probability*, 3(1):146 – 158, 1975. doi: [10.1214/aop/1176996454](https://doi.org/10.1214/aop/1176996454). URL <https://doi.org/10.1214/aop/1176996454>.
- Irina Higgins, Loïc Matthey, Arka Pal, Christopher P. Burgess, Xavier Glorot, Matthew M. Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *International Conference on Learning Representations*, 2016.
- Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International conference on learning representations*, pages 14–27, 2014.
- S. Kullback and R. A. Leibler. On Information and Sufficiency. *The Annals of Mathematical Statistics*, 22(1):79 – 86, 1951. doi: [10.1214/aoms/1177729694](https://doi.org/10.1214/aoms/1177729694). URL <https://doi.org/10.1214/aoms/1177729694>.
- Christos Louizos, Kevin Swersky, Yujia Li, Max Welling, and Richard Zemel. The variational fair autoencoder, 2017.
- Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, and Ian Goodfellow. Adversarial autoencoders. In *International Conference on Learning Representations*, 2016. URL <http://arxiv.org/abs/1511.05644>.
- Arash Vahdat and Jan Kautz. Nvae: a deep hierarchical variational autoencoder. In *NIPS’20: Proceedings of the 34th International Conference on Neural Information Processing Systems*, number 1650, page 19667–19679, Red Hook, NY, USA, 2020. Curran Associates Inc. ISBN 9781713829546.
- Ting Zhang, Tu Hongyan, Xia Pengfei, and Du Yi. Reconstruction of porous media using an information variational auto-encoder. *Transport in Porous Media*, 143(2):271–295, 2022. doi: [10.1007/s11242-022-01769-5](https://doi.org/10.1007/s11242-022-01769-5). URL <https://doi.org/10.1007/s11242-022-01769-5>.
- Huangjie Zheng, Jiangchao Yao, Ya Zhang, Ivor Tsang, and Jia Wang. Understanding vaes in fisher-shannon plane. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33: 5917–5924, 07 2019. doi: [10.1609/aaai.v33i01.33015917](https://doi.org/10.1609/aaai.v33i01.33015917).

INDEX

variational auto-encoding, [1](#)