



Laboratório  
Nacional de  
Computação  
Científica

**COMOD**  
Coordenação de Modelagem Computacional

# Relatório de Atividades

**Servidor:** Marcio Borges

Petrópolis-RJ  
September 4, 2023

### 1 INTRODUCTION

Natural reservoirs display a high degree of variability in their hydraulic properties in multiple length scales [3, 10]. Such variability plays a strong impact on fluid flow patterns in subsurface formations [15]. Due to operational difficulties and high cost, direct measurements of the properties of interest are scarce and, therefore, a deterministic description of the reservoirs cannot be achieved. Alternatively, a stochastic approach should be adopted to characterize uncertainties in reservoir parameters that, according to [8], are the primary factor contributing to reservoir forecasting uncertainties. In other words, the predictability of computational models is severely limited by the lack of an adequate description of reservoir properties.

Data acquisition along with the use of high-performance computing has encouraged the growing data acquisition along with the use of high-performance computing has encouraged the use of dynamic data directly in simulations to reduce the associated uncertainties and increase the predictability of the models. Well tests, production history, pressure variation on monitors, and tracer tests, among others, are direct measures of reservoir responses and can provide important information about the flow processes.

Matching field dynamic data with reservoir simulation results is a stochastic inverse problem that can be formalized in terms of Bayesian inference and Markov chain Monte Carlo methods (McMC). The Bayesian inference is convenient in quantifying the added value of information from several sources, while McMC methods provide a computational framework for sampling from a *posteriori* distribution [36, 26].

Despite its high computational cost that, in some cases, can be prohibitive, McMC methods are regarded as the gold standard technique for Bayesian inference [35]. In 2000, Computing in Science & Engineering, a joint publication of the IEEE Computer Society and the American Institute of Physics, placed the Metropolis Algorithm on the list of the 10 algorithms with the greatest impact on the development of science and engineering practice in the 20th century (“Top Ten Algorithms of the Century” [31]).

Within this context McMC methods have been widely used in the last decades in porous media flow problems [27, 7, 8, 30, 6, 4, 34, 12, 13, 22, 9]. **McMC algorithms typically require the design of proposal mechanisms to generate candidate hypotheses. Many existing machine learning algorithms can be adapted to become proposal mechanisms [5]. This is often essential to obtain McMC algorithms that converge quickly.**

#### 1.1 Random permeability fields

Due to incomplete knowledge about the rock properties that show variability at multiple length scales, input parameters such as the permeability field,  $\kappa(\mathbf{x}, \omega)$ , are treated as random space functions with statistics inferred from geostatistical models (here  $\mathbf{x} = (x_1, x_2, x_3)^\top \in \mathbb{R}^3$  and  $\omega$  is a random element in the probability space). In line with [3] and [10] the permeability field is modeled as a log-normally distributed random space function

$$\kappa(\mathbf{x}, \omega) = \beta \exp \left[ \rho Y(\mathbf{x}, \omega) \right], \quad (1)$$

## 1.2 Karhunen-Loève expansion

---

where  $\beta, \rho \in \mathbb{R}^+$  and  $\mathbf{Y}(\mathbf{x}, \omega) \sim \mathcal{N}(\boldsymbol{\mu}_Y, \mathcal{C}_Y)$  is a Gaussian random field characterized by its mean  $\boldsymbol{\mu}_Y = \langle \mathbf{Y}(\mathbf{x}) \rangle$  and two-point covariance function

$$\mathcal{C}_Y(\mathbf{x}, \mathbf{y}) = \text{Cov}(\mathbf{Y}(\mathbf{x}), \mathbf{Y}(\mathbf{y})) = \mathbb{E}[(\mathbf{Y}(\mathbf{x}) - \langle \mathbf{Y}(\mathbf{x}) \rangle)(\mathbf{Y}(\mathbf{y}) - \langle \mathbf{Y}(\mathbf{y}) \rangle)]. \quad (2)$$

Moreover, in this work,  $\mathbf{Y}$  is a second-order stationary process [10], that is:

$$\begin{aligned} \langle \mathbf{Y}(\mathbf{x}) \rangle &= \boldsymbol{\mu}_Y, \quad (\text{constant}) \\ \mathcal{C}_Y(\mathbf{x}, \mathbf{y}) &= \mathcal{C}_Y(\|\mathbf{x} - \mathbf{y}\|) = \mathcal{C}_Y(d). \end{aligned} \quad (3)$$

## 1.2 Karhunen-Loève expansion

The Gaussian field  $\mathbf{Y}$  can be represented as a series expansion involving a complete set of deterministic functions with correspondent random coefficients using the Karhunen-Loève (KL) expansion proposed independently by [23] and [28]. It is based on the eigen-decomposition of the covariance function. Depending on how fast the eigenvalues decay one may be able to retain only a small number of terms in a truncated expansion and, consequently, this procedure may reduce the search to a smaller parameter space. In uncertainty quantification methods for porous media flows, the KL expansion has been widely used to reduce the number of parameters used to represent the permeability field [7, 8, 4, 34, 12, 13]. Another advantage of KL expansion lies on the fact that it provides orthogonal deterministic basis functions and uncorrelated random coefficients, allowing for the optimal encapsulation of the information contained in the random process into a set of discrete uncorrelated random variables [11]. This remarkable feature can be used to simplify the Metropolis-Hastings MCMC Algorithm in the sense of the search may be performed in the space of discrete uncorrelated random variables ( $\boldsymbol{\theta}$ ), no longer in the space of permeabilities which have a more complex statistical structure.

In summary, we may have the reduction of the stochastic dimension and the sampling in the space of uncorrelated Gaussian variables.

## 2 MARKOV CHAIN MONTE CARLO METHOD MCMC

The Metropolis algorithm (MH) was originally introduced by [33] for computing properties of substances composed of interacting individual molecules (when a symmetric proposal is used). This algorithm has been used extensively in statistical physics. A generalization to non-symmetric proposals was introduced by [20].

The Metropolis algorithm or one of the variants, are often used in situations where the *a priori* knowledge of the target distribution is quite limited.

The drawback of MCMC is that the acceptance rate is generally very low due to the large dimensionality of the stochastic fields. Thus, MCMC simulations usually require thousands of iterations before converging to a steady state. Each iteration involves the computation of the

## 2.1 Differential Evolution Metropolis (DE)

---

fine-scale flow problem which is very CPU demanding. This makes McMC simulations very expensive from the computational point of view. In order to overcome this difficulty, we have introduced multi-stage, multi-physics McMC methods [12, 13, 14]. The shape and size of the proposal distribution  $q(\cdot)$  is known to be very crucial for the convergence of the Markov chain corresponding the McMC algorithm [16].

Several methods have been developed in order to speed up the convergence: Adaptive Proposal (AP) [16]; Adaptive Metropolis (AM) [18]; Delayed Rejection (DR) [40, 41]; Delayed Rejection Adaptive Metropolis algorithm (DRAM) [19]; Single Component Adaptive Metropolis (SCAM) [17]; Differential Evolution Markov Chain (DE) [43, 39]; DiffeREntial Evolution Adaptive Metropolis (DREAM) [44], among others.

### 2.1 Differential Evolution Metropolis (DE)

In this paper we choose the Differential Evolution Metropolis (DE) to perform our experiments. DE is a population McMC algorithm, in which multiple chains are run in parallel. The jumps are simply a fixed multiple of the differences of two random parameter vectors that are currently in the population.

[43] developed a population-based McMC algorithm to enhance the efficiency of McMC sampling integrating Differential Evolution genetic algorithm ideas to Metropolis algorithm, resulting in the Differential Evolution Markov chain Monte Carlo method (DE) that allows for the exchange of information among multiple chains running in parallel. According to [43, 38], this choice yields an appropriate scale and orientation for the jumping distribution.

Consider the  $N_c$ ,  $d$ -dimensional, parameters  $\theta_i^t$ ,  $i = 1, 2, \dots, N_c$ , members of population  $\mathbf{X}^{(t)}$  at state  $t$ . Thus,  $\mathbf{X}^{(t)}$  is a  $N_c \times d$  matrix. To draw the samples and to ensure that the whole parameter space can be reached we consider

$$\theta = \theta_{r_1}^t + g (\theta_{r_2}^t - \theta_{r_3}^t) + e, \quad (4)$$

where  $e$  is drawn from a symmetric distribution with a small variance compared to that of the target, but with unbounded support, e.g.  $e \sim \mathbb{N}(\mathbf{0}, b\mathbf{I}_d)$  with  $b$  small. Here,  $\theta_{r_2}^t$  and  $\theta_{r_3}^t$  are randomly selected without replacement from the population current  $\mathbf{X}^{(t)}$  (the population without  $\theta_{r_1}^t$ ), i.e.  $r_1 \neq r_2 \neq r_3$ .

For large  $N_c$  and small  $b$ , the proposal (Eq. 4) thus looks like  $\theta = \theta^t + g\varepsilon$  with  $\mathbb{E}[\varepsilon] = \mathbf{0}$  and  $\text{cov}(\varepsilon) = 2\Sigma$ , the covariance matrix of the target. In particular, if  $\pi(\cdot)$  is multivariate normal, then  $g\varepsilon \sim \mathbb{N}(\mathbf{0}, 2g^2\Sigma)$  so that DE is expected to behave like RW. From the guidelines for  $c_d$  in [37] the optimal choice of  $g$  is then  $2.38/\sqrt{2d}$ . This choice of  $g$  is expected to give an acceptance probability of 0.44 for  $d = 1$ , 0.28 for  $d = 5$  and 0.23 for large  $d$ . If the initial population is drawn from the prior, DE translates the “prior population” to the “posterior population”.

## 2.1 Differential Evolution Metropolis (DE)

### 2.1.1 Autoregressive Differential Evolution Metropolis

Consider a set of high dimensional ( $d \gg 1$ ) random vectors  $\theta_i^t$ ,  $i = 1, \dots, N_c$  independent and identically distributed. More specifically,  $\theta_i^t \sim \mathcal{N}(\mathbf{0}, \sigma_{\theta^t}^2 \mathbf{I}_d)$ ,  $\forall i$ . In other words,  $\theta_i^t$  are independent standard Gaussian random variables. Using (Eq. 4) to yield the new generation (proposals) and considering that  $\sigma_e^2$  is negligible, the variance of  $\theta$  is given by:

$$\begin{aligned} \sigma_{\theta}^2 &= \sigma_{\theta_{r_1}^t}^2 + g^2 (\sigma_{\theta_{r_2}^t}^2 + \sigma_{\theta_{r_3}^t}^2) \\ &= \sigma_{\theta^t}^2 (1 + 2g^2). \end{aligned} \quad (5)$$

The previous result of Eq. (5) shows that as the iterations  $t$  evolve, there is a progressive increase in the variance of the new proposals, which can cause problems in the convergence of the method. To overcome this problem, we propose a modification of DE sampler (Eq. 4) inspired by the autoregressive version of RW (Eq. (??)):

$$\theta = \left( \sqrt{1 - 2g^2} \right) \theta_{r_1}^t + g (\theta_{r_2}^t - \theta_{r_3}^t) + e, \quad (6)$$

with the following restriction:  $g = \min \left( 2.38/\sqrt{2d}, \sqrt{1/2} \right)$ . In other words, the minimal dimension is 6 ( $d \geq 6$ ). The proposal Eq. (6) ensures that  $\sigma_{\theta}^2 = \sigma_{\theta^t}^2$ ,  $\forall i$ . The variation of  $g(d)$  and  $f(d) = \sqrt{1 - 2 \left( \frac{2.38}{\sqrt{d}} \right)^2}$  are shown in Fig. 1. Again, this method is recommended for high-dimensional problems.




Figure 1: Coefficients associated with autoregressive jump for autoregressive DE.

## 2.2 Dimensionality reduction

### 2.2 Dimensionality reduction

Another technique that has been widely used to speed up the convergence in the MCMC framework is the reduction of the stochastic dimension using the Karhunen-Loève (KL) expansion [7, 8, 4, 34, 12, 13]. The subsurface stochastic field (permeability, porosity, Young's modulus, etc.) may be represented as a series expansion involving a complete set of deterministic functions with correspondent random coefficients using the KL expansion, proposed independently by [23] and [28], which is based on the eigen-decomposition of the covariance function. If the eigenvalues decay very fast for a specific covariance function, only a small number of terms need to be retained in the truncated expansion. This procedure allows us to perform the search in a smaller parameter space.

## 3 INTRODUCTION

Variational auto-encoder (VAE) model is a stochastic inference and learning algorithm based on variational Bayes (VB) inference proposed by [24]. This is a generative technique whose central idea is the development of representations in a low-dimensional latent space that can be mapped back into a realistic-looking image.

[21] introduced the  $\beta$ -VAE, a modification of the original VAE, that introduces an adjustable hyperparameter  $\beta$  to balance latent channel capacity and independence constraints with reconstruction accuracy. They demonstrate that with tuned values of  $\beta$  ( $\beta > 1$ ) the  $\beta$ -VAE outperforms VAE ( $\beta = 1$ ).


[32, 29, 1, 46, 42]

## 4 [45]

Variational auto-encoder (VAE) model is a generative network based on variational Bayes (VB) inference proposed by [24].

[45] proposed a method to reconstruct porous media based on VAE and Fisher information with good quality and efficiency.

Consider the input data  $\mathbb{X} = \{\mathbf{x}^{(i)}\}_{i=1}^N$  consisting of  $N$  independent and identically distributed (*i.i.d.*) samples of the continuous (or discrete) variable  $\mathbf{x}$ .



$$\mathbb{Z} = \mu_{\mathbb{Z}} + \sigma_{\mathbb{Z}} \cdot \varepsilon, \quad \text{where } \varepsilon \sim \mathbb{N}(0, 1) \quad (7)$$

The Kullback–Leibler divergence (also called relative entropy and I-divergence) is a measure of divergence between two distributions [25, 2]:

$$\mathcal{D}_{\text{KL}}(f_{\mathbb{P}} || f_{\mathbb{Q}}) = \quad (8)$$

## REFERENCES

---

### REFERENCES

- [1] Yuri Burda, Roger Grosse, and Ruslan Salakhutdinov. Importance weighted autoencoders, 2016.
- [2] I. Csiszar. *I*-Divergence Geometry of Probability Distributions and Minimization Problems. *The Annals of Probability*, 3(1):146 – 158, 1975. doi: [10.1214/aop/1176996454](https://doi.org/10.1214/aop/1176996454). URL <https://doi.org/10.1214/aop/1176996454>.
- [3] G. Dagan. *Flow and transport in porous formations*. Springer-Verlag, 1989.
- [4] N. N. Das, B. P. Mohanty, and Y. Efendiev. Characterization of effective saturated hydraulic conductivity in an agricultural field using Karhunen-Loève expansion with the Markov chain Monte Carlo technique. *Water Resources Research*, 46, W06521 2010. doi: [10.1029/2008WR007100](https://doi.org/10.1029/2008WR007100).
- [5] Nando de Freitas, Pedro Hojen-Sorensen, Michael I. Jordan, and Stuart Russell. Variational mcmc, 2013.
- [6] P. Dostert, Y. Efendiev, and B. Mohanty. Efficient uncertainty quantification techniques in inverse problems for richards’ equation using coarse-scale simulation models. *Advances in Water Resources*, 32(3):329–339, 2009. doi: [DOI:10.1016/j.advwatres.2008.11.009](https://doi.org/10.1016/j.advwatres.2008.11.009).
- [7] Y. Efendiev, A. Datta-gupta, V. Ginting, X. Ma, and B. Mallick. An efficient two-stage Markov chain Monte Carlo method for dynamic data integration. *Water Resources Research*, 41:12423, 2005.
- [8] Y. Efendiev, T. Hou, and W. Luo. Preconditioning Markov Chain Monte Carlo Simulations Using Coarse-Scale Models. *SIAM J. Sci. Comput.*, 28:776–803, 2006.
- [9] A. A. Emerick and A. C. Reynolds. Investigation of the sampling performance of ensemble-based methods with a simple reservoir model. *Computational Geosciences*, 17(2):325–350, 2013. ISSN 1420-0597. doi: [10.1007/s10596-012-9333-z](https://doi.org/10.1007/s10596-012-9333-z). URL <http://dx.doi.org/10.1007/s10596-012-9333-z>.
- [10] L. W. Gelhar. *Stochastic subsurface hydrology*. Englewood Cliffs. Prentice-Hall, 1993.
- [11] R. Ghanem and P.D. Spanos. *Stochastic Finite Element: A Spectral Approach*. Springer, New York, 1991.
- [12] V. Ginting, F. Pereira, M. Presho, and S. Wo. Application of the two-stage Markov chain Monte Carlo method for characterization of fractured reservoirs using a surrogate flow model. *Computational Geosciences*, 15:691–707, 2011.
- [13] V. Ginting, F. Pereira, and A. Rahunathan. Multiple Markov chains Monte Carlo approach for flow forecasting in porous media. *Procedia Computer Science*, 5:707–716, 2012.



## REFERENCES

---

- [14] V. Ginting, F. Pereira, and A. Rahunathan. A multi-stage bayesian prediction framework for subsurface flows. *International Journal for Uncertainty Quantification*, 2013. to appear.
- [15] J. Glimm, W. B. Lindquist, F. Pereira, and R. Peierls. The multi-fractal hypothesis and anomalous diffusion. *Mat. Applic. Comp.*, 11(2):189–207, 1992.
- [16] H. Haario, E. Saksman, and J. Tamminen. Adaptive proposal distribution for random walk metropolis algorithm. *Computational Statistics*, 14(3):375–395, 1999. doi: [10.1007/s001800050022](https://doi.org/10.1007/s001800050022). URL <http://dx.doi.org/10.1007/s001800050022>.
- [17] H. Haario, E. Saksman, and J. Tamminen. Componentwise adaptation for high dimensional mcmc. *Computational Statistics*, 20(2):265–273, 2005. ISSN 1613-9658. doi: [10.1007/BF02789703](https://doi.org/10.1007/BF02789703). URL <http://dx.doi.org/10.1007/BF02789703>.
- [18] Heikki Haario, Eero Saksman, and Johanna Tamminen. An adaptive metropolis algorithm. *Bernoulli*, 7(2):223–242, 04 2001. URL <http://projecteuclid.org/euclid.bj/1080222083>.
- [19] Heikki Haario, Marko Laine, Antonietta Mira, and Eero Saksman. Dram: Efficient adaptive mcmc. *Statistics and Computing*, 16(4):339–354, 2006. ISSN 1573-1375. doi: [10.1007/s11222-006-9438-0](https://doi.org/10.1007/s11222-006-9438-0). URL <http://dx.doi.org/10.1007/s11222-006-9438-0>.
- [20] W. K. Hastings. Monte carlo sampling methods using markov chains and their applications. *Biometrika*, 57(1):97, 1970.
- [21] Irina Higgins, Loïc Matthey, Arka Pal, Christopher P. Burgess, Xavier Glorot, Matthew M. Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *International Conference on Learning Representations*, 2016.
- [22] M. A. Iglesias, K. J. H. Law, and A. M. Stuart. Evaluation of gaussian approximations for data assimilation in reservoir models. *Computational Geosciences*, pages 1–35, 2013. doi: [10.1007/s10596-013-9359-x](https://doi.org/10.1007/s10596-013-9359-x).
- [23] K. Karhunen. Zur spektraltheorie stochastischer prozesse. *Ann. Acad. Sci. Fennicae*, 1946.
- [24] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International conference on learning representations*, pages 14–27, 2014.
- [25] S. Kullback and R. A. Leibler. On Information and Sufficiency. *The Annals of Mathematical Statistics*, 22(1):79 – 86, 1951. doi: [10.1214/aoms/1177729694](https://doi.org/10.1214/aoms/1177729694). URL <https://doi.org/10.1214/aoms/1177729694>.
- [26] Gaisheng Liu, Yan Chen, and Dongxiao Zhang. Investigation of flow and transport processes at the made site using ensemble kalman filter. *Advances in Water Resources*, 31(7): 975–986, 2008. doi: [10.1016/j.advwatres.2008.03.006](https://doi.org/10.1016/j.advwatres.2008.03.006).

## REFERENCES

---

- [27] N. Liu and D. S. Oliver. Evaluation of monte carlo methods for assessing uncertainty. *SPE Journal*, 8:188–195, 2003. doi: [10.2118/84936-PA](https://doi.org/10.2118/84936-PA).
- [28] M. M. Loève. *Probability Theory*. Princeton, N.J., 1955.
- [29] Christos Louizos, Kevin Swersky, Yujia Li, Max Welling, and Richard Zemel. The variational fair autoencoder, 2017.
- [30] X. Ma, M. Al-Harbi, A. Datta-Gupta, and Y. Efendiev. An efficient two-stage sampling method for uncertainty quantification in hystory matching geological models. *SPE Journal*, 2008.
- [31] G. Madey, X. Xiang, S. E. Cabaniss, and Y. Huang. Agent-based scientific simulation. *Computing in Science & Engineering*, 2(01):22–29, jan 2005. ISSN 1558-366X. doi: [10.1109/MCSE.2005.7](https://doi.org/10.1109/MCSE.2005.7).
- [32] Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, and Ian Goodfellow. Adversarial autoencoders. In *International Conference on Learning Representations*, 2016. URL <http://arxiv.org/abs/1511.05644>.
- [33] Nicholas Metropolis, Arianna W. Rosenbluth, Marshall N. Rosenbluth, Augusta H. Teller, and Edward Teller. Equation of state calculations by fast computing machines. *The Journal of Chemical Physics*, 21(6):1087–1092, 1953. doi: [10.1063/1.1699114](https://doi.org/10.1063/1.1699114). URL <http://dx.doi.org/10.1063/1.1699114>.
- [34] A. Mondal, Y. Efendiev, B. Mallick, and A. Datta-Gupta. Bayesian uncertainty quantification for flows in heterogeneous porous media using reversible jump Markov chain Monte Carlo methods. *Advances in Water Resources*, 33(3):241 – 256, 2010.
- [35] Christopher Nemeth and Paul Fearnhead. Stochastic gradient markov chain monte carlo. *Journal of the American Statistical Association*, 116(533):433–450, 2021. doi: [10.1080/01621459.2020.1847120](https://doi.org/10.1080/01621459.2020.1847120). URL <https://doi.org/10.1080/01621459.2020.1847120>.
- [36] C. P. Robert and G. Casella. *Monte Carlo Statistical Methods (Springer Texts in Statistics)*. Springer-Verlag New York, Inc., Secaucus, NJ, USA, 2005.
- [37] Gareth O. Roberts and Jeffrey S. Rosenthal. Optimal scaling for various metropolis-hastings algorithms. *Statist. Sci.*, 16(4):351–367, 11 2001. doi: [10.1214/ss/1015346320](https://doi.org/10.1214/ss/1015346320). URL <http://dx.doi.org/10.1214/ss/1015346320>.
- [38] Cajo J. F. Ter Braak. A markov chain monte carlo version of the genetic algorithm differential evolution: easy bayesian computing for real parameter spaces. *Statistics and Computing*, 16(3):239–249, 2006. ISSN 1573-1375. doi: [10.1007/s11222-006-8769-1](https://doi.org/10.1007/s11222-006-8769-1). URL <http://dx.doi.org/10.1007/s11222-006-8769-1>.

## REFERENCES

---

- [39] Cajo J. F. Ter Braak. A markov chain monte carlo version of the genetic algorithm differential evolution: easy bayesian computing for real parameter spaces. *Statistics and Computing*, 16(3):239–249, Sep 2006. ISSN 1573-1375. doi: [10.1007/s11222-006-8769-1](https://doi.org/10.1007/s11222-006-8769-1). URL <https://doi.org/10.1007/s11222-006-8769-1>.
- [40] Luke Tierney. Markov chains for exploring posterior distributions. *Annals of Statistics*, 22:1701–1762, 1994.
- [41] Luke Tierney and Antonietta Mira. Some adaptive monte carlo methods for bayesian inference. *Statistics in Medicine*, 18(17-18):2507–2515, 1999. ISSN 1097-0258. doi: [10.1002/\(SICI\)1097-0258\(19990915/30\)18:17/18<2507::AID-SIM272>3.0.CO;2-J](https://doi.org/10.1002/(SICI)1097-0258(19990915/30)18:17/18<2507::AID-SIM272>3.0.CO;2-J).
- [42] Arash Vahdat and Jan Kautz. Nvae: a deep hierarchical variational autoencoder. In *NIPS'20: Proceedings of the 34th International Conference on Neural Information Processing Systems*, number 1650, page 19667–19679, Red Hook, NY, USA, 2020. Curran Associates Inc. ISBN 9781713829546.
- [43] J.A. Vrugt, H. V. Gupta, W. Bouten, and S. Sorooshian. A shuffled complex evolution Metropolis algorithm for optimization and uncertainty assessment of hydrologic model parameters. *Water Resources Research*, 39(8):1201–1217, 2003.
- [44] Jasper A. Vrugt, Cajo J. F. Ter Braak, Martyn P. Clark, James M. Hyman, and Bruce A. Robinson. Treatment of input uncertainty in hydrologic modeling: Doing hydrology backward with markov chain monte carlo simulation. *Water Resources Research*, 44(12):n/a–n/a, 2008. ISSN 1944-7973. doi: [10.1029/2007WR006720](https://doi.org/10.1029/2007WR006720). URL <http://dx.doi.org/10.1029/2007WR006720>. W00B09.
- [45] Ting Zhang, Tu Hongyan, Xia Pengfei, and Du Yi. Reconstruction of porous media using an information variational auto-encoder. *Transport in Porous Media*, 143(2):271–295, 2022. doi: [10.1007/s11242-022-01769-5](https://doi.org/10.1007/s11242-022-01769-5). URL <https://doi.org/10.1007/s11242-022-01769-5>.
- [46] Huangjie Zheng, Jiangchao Yao, Ya Zhang, Ivor Tsang, and Jia Wang. Understanding vaes in fisher-shannon plane. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33:5917–5924, 07 2019. doi: [10.1609/aaai.v33i01.33015917](https://doi.org/10.1609/aaai.v33i01.33015917).

## INDEX

second-order stationary process, [2](#)

variational auto-encoding, [5](#)