



Laboratório
Nacional de
Computação
Científica

COMOD
Coordenação de Modelagem Computacional

Relatório de Atividades

Servidor: Marcio Borges

Petrópolis-RJ
September 30, 2023

1 Introduction

1 INTRODUCTION

Variational auto-encoder (VAE) model is a stochastic inference and learning algorithm based on variational Bayes (VB) inference proposed by [Kingma and Welling \(2014\)](#). This is a generative that enforces a *prior* on the low-dimensional latent space that can be mapped back into a realistic-looking image. Therefore, the most important characteristic of VAEs, in the context of Monte Carlo methods with Markov chains, is their ability to represent high-dimensional parametric spaces in a low-dimensional latent space.


[Higgins et al. \(2016\)](#) introduced the β -VAE, a modification of the original VAE, that introduces an adjustable hyperparameter β to balance latent channel capacity and independence constraints with reconstruction accuracy. They demonstrate that with tuned values of β ($\beta > 1$) the β -VAE outperforms VAE ($\beta = 1$).

[Makhzani et al. \(2016\)](#); [Louizos et al. \(2017\)](#); [Burda et al. \(2016\)](#); [Zheng et al. \(2019\)](#); [Vahdat and Kautz \(2020\)](#)

2 ZHANG ET AL. (2022)

[Zhang et al. \(2022\)](#) proposed a method to reconstruct porous media based on VAE and Fisher information with good quality and efficiency.

Consider the input data set $\mathbb{X} = \{\mathbf{x}^{(i)}\}_{i=1}^N$ ($\mathbf{x}^{(i)} \in \mathbb{R}^{N_x}$) consisting of N independent and identically distributed (*i.i.d.*) samples of the continuous (or discrete) variable drawn from the prior distribution $p(\mathbf{x})$.



$$\mathbb{Z} = \mu_{\mathbb{Z}} + \sigma_{\mathbb{Z}} \cdot \varepsilon, \quad \text{where } \varepsilon \sim \mathbb{N}(0, 1) \quad (1)$$

The reconstruction loss is used to ensure that input image is reconstructed at the output one and, here, is given by the mean squared error (MSE):

$$\mathcal{L}_{\text{MSE}}(\theta, \phi, \mathbf{x}) = \frac{1}{N_b} \sum_{i=1}^{N_b} [\mathbf{x}^{(i)} - D_{\phi}(E_{\theta}(\mathbf{x}^{(i)}))]^2, \quad (2)$$

where \mathbf{E} and \mathbf{D} represent the encoder and decoder and θ, ϕ are their parameters, respectively.

In VAE, we assume that both *prior* distribution $p(\mathbb{Z}) \simeq \mathbb{N}(0, 1)$ and *posterior* approximation of the latent space follow a standard Gaussian distribution, i.e., $q(\mathbb{Z}|\mathbf{x}) \simeq \mathbb{N}(0, 1)$.

To keep the encoder outputs \mathbb{Z} close to a standard normal distribution and sufficiently diverse we use the Kullback–Leibler divergence (\mathcal{D}_{KL} , also called relative entropy and I-divergence). \mathcal{D}_{KL} is a measure of divergence between two distributions (Kullback and Leibler, 1951; Csiszar, 1975):

$$\mathcal{D}_{\text{KL}}(p(\mathbb{Z})||\mathbb{N}(0, 1)) = -\frac{1}{2} \sum_{i=1}^{N_z} [1 + \log(\sigma_{\mathbb{Z}_i}^2) - \mu_{\mathbb{Z}_i}^2 - \sigma_{\mathbb{Z}_i}^2] \quad (3)$$

Zheng et al. (2019) proposed a Fisher autoencoder Xia and Zabaras (2022); Xu et al. (2023); Xia et al. (2023)

Xia et al. (2023) proposed a multiscale Bayesian inference approach based on a multiscale deep generative model (MDGM)

REFERENCES

REFERENCES

- Yuri Burda, Roger Grosse, and Ruslan Salakhutdinov. Importance weighted autoencoders, 2016.
- I. Csiszar. *I-Divergence Geometry of Probability Distributions and Minimization Problems. The Annals of Probability*, 3(1):146 – 158, 1975. doi: [10.1214/aop/1176996454](https://doi.org/10.1214/aop/1176996454). URL <https://doi.org/10.1214/aop/1176996454>.
- Irina Higgins, Loïc Matthey, Arka Pal, Christopher P. Burgess, Xavier Glorot, Matthew M. Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. In *International Conference on Learning Representations*, 2016.
- Diederik P Kingma and Max Welling. Auto-encoding variational bayes. In *International conference on learning representations*, pages 14–27, 2014.
- S. Kullback and R. A. Leibler. On Information and Sufficiency. *The Annals of Mathematical Statistics*, 22(1):79 – 86, 1951. doi: [10.1214/aoms/1177729694](https://doi.org/10.1214/aoms/1177729694). URL <https://doi.org/10.1214/aoms/1177729694>.
- Christos Louizos, Kevin Swersky, Yujia Li, Max Welling, and Richard Zemel. The variational fair autoencoder, 2017.
- Alireza Makhzani, Jonathon Shlens, Navdeep Jaitly, and Ian Goodfellow. Adversarial autoencoders. In *International Conference on Learning Representations*, 2016. URL <http://arxiv.org/abs/1511.05644>.
- Arash Vahdat and Jan Kautz. Nvae: a deep hierarchical variational autoencoder. In *NIPS’20: Proceedings of the 34th International Conference on Neural Information Processing Systems*, number 1650, page 19667–19679, Red Hook, NY, USA, 2020. Curran Associates Inc. ISBN 9781713829546.
- Yingzhi Xia and Nicholas Zabaras. Bayesian multiscale deep generative model for the solution of high-dimensional inverse problems. *Journal of Computational Physics*, 455:111008, 2022. ISSN 0021-9991. doi: <https://doi.org/10.1016/j.jcp.2022.111008>. URL <https://www.sciencedirect.com/science/article/pii/S0021999122000705>.
- Yingzhi Xia, Qifeng Liao, and Jinglai Li. Vi-dgp: A variational inference method with deep generative prior for solving high-dimensional inverse problems. *Journal of Scientific Computing*, 97(16), 2023.
- Zhihang Xu, Yingzhi Xia, and Qifeng Liao. A domain-decomposed VAE method for bayesian inverse problems. *CoRR*, abs/2301.05708, 2023. doi: [10.48550/arXiv.2301.05708](https://doi.org/10.48550/arXiv.2301.05708). URL <https://doi.org/10.48550/arXiv.2301.05708>.

REFERENCES

- Ting Zhang, Tu Hongyan, Xia Pengfei, and Du Yi. Reconstruction of porous media using an information variational auto-encoder. *Transport in Porous Media*, 143(2):271–295, 2022. doi: [10.1007/s11242-022-01769-5](https://doi.org/10.1007/s11242-022-01769-5). URL <https://doi.org/10.1007/s11242-022-01769-5>.
- Huangjie Zheng, Jiangchao Yao, Ya Zhang, Ivor Tsang, and Jia Wang. Understanding vaes in fisher-shannon plane. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33: 5917–5924, 07 2019. doi: [10.1609/aaai.v33i01.33015917](https://doi.org/10.1609/aaai.v33i01.33015917).

INDEX

variational auto-encoding, [1](#)