



Course name: **Python programming and analytics by Rahul Sir**

Topic name: **basic of statistics**

Video name: **basic of statistics(correlation)**

Video length: **51 minutes 26 seconds**

Content of the video: Mean, Median, Mode

Standard Deviation, Variance

how to import matplotlib and seaborn?

Outliers, correlation

What are NumPy and pandas?

NumPy and pandas are mathematical operation package in python programming.

pandas include three data structures: Data Frame, Series, Index. In pandas, Series and Data Frame elements can be altered but Index elements can't be altered

Both NumPy and Pandas have emerged to be essential libraries for any scientific computation, including machine learning, in python due to their intuitive syntax and high-performance matrix computation capabilities.

By using the **import function**, you can import the NumPy and Pandas package in the notebook.

Like, `import NumPy as np`
`import Pandas as pd`

how to import the data in a Jupyter notebook?

```
data = pd.read_csv("C:/Users/Sahibjot/Desktop/wine data.csv")
```

`Pd.read_csv()` function is used to import the data. In the brackets, you need to mention the location of the data file in your computer/laptop and it must be in quotes.

If you don't know how to find the location of the data file;


Right click on the data file, there you will see properties click on that then there you can find the location column. copy the location

How you can read the data?

`data.head()`

	SN	country	points	price	province	region_1	variety	winery
0	1	US	96	235	California	Napa Valley	Cabernet Sauvignon	Heitz
1	2	Spain	96	110	Northern Spain	Toro	Tinta de Toro	Bodega Carmen Rodríguez
2	3	US	96	90	California	Knights Valley	Sauvignon Blanc	Macauley
3	4	US	96	65	Oregon	Willamette Valley	Pinot Noir	Ponzi
4	5	France	95	66	Provence	Bandol	Provence red blend	Domaine de la Bégude

Mean: The mean (average) of a data set is found by adding all numbers in the data set and then dividing by the number of values in the set. If you want to find the mean of the price column in the above pictured data, then first you need to find the sum and then count and then for mean, divide the sum by count. Like this,



```
sum_price = sum(price)
```

```
sum_price
```

```
1862482
```

```
count = len(price)
```

```
count
```

```
53518
```

```
average = sum_price/count
```

```
average
```


```
34.80103890279906
```

With the help of packages,

```
mean = np.mean(price)
```

```
mean
```

```
34.80103890279906
```



```
from statistics import mean
```

```
import statistics as st
```

```
st.mean(price)
```

```
34.80103890279906
```



Median: The median is a simple measure of central tendency. To find the median, we arrange the observations in order from smallest to largest value. If there is an odd number of observations, the median is the middle value. If there is an even number of observations, the median is the average of the two middle values.

```
n = len(price)    #(n+1)/2  
n
```

53518

```
sorted_prices = np.sort(price)
```

```
median = (n+1)/2  
median
```

26759.5

```
sorted_prices[int(median)]
```


25

```
Median_1 = np.median(price)  
Median_1
```

25.0

```
st.median(price)
```

25.0



Before median calculation, you need to sort the data either in ascending order or descending order

Mode: Mode is the value which occurs most frequently in a set of observations. Simply put, it is the number which is repeated most, i.e. the number with the highest frequency.

```
from statistics import mode  
Mode = mode(price)
```

Mode

20

Outliers: Outliers are data values that differ greatly from the majority of a set of data. These values fall outside of an overall trend that is present in the data. Strong Outliers show extreme deviation from the rest of a data set. If a data value is an outlier, but not a strong outlier, then we say that the value is a weak outlier.

```
min_price = min(price)
max_price = max(price)

print(min_price, max_price)
```

4 2300

Range: The difference between the lowest and highest values.

```
price_range = max_price - min_price
print(price_range)
```

2296

Quartile and inter-quartile range : The interquartile range (IQR) is a measure of variability, based on dividing a data set into [quartiles](#).

Quartiles divide a rank-ordered data set into four equal parts. The values that divide each part are called the first, second, and third quartiles; and they are denoted by Q1, Q2, and Q3, respectively.

- Q1 is the "middle" value in the *first* half of the rank-ordered data set.
- Q2 is the [median](#) value in the set.
- Q3 is the "middle" value in the *second* half of the rank-ordered data set.

The interquartile range is equal to Q3 minus Q1

```
print(price.quantile([0.25]))
print(price.quantile([0.50]))
print(price.quantile([0.75]))
print(price.quantile([1]))
print(price.quantile([0]))
```

```
0.25    17.0
Name: price, dtype: float64
0.5     25.0
Name: price, dtype: float64
0.75    40.0
Name: price, dtype: float64
1.0    2300.0
Name: price, dtype: float64
0.0     4.0
Name: price, dtype: float64
```

```
price_quantile_Q1 = price.quantile([0.25])
price_quantile_Q3 = price.quantile([0.75])
```

```
IQR = price_quantile_Q3[0.75]-price_quantile_Q1[0.25]
IQR
```

```
23.0
```

Standard deviation: The standard deviation is also a measure of the spread of your observations, but is a statement of how much your data deviates from a typical data point. That is to say, the standard deviation summarizes how much your data differs from the mean. This relationship to the mean is apparent in standard deviation's calculation.

Standard deviation is a measure that is used to quantify the amount of variation or dispersion of a set of data values.

```
print(stdev(price))
```

```
41.453611192987836
```

```
std_dev = np.std(price)
```

```
std_dev
```

```
41.45322390455368
```

```
import statistics  
from statistics import stdev
```

```
stdev(price)
```

```
41.45361119298847
```

Variance: Variance and standard deviation are almost the exact same thing!

Variance is just the square of the standard deviation. Likewise, variance and standard deviation represent the same thing — a measure of spread — but it's worth noting that the units are different. Whatever units your data are in, standard deviation will be the same, and variation will be in that units-squared.

variance is the expectation of the squared deviation of a random variable from its mean

```
variance = np.square(std_dev)
```

```
variance
```

```
1718.3697720810608
```

```
from statistics import variance  
variance(price)
```

```
1718.4018809394586
```

```
data.dtypes
```

```
SN          int64
country     object
points      int64
price       int64
province    object
region_1    object
variety     object
winery      object
dtype: object
```

Data.dtypes is used when you want to find the data type of each column in your data

```
data.describe()
```

	SN	points	price
count	53518.00000	53518.000000	53518.000000
mean	26759.50000	88.186106	34.801039
std	15449.46019	3.102856	41.453611
min	1.00000	80.000000	4.000000
25%	13380.25000	86.000000	17.000000
50%	26759.50000	88.000000	25.000000
75%	40138.75000	90.000000	40.000000
max	53518.00000	100.000000	2300.000000

Data.describe() function is used to view some basic statistical details like percentile, mean, std etc. of a data frame or a series of numeric values.

How to create Boxplot?

Boxplot is a graph that gives you a good indication of how the values in the data are spread out. Boxplots are a standardized way of displaying the distribution of data based on "minimum", first quartile (Q1), median, third quartile (Q3), and "maximum".


Code:

```
import matplotlib.pyplot as plt
plt.figure(figsize = (5, 10))
data['price'].plot(kind = "box")
```

Import **matplotlib** for
creating graphs

Output:


<matplotlib.axes._subplots.AxesSubplot at 0x1e5d9fd2400>



Other graphs:

```
plt.figure(figsize = (10, 5))  
data['price'].plot(kind = "hist")
```

<matplotlib.axes._subplots.AxesSubplot at 0x15ca71d0>




Matplotlib and seaborn:

Matplotlib is a Python 2D plotting library which produces publication quality figures in a variety of hardcopy formats and interactive environments across platforms. Matplotlib tries to make easy things easy and hard things possible. You can generate plots, histograms, power spectra, bar charts, error charts, scatterplots, etc., with just a few lines of code

Seaborn is a Python data visualization library based on [matplotlib](#). It provides a high-level interface for drawing attractive and informative statistical graphics.

Correlation: Correlation is used to test relationships between [quantitative variables](#) or [categorical variables](#). In other words, it's a measure of how things are related. The study of how variables are correlated is called correlation analysis

A **correlation coefficient** is a way to put a value to the relationship. Correlation coefficients have a value of between -1 and 1. A "0" means there is no relationship between the variables at all, while -1 or 1 means that there is a perfect negative or positive correlation (negative or positive correlation here refers to the type of graph the relationship will produce).




Creating a correlation matrix using *seaborn*:

```
import seaborn as sns
corrmat = data.corr()

f, ax = plt.subplots(figsize =(9, 8))
sns.heatmap(corrmat)
```

<matplotlib.axes._subplots.AxesSubplot at 0x14a4b0b8>



Seaborn used to create correlation matrix which allows to quickly observe the relationship between every variable of your matrix.

In the above pictured correlation matrix, you can see that the correlation between the two same columns shows pale pink color which means 1.0 value that is perfect correlation. correlation between the SN and points column is 0.0 represented by black color means no correlation. The correlation between price and points column is around 0.4 denoted by dark pink color means medium correlation