Solution #1

```
public class Pig1 {
	public static void main(String[] args) {
		int p1OVERALL_SCORE = 0, p2OVERALL_SCORE = 0, TURN_SCORE = 0, playerTurn = 1;
		Random a = new Random();
		while (p1OVERALL_SCORE < 100 && p2OVERALL_SCORE < 100) {
			while (playerTurn == 1 && p1OVERALL_SCORE < 100) {
				String response = JOptionPane.showInputDialog("Roll or Hold");

				if (response.equals("Roll")) {
					TURN_SCORE = doTurn(TURN_SCORE);
					p1OVERALL_SCORE += TURN_SCORE;
					if (checkPig(TURN_SCORE) == true && p1OVERALL_SCORE < 100) {
						playerTurn = 2;
						System.out.println("Player 2's turn is next.");
					}

					System.out.println("Player 1's score: " + p1OVERALL_SCORE);
					TURN_SCORE = 0;
				} else if (response.equals("Hold")) {
					playerTurn = 2;
					System.out.println("Player 1 holds. Player 2's turn is next.");
				}
			}
			while (playerTurn == 2 && p2OVERALL_SCORE < 100) {
				int computerChoose = a.nextInt(2) + 1;

				if (computerChoose == 1) {
					TURN_SCORE = doTurn(TURN_SCORE);
					p2OVERALL_SCORE += TURN_SCORE;
					if (checkPig(TURN_SCORE) == true && p2OVERALL_SCORE < 100) {
						playerTurn = 1;
						System.out.println("Player 1's turn is next.");
					}
					TURN_SCORE = 0;
					System.out.println("Player 2 score: " + p2OVERALL_SCORE);
				} else if (computerChoose == 2) {
					playerTurn = 1;
					System.out.println("Player 2 holds. Player 1's turn is next.");
				}
			}
		}
		if (p1OVERALL_SCORE >= 100) {
			System.out.println("Player 1 wins!");
		} else if (p2OVERALL_SCORE >= 100) {
			System.out.println("Player 2 wins!");
		}
	}
```

(More code on back).

```
	public static int doTurn(int TURN_SCORE) {
		Random die = new Random();
		int die1 = die.nextInt(6) + 1;
		int die2 = die.nextInt(6) + 1;
		if (die1 != 1 && die2 != 1 && die1 != die2) {
			return die1 + die2;
		} else if ((die1 == 1 && die2 != 1) || (die1 != 1 && die2 == 1)) {
			return 1;
		} else if (die1 == die2 && die1 != 1) {
			return (die1 + die2) * 2;
		}
		return 0;

	}

	public static boolean checkPig(int TURN_SCORE) {
		return TURN_SCORE == 0 || TURN_SCORE == 1;

	}
}
```

Solution #2

```
public class Pig1 {
	static int[] playerOverallScore = new int[2];
	static int[] playerTurnScore = new int[2];
	static int playerTurn = 0;
	static boolean endturn = false;
	static Random g = new Random();
	static Scanner userIn = new Scanner(System.in);
	static int die1, die2;

	public static void main(String[] args) {
		do {
			printPlayerTurn();
			rollDice();
			printDice();
			checkDice(die1, die2);

			if (endturn) {
				System.out.println("It is now the other Player's turn\n\n");
				turnEnded();
			} else {
				System.out.println("Do you want to roll again?\nyou have a turn score of "
									+ getPlayerTurnScore(pTurn())
									+ " and with an Overall score of "
									+ getPlayerOverScore(pTurn()));

				if (userInputEqualsNo()) {
					turnEnded();
				}
			}
		} while (noWinner());

		System.out.println("CONGRATS Player " + (pTurn() + 1) + " you have WON");
	}

	public static void printPlayerTurn() {
		System.out.println("Player" + ((pTurn()) + 1));
	}
(more code on back)
```

```
public static void printDice() {
	System.out.println("your dice sum is " + (die1 + die2)
			+ " with a roll of " + die1 + " and " + die2);
}

public static boolean userInputEqualsNo() {
	if (userIn.next().equals("no")) {
		return true;
	}
	return false;
}

public static void rollDice() {
	die1 = rollDie();
	die2 = rollDie();
}

public static void turnEnded() {
	addToPlayerOverScore(pTurn(), getPlayerTurnScore(pTurn()));
	playerTurn++;
	endturn = false;
	resetPlayerTurnScore(pTurn());
}

public static int pTurn() {
	return playerTurn % 2;
}

public static void checkDice(int die1, int die2) {
	if (die1 == 1 || die2 == 1) {

		playerTurnScore[pTurn()] += 1;
		if (die1 == die2) {
			playerTurnScore[pTurn()] = 0;
		}
		endturn = true;
	} else if (die1 == die2) {
		playerTurnScore[pTurn()] += (die1 + die2) * 2;
	} else {
```

```
                playerTurnScore[pTurn()] += die1 + die2;
            }
        }

        public static void resetPlayerTurnScore(int player) {
            playerTurnScore[player] = 0;
        }

        public static int getPlayerOverScore(int player) {
            return playerOverallScore[player];
        }

        public static void addToPlayerOverScore(int player, int score) {
            playerOverallScore[player] += score;
        }

        public static int getPlayerTurnScore(int player) {
            return playerTurnScore[player];
        }

        public static void addToPlayerTurnScore(int player, int score) {
            playerTurnScore[player] += score;
        }

        public static boolean noWinner() {
            if (playerOverallScore[0] >= 100 || playerOverallScore[1] >= 100) {
                playerTurn--;
                return false;
            }
            return true;
        }

        public static int rollDie() {
            return g.nextInt(6) + 1;
        }
}
```

Solution #3

```
public class Pig1 {
	static int playerTurn = 1, roundScore = 0;
	static int player1Score = 0, player2Score = 0;

	public static void main(String[] args) {
		String response;
		int die1, die2;

		while (player1Score < 100 && player2Score < 100) {
			do {
				response = JOptionPane
					.showInputDialog("Player "
							+ playerTurn
							+ " would you like to roll or hold? Press 1 to hold and 2 to
							   roll. \nPlayer 1 Score: "
							+ player1Score + "\nPlayer 2 Score: "
							+ player2Score + "\nCurrent Round Score: "
							+ roundScore);
				if (Integer.parseInt(response) == 1) {
					addToPlayerScore(playerTurn, roundScore);
					roundScore = 0;
					switchPlayerTurn();
					break;
				} else if (Integer.parseInt(response) == 2) {
					die1 = rollDie();
					die2 = rollDie();
					JOptionPane.showMessageDialog(null, "You rolled a " + die1
							+ " and a " + die2);
					checkRollPossibilities(die1, die2);
				}

			} while (Integer.parseInt(response) == 2);
		}
	}
```

(more code on back).

```
	public static void checkRollPossibilities(int die1, int die2) {
		if (die1 == 1 && die2 == 1) {
			addToPlayerScore(playerTurn, 0);
			roundScore = 0;
			switchPlayerTurn();
		}
		if (die1 == 1 || die2 == 1) {
			addToPlayerScore(playerTurn, roundScore + 1);
			roundScore = 0;
			switchPlayerTurn();
		}
		if (die1 != die2 && die1 != 1)
			roundScore += die1 + die2;
		if (die1 == die2 && die1 != 1)
			roundScore += 2 * (die1 + die2);

	}

	public static int rollDie() {
		Random rand = new Random();
		return rand.nextInt(6) + 1; // + 1 shifts range of values from 0-5 to
					    // 1-6
	}

	public static void addToPlayerScore(int player, int roundScore) {
		if (player == 1)  player1Score += roundScore;
		if (player == 2)  player2Score += roundScore
	}

	public static void switchPlayerTurn() {
		if (playerTurn == 1)   playerTurn = 2;
		if (playerTurn == 2)   playerTurn = 1;
	}

}
```