

# 2657 Functions

Ananda Mahto

July 29, 2012

# Contents

<b>I</b>	<b>Function Descriptions and Examples</b>	<b>1</b>
	concat.split . . . . .	3
	What it Does . . . . .	3
	Arguments . . . . .	3
	Examples . . . . .	3
	Advanced Usage . . . . .	6
	References . . . . .	7
	df.sorter . . . . .	8
	What it Does . . . . .	8
	Arguments . . . . .	8
	Examples . . . . .	8
	To Do . . . . .	10
	multi.freq.table . . . . .	11
	What it Does . . . . .	11
	Arguments . . . . .	11
	Examples . . . . .	11
	To Do . . . . .	13
	References . . . . .	13
	row.extractor . . . . .	14
	What it Does . . . . .	14
	Arguments . . . . .	14
	Examples . . . . .	14
	References . . . . .	15
<b>II</b>	<b>The Functions</b>	<b>17</b>
	Where to Get the Functions . . . . .	19
	concat.split . . . . .	20
	df.sorter . . . . .	22
	multi.freq.table . . . . .	23
	row.extractor . . . . .	24

<b>III</b>	<b>Snippets and Tips</b>	<b>27</b>
Snippets		29
Load All Scripts and Data Files From Multiple Directories		29
Convert a List of Data Frames Into Individual Data Frames		29
Convert a Data Frame Into a List With Each Column Becoming a List Item		30
Rename an Object in the Workplace		31
Tips		32
Batch Convert Factor Variables to Character Variables		32
Using Reduce to Merge Multiple Data Frames at Once		32

## Part I

# Function Descriptions and Examples



## concat.split

### What it Does

The `concat.split` function takes a column with multiple values, splits the values into a list or into separate columns, and returns a new `data.frame`.

### Arguments

- `data`: the source `data.frame`.
- `split.col`: the variable that needs to be split; can be specified either by the column number or the variable name.
- `to.list`: logical; should the split column be returned as a single variable list (named “original-variable.list”) or multiple new variables? If `to.list` is `TRUE`, the `mode` argument is ignored and a list of the original values are returned.
- `mode`: can be either `binary` or `value` (where `binary` is default and it recodes values to 1 or NA, like Boolean, but without assuming 0 when data is not available).
- `sep`: the character separating each value (defaults to “,”).
- `drop.col`: logical (whether to remove the original variable from the output or not; defaults to `TRUE`).

### Examples

First load some data from a CSV stored at [github](#). The URL is an HTTPS, so we need to use `getURL` from `RCurl`.

```
require(RCurl)

## Loading required package: RCurl

## Loading required package: bitops

baseUrl = c("https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/")
temp = getURL(paste0(baseUrl, "data/concatenated-cells.csv"))
concat.test = read.csv(textConnection(temp))
rm(temp)

# How big is the dataset?
dim(concat.test)

## [1] 48  4

# Just show me the first few rows
head(concat.test)
```

	Name	Likes	Siblings	Hates
## 1	Boyd	1,2,4,5,6	Reynolds , Albert , Ortega	2;4;
## 2	Rufus	1,2,4,5,6	Cohen , Bert , Montgomery	1;2;3;4;
## 3	Dana	1,2,4,5,6	Pierce	2;
## 4	Carole	1,2,4,5,6	Colon , Michelle , Ballard	1;4;
## 5	Ramona	1,2,5,6	Snyder , Joann ,	1;2;3;
## 6	Kelley	1,2,5,6	James , Roxanne ,	1;4;

Notice that the data have been entered in a very silly manner. Let's split it up!

```
# Load the function!
# require(RCurl)
# baseURL = c("https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/")
source(textConnection(getURL(paste0(baseURL, "scripts/concat.split.R"))))
```

```
# Split up the second column, selecting by column number
head(concat.split(concat.test, 2))
```

```
##      Name      Likes      Siblings      Hates Likes_1 Likes_2 Likes_3
## 1  Boyd 1,2,4,5,6 Reynolds , Albert , Ortega      2;4;      1      1      NA
## 2  Rufus 1,2,4,5,6 Cohen , Bert , Montgomery 1;2;3;4;      1      1      NA
## 3   Dana 1,2,4,5,6      Pierce      2;      1      1      NA
## 4 Carole 1,2,4,5,6 Colon , Michelle , Ballard      1;4;      1      1      NA
## 5 Ramona 1,2,5,6      Snyder , Joann ,      1;2;3;      1      1      NA
## 6 Kelley 1,2,5,6      James , Roxanne ,      1;4;      1      1      NA
## Likes_4 Likes_5 Likes_6
## 1      1      1      1
## 2      1      1      1
## 3      1      1      1
## 4      1      1      1
## 5     NA      1      1
## 6     NA      1      1
```

```
# ... or by name, and drop the offensive first column
head(concat.split(concat.test, "Likes", drop.col=TRUE))
```

```
##      Name      Siblings      Hates Likes_1 Likes_2 Likes_3 Likes_4
## 1  Boyd Reynolds , Albert , Ortega      2;4;      1      1      NA      1
## 2  Rufus Cohen , Bert , Montgomery 1;2;3;4;      1      1      NA      1
## 3   Dana      Pierce      2;      1      1      NA      1
## 4 Carole Colon , Michelle , Ballard      1;4;      1      1      NA      1
## 5 Ramona      Snyder , Joann ,      1;2;3;      1      1      NA      NA
## 6 Kelley      James , Roxanne ,      1;4;      1      1      NA      NA
## Likes_5 Likes_6
## 1      1      1
## 2      1      1
## 3      1      1
## 4      1      1
## 5      1      1
## 6      1      1
```

```
# The "Hates" column uses a different separator:
head(concat.split(concat.test, "Hates", sep=";", drop.col=TRUE))
```

```
##      Name      Likes      Siblings Hates_1 Hates_2 Hates_3 Hates_4
## 1  Boyd 1,2,4,5,6 Reynolds , Albert , Ortega      NA      1      NA      1
## 2  Rufus 1,2,4,5,6 Cohen , Bert , Montgomery      1      1      1      1
## 3   Dana 1,2,4,5,6      Pierce      NA      1      NA      NA
## 4 Carole 1,2,4,5,6 Colon , Michelle , Ballard      1      NA      NA      1
## 5 Ramona 1,2,5,6      Snyder , Joann ,      1      1      1      NA
## 6 Kelley 1,2,5,6      James , Roxanne ,      1      NA      NA      1
```

```
# Retain the original values
head(concat.split(concat.test, 2, mode="value", drop.col=TRUE))
```

```
##      Name                Siblings    Hates Likes_1 Likes_2 Likes_3 Likes_4
## 1  Boyd Reynolds , Albert , Ortega    2;4;      1      2      NA      4
## 2  Rufus  Cohen , Bert , Montgomery 1;2;3;4;    1      2      NA      4
## 3   Dana                Pierce        2;      1      2      NA      4
## 4 Carole Colon , Michelle , Ballard    1;4;      1      2      NA      4
## 5 Ramona                Snyder , Joann , 1;2;3;    1      2      NA      NA
## 6 Kelley                James , Roxanne , 1;4;      1      2      NA      NA
## Likes_5 Likes_6
## 1      5      6
## 2      5      6
## 3      5      6
## 4      5      6
## 5      5      6
## 6      5      6
```

```
# Let's try splitting some strings... Same syntax
head(concat.split(concat.test, 3, drop.col=TRUE))
```

```
##      Name    Likes    Hates Siblings_1 Siblings_2 Siblings_3
## 1  Boyd 1,2,4,5,6    2;4; Reynolds    Albert    Ortega
## 2  Rufus 1,2,4,5,6 1;2;3;4;    Cohen      Bert Montgomery
## 3   Dana 1,2,4,5,6      2;    Pierce      <NA>      <NA>
## 4 Carole 1,2,4,5,6    1;4;    Colon    Michelle    Ballard
## 5 Ramona 1,2,5,6    1;2;3;    Snyder      Joann      <NA>
## 6 Kelley 1,2,5,6    1;4;    James    Roxanne      <NA>
```

```
# Split up the "Likes column" into a list variable; retain original column
head(concat.split(concat.test, 2, to.list=TRUE, drop.col=FALSE))
```

```
##      Name    Likes                Siblings    Hates    Likes_list
## 1  Boyd 1,2,4,5,6 Reynolds , Albert , Ortega    2;4; 1, 2, 4, 5, 6
## 2  Rufus 1,2,4,5,6 Cohen , Bert , Montgomery 1;2;3;4; 1, 2, 4, 5, 6
## 3   Dana 1,2,4,5,6                Pierce        2; 1, 2, 4, 5, 6
## 4 Carole 1,2,4,5,6 Colon , Michelle , Ballard    1;4; 1, 2, 4, 5, 6
## 5 Ramona 1,2,5,6                Snyder , Joann , 1;2;3; 1, 2, 5, 6
## 6 Kelley 1,2,5,6                James , Roxanne , 1;4; 1, 2, 5, 6
```

```
# View the structure of the output for the first 10 rows to verify
# that the new column is a list; note the difference between "Likes"
# and "Likes_list".
str(concat.split(concat.test, 2, to.list=TRUE, drop.col=FALSE)[1:10, c(2, 5)])
```

```
## 'data.frame': 10 obs. of 2 variables:
## $ Likes : Factor w/ 5 levels "1,2,3,4,5","1,2,4,5",...: 3 3 3 3 5 5 3 3 3 4
## $ Likes_list:List of 10
## ..$ : num 1 2 4 5 6
## ..$ : num 1 2 4 5 6
## ..$ : num 1 2 4 5 6
## ..$ : num 1 2 4 5 6
## ..$ : num 1 2 5 6
## ..$ : num 1 2 5 6
## ..$ : num 1 2 4 5 6
## ..$ : num 1 2 4 5 6
## ..$ : num 1 2 4 5 6
## ..$ : num 1 2 5
```



## Advanced Usage

It is also possible to use `concat.split` to split multiple columns at once. This can be done in stages, or it can be all wrapped in nested statements, as follows:

```
do.call(cbind, c(concat.test[1],
  lapply(lapply(2:ncol(concat.test),
    function(x) concat.test[x]),
    concat.split, split.col=1, drop=TRUE, sep=";|,")))
```

In the example above (working from the inside of the function outwards):

- First, `lapply(2:ncol(concat.test), ...)` splits the columns of the `data.frame` into a list.
- Second, `lapply(lapply(...))` does the splitting work.
  - Note the use of `sep=";|,"` to match multiple separators on which to split; if further separators are required, they can be specified by using the pipe symbol (`|`) *with no leading or trailing spaces*.
- Finally, `do.call(cbind, ...)` is evaluated last, “binding” the data together by columns. In this case, the data being bound together is the first column from the `concat.test` dataset, and the splitted output of the remaining columns.

Alternatively, a similar approach can be taken using the function `dfcols.list` (see the “Snippets and Tips” section of this manual for the `dfcols.list` function).

*# Show just the first few lines, Boolean mode*

```
head(do.call(cbind, c(concat.test[1],
  lapply(dfcols.list(concat.test[-1]),
    concat.split, split.col=1, drop=TRUE, sep=";|,")))

##      Name Likes_1 Likes_2 Likes_3 Likes_4 Likes_5 Likes_6 Siblings_1 Siblings_2
## 1   Boyd      1      1      NA      1      1      1   Reynolds   Albert
## 2  Rufus      1      1      NA      1      1      1     Cohen    Bert
## 3   Dana      1      1      NA      1      1      1     Pierce   <NA>
## 4 Carole      1      1      NA      1      1      1      Colon  Michelle
## 5 Ramona      1      1      NA      NA      1      1     Snyder   Joann
## 6 Kelley      1      1      NA      NA      1      1      James   Roxanne

##      Siblings_3 Hates_1 Hates_2 Hates_3 Hates_4
## 1   Ortega      NA      1      NA      1
## 2 Montgomery      1      1      1      1
## 3      <NA>      NA      1      NA      NA
## 4   Ballard      1      NA      NA      1
## 5      <NA>      1      1      1      NA
## 6      <NA>      1      NA      NA      1
```

*# Show just the first few lines, value mode*

```
head(do.call(cbind, c(concat.test[1],
  lapply(dfcols.list(concat.test[-1]),
    concat.split, split.col=1, drop=TRUE,
    sep=";|,", mode="value"))))

##      Name Likes_1 Likes_2 Likes_3 Likes_4 Likes_5 Likes_6 Siblings_1 Siblings_2
## 1   Boyd      1      2      NA      4      5      6   Reynolds   Albert
## 2  Rufus      1      2      NA      4      5      6     Cohen    Bert
## 3   Dana      1      2      NA      4      5      6     Pierce   <NA>
```

```
## 4 Carole      1      2      NA      4      5      6      Colon  Michelle
## 5 Ramona      1      2      NA      NA      5      6      Snyder   Joann
## 6 Kelley      1      2      NA      NA      5      6      James    Roxanne
##  Siblings_3 Hates_1 Hates_2 Hates_3 Hates_4
## 1 Ortega      NA      2      NA      4
## 2 Montgomery  1      2      3      4
## 3 <NA>         NA      2      NA      NA
## 4 Ballard     1      NA      NA      4
## 5 <NA>         1      2      3      NA
## 6 <NA>         1      NA      NA      4
```

*# Show just the first few lines, list output mode*

```
head(do.call(cbind, c(concat.test[1],
                      lapply(dfcols.list(concat.test[-1]),
                             concat.split, split.col=1, drop=TRUE,
                             sep=";", to.list=TRUE))))
```

```
##      Name      Likes_list      Siblings_list Hates_list
## 1 Boyd 1, 2, 4, 5, 6 Reynolds, Albert, Ortega      2, 4
## 2 Rufus 1, 2, 4, 5, 6 Cohen, Bert, Montgomery 1, 2, 3, 4
## 3 Dana 1, 2, 4, 5, 6 Pierce      2
## 4 Carole 1, 2, 4, 5, 6 Colon, Michelle, Ballard      1, 4
## 5 Ramona 1, 2, 5, 6 Snyder, Joann      1, 2, 3
## 6 Kelley 1, 2, 5, 6 James, Roxanne      1, 4
```

## References

See: <http://stackoverflow.com/q/10100887/1270695>

## df.sorter

### What it Does

The `df.sorter` function allows you to sort a `data.frame` by columns or rows or both. You can also quickly subset data columns by using the `var.order` argument.

### Arguments

- **data**: the source `data.frame`.
- **var.order**: the new order in which you want the variables to appear.
  - Defaults to `names(data)`, which keeps the variables in the original order.
  - Variables can be referred to either by a vector of their index numbers or by a vector of the variable name; partial name matching also works, but requires that the partial match identifies similar columns uniquely (see examples).
  - Basic subsetting can also be done using `var.order` simply by omitting the variables you want to drop.
- **col.sort**: the columns *within* which there is data that need to be sorted.
  - Defaults to `NULL`, which means no sorting takes place.
  - Variables can be referred to either by a vector of their index numbers or by a vector of the variable names; full names must be provided.
- **at.start**: Should the pattern matching be from the start of the variable name? Defaults to `"TRUE"`.

NOTE: If you are sorting both by variables and within the columns, the `col.sort` order should be based on the location of the columns in the *new data.frame*, not the original `data.frame`.

### Examples

```
# Load the function!
# require(RCurl)
# baseURL = c("https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/")
source(textConnection(getURL(paste0(baseURL, "scripts/df.sorter.R"))))

# Make up some data
set.seed(1)
dat = data.frame(id = rep(1:5, each=3), times = rep(1:3, 5),
  measure1 = rnorm(15), score1 = sample(300, 15),
  code1 = replicate(15, paste(sample(LETTERS[1:5], 3),
    sep="", collapse="")),
  measure2 = rnorm(15), score2 = sample(150:300, 15),
  code2 = replicate(15, paste(sample(LETTERS[1:5], 3),
    sep="", collapse="")))

# Preview your data
dat
```

	id	times	measure1	score1	code1	measure2	score2	code2
## 1	1	1	-0.6265	145	DAB	-0.7075	299	CEB
## 2	1	2	0.1836	180	DCB	0.3646	224	ECD
## 3	1	3	-0.8356	148	EBA	0.7685	222	DAE

```
## 4  2  1  1.5953    56  AED -0.1123    175  DBA
## 5  2  2  0.3295   245  CEB  0.8811    260  DAC
## 6  2  3 -0.8205   198  EBD  0.3981    216  DCA
## 7  3  1  0.4874   234  BCA -0.6120    300  CEA
## 8  3  2  0.7383    32  CDA  0.3411    179  CAD
## 9  3  3  0.5758   212  EBC -1.1294    182  BEC
## 10 4  1 -0.3054   120  BED  1.4330    234  CDE
## 11 4  2  1.5118   239  EDB  1.9804    231  CAB
## 12 4  3  0.3898   188  DEB -0.3672    160  DBE
## 13 5  1 -0.6212   226  DBA -1.0441    154  EDB
## 14 5  2 -2.2147   159  DAC  0.5697    238  BDE
## 15 5  3  1.1249   152  AED -0.1351    277  DCE
```

```
# Change the variable order, grouping related columns
# Note that you do not need to specify full variable names,
# just enough that the variables can be uniquely identified
head(df.sorter(dat, var.order = c("id", "ti", "cod", "mea", "sco")))
```

```
##   id times code1 code2 measure1 measure2 score1 score2
## 1  1     1   DAB   CEB  -0.6265  -0.7075   145   299
## 2  1     2  DCB   ECD   0.1836   0.3646   180   224
## 3  1     3  EBA   DAE -0.8356   0.7685   148   222
## 4  2     1  AED   DBA   1.5953  -0.1123    56   175
## 5  2     2  CEB   DAC   0.3295   0.8811   245   260
## 6  2     3  EBD   DCA -0.8205   0.3981   198   216
```

```
# Same output, but with a more awkward syntax
head(df.sorter(dat, var.order = c(1, 2, 5, 8, 3, 6, 4, 7)))
```

```
##   id times code1 code2 measure1 measure2 score1 score2
## 1  1     1   DAB   CEB  -0.6265  -0.7075   145   299
## 2  1     2  DCB   ECD   0.1836   0.3646   180   224
## 3  1     3  EBA   DAE -0.8356   0.7685   148   222
## 4  2     1  AED   DBA   1.5953  -0.1123    56   175
## 5  2     2  CEB   DAC   0.3295   0.8811   245   260
## 6  2     3  EBD   DCA -0.8205   0.3981   198   216
```

```
# As above, but sorted by 'times' and then 'id'
head(df.sorter(dat, var.order = c("id", "tim", "cod", "mea", "sco"),
  col.sort = c(2, 1)))
```

```
##   id times code1 code2 measure1 measure2 score1 score2
## 1  1     1   DAB   CEB  -0.6265  -0.7075   145   299
## 4  2     1  AED   DBA   1.5953  -0.1123    56   175
## 7  3     1  BCA   CEA   0.4874  -0.6120   234   300
## 10 4     1  BED   CDE -0.3054   1.4330   120   234
## 13 5     1  DBA   EDB -0.6212  -1.0441   226   154
## 2  1     2  DCB   ECD   0.1836   0.3646   180   224
```

```
# Drop 'measure1' and 'measure2', sort by 'times', and 'score1'
head(df.sorter(dat, var.order = c("id", "tim", "sco", "cod"),
  col.sort = c(2, 3)))
```

```
##   id times score1 score2 code1 code2
## 4  2     1     56    175  AED   DBA
## 10 4     1    120    234  BED   CDE
```

```
## 1 1 1 145 299 DAB CEB
## 13 5 1 226 154 DBA EDB
## 7 3 1 234 300 BCA CEA
## 8 3 2 32 179 CDA CAD
```

*# As above, but using names*

```
head(df.sorter(dat, var.order = c("id", "tim", "sco", "cod"),
  col.sort = c("times", "score1")))
```

```
## id times score1 score2 code1 code2
## 4 2 1 56 175 AED DBA
## 10 4 1 120 234 BED CDE
## 1 1 1 145 299 DAB CEB
## 13 5 1 226 154 DBA EDB
## 7 3 1 234 300 BCA CEA
## 8 3 2 32 179 CDA CAD
```

*# Just sort by columns, first by 'times' then by 'id'*

```
head(df.sorter(dat, col.sort = c("times", "id")))
```

```
## id times measure1 score1 code1 measure2 score2 code2
## 1 1 1 -0.6265 145 DAB -0.7075 299 CEB
## 4 2 1 1.5953 56 AED -0.1123 175 DBA
## 7 3 1 0.4874 234 BCA -0.6120 300 CEA
## 10 4 1 -0.3054 120 BED 1.4330 234 CDE
## 13 5 1 -0.6212 226 DBA -1.0441 154 EDB
## 2 1 2 0.1836 180 DCB 0.3646 224 ECD
```

```
head(df.sorter(dat, col.sort = c("code1"))) # Sorting by character values
```

```
## id times measure1 score1 code1 measure2 score2 code2
## 4 2 1 1.5953 56 AED -0.1123 175 DBA
## 15 5 3 1.1249 152 AED -0.1351 277 DCE
## 7 3 1 0.4874 234 BCA -0.6120 300 CEA
## 10 4 1 -0.3054 120 BED 1.4330 234 CDE
## 8 3 2 0.7383 32 CDA 0.3411 179 CAD
## 5 2 2 0.3295 245 CEB 0.8811 260 DAC
```

*# Pattern matching anywhere in the variable name*

```
head(df.sorter(dat, var.order= "co", at.start=FALSE))
```

```
## code1 code2 score1 score2
## 1 DAB CEB 145 299
## 2 DCB ECD 180 224
## 3 EBA DAE 148 222
## 4 AED DBA 56 175
## 5 CEB DAC 245 260
## 6 EBD DCA 198 216
```

## To Do

- Add an option to sort ascending or descending—at the moment, not supported.

## multi.freq.table

### What it Does

The `multi.freq.table` function takes a data frame containing Boolean responses to multiple response questions and tabulates the number of responses by the possible combinations of answers. In addition to tabulating the frequency (**Freq**), there are two other columns in the output: *Percent of Responses* (**Pct.of.Resp**) and *Percent of Cases* (**Pct.of.Cases**). *Percent of Responses* is the frequency divided by the total number of answers provided; this column should sum to 100%. *Percent of Cases* is the frequency divided by the total number of valid cases; this column would not likely sum to more than 100% since each respondent (case) can select multiple answers.

### Arguments

- **data**: The multiple responses that need to be tabulated.
- **sep**: The desired separator for collapsing the combinations of options; defaults to "" (collapsing with no space between each option name).
- **dropzero**: Should combinations with a frequency of zero be dropped from the final table? Defaults to FALSE.
- **clean**: Should the original tabulated data be retained or dropped from the final table? Defaults to TRUE.
- **basic**: Should a basic table of each item, rather than combinations of items, be created? Defaults to FALSE.

### Examples

```
# Load the function!
# require(RCurl)
# baseURL = c("https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/")
source(textConnection(getURL(paste0(baseURL, "scripts/multi.freq.table.R"))))

# Make up some data
set.seed(1)
dat = data.frame(A = sample(c(0, 1), 20, replace=TRUE),
                  B = sample(c(0, 1), 20, replace=TRUE),
                  C = sample(c(0, 1), 20, replace=TRUE),
                  D = sample(c(0, 1), 20, replace=TRUE),
                  E = sample(c(0, 1), 20, replace=TRUE))

# View your data
dat

##      A B C D E
## 1  0 1 1 1 0
## 2  0 0 1 0 1
## 3  1 1 1 0 0
## 4  1 0 1 0 0
## 5  0 0 1 1 1
## 6  1 0 1 0 0
## 7  1 0 0 0 1
## 8  1 0 0 1 0
## 9  1 1 1 0 0
## 10 0 0 1 1 0
## 11 0 0 0 0 0
```

```
## 12 0 1 1 1 0
## 13 1 0 0 0 1
## 14 0 0 0 0 1
## 15 1 1 0 0 1
## 16 0 1 0 1 1
## 17 1 1 0 1 0
## 18 1 0 1 0 0
## 19 0 1 1 1 1
## 20 1 0 0 1 1
```

```
# Apply the function with all defaults accepted
multi.freq.table(dat)
```

##	Combn	Freq	Pct.of.Resp	Pct.of.Cases
## 1		1	2.083	5
## 2	A	0	0.000	0
## 3	B	0	0.000	0
## 4	AB	0	0.000	0
## 5	C	0	0.000	0
## 6	AC	3	6.250	15
## 7	BC	0	0.000	0
## 8	ABC	2	4.167	10
## 9	D	0	0.000	0
## 10	AD	1	2.083	5
## 11	BD	0	0.000	0
## 12	ABD	1	2.083	5
## 13	CD	1	2.083	5
## 14	ACD	0	0.000	0
## 15	BCD	2	4.167	10
## 16	ABCD	0	0.000	0
## 17	E	1	2.083	5
## 18	AE	2	4.167	10
## 19	BE	0	0.000	0
## 20	ABE	1	2.083	5
## 21	CE	1	2.083	5
## 22	ACE	0	0.000	0
## 23	BCE	0	0.000	0
## 24	ABCE	0	0.000	0
## 25	DE	0	0.000	0
## 26	ADE	1	2.083	5
## 27	BDE	1	2.083	5
## 28	ABDE	0	0.000	0
## 29	CDE	1	2.083	5
## 30	ACDE	0	0.000	0
## 31	BCDE	1	2.083	5
## 32	ABCDE	0	0.000	0

```
# Tabulate only on variables "A", "B", and "D", with a different
# separator, dropping any zero frequency values, and keeping the original tabulations.
# Note that there are no solitary "B" responses.
multi.freq.table(dat[c(1, 2, 4)], sep="-", dropzero=TRUE, clean=FALSE)
```

##	A	B	D	Freq	Combn	Pct.of.Resp	Pct.of.Cases
## 1	0	0	0	3		10.714	15
## 2	1	0	0	5	A	17.857	25
## 4	1	1	0	3	A-B	10.714	15
## 5	0	0	1	2	D	7.143	10

```
## 6 1 0 1    2    A-D      7.143      10
## 7 0 1 1    4    B-D     14.286     20
## 8 1 1 1    1 A-B-D      3.571      5
```

```
# View a basic table.
multi.freq.table(dat, basic=TRUE)
```

```
##   Freq Pct.of.Resp Pct.of.Cases
## A   11      22.92         55
## B    8      16.67         40
## C   11      22.92         55
## D    9      18.75         45
## E    9      18.75         45
```

## To Do

- Update docs with `useNA`.
- Update function to deal with NA responses better.
- Update function for dealing with different types of multiple response questions input formats.

## References

apply shortcut for creating the `Combn` column in the output by [Justin](#)

See: <http://stackoverflow.com/q/11348391/1270695> and <http://stackoverflow.com/q/11622660/1270695>



## row.extractor

### What it Does

The `row.extractor` function takes a `data.frame` and extracts rows with the `min`, `median`, or `max` values of a given variable, or extracts rows with specific quantiles of a given variable.

### Arguments

- `data`: the source `data.frame`.
- `extract.by`: the column which will be used as the reference for extraction; can be specified either by the column number or the variable name.
- `what`: options are `min` (for all rows matching the minimum value), `median` (for the median row or rows), `max` (for all rows matching the maximum value), or `all` (for `min`, `median`, and `max`); alternatively, a numeric vector can be specified with the desired quantiles, for instance `c(0, .25, .5, .75, 1)`

### Examples

```
# Load the function!
# require(RCurl)
# baseURL = c("https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/")
source(textConnection(getURL(paste0(baseURL, "scripts/row.extractor.R"))))

# Make up some data
set.seed(1)
dat = data.frame(V1 = 1:50, V2 = rnorm(50),
                 V3 = round(abs(rnorm(50)), digits=2),
                 V4 = sample(1:30, 50, replace=TRUE))

# Get a summary of the data
summary(dat)
```

	V1	V2	V3	V4
## Min.	: 1.0	Min. : -2.215	Min. : 0.000	Min. : 2.00
## 1st Qu.	: 13.2	1st Qu.: -0.372	1st Qu.: 0.347	1st Qu.: 8.25
## Median	: 25.5	Median : 0.129	Median : 0.590	Median : 13.00
## Mean	: 25.5	Mean : 0.100	Mean : 0.774	Mean : 14.80
## 3rd Qu.	: 37.8	3rd Qu.: 0.728	3rd Qu.: 1.175	3rd Qu.: 20.75
## Max.	: 50.0	Max. : 1.595	Max. : 2.400	Max. : 29.00

```
# Get the rows corresponding to the 'min', 'median', and 'max' of 'V4'
row.extractor(dat, 4)
```

	V1	V2	V3	V4
## 28 28	-1.4708	0.00	2	
## 47 47	0.3646	1.28	13	
## 29 29	-0.4782	0.07	13	
## 11 11	1.5118	2.40	29	
## 14 14	-2.2147	0.03	29	
## 18 18	0.9438	1.47	29	
## 19 19	0.8212	0.15	29	
## 50 50	0.8811	0.47	29	

```
# Get the 'min' rows only, referenced by the variable name
row.extractor(dat, "V4", "min")
```

```
##      V1      V2 V3 V4
## 28 28 -1.471  0  2
```

```
# Get the 'median' rows only. Notice that there are two rows
#   since we have an even number of cases and true median
#   is the mean of the two central sorted values
row.extractor(dat, "V4", "median")
```

```
##      V1      V2  V3 V4
## 47 47  0.3646 1.28 13
## 29 29 -0.4782 0.07 13
```

```
# Get the rows corresponding to the deciles of 'V3'
row.extractor(dat, "V3", seq(0.1, 1, 0.1))
```

```
##      V1      V2  V3 V4
## 10 10 -0.30539 0.14 22
## 26 26 -0.05613 0.29 16
## 39 39  1.10003 0.37 13
## 41 41 -0.16452 0.54 10
## 30 30  0.41794 0.59 26
## 44 44  0.55666 0.70  5
## 37 37 -0.39429 1.06 21
## 49 49 -0.11235 1.22 14
## 34 34 -0.05381 1.52 19
## 11 11  1.51178 2.40 29
```

## References

which.quantile function by [cbeleites](#)  
 See: <http://stackoverflow.com/q/10256503/1270695>



## **Part II**

# **The Functions**



## Where to Get the Functions

The most current source code for the functions described in this document follow.

To load the functions, you can directly source them from the 2657 R Functions page at github: <https://github.com/mrdwab/2657-R-Functions>

You should be able to load the functions using the following (replace ----- with the function name<sup>1</sup>):

```
require(RCurl)
baseURL = c("https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/")
source(textConnection(getURL(paste0(baseURL, "scripts/-----R"))))
```

---

<sup>1</sup>The “snippets” in Part III of this document can all be loaded from the script `snippets.R`.

## concat.split

```
concat.split = function(data, split.col, to.list=FALSE, mode=NULL,
                        sep=",", drop.col=FALSE) {
  # Takes a column with multiple values, splits the values into
  # separate columns, and returns a new data.frame.
  # 'data' is the source data.frame; 'split.col' is the variable that
  # needs to be split; 'to.list' is whether the split output should
  # be added as a single variable list (defaults to "FALSE");
  # mode' can be either 'binary' or 'value' (where 'binary' is
  # default and it recodes values to 1 or NA); 'sep' is the
  # character separating each value (defaults to ',');
  # and 'drop.col' is logical (whether to remove the original
  # variable from the output or not.
  #
  # === EXAMPLES ===
  #
  #       dat = data.frame(V1 = c("1, 2, 4", "3, 4, 5",
  #                               "1, 2, 5", "4", "1, 2, 3, 5"),
  #                         V2 = c("1;2;3;4", "1", "2;5",
  #                               "3;2", "2;3;4"))
  #       dat2 = data.frame(V1 = c("Fred, John, Sue", "Jerry, Jill",
  #                                 "Sally, Ryan", "Susan, Amos, Ben"))
  #
  #       concat.split(dat, 1)
  #       concat.split(dat, 2, sep=";")
  #       concat.split(dat, "V2", sep=";", mode="value")
  #       concat.split(dat, "V1", mode="binary")
  #       concat.split(dat2, 1)
  #       concat.split(dat2, "V1", drop.col=TRUE)
  #
  # See: http://stackoverflow.com/q/10100887/1270695

  if (is.numeric(split.col)) split.col = split.col
  else split.col = which(colnames(data) %in% split.col)

  a = as.character(data[, split.col])
  b = strsplit(a, sep)

  if (isTRUE(to.list)) {
    varname = paste(names(data[split.col]), "_list", sep="")
    if (suppressWarnings(is.na(try(max(as.numeric(unlist(b))))))) {
      data[varname] = list(lapply(lapply(b, as.character),
                                     function(x) gsub("^\\s+|\\s+$",
                                                         "", x)))
    } else if (!is.na(try(max(as.numeric(unlist(b)))))) {
      data[varname] = list(lapply(b, as.numeric))
    }
  }
  if (isTRUE(drop.col)) data[-split.col]
  else data
} else if (!isTRUE(to.list)) {
  if (suppressWarnings(is.na(try(max(as.numeric(unlist(b))))))) {
    what = "string"
    ncol = max(unlist(lapply(b, function(i) length(i))))
  } else if (!is.na(try(max(as.numeric(unlist(b)))))) {
    what = "numeric"
    ncol = max(as.numeric(unlist(b)))
  }
}
```

```

m = matrix(nrow = nrow(data), ncol = ncol)
v = vector("list", nrow(data))

if (identical(what, "string")) {
  temp = as.data.frame(t(sapply(b, '[', 1:ncol)))
  names(temp) = paste(names(data[split.col]), "_", 1:ncol, sep="")
  temp = apply(temp, 2, function(x) gsub("^\\s+|\\s+$", "", x))
  temp1 = cbind(data, temp)
} else if (identical(what, "numeric")) {
  for (i in 1:nrow(data)) {
    v[[i]] = as.numeric(strsplit(a, sep)[[i]])
  }

  temp = v

  for (i in 1:nrow(data)) {
    m[i, temp[[i]]] = temp[[i]]
  }

  m = data.frame(m)
  names(m) = paste(names(data[split.col]), "_", 1:ncol, sep="")

  if (is.null(mode) || identical(mode, "binary")) {
    temp1 = cbind(data, replace(m, m != "NA", 1))
  } else if (identical(mode, "value")) {
    temp1 = cbind(data, m)
  }
}

if (isTRUE(drop.col)) temp1[-split.col]
else temp1
}

```



## df.sorter

```
df.sorter = function(data, var.order=names(data), col.sort=NULL, at.start=TRUE ) {
  # Sorts a data.frame by columns or rows or both.
  # Can also subset the data columns by using 'var.order'.
  # Can refer to variables either by names or number.
  # If referring to variable by number, and sorting both the order
  #   of variables and the sorting within variables, refer to the
  #   variable numbers of the final data.frame.
  #
  # === EXAMPLES ===
  #
  #   library(foreign)
  #   temp = "http://www.ats.ucla.edu/stat/stata/modules/kidshtwt.dta"
  #   kidshtwt = read.dta(temp); rm(temp)
  #   df.sorter(kidshtwt, var.order = c("fam", "bir", "wt", "ht"))
  #   df.sorter(kidshtwt, var.order = c("fam", "bir", "wt", "ht"),
  #             col.sort = c("birth", "famid")) # USE FULL NAMES HERE
  #   df.sorter(kidshtwt, var.order = c(1:4),    # DROP THE WT COLUMNS
  #             col.sort = 3)                   # SORT BY HT1

  if (is.numeric(var.order))
    var.order = colnames(data)[var.order]
  else var.order = var.order

  a = names(data)
  b = length(var.order)
  subs = vector("list", b)

  if (isTRUE(at.start)) {
    for (i in 1:b) {
      subs[[i]] = sort(grep(paste("^", var.order[i],
                                sep="", collapse=""),
                            a, value=TRUE))
    }
  } else if (!isTRUE(at.start)) {
    for (i in 1:b) {
      subs[[i]] = sort(grep(var.order[i], a, value=TRUE))
    }
  }

  x = unlist(subs)
  y = data[ , x ]

  if (is.null(col.sort)) {
    y
  } else if (is.numeric(col.sort)) {
    col.sort = colnames(y)[col.sort]
    y[do.call(order, y[col.sort]), ]
  } else if (!is.numeric(col.sort)) {
    col.sort = col.sort
    y[do.call(order, y[col.sort]), ]
  }
}
```

## multi.freq.table

```

multi.freq.table = function(data, sep="", dropzero=FALSE,
                             clean=TRUE, basic=FALSE, useNA="always") {
  # Takes boolean multiple-response data and tabulates it according
  #   to the possible combinations of each variable.
  #
  # === EXAMPLES ===
  #   set.seed(1)
  #   dat = data.frame(A = sample(c(0, 1), 20, replace=TRUE),
  #                     B = sample(c(0, 1), 20, replace=TRUE),
  #                     C = sample(c(0, 1), 20, replace=TRUE),
  #                     D = sample(c(0, 1), 20, replace=TRUE),
  #                     E = sample(c(0, 1), 20, replace=TRUE))
  #   multi.freq.table(dat)
  #   multi.freq.table(dat[1:3], sep="-", dropzero=TRUE)
  #
  # See: http://stackoverflow.com/q/11348391/1270695
  #      http://stackoverflow.com/q/11622660/1270695

  if(isTRUE(basic)) {
    counts = data.frame(Freq = colSums(data),
                        Pct.of.Resp = (colSums(data)/sum(data))*100,
                        Pct.of.Cases = (colSums(data)/nrow(data))*100)
  } else if (!isTRUE(basic)) {
    counts = data.frame(table(data, useNA = useNA))
    N = ncol(counts)
    counts$Combn = apply(counts[-N] == 1, 1,
                         function(x) paste(names(counts[-N])[x],
                                             collapse=sep))

    counts$Pct.of.Resp = (counts$Freq/sum(data))*100
    counts$Pct.of.Cases = (counts$Freq/nrow(data))*100
    if (isTRUE(dropzero)) {
      counts = counts[counts$Freq != 0, ]
    } else if (!isTRUE(dropzero)) {
      counts = counts
    }
    if (isTRUE(clean)) {
      counts = data.frame(Combn = counts$Combn, Freq = counts$Freq,
                          Pct.of.Resp = counts$Pct.of.Resp,
                          Pct.of.Cases = counts$Pct.of.Cases)
    }
  }
  counts
}

```

## row.extractor

```

row.extractor = function(data, extract.by, what="all") {
  # Extracts rows with min, median, and max values, or by quantiles.
  # Values for "what" can be "min", "median", "max", "all", or a
  # vector specifying the desired quantiles.
  # Values for "extract.by" can be the variable name or number.
  #
  # === EXAMPLES ===
  #
  #   set.seed(1)
  #   dat = data.frame(V1 = 1:10, V2 = rnorm(10), V3 = rnorm(10),
  #                     V4 = sample(1:20, 10, replace=T))
  #   dat2 = dat[-10,]
  #   row.extractor(dat, 4, "all")
  #   row.extractor(dat1, 4, "min")
  #   row.extractor(dat, "V4", "median")
  #   row.extractor(dat, 4, c(0, .5, 1))
  #   row.extractor(dat, "V4", c(0, .25, .5, .75, 1))
  #
  # "which.quantile" function by cbeleites:
  # http://stackoverflow.com/users/755257/cbeleites
  # See: http://stackoverflow.com/q/10256503/1270695

  if (is.numeric(extract.by)) {
    extract.by = extract.by
  } else if (is.numeric(extract.by) != 0) {
    extract.by = which(colnames(data) %in% "extract.by")
  }

  if (is.character(what)) {
    which.median = function(data, extract.by) {
      a = data[, extract.by]
      if (length(a) %% 2 != 0) {
        which(a == median(a))
      } else if (length(a) %% 2 == 0) {
        b = sort(a)[c(length(a)/2, length(a)/2+1)]
        c(max(which(a == b[1])), min(which(a == b[2])))
      }
    }
  }

  X1 = data[which(data[extract.by] == min(data[extract.by])), ] # min
  X2 = data[which(data[extract.by] == max(data[extract.by])), ] # max
  X3 = data[which.median(data, extract.by), ] # median

  if (identical(what, "min")) {
    X1
  } else if (identical(what, "max")) {
    X2
  } else if (identical(what, "median")) {
    X3
  } else if (identical(what, "all")) {
    rbind(X1, X3, X2)
  }
} else if (is.numeric(what)) {
  which.quantile <- function (data, extract.by, what, na.rm = FALSE) {

    x = data[, extract.by]

```

```

    if (! na.rm & any (is.na (x)))
      return (rep (NA_integer_, length (what)))

    o <- order (x)
    n <- sum (! is.na (x))
    o <- o [seq_len (n)]

    nppm <- n * what - 0.5
    j <- floor(nppm)
    h <- ifelse((nppm == j) & ((j%2L) == 0L), 0, 1)
    j <- j + h

    j [j == 0] <- 1
    o[j]
  }
  data[which.quantile(data, extract.by, what), ] # quantile
}

```



## Part III

# Snippets and Tips



## Snippets

### Load All Scripts and Data Files From Multiple Directories

```
load.scripts.and.data = function(path,
                                pattern=list(scripts = "*.R$",
                                              data = "*.rda$|*.Rdata$"),
                                ignore.case=TRUE) {
  # Reads all the data files and scripts from specified directories.
  #   In general, should only need to specify the directories.
  #   Specify directories without trailing slashes.
  #
  # === EXAMPLE ===
  #
  #   load.scripts.and.data(c("~/Dropbox/Public",
  #                           "~/Dropbox/Public/R Functions"))

  file.sources = list.files(path, pattern=pattern$scripts,
                            full.names=TRUE, ignore.case=ignore.case)
  data.sources = list.files(path, pattern=pattern$data,
                            full.names=TRUE, ignore.case=ignore.case)
  sapply(data.sources, load, .GlobalEnv)
  sapply(file.sources, source, .GlobalEnv)
}
```

### Convert a List of Data Frames Into Individual Data Frames

```
unlist.dfs = function(data) {
  # Specify the quoted name of the source list.
  q = get(data)
  prefix = paste0(data, "_", 1:length(q))
  for (i in 1:length(q)) assign(prefix[i], q[[i]], envir=.GlobalEnv)
}
```

#### Example

*Note that the list name must be quoted.*

```
# Sample data
temp = list(A = data.frame(A = 1:2, B = 3:4),
            B = data.frame(C = 5:6, D = 7:8))
temp

## $A
##   A B
## 1 1 3
## 2 2 4
##
## $B
##   C D
## 1 5 7
## 2 6 8
##

# Remove any files with similar names to output
rm(list=ls(pattern="temp_"))
```



```

# The following should not work
temp_1

## Error: object 'temp_1' not found

# Split it up!
unlist.dfs("temp")
# List files with the desired pattern
ls(pattern="temp_")

## [1] "temp_1" "temp_2"

# View the new files
temp_1

##      A B
## 1 1 3
## 2 2 4

temp_2

##      C D
## 1 5 7
## 2 6 8

```

## Convert a Data Frame Into a List With Each Column Becoming a List Item

```

dfcols.list = function(data, vectorize=FALSE) {
  # Specify the unquoted name of the data.frame to convert
  if (isTRUE(vectorize)) {
    dat.list = sapply(1:ncol(data), function(x) data[x])
  } else if (!isTRUE(vectorize)) {
    dat.list = lapply(names(data), function(x) data[x])
  }
  dat.list
}

```

### Examples

```

# Sample data
dat = data.frame(A = c(1:2), B = c(3:4), C = c(5:6))
dat

##      A B C
## 1 1 3 5
## 2 2 4 6

# Split into a list, retaining data.frame structure
dfcols.list(dat)

## [[1]]
##      A
## 1 1
## 2 2

```

```
##
## [[2]]
##    B
## 1 3
## 2 4
##
## [[3]]
##    C
## 1 5
## 2 6
##
```

```
# Split into a list, converting to vector
dfcols.list(dat, vectorize=TRUE)
```

```
## $A
## [1] 1 2
##
## $B
## [1] 3 4
##
## $C
## [1] 5 6
##
```

## Rename an Object in the Workplace

```
mv <- function (a, b) {
  # Source: https://stat.ethz.ch/pipermail/r-help/2008-March/156035.html
  anm <- deparse(substitute(a))
  bnm <- deparse(substitute(b))
  if (!exists(anm, where=1, inherits=FALSE))
    stop(paste(anm, "does not exist.\n"))
  if (exists(bnm, where=1, inherits=FALSE)) {
    ans <- readline(paste("Overwrite ", bnm, "? (y/n) ", sep = ""))
    if (ans != "y")
      return(invisible())
  }
  assign(bnm, a, pos = 1)
  rm(list = anm, pos = 1)
  invisible()
}
```

## Basic Usage

If there is already an object with the same name in the workplace, the function will ask you if you want to replace the object or not. Otherwise, the basic usage is:

```
# Rename "object_1" to "object_2"
mv(object_1, object_2)
```

## Tips

Many of the following tips are useful for reducing repetitious tasks. They might seem silly or unnecessary with the small examples provided, but they can be *huge* time-savers when dealing with larger objects or larger sets of data.

### Batch Convert Factor Variables to Character Variables

In the example data below, `author` and `title` are automatically converted to factor (unless you add the argument `stringsAsFactor = FALSE` when you are creating the data). What if you forgot and actually needed the variables to be in mode `as.character` instead?

Use `sapply` to identify which variables are currently factors and convert them to `as.character`.

```
dat = data.frame(title = c("title1", "title2", "title3"),
                 author = c("author1", "author2", "author3"),
                 customerID = c(1, 2, 1))

str(dat)

## 'data.frame':   3 obs. of  3 variables:
## $ title      : Factor w/ 3 levels "title1","title2",...: 1 2 3
## $ author     : Factor w/ 3 levels "author1","author2",...: 1 2 3
## $ customerID: num  1 2 1

# Left of the equal sign identifies and extracts the factor variables;
# right converts them from factor to character
dat[sapply(dat, is.factor)] = lapply(dat[sapply(dat, is.factor)],
                                     as.character)

str(dat)

## 'data.frame':   3 obs. of  3 variables:
## $ title      : chr  "title1" "title2" "title3"
## $ author     : chr  "author1" "author2" "author3"
## $ customerID: num  1 2 1
```

### Using Reduce to Merge Multiple Data Frames at Once

The `merge` function in R only merges two objects at a time. This is usually fine, but what if you had several `data.frames` that needed to be merged?

Consider the following data, where we want to take monthly tables and merge them into an annual table:

```
set.seed(1)
JAN = data.frame(ID = sample(5, 3), JAN = sample(LETTERS, 3))
FEB = data.frame(ID = sample(5, 3), FEB = sample(LETTERS, 3))
MAR = data.frame(ID = sample(5, 3), MAR = sample(LETTERS, 3))
APR = data.frame(ID = sample(5, 3), APR = sample(LETTERS, 3))
```

If we wanted to merge these into a single `data.frame` using `merge`, we might end up creating several temporary objects and merging those, like this:

```
temp_1 = merge(JAN, FEB, all=TRUE)
temp_2 = merge(temp_1, MAR, all=TRUE)
temp_3 = merge(temp_2, APR, all=TRUE)
```

Or, we might nest a whole bunch of `merge` commands together, something like this:

```
merge(merge(merge(JAN, FEB, all=TRUE),
               MAR, all=TRUE),
      APR, all=TRUE)
```

However, that first option requires a lot of unnecessary typing and produces unnecessary objects that we then need to remember to remove, and the second option is not very reader-friendly—try doing a merge like that with, say, 12 `data.frames` if we had an entire year of data!

Use `Reduce` instead, simply specifying all the objects to be merged in a `list`:

```
Reduce(function(x, y) merge(x, y, all=TRUE),
       list(JAN, FEB, MAR, APR))
```

```
##   ID  JAN  FEB  MAR  APR
## 1  2    X    E    R    F
## 2  3 <NA>    F    X    D
## 3  4    V <NA>    M    Q
## 4  5    F    B <NA> <NA>
```

### How Much Memory Are the Objects in Your Workspace Using?

Sometimes you need to just check and see how much memory the objects in your workspace occupy.

```
sort(sapply(ls(), function(x) {object.size(get(x))}))
```