

2657 Functions

Ananda Mahto

July 14, 2012

Contents

concat.split	3
What it Does	3
Arguments	3
Examples	3
To Do	5
References	5
df.sorter	6
What it Does	6
Arguments	6
Examples	6
To Do	8
multi.freq.table	9
What it Does	9
Arguments	9
Examples	9
References	10
row.extractor	11
What it Does	11
Arguments	11
The Function	11
Examples	12
References	13
The Functions	14
concat.split	15
df.sorter	17
multi.freq.table	18

concat.split

What it Does

The `concat.split` function takes a column with multiple values, splits the values into separate columns, and returns a new `data.frame`.

Arguments

- `data`: the source `data.frame`.
- `split.col`: the variable that needs to be split; can be specified either by the column number or the variable name.
- `mode`: can be either `binary` or `value` (where `binary` is default and it recodes values to 1 or NA).
- `sep`: the character separating each value (defaults to ",").
- `drop.col`: logical (whether to remove the original variable from the output or not; defaults to TRUE).

Examples

First load some data from a CSV stored at [github](https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/data/concatenated-cells.csv). The URL is an HTTPS, so we need to use `getURL` from `RCurl`.

```
require(RCurl)

## Loading required package: RCurl

## Loading required package: bitops

baseURL = c("https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/")
temp = getURL(paste0(baseURL, "data/concatenated-cells.csv"))
concat.test = read.csv(textConnection(temp))
rm(temp)

# How big is the dataset?
dim(concat.test)

## [1] 48  4

# Just show me the first few rows
head(concat.test)

##      Name      Likes      Siblings      Hates
## 1  Boyd 1,2,4,5,6 Reynolds , Albert , Ortega      2;4;
## 2  Rufus 1,2,4,5,6 Cohen , Bert , Montgomery 1;2;3;4;
## 3   Dana 1,2,4,5,6      Pierce      2;
## 4 Carole 1,2,4,5,6 Colon , Michelle , Ballard      1;4;
## 5 Ramona  1,2,5,6      Snyder , Joann ,      1;2;3;
## 6 Kelley  1,2,5,6      James , Roxanne ,      1;4;
```

Notice that the data have been entered in a very silly manner. Let's split it up!

```
# Load the function! require(RCurl) baseURL =
# c('https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/')
source(textConnection(getURL(paste0(baseURL, "scripts/concat.split.R"))))
```

```
# Split up the second column, selecting by column number
head(concat.split(concat.test, 2))
```

```
##      Name      Likes      Siblings      Hates Likes_1 Likes_2
## 1   Boyd 1,2,4,5,6 Reynolds , Albert , Ortega      2;4;      1      1
## 2   Rufus 1,2,4,5,6 Cohen , Bert , Montgomery 1;2;3;4;      1      1
## 3    Dana 1,2,4,5,6      Pierce      2;      1      1
## 4  Carole 1,2,4,5,6 Colon , Michelle , Ballard      1;4;      1      1
## 5  Ramona 1,2,5,6      Snyder , Joann ,      1;2;3;      1      1
## 6  Kelley 1,2,5,6      James , Roxanne ,      1;4;      1      1
## Likes_3 Likes_4 Likes_5 Likes_6
## 1      NA      1      1      1
## 2      NA      1      1      1
## 3      NA      1      1      1
## 4      NA      1      1      1
## 5      NA      NA      1      1
## 6      NA      NA      1      1
```

```
# ... or by name, and drop the offensive first column
head(concat.split(concat.test, "Likes", drop.col = TRUE))
```

```
##      Name      Siblings      Hates Likes_1 Likes_2 Likes_3
## 1   Boyd Reynolds , Albert , Ortega      2;4;      1      1      NA
## 2   Rufus Cohen , Bert , Montgomery 1;2;3;4;      1      1      NA
## 3    Dana      Pierce      2;      1      1      NA
## 4  Carole Colon , Michelle , Ballard      1;4;      1      1      NA
## 5  Ramona      Snyder , Joann ,      1;2;3;      1      1      NA
## 6  Kelley      James , Roxanne ,      1;4;      1      1      NA
## Likes_4 Likes_5 Likes_6
## 1      1      1      1
## 2      1      1      1
## 3      1      1      1
## 4      1      1      1
## 5      NA      1      1
## 6      NA      1      1
```

```
# The 'Hates' column uses a different separator:
head(concat.split(concat.test, "Hates", sep = ";", drop.col = TRUE))
```

```
##      Name      Likes      Siblings Hates_1 Hates_2 Hates_3
## 1   Boyd 1,2,4,5,6 Reynolds , Albert , Ortega      NA      1      NA
## 2   Rufus 1,2,4,5,6 Cohen , Bert , Montgomery      1      1      1
## 3    Dana 1,2,4,5,6      Pierce      NA      1      NA
## 4  Carole 1,2,4,5,6 Colon , Michelle , Ballard      1      NA      NA
## 5  Ramona 1,2,5,6      Snyder , Joann ,      1      1      1
## 6  Kelley 1,2,5,6      James , Roxanne ,      1      NA      NA
## Hates_4
## 1      1
## 2      1
## 3      NA
## 4      1
## 5      NA
## 6      1
```

```
# Retain the original values
head(concat.split(concat.test, 2, mode = "value", drop.col = TRUE))
```

##	Name	Siblings	Hates	Likes_1	Likes_2	Likes_3
## 1	Boyd Reynolds , Albert , Ortega	2;4;		1	2	NA
## 2	Rufus Cohen , Bert , Montgomery	1;2;3;4;		1	2	NA
## 3	Dana	Pierce	2;	1	2	NA
## 4	Carole Colon , Michelle , Ballard	1;4;		1	2	NA
## 5	Ramona Snyder , Joann ,	1;2;3;		1	2	NA
## 6	Kelley James , Roxanne ,	1;4;		1	2	NA

##	Likes_4	Likes_5	Likes_6
## 1	4	5	6
## 2	4	5	6
## 3	4	5	6
## 4	4	5	6
## 5	NA	5	6
## 6	NA	5	6

```
# Let's try splitting some strings... Same syntax
head(concat.split(concat.test, 3, drop.col = TRUE))
```

##	Name	Likes	Hates	Siblings_1	Siblings_2	Siblings_3
## 1	Boyd	1,2,4,5,6	2;4;	Reynolds	Albert	Ortega
## 2	Rufus	1,2,4,5,6	1;2;3;4;	Cohen	Bert	Montgomery
## 3	Dana	1,2,4,5,6	2;	Pierce	<NA>	<NA>
## 4	Carole	1,2,4,5,6	1;4;	Colon	Michelle	Ballard
## 5	Ramona	1,2,5,6	1;2;3;	Snyder	Joann	<NA>
## 6	Kelley	1,2,5,6	1;4;	James	Roxanne	<NA>

To Do

- Modify the function so that you can split multiple columns in one go?

References

See: <http://stackoverflow.com/q/10100887/1270695>

df.sorter

What it Does

The `df.sorter` function allows you to sort a `data.frame` by columns or rows or both. You can also quickly subset data solums by using the `var.order` argument.

Arguments

- `data`: the source `data.frame`.
- `var.order`: the new order in which you want the variables to appear.
 - Defaults to `names(data)`, which keeps the variables in the original order.
 - Variables can be referred to either by a vector of their index numbers or by a vector of the variable name; partial name matching also works, but requires that the partial match identifies similar columns uniquely (see examples).
 - Basic subsetting can also be done using `var.order` simply by omitting the variables you want to drop.
- `col.sort`: the columns *within* which there is data that need to be sorted.
 - Defaults to `NULL`, which means no sorting takes place.
 - Variables can be referred to either by a vector of their index numbers or by a vector of the variable names; full names must be provided.
- `at.start`: Should the pattern matching be from the start of the variable name? Defaults to `"TRUE"`.

NOTE: If you are sorting both by variables and within the columns, the `col.sort` order should be based on the location of the columns in the *new data.frame*, not the original `data.frame`.

Examples

```
# Load the function! require(RCurl) baseURL =
# c('https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/')
source(textConnection(getURL(paste0(baseURL, "scripts/df.sorter.R"))))

# Make up some data
set.seed(1)
dat = data.frame(id = rep(1:5, each = 3), times = rep(1:3, 5), measure1 = rnorm(15),
  score1 = sample(300, 15), code1 = replicate(15, paste(sample(LETTERS[1:5],
    3), sep = "", collapse = "")), measure2 = rnorm(15), score2 = sample(150:300,
    15), code2 = replicate(15, paste(sample(LETTERS[1:5], 3), sep = "",
    collapse = "")))
# Preview your data
dat
```

	id	times	measure1	score1	code1	measure2	score2	code2
## 1	1	1	-0.6265	145	DAB	-0.7075	299	CEB
## 2	1	2	0.1836	180	DCB	0.3646	224	ECD
## 3	1	3	-0.8356	148	EBA	0.7685	222	DAE
## 4	2	1	1.5953	56	AED	-0.1123	175	DBA
## 5	2	2	0.3295	245	CEB	0.8811	260	DAC
## 6	2	3	-0.8205	198	EBD	0.3981	216	DCA

```
## 7 3 1 0.4874 234 BCA -0.6120 300 CEA
## 8 3 2 0.7383 32 CDA 0.3411 179 CAD
## 9 3 3 0.5758 212 EBC -1.1294 182 BEC
## 10 4 1 -0.3054 120 BED 1.4330 234 CDE
## 11 4 2 1.5118 239 EDB 1.9804 231 CAB
## 12 4 3 0.3898 188 DEB -0.3672 160 DBE
## 13 5 1 -0.6212 226 DBA -1.0441 154 EDB
## 14 5 2 -2.2147 159 DAC 0.5697 238 BDE
## 15 5 3 1.1249 152 AED -0.1351 277 DCE
```

*# Change the variable order, grouping related columns Note that you do not
need to specify full variable names, just enough that the variables can
be uniquely identified*

```
head(df.sorter(dat, var.order = c("id", "ti", "cod", "mea", "sco")))
```

```
## id times code1 code2 measure1 measure2 score1 score2
## 1 1 1 DAB CEB -0.6265 -0.7075 145 299
## 2 1 2 DCB ECD 0.1836 0.3646 180 224
## 3 1 3 EBA DAE -0.8356 0.7685 148 222
## 4 2 1 AED DBA 1.5953 -0.1123 56 175
## 5 2 2 CEB DAC 0.3295 0.8811 245 260
## 6 2 3 EBD DCA -0.8205 0.3981 198 216
```

Same output, but with a more awkward syntax

```
head(df.sorter(dat, var.order = c(1, 2, 5, 8, 3, 6, 4, 7)))
```

```
## id times code1 code2 measure1 measure2 score1 score2
## 1 1 1 DAB CEB -0.6265 -0.7075 145 299
## 2 1 2 DCB ECD 0.1836 0.3646 180 224
## 3 1 3 EBA DAE -0.8356 0.7685 148 222
## 4 2 1 AED DBA 1.5953 -0.1123 56 175
## 5 2 2 CEB DAC 0.3295 0.8811 245 260
## 6 2 3 EBD DCA -0.8205 0.3981 198 216
```

As above, but sorted by 'times' and then 'id'

```
head(df.sorter(dat, var.order = c("id", "tim", "cod", "mea", "sco"),
  col.sort = c(2, 1)))
```

```
## id times code1 code2 measure1 measure2 score1 score2
## 1 1 1 DAB CEB -0.6265 -0.7075 145 299
## 4 2 1 AED DBA 1.5953 -0.1123 56 175
## 7 3 1 BCA CEA 0.4874 -0.6120 234 300
## 10 4 1 BED CDE -0.3054 1.4330 120 234
## 13 5 1 DBA EDB -0.6212 -1.0441 226 154
## 2 1 2 DCB ECD 0.1836 0.3646 180 224
```

Drop 'measure1' and 'measure2', sort by 'times', and 'score1'

```
head(df.sorter(dat, var.order = c("id", "tim", "sco", "cod"), col.sort = c(2,
  3)))
```

```
## id times score1 score2 code1 code2
## 4 2 1 56 175 AED DBA
## 10 4 1 120 234 BED CDE
## 1 1 1 145 299 DAB CEB
## 13 5 1 226 154 DBA EDB
## 7 3 1 234 300 BCA CEA
## 8 3 2 32 179 CDA CAD
```

```
# As above, but using names
head(df.sorter(dat, var.order = c("id", "tim", "sco", "cod"), col.sort = c("times",
"score1")))
```

```
##      id times score1 score2 code1 code2
## 4      2      1      56      175  AED  DBA
## 10     4      1     120      234  BED  CDE
## 1      1      1     145      299  DAB  CEB
## 13     5      1     226      154  DBA  EDB
## 7      3      1     234      300  BCA  CEA
## 8      3      2      32      179  CDA  CAD
```

```
# Just sort by columns, first by 'times' then by 'id'
head(df.sorter(dat, col.sort = c("times", "id")))
```

```
##      id times measure1 score1 code1 measure2 score2 code2
## 1      1      1 -0.6265     145  DAB  -0.7075     299  CEB
## 4      2      1  1.5953      56  AED  -0.1123     175  DBA
## 7      3      1  0.4874     234  BCA  -0.6120     300  CEA
## 10     4      1 -0.3054     120  BED   1.4330     234  CDE
## 13     5      1 -0.6212     226  DBA  -1.0441     154  EDB
## 2      1      2  0.1836     180  DCB   0.3646     224  ECD
```

```
head(df.sorter(dat, col.sort = c("code1"))) # Sorting by character values
```

```
##      id times measure1 score1 code1 measure2 score2 code2
## 4      2      1  1.5953      56  AED  -0.1123     175  DBA
## 15     5      3  1.1249     152  AED  -0.1351     277  DCE
## 7      3      1  0.4874     234  BCA  -0.6120     300  CEA
## 10     4      1 -0.3054     120  BED   1.4330     234  CDE
## 8      3      2  0.7383      32  CDA   0.3411     179  CAD
## 5      2      2  0.3295     245  CEB   0.8811     260  DAC
```

```
# Pattern matching anywhere in the variable name
head(df.sorter(dat, var.order = "co", at.start = FALSE))
```

```
##      code1 code2 score1 score2
## 1      DAB  CEB     145     299
## 2      DCB  ECD     180     224
## 3      EBA  DAE     148     222
## 4      AED  DBA      56     175
## 5      CEB  DAC     245     260
## 6      EBD  DCA     198     216
```

To Do

- Add an option to sort ascending or descending—at the moment, not supported.

multi.freq.table

What it Does

The `multi.freq.table` function takes a data frame containing boolean responses to multiple response questions and tabulates the number of responses by the possible combinations of answers.

Arguments

- `data`: The multiple responses that need to be tabulated.
- `sep`: The desired separator for collapsing the combinations of options; defaults to "" (collapsing with no space between each option name).
- `dropzero`: Should combinations with a frequency of zero be dropped from the final table? Defaults to FALSE.
- `clean`: Should the original tabulated data be retained or dropped from the final table? Defaults to TRUE.

Examples

```
# Load the function! require(RCurl) baseURL =
# c('https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/')
source(textConnection(getURL(paste0(baseURL, "scripts/multi.freq.table.R"))))

# Make up some data
set.seed(1)
dat = data.frame(A = sample(c(0, 1), 20, replace = TRUE), B = sample(c(0,
  1), 20, replace = TRUE), C = sample(c(0, 1), 20, replace = TRUE), D = sample(c(0,
  1), 20, replace = TRUE), E = sample(c(0, 1), 20, replace = TRUE))
# View your data
dat

##      A B C D E
## 1  0 1 1 1 0
## 2  0 0 1 0 1
## 3  1 1 1 0 0
## 4  1 0 1 0 0
## 5  0 0 1 1 1
## 6  1 0 1 0 0
## 7  1 0 0 0 1
## 8  1 0 0 1 0
## 9  1 1 1 0 0
## 10 0 0 1 1 0
## 11 0 0 0 0 0
## 12 0 1 1 1 0
## 13 1 0 0 0 1
## 14 0 0 0 0 1
## 15 1 1 0 0 1
## 16 0 1 0 1 1
## 17 1 1 0 1 0
## 18 1 0 1 0 0
## 19 0 1 1 1 1
## 20 1 0 0 1 1

# Apply the function with all defaults accepted
multi.freq.table(dat)
```

```
##      Combn Freq
## 1      1
## 2      A      0
## 3      B      0
## 4      AB     0
## 5      C      0
## 6      AC     3
## 7      BC     0
## 8      ABC    2
## 9      D      0
## 10     AD     1
## 11     BD     0
## 12     ABD    1
## 13     CD     1
## 14     ACD    0
## 15     BCD    2
## 16     ABCD   0
## 17     E      1
## 18     AE     2
## 19     BE     0
## 20     ABE    1
## 21     CE     1
## 22     ACE    0
## 23     BCE    0
## 24     ABCE   0
## 25     DE     0
## 26     ADE    1
## 27     BDE    1
## 28     ABDE   0
## 29     CDE    1
## 30     ACDE   0
## 31     BCDE   1
## 32     ABCDE  0
```

```
# Tabulate only on variables 'A', 'B', and 'D', with a different
# separator, dropping any zero frequency values, and keeping the original
# tabulations. Note that there are no solitary 'B' responses.
multi.freq.table(dat[c(1, 2, 4)], sep = "-", dropzero = TRUE, clean = FALSE)
```

```
##   A B D Freq Combn
## 1 0 0 0     3
## 2 1 0 0     5      A
## 4 1 1 0     3    A-B
## 5 0 0 1     2      D
## 6 1 0 1     2    A-D
## 7 0 1 1     4    B-D
## 8 1 1 1     1  A-B-D
```

References

apply shortcut for creating the Combn column in the output by [Justin](#)
 See: <http://stackoverflow.com/q/11348391/1270695>

row.extractor

What it Does

The `row.extractor` function takes a `data.frame` and extracts rows with the `min`, `median`, or `max` values of a given variable, or extracts rows with specific quantiles of a given variable.

Arguments

- `data`: the source `data.frame`.
- `extract.by`: the column which will be used as the reference for extraction; can be specified either by the column number or the variable name.
- `what`: options are `min` (for all rows matching the minimum value), `median` (for the median row or rows), `max` (for all rows matching the maximum value), or `all` (for `min`, `median`, and `max`); alternatively, a numeric vector can be specified with the desired quantiles, for instance `c(0, .25, .5, .75, 1)`

The Function

```
row.extractor = function(data, extract.by, what = "all") {  
  
  if (is.numeric(extract.by)) {  
    extract.by = extract.by  
  } else if (is.numeric(extract.by) != 0) {  
    extract.by = which(colnames(data) %in% "extract.by")  
  }  
  
  if (is.character(what)) {  
    which.median = function(data, extract.by) {  
      a = data[, extract.by]  
      if (length(a)%2 != 0) {  
        which(a == median(a))  
      } else if (length(a)%2 == 0) {  
        b = sort(a)[c(length(a)/2, length(a)/2 + 1)]  
        c(max(which(a == b[1])), min(which(a == b[2])))  
      }  
    }  
  
    X1 = data[which(data[extract.by] == min(data[extract.by])), ] # min  
    X2 = data[which(data[extract.by] == max(data[extract.by])), ] # max  
    X3 = data[which.median(data, extract.by), ] # median  
  
    if (identical(what, "min")) {  
      X1  
    } else if (identical(what, "max")) {  
      X2  
    } else if (identical(what, "median")) {  
      X3  
    } else if (identical(what, "all")) {  
      rbind(X1, X3, X2)  
    }  
  } else if (is.numeric(what)) {  
    which.quantile <- function(data, extract.by, what, na.rm = FALSE) {  
  
      x = data[, extract.by]
```

```

    if (!na.rm & any(is.na(x)))
      return(rep(NA_integer_, length(what)))

    o <- order(x)
    n <- sum(!is.na(x))
    o <- o[seq_len(n)]

    nppm <- n * what - 0.5
    j <- floor(nppm)
    h <- ifelse((nppm == j) & ((j%%2L) == 0L), 0, 1)
    j <- j + h

    j[j == 0] <- 1
    o[j]

  }
  data[which.quantile(data, extract.by, what), ] # quantile
}

```

Examples

```

# Make up some data
set.seed(1)
dat = data.frame(V1 = 1:50, V2 = rnorm(50), V3 = round(abs(rnorm(50)),
  digits = 2), V4 = sample(1:30, 50, replace = TRUE))
# Get a summary of the data
summary(dat)

##           V1           V2           V3           V4
## Min.      : 1.0    Min.   :-2.215    Min.    :0.000    Min.    : 2.00
## 1st Qu.:13.2    1st Qu.: -0.372    1st Qu.:0.347    1st Qu.: 8.25
## Median :25.5    Median : 0.129    Median :0.590    Median :13.00
## Mean   :25.5    Mean    : 0.100    Mean    :0.774    Mean    :14.80
## 3rd Qu.:37.8    3rd Qu.: 0.728    3rd Qu.:1.175    3rd Qu.:20.75
## Max.   :50.0    Max.    : 1.595    Max.    :2.400    Max.    :29.00

# Get the rows corresponding to the 'min', 'median', and 'max' of 'V4'
row.extractor(dat, 4)

##      V1      V2    V3 V4
## 28 28 -1.4708 0.00  2
## 47 47  0.3646 1.28 13
## 29 29 -0.4782 0.07 13
## 11 11  1.5118 2.40 29
## 14 14 -2.2147 0.03 29
## 18 18  0.9438 1.47 29
## 19 19  0.8212 0.15 29
## 50 50  0.8811 0.47 29

# Get the 'min' rows only, referenced by the variable name
row.extractor(dat, "V4", "min")

##      V1      V2 V3 V4
## 28 28 -1.471  0  2

```

```

# Get the 'median' rows only. Notice that there are two rows since we have
# an even number of cases and true median is the mean of the two central
# sorted values
row.extractor(dat, "V4", "median")

```

```

##      V1      V2  V3 V4
## 47 47  0.3646 1.28 13
## 29 29 -0.4782 0.07 13

```

```

# Get the rows corresponding to the deciles of 'V3'
row.extractor(dat, "V3", seq(0.1, 1, 0.1))

```

```

##      V1      V2  V3 V4
## 10 10 -0.30539 0.14 22
## 26 26 -0.05613 0.29 16
## 39 39  1.10003 0.37 13
## 41 41 -0.16452 0.54 10
## 30 30  0.41794 0.59 26
## 44 44  0.55666 0.70  5
## 37 37 -0.39429 1.06 21
## 49 49 -0.11235 1.22 14
## 34 34 -0.05381 1.52 19
## 11 11  1.51178 2.40 29

```

References

which.quantile function by [cbeleites](#)
 See: <http://stackoverflow.com/q/10256503/1270695>

The Functions

The most current source code for the functions described in this document follow.

To load the functions, you can directly source them from the 2657 R Functions page at github:
<https://github.com/mrdwab/2657-R-Functions>

You should be able to load the functions using the following (replace ----- with the function name):

```
require(RCurl)
baseURL = c("https://raw.githubusercontent.com/mrdwab/2657-R-Functions/master/")
source(textConnection(getURL(paste0(baseURL, "scripts/-----.R"))))
```

concat.split

```
concat.split = function(data, split.col, mode=NULL,
                        sep=",", drop.col=FALSE) {
  # Takes a column with multiple values, splits the values into
  # separate columns, and returns a new data.frame.
  # 'data' is the source data.frame; 'split.col' is the variable that
  # needs to be split; 'mode' can be either 'binary' or 'value'
  # (where 'binary' is default and it recodes values to 1 or NA);
  # 'sep' is the character separating each value (defaults to ',');
  # and 'drop.col' is logical (whether to remove the original
  # variable from the output or not.
  #
  # === EXAMPLES ===
  #
  #   dat = data.frame(V1 = c("1, 2, 4", "3, 4, 5",
  #                           "1, 2, 5", "4", "1, 2, 3, 5"),
  #                     V2 = c("1;2;3;4", "1", "2;5",
  #                           "3;2", "2;3;4"))
  #   dat2 = data.frame(V1 = c("Fred, John, Sue", "Jerry, Jill",
  #                             "Sally, Ryan", "Susan, Amos, Ben"))
  #
  #   concat.split(dat, 1)
  #   concat.split(dat, 2, sep=";")
  #   concat.split(dat, "V2", sep=";", mode="value")
  #   concat.split(dat, "V1", mode="binary")
  #   concat.split(dat2, 1)
  #   concat.split(dat2, "V1", drop.col=TRUE)
  #
  # See: http://stackoverflow.com/q/10100887/1270695

  if (is.numeric(split.col)) split.col = split.col
  else split.col = which(colnames(data) %in% split.col)

  a = as.character(data[, split.col])
  b = strsplit(a, sep)

  if (suppressWarnings(is.na(try(max(as.numeric(unlist(b))))))) {
    what = "string"
    ncol = max(unlist(lapply(b, function(i) length(i))))
  } else if (!is.na(try(max(as.numeric(unlist(b)))))) {
    what = "numeric"
    ncol = max(as.numeric(unlist(b)))
  }

  m = matrix(nrow = nrow(data), ncol = ncol)
  v = vector("list", nrow(data))

  if (identical(what, "string")) {
    temp = as.data.frame(t(sapply(b, '[', 1:ncol)))
    names(temp) = paste(names(data[split.col]), "_", 1:ncol, sep="")
    temp = apply(temp, 2, function(x) gsub("^\\s+|\\s+$", "", x))
    temp1 = cbind(data, temp)
  } else if (identical(what, "numeric")) {
    for (i in 1:nrow(data)) {
      v[[i]] = as.numeric(strsplit(a, sep)[[i]])
    }
  }
}
```

```

temp = v

for (i in 1:nrow(data)) {
  m[i, temp[[i]]] = temp[[i]]
}

m = data.frame(m)
names(m) = paste(names(data[split.col]), "_", 1:ncol, sep="")

if (is.null(mode) || identical(mode, "binary")) {
  temp1 = cbind(data, replace(m, m != "NA", 1))
} else if (identical(mode, "value")) {
  temp1 = cbind(data, m)
}

if (isTRUE(drop.col)) temp1[~split.col]
else temp1
}

```


df.sorter

```
df.sorter = function(data, var.order=names(data), col.sort=NULL, at.start=TRUE ) {
  # Sorts a data.frame by columns or rows or both.
  # Can also subset the data columns by using 'var.order'.
  # Can refer to variables either by names or number.
  # If referring to variable by number, and sorting both the order
  #   of variables and the sorting within variables, refer to the
  #   variable numbers of the final data.frame.
  #
  # === EXAMPLES ===
  #
  #   library(foreign)
  #   temp = "http://www.ats.ucla.edu/stat/stata/modules/kidshtwt.dta"
  #   kidshtwt = read.dta(temp); rm(temp)
  #   df.sorter(kidshtwt, var.order = c("fam", "bir", "wt", "ht"))
  #   df.sorter(kidshtwt, var.order = c("fam", "bir", "wt", "ht"),
  #             col.sort = c("birth", "famid")) # USE FULL NAMES HERE
  #   df.sorter(kidshtwt, var.order = c(1:4),    # DROP THE WT COLUMNS
  #             col.sort = 3)                   # SORT BY HT1

  if (is.numeric(var.order))
    var.order = colnames(data)[var.order]
  else var.order = var.order

  a = names(data)
  b = length(var.order)
  subs = vector("list", b)

  if (isTRUE(at.start)) {
    for (i in 1:b) {
      subs[[i]] = sort(grep(paste("^", var.order[i],
                                sep="", collapse=""),
                            a, value=TRUE))
    }
  } else if (!isTRUE(at.start)) {
    for (i in 1:b) {
      subs[[i]] = sort(grep(var.order[i], a, value=TRUE))
    }
  }

  x = unlist(subs)
  y = data[ , x ]

  if (is.null(col.sort)) {
    y
  } else if (is.numeric(col.sort)) {
    col.sort = colnames(y)[col.sort]
    y[do.call(order, y[col.sort]), ]
  } else if (!is.numeric(col.sort)) {
    col.sort = col.sort
    y[do.call(order, y[col.sort]), ]
  }
}
```

multi.freq.table

Warning: incomplete final line found on '~'

```
multi.freq.table = function(data, sep="", dropzero=FALSE, clean=TRUE) {
  # Takes boolean multiple-response data and tabulates it according
  #   to the possible combinations of each variable.
  #
  # === EXAMPLES ===
  #   set.seed(1)
  #   dat = data.frame(A = sample(c(0, 1), 20, replace=TRUE),
  #                     B = sample(c(0, 1), 20, replace=TRUE),
  #                     C = sample(c(0, 1), 20, replace=TRUE),
  #                     D = sample(c(0, 1), 20, replace=TRUE),
  #                     E = sample(c(0, 1), 20, replace=TRUE))
  #   multi.freq.table(dat)
  #   multi.freq.table(dat[1:3], sep="-", dropzero=TRUE)
  #
  # See: http://stackoverflow.com/q/11348391/1270695

  counts = data.frame(table(data))
  N = ncol(counts)
  counts$Combn = apply(counts[-N] == 1, 1,
                       function(x) paste(names(counts[-N])[x],
                                           collapse=sep))

  if (isTRUE(dropzero)) {
    counts = counts[counts$Freq != 0, ]
  } else if (!isTRUE(dropzero)) {
    counts = counts
  }
  if (isTRUE(clean)) {
    counts = data.frame(Combn = counts$Combn, Freq = counts$Freq)
  }
  counts
}
```