

# LOGIC AND THEORETICAL FOUNDATION OF COMPUTER SCIENCE

LATFoCS

---

Pamela Fleischmann

fpa@informatik.uni-kiel.de

Winter Semester 2019

Kiel University  
Dependable Systems Group



# CONTEXT-FREE GRAMMARS AND LANGUAGES

---

# New Approach

- Goal: Automaton that can recognize  $\{a^n b^n \mid n \in \mathbb{N}\}$



# New Approach

- Goal: Automaton that can recognize  $\{a^n b^n \mid n \in \mathbb{N}\}$
- Ideas:



# New Approach

- Goal: Automaton that can recognize  $\{a^n b^n \mid n \in \mathbb{N}\}$
- Ideas:
  - Each time we read an  $a$ , we read simultaneously an  $b$



# New Approach

- Goal: Automaton that can recognize  $\{a^n b^n \mid n \in \mathbb{N}\}$
- Ideas:
  - Each time we read an  $a$ , we read simultaneously an  $b$
  - We have to ensure that all  $a$ s are before the  $b$ s



# New Approach

- Goal: Automaton that can recognize  $\{a^n b^n \mid n \in \mathbb{N}\}$
- Ideas:
  - Each time we read an  $a$ , we read simultaneously an  $b$
  - We have to ensure that all  $a$ s are before the  $b$ s
- Constructive Approach with rules:  $S \rightarrow aSb \mid \varepsilon$



# (Context-Free) Grammars

## Definition

○  $G = (V, \Sigma, S, P)$  **grammar** iff





# (Context-Free) Grammars

## Definition

- $G = (V, \Sigma, S, P)$  **grammar** iff
  - $V$  finite set of variables



# (Context-Free) Grammars

## Definition

- $G = (V, \Sigma, S, P)$  **grammar** iff
  - $V$  finite set of variables
  - $\Sigma$  alphabet with  $V \cap \Sigma = \emptyset$



# (Context-Free) Grammars

## Definition

- $G = (V, \Sigma, S, P)$  **grammar** iff
  - $V$  finite set of variables
  - $\Sigma$  alphabet with  $V \cap \Sigma = \emptyset$
  - $S \in V$  start symbol



# (Context-Free) Grammars

## Definition

- $G = (V, \Sigma, S, P)$  **grammar** iff
  - $V$  finite set of variables
  - $\Sigma$  alphabet with  $V \cap \Sigma = \emptyset$
  - $S \in V$  start symbol
  - $P \subseteq (V \cup \Sigma)^* \times (V \cup \Sigma \cup \{\varepsilon\})^*$  production rules



# (Context-Free) Grammars

## Definition

- $G = (V, \Sigma, S, P)$  **grammar** iff
  - $V$  finite set of variables
  - $\Sigma$  alphabet with  $V \cap \Sigma = \emptyset$
  - $S \in V$  start symbol
  - $P \subseteq (V \cup \Sigma)^* \times (V \cup \Sigma \cup \{\varepsilon\})^*$  production rules
- $G$  **context-free**:  $P \subseteq V \times (V \cup \Sigma \cup \{\varepsilon\})^*$



# A Grammar's Language

## Definition

$G$  context-free grammar,  $\alpha, \beta \in (V \cup \Sigma)^*$

○  $\alpha \vdash \beta$  ( $\beta$  is **derivable** from  $\alpha$  **in one step**) iff

$$\exists(A, \gamma) \in P : \alpha = \alpha_1 A \alpha_2 \wedge \beta = \alpha_1 \gamma \alpha_2$$



# A Grammar's Language

## Definition

$G$  context-free grammar,  $\alpha, \beta \in (V \cup \Sigma)^*$

- $\alpha \vdash \beta$  ( $\beta$  is **derivable** from  $\alpha$  **in one step**) iff

$$\exists (A, \gamma) \in P : \alpha = \alpha_1 A \alpha_2 \wedge \beta = \alpha_1 \gamma \alpha_2$$

- $\vdash^*$  reflexive-transitive closure



# A Grammar's Language

## Definition

$G$  context-free grammar,  $\alpha, \beta \in (V \cup \Sigma)^*$

- $\alpha \vdash \beta$  ( $\beta$  is **derivable** from  $\alpha$  **in one step**) iff

$$\exists(A, \gamma) \in P : \alpha = \alpha_1 A \alpha_2 \wedge \beta = \alpha_1 \gamma \alpha_2$$

- $\vdash^*$  reflexive-transitive closure
- $L(G) = \{w \in \Sigma^* \mid S \vdash^* w\}$





## BALANCED PARANTHESIS

---

- arithmetics:  $(5 + 3) \cdot 2, (7 + (8 \div 2)) \cdot 4$



# Motivation

- arithmetics:  $(5 + 3) \cdot 2, (7 + (8 \div 2)) \cdot 4$
- programming languages:  
if (everything alright) { do a lot of stuff }



# Motivation

- arithmetics:  $(5 + 3) \cdot 2, (7 + (8 \div 2)) \cdot 4$
- programming languages:  
if (everything alright) { do a lot of stuff }
- can we detect if something is not correct?



# Balanced Parenthesis

informal:

- number of left parenthesis = number of right parenthesis



# Balanced Parenthesis

informal:

- number of left parenthesis = number of right parenthesis
- the number of right parenthesis in every prefix is at most the number of left parenthesis



# Balanced Parenthesis

informal:

- number of left parenthesis = number of right parenthesis
- the number of right parenthesis in every prefix is at most the number of left parenthesis

formal:

## Definition (Balanced Parenthesis)

$$\Sigma_P = \Sigma \cup \{ (, ) \}$$

$x \in \Sigma_P^*$  **balanced** iff

1.  $|x|_ ( = |x|_ )$
2.  $\forall y \in \text{Pref}(x) : |y|_ ( \geq |y|_ )$



# Checking the Balanced Property

## Definition

$G_P = (\{S\}, \Sigma_P, S, P)$  with the productions  $P$

$$S \rightarrow (S) | SS | \varepsilon$$

$$\forall a \in \Sigma : S \rightarrow a$$





# Checking the Balanced Property

## Definition

$G_P = (\{S\}, \Sigma_P, S, P)$  with the productions  $P$

$$S \rightarrow (S) | SS | \varepsilon$$

$$\forall a \in \Sigma : S \rightarrow a$$

## Theorem

$$L(G_P) = \{x \in \Sigma_P \mid x \text{ balanced}\}$$



Induction on length of derivation:

- Start:  $S \vdash_G^0 x \Rightarrow$  no step  $\Rightarrow$  no parenthesis  $\Rightarrow \checkmark$



Induction on length of derivation:

- Start:  $S \vdash_G^0 x \Rightarrow$  no step  $\Rightarrow$  no parenthesis  $\Rightarrow \checkmark$
- Hypothesis: if  $S \vdash_G^n x$  for an arbitrary but fixed  $n \in \mathbb{N}$  then  $x$  is balanced



Induction on length of derivation:

- Start:  $S \vdash_G^0 x \Rightarrow$  no step  $\Rightarrow$  no parenthesis  $\Rightarrow \checkmark$
- Hypothesis: if  $S \vdash_G^n x$  for an arbitrary but fixed  $n \in \mathbb{N}$  then  $x$  is balanced
- Step: Consider  $S \vdash_G^{n+1} x$



Induction on length of derivation:

- Start:  $S \vdash_G^0 x \Rightarrow$  no step  $\Rightarrow$  no parenthesis  $\Rightarrow \checkmark$
- Hypothesis: if  $S \vdash_G^n x$  for an arbitrary but fixed  $n \in \mathbb{N}$  then  $x$  is balanced
- Step: Consider  $S \vdash_G^{n+1} x$ 
  - definition of derivation  $\Rightarrow \exists z \in \Sigma_P^* : S \vdash_G^n z \vdash_G^1 x$



Induction on length of derivation:

- Start:  $S \vdash_G^0 x \Rightarrow$  no step  $\Rightarrow$  no parenthesis  $\Rightarrow \checkmark$
- Hypothesis: if  $S \vdash_G^n x$  for an arbitrary but fixed  $n \in \mathbb{N}$  then  $x$  is balanced
- Step: Consider  $S \vdash_G^{n+1} x$ 
  - definition of derivation  $\Rightarrow \exists z \in \Sigma_P^* : S \vdash_G^n z \vdash_G^1 x$
  - hypothesis  $\Rightarrow z$  balanced



- case 1: second, third or fourth rule applied



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced





- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1(S)z_2$



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1(S)z_2$
  - obviously first property is satisfied



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1(S)z_2$
  - obviously first property is satisfied
  - for the second property:  $y \in \text{Pref}(x)$



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1(S)z_2$
  - obviously first property is satisfied
  - for the second property:  $y \in \text{Pref}(x)$
  - case a:  $|y| \leq |z_1|$



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1(S)z_2$
  - obviously first property is satisfied
  - for the second property:  $y \in \text{Pref}(x)$
  - case a:  $|y| \leq |z_1|$ 
    - hypothesis  $\Rightarrow \checkmark$



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1(S)z_2$
  - obviously first property is satisfied
  - for the second property:  $y \in \text{Pref}(x)$
  - case a:  $|y| \leq |z_1|$ 
    - hypothesis  $\Rightarrow \checkmark$
  - case b:  $|y| \leq |z_1| + 2$



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1(S)z_2$
  - obviously first property is satisfied
  - for the second property:  $y \in \text{Pref}(x)$
  - case a:  $|y| \leq |z_1|$ 
    - hypothesis  $\Rightarrow \checkmark$
  - case b:  $|y| \leq |z_1| + 2$ 
    - $|y|_c = |z_1|_c + 1$  and  $|y|_b = |z_1|_b$





- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1 (S) z_2$
  - obviously first property is satisfied
  - for the second property:  $y \in \text{Pref}(x)$
  - case a:  $|y| \leq |z_1|$ 
    - hypothesis  $\Rightarrow \checkmark$
  - case b:  $|y| \leq |z_1| + 2$ 
    - $|y|_c = |z_1|_c + 1$  and  $|y| = |z_1|$
    - $\Rightarrow |y|_c = |z_1|_c + 1 = |z_1| + 1 = |y| + 1 \Rightarrow \checkmark$



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1(S)z_2$
  - obviously first property is satisfied
  - for the second property:  $y \in \text{Pref}(x)$
  - case a:  $|y| \leq |z_1|$ 
    - hypothesis  $\Rightarrow \checkmark$
  - case b:  $|y| \leq |z_1| + 2$ 
    - $|y|_c = |z_1|_c + 1$  and  $|y| = |z_1|$
    - $\Rightarrow |y|_c = |z_1|_c + 1 = |z_1| + 1 = |y| + 1 \Rightarrow \checkmark$
  - case c:  $|y| > |z_1| + 2$



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1(S)z_2$
  - obviously first property is satisfied
  - for the second property:  $y \in \text{Pref}(x)$
  - case a:  $|y| \leq |z_1|$ 
    - hypothesis  $\Rightarrow \checkmark$
  - case b:  $|y| \leq |z_1| + 2$ 
    - $|y|_c = |z_1|_c + 1$  and  $|y| = |z_1|$
    - $\Rightarrow |y|_c = |z_1|_c + 1 = |z_1| + 1 = |y| + 1 \Rightarrow \checkmark$
  - case c:  $|y| > |z_1| + 2$ 
    - $|y|_c = |z_1|_c + 1$  and  $|y| = |z_1| + 1$



- case 1: second, third or fourth rule applied
  - no change in number or order of parenthesis  $\Rightarrow x$  balanced
- case 2: first rule applied
  - $z = z_1 S z_2, x = z_1(S)z_2$
  - obviously first property is satisfied
  - for the second property:  $y \in \text{Pref}(x)$
  - case a:  $|y| \leq |z_1|$ 
    - hypothesis  $\Rightarrow \checkmark$
  - case b:  $|y| \leq |z_1| + 2$ 
    - $|y|_c = |z_1|_c + 1$  and  $|y| = |z_1|$
    - $\Rightarrow |y|_c = |z_1|_c + 1 = |z_1| + 1 = |y| + 1 \Rightarrow \checkmark$
  - case c:  $|y| > |z_1| + 2$ 
    - $|y|_c = |z_1|_c + 1$  and  $|y| = |z_1| + 1$
    - $\Rightarrow |y|_c = |z_1|_c + 1 = |z_1| + 1 = |y| \Rightarrow \checkmark$



Induction on  $|x|$

- Start:  $x = \varepsilon \Rightarrow S \vdash x$  by production  $S \rightarrow \varepsilon$



Induction on  $|x|$

- Start:  $x = \varepsilon \Rightarrow S \vdash x$  by production  $S \rightarrow \varepsilon$
- Hypothesis: if  $x$  balanced with  $|x| = n \in \mathbb{N}$  for  $n$  arbitrary but fixed then  $x$  is producible by  $G_P$



Induction on  $|x|$

- Start:  $x = \varepsilon \Rightarrow S \vdash x$  by production  $S \rightarrow \varepsilon$
- Hypothesis: if  $x$  balanced with  $|x| = n \in \mathbb{N}$  for  $n$  arbitrary but fixed then  $x$  is producible by  $G_P$
- Step: 2 cases



Induction on  $|x|$

- Start:  $x = \varepsilon \Rightarrow S \vdash x$  by production  $S \rightarrow \varepsilon$
- Hypothesis: if  $x$  balanced with  $|x| = n \in \mathbb{N}$  for  $n$  arbitrary but fixed then  $x$  is producible by  $G_P$
- Step: 2 cases
- case 1:  $\exists y, z \in \Sigma^+ : y, z$  balanced and  $x = yz$





Induction on  $|x|$

- Start:  $x = \varepsilon \Rightarrow S \vdash x$  by production  $S \rightarrow \varepsilon$
- Hypothesis: if  $x$  balanced with  $|x| = n \in \mathbb{N}$  for  $n$  arbitrary but fixed then  $x$  is producible by  $G_P$
- Step: 2 cases
- case 1:  $\exists y, z \in \Sigma^+ : y, z$  balanced and  $x = yz$ 
  - $|y|, |z| < |x| \Rightarrow S \vdash_G^* y$  and  $S \vdash_G^* z$



Induction on  $|x|$

- Start:  $x = \varepsilon \Rightarrow S \vdash x$  by production  $S \rightarrow \varepsilon$
- Hypothesis: if  $x$  balanced with  $|x| = n \in \mathbb{N}$  for  $n$  arbitrary but fixed then  $x$  is producible by  $G_P$
- Step: 2 cases
- case 1:  $\exists y, z \in \Sigma^+ : y, z$  balanced and  $x = yz$ 
  - $|y|, |z| < |x| \Rightarrow S \vdash_G^* y$  and  $S \vdash_G^* z$
  - derivation for  $x$ :  $S \vdash_G^1 SS \vdash_G^* yS \vdash_G^* yz = x$



Induction on  $|x|$

- Start:  $x = \varepsilon \Rightarrow S \vdash x$  by production  $S \rightarrow \varepsilon$
- Hypothesis: if  $x$  balanced with  $|x| = n \in \mathbb{N}$  for  $n$  arbitrary but fixed then  $x$  is producible by  $G_P$
- Step: 2 cases
- case 1:  $\exists y, z \in \Sigma^+ : y, z$  balanced and  $x = yz$ 
  - $|y|, |z| < |x| \Rightarrow S \vdash_G^* y$  and  $S \vdash_G^* z$
  - derivation for  $x$ :  $S \vdash_G^1 SS \vdash_G^* yS \vdash_G^* yz = x$
- case 2:  $x$  not splittable into two balanced parts



Induction on  $|x|$

- Start:  $x = \varepsilon \Rightarrow S \vdash x$  by production  $S \rightarrow \varepsilon$
- Hypothesis: if  $x$  balanced with  $|x| = n \in \mathbb{N}$  for  $n$  arbitrary but fixed then  $x$  is producible by  $G_P$
- Step: 2 cases
- case 1:  $\exists y, z \in \Sigma^+ : y, z$  balanced and  $x = yz$ 
  - $|y|, |z| < |x| \Rightarrow S \vdash_G^* y$  and  $S \vdash_G^* z$
  - derivation for  $x$ :  $S \vdash_G^1 SS \vdash_G^* yS \vdash_G^* yz = x$
- case 2:  $x$  not splittable into two balanced parts
  - first rule is the first  $\Rightarrow x = (z) \Rightarrow |z| < |x|$



Induction on  $|x|$

- Start:  $x = \varepsilon \Rightarrow S \vdash x$  by production  $S \rightarrow \varepsilon$
- Hypothesis: if  $x$  balanced with  $|x| = n \in \mathbb{N}$  for  $n$  arbitrary but fixed then  $x$  is producible by  $G_P$
- Step: 2 cases
- case 1:  $\exists y, z \in \Sigma^+ : y, z$  balanced and  $x = yz$ 
  - $|y|, |z| < |x| \Rightarrow S \vdash_G^* y$  and  $S \vdash_G^* z$
  - derivation for  $x$ :  $S \vdash_G^1 SS \vdash_G^* yS \vdash_G^* yz = x$
- case 2:  $x$  not splittable into two balanced parts
  - first rule is the first  $\Rightarrow x = (z) \Rightarrow |z| < |x|$
  - is  $z$  balanced?



- Ind. Step, case 2:  $x$  not splittable into two balanced parts
  - first rule is the first  $\Rightarrow x = (z) \Rightarrow |z| < |x|$
  - is  $z$  balanced?



- Ind. Step, case 2:  $x$  not splittable into two balanced parts
  - first rule is the first  $\Rightarrow x = (z) \Rightarrow |z| < |x|$
  - is  $z$  balanced?
    - $|z|_l = |x|_l - 1 = |x|_r - 1 = |z|_r \Rightarrow 1$ .



- Ind. Step, case 2:  $x$  not splittable into two balanced parts
  - first rule is the first  $\Rightarrow x = (z) \Rightarrow |z| < |x|$
  - is  $z$  balanced?
    - $|z|_l = |x|_l - 1 = |x|_r - 1 = |z|_r \Rightarrow 1$ .
    - $u \in \text{Pref}(z)$ ,  $x$  balanced  $\Rightarrow |u|_l - |u|_r = (|u|_l - 1 - |u|_r) \geq 0$





- Ind. Step, case 2:  $x$  not splittable into two balanced parts
  - first rule is the first  $\Rightarrow x = (z) \Rightarrow |z| < |x|$
  - is  $z$  balanced?
    - $|z|_l = |x|_l - 1 = |x|_r - 1 = |z|_r \Rightarrow 1$ .
    - $u \in \text{Pref}(z)$ ,  $x$  balanced  $\Rightarrow |u|_l - |u|_r = (|u|_l - 1 - |u|_r) \geq 0$
    - $\Rightarrow z$  balanced



- Ind. Step, case 2:  $x$  not splittable into two balanced parts
  - first rule is the first  $\Rightarrow x = (z) \Rightarrow |z| < |x|$
  - is  $z$  balanced?
    - $|z|_l = |x|_l - 1 = |x|_r - 1 = |z|_r \Rightarrow 1$ .
    - $u \in \text{Pref}(z)$ ,  $x$  balanced  $\Rightarrow |u|_l - |u|_r = (|u|_l - 1 - |u|_r) \geq 0$
    - $\Rightarrow z$  balanced
  - $\Rightarrow S \vdash_G^* z$



- Ind. Step, case 2:  $x$  not splittable into two balanced parts
  - first rule is the first  $\Rightarrow x = (z) \Rightarrow |z| < |x|$
  - is  $z$  balanced?
    - $|z|_{\zeta} = |x|_{\zeta} - 1 = |x|_{\eta} - 1 = |z|_{\eta} \Rightarrow 1.$
    - $u \in \text{Pref}(z), x \text{ balanced} \Rightarrow |u|_{\zeta} - |u|_{\eta} = (|u|_{\zeta} - 1 - |u|_{\eta}) \geq 0$
    - $\Rightarrow z$  balanced
  - $\Rightarrow S \vdash_G^* z$
  - $\Rightarrow S \vdash_G^1 (S) \vdash_G^* (z) = x$

□



# NORMAL FORMS

---

# Why normal forms?

- general grammar: everything is allowed
- $\Rightarrow$  complicated to reason with it
- first restriction: context-freedom
  - rule depends on one variable
  - rule does not depend on the variable's *neighbours*
- the right-hand side may be as *insane* as we can imagine
  - $A \rightarrow B$  and  $B \rightarrow A$
  - $A \rightarrow \varepsilon$



# Chomsky and Greibach Normalform

## Definition (Chomsky Normalform)

$G$  context-free grammar;  $G$  in **CNF** iff  $P \subseteq (V \times V^2) \cup (V \times \Sigma)$ .



# Chomsky and Greibach Normalform

## Definition (Chomsky Normalform)

$G$  context-free grammar;  $G$  in **CNF** iff  $P \subseteq (V \times V^2) \cup (V \times \Sigma)$ .

## Definition (Greibach Normalform)

$G$  context-free grammar;  $G$  in **GNF** iff  $P \subseteq V \times \Sigma V^*$



# Chomsky and Greibach Normalform

## Definition (Chomsky Normalform)

$G$  context-free grammar;  $G$  in **CNF** iff  $P \subseteq (V \times V^2) \cup (V \times \Sigma)$ .

## Definition (Greibach Normalform)

$G$  context-free grammar;  $G$  in **GNF** iff  $P \subseteq V \times \Sigma V^*$

Notice:  $\varepsilon$  is not producible in CNF or GNF





# What do we want?

we would like to work and prove with CFG in CNF or GNF, i.e.  
we'd like to have

## Theorem

*For all CFG  $G$  exists CNF  $G'$  and GNF  $G''$  with*

$$L(G'') = L(G') = L(G) \setminus \{\varepsilon\}.$$



# What do we want?

we would like to work and prove with CFG in CNF or GNF, i.e.  
we'd like to have

## Theorem

*For all CFG  $G$  exists CNF  $G'$  and GNF  $G''$  with*

$$L(G'') = L(G') = L(G) \setminus \{\varepsilon\}.$$

- can we prove that?



# What do we want?

we would like to work and prove with CFG in CNF or GNF, i.e.  
we'd like to have

## Theorem

*For all CFG  $G$  exists CNF  $G'$  and GNF  $G''$  with*

$$L(G'') = L(G') = L(G) \setminus \{\varepsilon\}.$$

- can we prove that?
- hope: in NFA the  $\varepsilon$ -transitions were not needed



# Getting rid of $\varepsilon$

## Lemma

*For all CFG  $G$  exists CFG  $G'$  without  $\varepsilon$ -production or unit-production such that  $L(G') = L(G) \setminus \{\varepsilon\}$ .*



# Getting rid of $\varepsilon$

## Lemma

*For all CFG  $G$  exists CFG  $G'$  without  $\varepsilon$ -production or unit-production such that  $L(G') = L(G) \setminus \{\varepsilon\}$ .*

Construction of  $G'$ :



# Getting rid of $\varepsilon$

## Lemma

*For all CFG  $G$  exists CFG  $G'$  without  $\varepsilon$ -production or unit-production such that  $L(G') = L(G) \setminus \{\varepsilon\}$ .*

Construction of  $G'$ :

○  $\hat{P} := P$



# Getting rid of $\varepsilon$

## Lemma

*For all CFG  $G$  exists CFG  $G'$  without  $\varepsilon$ -production or unit-production such that  $L(G') = L(G) \setminus \{\varepsilon\}$ .*

Construction of  $G'$ :

- $\hat{P} := P$
- while changes



# Getting rid of $\varepsilon$

## Lemma

*For all CFG  $G$  exists CFG  $G'$  without  $\varepsilon$ -production or unit-production such that  $L(G') = L(G) \setminus \{\varepsilon\}$ .*

Construction of  $G'$ :

- $\hat{P} := P$
- while changes
  - $A \rightarrow \alpha B \beta \in \hat{P} \wedge B \rightarrow \varepsilon \in \hat{P} \Rightarrow A \rightarrow \alpha \beta \in \hat{P}$





# Getting rid of $\varepsilon$

## Lemma

*For all CFG  $G$  exists CFG  $G'$  without  $\varepsilon$ -production or unit-production such that  $L(G') = L(G) \setminus \{\varepsilon\}$ .*

Construction of  $G'$ :

- $\hat{P} := P$
- while changes
  - $A \rightarrow \alpha B \beta \in \hat{P} \wedge B \rightarrow \varepsilon \in \hat{P} \Rightarrow A \rightarrow \alpha \beta \in \hat{P}$
  - $A \rightarrow B \in \hat{P} \wedge B \rightarrow \gamma \in \hat{P} \Rightarrow A \rightarrow \gamma \in \hat{P}$



# Getting rid of $\varepsilon$

## Lemma

*For all CFG  $G$  exists CFG  $G'$  without  $\varepsilon$ -production or unit-production such that  $L(G') = L(G) \setminus \{\varepsilon\}$ .*

Construction of  $G'$ :

- $\hat{P} := P$
- while changes
  - $A \rightarrow \alpha B \beta \in \hat{P} \wedge B \rightarrow \varepsilon \in \hat{P} \Rightarrow A \rightarrow \alpha \beta \in \hat{P}$
  - $A \rightarrow B \in \hat{P} \wedge B \rightarrow \gamma \in \hat{P} \Rightarrow A \rightarrow \gamma \in \hat{P}$
- for  $P'$  delete all  $\varepsilon$ -productions and unit-productions from  $\hat{P}$



# Constructing a CNF

$G$  context-free grammar without  $\varepsilon$ -productions or unit-productions

1. replace all  $a \in \Sigma$  on right-hand sides by new variable  $A_a$  and introduce  $A_a \rightarrow a$
2. for all  $A \rightarrow B_1 \dots B_k$  introduce  $A \rightarrow B_1 C$  and  $C \rightarrow B_2 \dots B_k$  for fresh variable  $C$



# Constructing a GNF: Step 1

$G$  grammar in CNF (for convenience)



# Constructing a GNF: Step 1

$G$  grammar in CNF (for convenience)

## Definition

- $\alpha \rightarrow_G^L \beta$  **leftmost derivation**: derive  $\beta$  from  $\alpha$  by always replacing the left-most variable



# Constructing a GNF: Step 1

$G$  grammar in CNF (for convenience)

## Definition

- $\alpha \rightarrow_G^L \beta$  **leftmost derivation**: derive  $\beta$  from  $\alpha$  by always replacing the left-most variable
- $R_{A,a} = \{\beta \in N^* \mid A \rightarrow_G^L a\beta\}$  (regular over  $N$ )



# Constructing a GNF: Step 1

$G$  grammar in CNF (for convenience)

## Definition

- $\alpha \rightarrow_G^L \beta$  **leftmost derivation**: derive  $\beta$  from  $\alpha$  by always replacing the left-most variable
- $R_{A,a} = \{\beta \in N^* \mid A \rightarrow_G^L a\beta\}$  (regular over  $N$ )
- $G_{A,a}$  grammar with  $L(G_{A,a}) = R_{A,a}$



# Constructing a GNF: Step 1

$G$  grammar in CNF (for convenience)

## Definition

- $\alpha \rightarrow_G^L \beta$  **leftmost derivation**: derive  $\beta$  from  $\alpha$  by always replacing the left-most variable
- $R_{A,a} = \{\beta \in N^* \mid A \rightarrow_G^L a\beta\}$  (regular over  $N$ )
- $G_{A,a}$  grammar with  $L(G_{A,a}) = R_{A,a}$
- w.l.o.g.  $T_{A,a}$  start symbol of  $G_{A,a}$





# Constructing a GNF: Step 1

$G$  grammar in CNF (for convenience)

## Definition

- $\alpha \rightarrow_G^L \beta$  **leftmost derivation**: derive  $\beta$  from  $\alpha$  by always replacing the left-most variable
- $R_{A,a} = \{\beta \in N^* \mid A \rightarrow_G^L a\beta\}$  (regular over  $N$ )
- $G_{A,a}$  grammar with  $L(G_{A,a}) = R_{A,a}$
- w.l.o.g.  $T_{A,a}$  start symbol of  $G_{A,a}$
- w.l.o.g. variables of  $G_{A,a}$  and  $G$  disjoint (renaming)



- $G_{A,a}$  strongly right-linear, i.e. all productions of form
  - $X \rightarrow BY$  for  $X, Y$  non-terminals of  $G_{A,a}$ ,  $B \in N$
  - $X \rightarrow \varepsilon$



# Constructing a GNF: Step 2

## Constructing $G_1$

- take all non-terminals and productions from  $G_{A,a}$  and  $G$
- $S$  start symbol of  $G_1$
- $\Rightarrow$  production in  $G_1$  of form
  - $X \rightarrow b$
  - $X \rightarrow \varepsilon$
  - $X \rightarrow BY$



# Constructing a GNF: Step 3

## Constructing $G_2$

- replace every  $X \rightarrow BY$  by  $X \rightarrow bT_{B,b}Y$



# Constructing a GNF: Step 3

## Constructing $G_2$

- replace every  $X \rightarrow BY$  by  $X \rightarrow bT_{B,b}Y$

## Constructing $G_3$

- get rid of  $\varepsilon$ -transitions by known mechanism



# Correctness of Construction

## Lemma

$$\forall X \in N \forall x \in \Sigma^* : (X \rightarrow_{G_1}^* x \Leftrightarrow X \rightarrow_{G_2}^* x)$$



# Correctness of Construction

## Lemma

$$\forall X \in N \forall x \in \Sigma^* : (X \rightarrow_{G_1}^* x \Leftrightarrow X \rightarrow_{G_2}^* x)$$

## Theorem

*$G_3$  is in GNF and  $L(G_3) = L(G)$  holds.*



# Correctness of Construction

## Lemma

$$\forall X \in N \forall x \in \Sigma^* : (X \rightarrow_{G_1}^* x \Leftrightarrow X \rightarrow_{G_2}^* x)$$

## Theorem

*$G_3$  is in GNF and  $L(G_3) = L(G)$  holds.*

having in mind that  $\varepsilon$  is not producible we are able to use CNF in GNF or CNF whenever we want





# PUSHDOWN AUTOMATA

---

# How to transform Grammars in Automata?

- let's try it with the idea of a memory



# How to transform Grammars in Automata?

- let's try it with the idea of a memory
- everything as simple as possible:
  - Automaton: only reading from left to right
  - Memory: stack (last-in-first-out)



# How to transform Grammars in Automata?

- let's try it with the idea of a memory
- everything as simple as possible:
  - Automaton: only reading from left to right
  - Memory: stack (last-in-first-out)
- we have access to:
  - 1 letter of the word
  - top element of the stack
  - state the machine is in



## Definition

$\mathcal{A} = (Q, \Sigma, \Gamma, \Delta, q_0, \perp, F)$  **PDA** iff



## Definition

$\mathcal{A} = (Q, \Sigma, \Gamma, \Delta, q_0, \perp, F)$  **PDA** iff

- $Q$  finite set of states,  $q_0$  initial state



## Definition

$\mathcal{A} = (Q, \Sigma, \Gamma, \Delta, q_0, \perp, F)$  **PDA** iff

- $Q$  finite set of states,  $q_0$  initial state
- $\Sigma$  input alphabet,  $\Gamma$  stack alphabet



## Definition

$\mathcal{A} = (Q, \Sigma, \Gamma, \Delta, q_0, \perp, F)$  **PDA** iff

- $Q$  finite set of states,  $q_0$  initial state
- $\Sigma$  input alphabet,  $\Gamma$  stack alphabet
- $\perp$  initial stack symbol





## Definition

$\mathcal{A} = (Q, \Sigma, \Gamma, \Delta, q_0, \perp, F)$  **PDA** iff

- $Q$  finite set of states,  $q_0$  initial state
- $\Sigma$  input alphabet,  $\Gamma$  stack alphabet
- $\perp$  initial stack symbol
- $F \subseteq Q$  final states



## Definition

$\mathcal{A} = (Q, \Sigma, \Gamma, \Delta, q_0, \perp, F)$  **PDA** iff

- $Q$  finite set of states,  $q_0$  initial state
- $\Sigma$  input alphabet,  $\Gamma$  stack alphabet
- $\perp$  initial stack symbol
- $F \subseteq Q$  final states
- $\Delta \subseteq (Q \times \Sigma \cup \{\varepsilon\} \cup \Gamma) \times (Q \times \Gamma^*)$



# Pushdown Automata

## Definition

$\mathcal{A} = (Q, \Sigma, \Gamma, \Delta, q_0, \perp, F)$  **PDA** iff

- $Q$  finite set of states,  $q_0$  initial state
- $\Sigma$  input alphabet,  $\Gamma$  stack alphabet
- $\perp$  initial stack symbol
- $F \subseteq Q$  final states
- $\Delta \subseteq (Q \times \Sigma \cup \{\varepsilon\} \cup \Gamma) \times (Q \times \Gamma^*)$

Notice: PDAs are non-deterministic!



# Explanations

- $((p, a, \alpha), (q, \beta)) \in \Delta$ :
  - I am in  $p$ ,
  - I read  $a$ ,
  - $\alpha$  is on the stack,
  - I go to  $q$ , and
  - I write  $\beta$  on the stack



# Configurations of a PDA

informal: what is the current state of the machine?



# Configurations of a PDA

informal: what is the current state of the machine?

## Definition

- start configuration  $(q_0, w, \perp)$

- next configuration relation

  - 1 step:  $\xrightarrow[A]{1}$  defined by

$$((p, a, \alpha), (q, \gamma)) \in \Delta \Rightarrow$$

$$\forall y \in \Sigma^* \forall \beta \in \Gamma^* : (p, ay, \alpha\beta) \xrightarrow[A]{1} (q, y, \gamma\beta)$$

- $C \xrightarrow[A]{n} D, C \xrightarrow[A]{*} D$  as usual



# Acceptances

What could it mean that PDA *accepts* word  $w$ ?



# Acceptances

What could it mean that PDA *accepts* word  $w$ ?

- PDA is in final state





# Acceptances

What could it mean that PDA *accepts* word  $w$ ?

- PDA is in final state
- stack is empty



## Definition

$\mathcal{A}$  accepts  $w$  by final state:  $\exists q \in F \exists \gamma \in \Gamma^* : (q_0, w, \perp) \xrightarrow[\mathcal{A}]{}^* (q, \varepsilon, \gamma)$



## Definition

$\mathcal{A}$  accepts  $w$  by final state:  $\exists q \in F \exists \gamma \in \Gamma^* : (q_0, w, \perp) \xrightarrow[\mathcal{A}]^* (q, \varepsilon, \gamma)$

## Definition

$\mathcal{A}$  accepts  $w$  by empty stack:  $\exists q \in Q : (q_0, w, \perp) \xrightarrow[\mathcal{A}]^* (q, \varepsilon, \varepsilon)$



# Technical Remarks about PDAs

- deterministic variant possible (see later)



# Technical Remarks about PDAs

- deterministic variant possible (see later)
- $\perp$  only for defining start configuration



# Technical Remarks about PDAs

- deterministic variant possible (see later)
- $\perp$  only for defining start configuration
- PDA can be stuck, if stack symbol does not match any transition



# Technical Remarks about PDAs

- deterministic variant possible (see later)
- $\perp$  only for defining start configuration
- PDA can be stuck, if stack symbol does not match any transition
- the infinitely short time between popping and pushing **does not** count as empty stack



## PDAS AND CFGs

---



Did we do the right thing, i.e. do we have an automata-model being equivalent to context-free grammars?



Did we do the right thing, i.e. do we have an automata-model being equivalent to context-free grammars?

Let's try to prove it.



Given: CFG  $G = (V, \Sigma, P, S)$  w.l.o.g. in GNF

- PDA  $\mathcal{A} = (\{q\}, \Sigma, V, \Delta, q, S, \emptyset)$  with acceptance by empty stack and
- $((q, c, A), (q, B_1 B_2 \dots B_k)) \in \Delta$  iff  $A \rightarrow c B_1 B_2 \dots B_k$  in  $P$



Given: CFG  $G = (V, \Sigma, P, S)$  w.l.o.g. in GNF

- PDA  $\mathcal{A} = (\{q\}, \Sigma, V, \Delta, q, S, \emptyset)$  with acceptance by empty stack and
- $((q, c, A), (q, B_1 B_2 \dots B_k)) \in \Delta$  iff  $A \rightarrow c B_1 B_2 \dots B_k$  in  $P$

Plan: Prove that leftmost derivation corresponds to accepting computation in  $\mathcal{A}$



## Lemma

$\forall z, y \in \Sigma^* \forall \gamma \in N^* \forall A \in N:$

$$A \xrightarrow[G, L]{n} z\gamma \Leftrightarrow (q, zy, A) \xrightarrow[\mathcal{A}]{n} (q, y, \gamma)$$



## Lemma

$\forall z, y \in \Sigma^* \forall \gamma \in N^* \forall A \in N$ :

$$A \xrightarrow[G, L]{n} z\gamma \Leftrightarrow (q, zy, A) \xrightarrow{\mathcal{A}}^n (q, y, \gamma)$$

Proof (induction on  $n$ ):

○  $n = 0 \Rightarrow$

$$\begin{aligned} A \xrightarrow[G]{0} z\gamma &\Leftrightarrow A = z\gamma \Leftrightarrow z = \varepsilon \wedge \gamma = A \\ &\Leftrightarrow (q, zy, A) = (q, y, \gamma) \\ &\Leftrightarrow (q, zy, A) \xrightarrow{\mathcal{A}}^0 (q, y, \gamma) \end{aligned}$$



# Proof: Induction Step, $\Rightarrow$

$$\bigcirc A \xrightarrow[G,L]{n+1} z\gamma$$



# Proof: Induction Step, $\Rightarrow$

- $A \xrightarrow[n+1]{G,L} z\gamma$
- assume:  $B \rightarrow c\beta$  was last production applied  
( $c \in \Sigma \cup \{\varepsilon\}, \beta \in V^*$ )





# Proof: Induction Step, $\Rightarrow$

- $A \xrightarrow[n+1]{G,L} z\gamma$
- assume:  $B \rightarrow c\beta$  was last production applied  
( $c \in \Sigma \cup \{\varepsilon\}, \beta \in V^*$ )
- left-most derivation  $\Rightarrow$  before  $B$  only  $u \in \Sigma^*$



# Proof: Induction Step, $\Rightarrow$

- $A \xrightarrow[n+1]{G,L} z\gamma$
- assume:  $B \rightarrow c\beta$  was last production applied  
( $c \in \Sigma \cup \{\varepsilon\}, \beta \in V^*$ )
- left-most derivation  $\Rightarrow$  before  $B$  only  $u \in \Sigma^*$
- $\Rightarrow A \xrightarrow[n]{G,L} uB\alpha \xrightarrow[1]{G,L} uc\beta\alpha = z\gamma \Rightarrow z = uc, \gamma = \beta\alpha$



# Proof: Induction Step, $\Rightarrow$

- $A \xrightarrow[n+1]{G,L} z\gamma$
- assume:  $B \rightarrow c\beta$  was last production applied  
( $c \in \Sigma \cup \{\varepsilon\}, \beta \in V^*$ )
- left-most derivation  $\Rightarrow$  before  $B$  only  $u \in \Sigma^*$
- $\Rightarrow A \xrightarrow[n]{G,L} uB\alpha \xrightarrow[1]{G,L} uc\beta\alpha = z\gamma \Rightarrow z = uc, \gamma = \beta\alpha$
- IH  $\Rightarrow (q, ucy, A) \xrightarrow[n]{\mathcal{A}} (q, cy, B\alpha)$



# Proof: Induction Step, $\Rightarrow$

- $A \xrightarrow[n+1]{G,L} z\gamma$
- assume:  $B \rightarrow c\beta$  was last production applied  
( $c \in \Sigma \cup \{\varepsilon\}, \beta \in V^*$ )
- left-most derivation  $\Rightarrow$  before  $B$  only  $u \in \Sigma^*$
- $\Rightarrow A \xrightarrow[n]{G,L} uB\alpha \xrightarrow[1]{G,L} uc\beta\alpha = z\gamma \Rightarrow z = uc, \gamma = \beta\alpha$
- IH  $\Rightarrow (q, ucy, A) \xrightarrow[n]{\mathcal{A}} (q, cy, B\alpha)$
- definition of  $\mathcal{A} \Rightarrow ((q, c, B), (q, \beta)) \in \Delta$



# Proof: Induction Step, $\Rightarrow$

- $A \xrightarrow[n+1]{G,L} z\gamma$
- assume:  $B \rightarrow c\beta$  was last production applied  
( $c \in \Sigma \cup \{\varepsilon\}, \beta \in V^*$ )
- left-most derivation  $\Rightarrow$  before  $B$  only  $u \in \Sigma^*$
- $\Rightarrow A \xrightarrow[n]{G,L} uB\alpha \xrightarrow[1]{G,L} uc\beta\alpha = z\gamma \Rightarrow z = uc, \gamma = \beta\alpha$
- IH  $\Rightarrow (q, ucy, A) \xrightarrow[n]{\mathcal{A}} (q, cy, B\alpha)$
- definition of  $\mathcal{A} \Rightarrow ((q, c, B), (q, \beta)) \in \Delta$
- $\Rightarrow (q, cy, B\alpha) \xrightarrow[1]{\mathcal{A}} (q, y, \beta\alpha)$



# Proof: Induction Step, $\Rightarrow$

- $A \xrightarrow[n+1]{G,L} z\gamma$
- assume:  $B \rightarrow c\beta$  was last production applied  
( $c \in \Sigma \cup \{\varepsilon\}, \beta \in V^*$ )
- left-most derivation  $\Rightarrow$  before  $B$  only  $u \in \Sigma^*$
- $\Rightarrow A \xrightarrow{n}{G,L} uB\alpha \xrightarrow{1}{G,L} uc\beta\alpha = z\gamma \Rightarrow z = uc, \gamma = \beta\alpha$
- IH  $\Rightarrow (q, ucy, A) \xrightarrow[n]{\mathcal{A}} (q, cy, B\alpha)$
- definition of  $\mathcal{A} \Rightarrow ((q, c, B), (q, \beta)) \in \Delta$
- $\Rightarrow (q, cy, B\alpha) \xrightarrow{1}{\mathcal{A}} (q, y, \beta\alpha)$
- $\Rightarrow (q, zy, A) = (q, ucy, A) \xrightarrow[n+1]{\mathcal{A}} (q, y, \beta\alpha) = (q, y, \gamma)$



# Proof: Induction Step, $\Leftarrow$

$$\bigcirc (q, zy, A) \xrightarrow[\mathcal{A}]{n+1} (q, y, \gamma)$$



# Proof: Induction Step, $\Leftarrow$

- $(q, zy, A) \xrightarrow[n+1]{\mathcal{A}} (q, y, \gamma)$
- assume  $((q, c, B), (q, \beta)) \in \Delta$  last transition taken





# Proof: Induction Step, $\Leftarrow$

- $(q, zy, A) \xrightarrow[n+1]{\mathcal{A}} (q, y, \gamma)$
- assume  $((q, c, B), (q, \beta)) \in \Delta$  last transition taken
- $\Rightarrow z = uc, u \in \Sigma^*, \gamma = \beta\alpha, \alpha \in \Gamma^*$



# Proof: Induction Step, $\Leftarrow$

- $(q, zy, A) \xrightarrow[n+1]{\mathcal{A}} (q, y, \gamma)$
- assume  $((q, c, B), (q, \beta)) \in \Delta$  last transition taken
- $\Rightarrow z = uc, u \in \Sigma^*, \gamma = \beta\alpha, \alpha \in \Gamma^*$
- $\Rightarrow (q, ucy, A) \xrightarrow[n]{\mathcal{A}} (q, cy, B\alpha) \xrightarrow[1]{\mathcal{A}} (q, y, \beta\alpha)$



# Proof: Induction Step, $\Leftarrow$

- $(q, zy, A) \xrightarrow[n+1]{\mathcal{A}} (q, y, \gamma)$
- assume  $((q, c, B), (q, \beta)) \in \Delta$  last transition taken
- $\Rightarrow z = uc, u \in \Sigma^*, \gamma = \beta\alpha, \alpha \in \Gamma^*$
- $\Rightarrow (q, ucy, A) \xrightarrow[n]{\mathcal{A}} (q, cy, B\alpha) \xrightarrow[1]{\mathcal{A}} (q, y, \beta\alpha)$
- IH  $\Rightarrow A \xrightarrow[n]{G, L} uB\alpha$



# Proof: Induction Step, $\Leftarrow$

- $(q, zy, A) \xrightarrow[n+1]{\mathcal{A}} (q, y, \gamma)$
- assume  $((q, c, B), (q, \beta)) \in \Delta$  last transition taken
- $\Rightarrow z = uc, u \in \Sigma^*, \gamma = \beta\alpha, \alpha \in \Gamma^*$
- $\Rightarrow (q, ucy, A) \xrightarrow[n]{\mathcal{A}} (q, cy, B\alpha) \xrightarrow[1]{\mathcal{A}} (q, y, \beta\alpha)$
- IH  $\Rightarrow A \xrightarrow[n]{G, L} uB\alpha$
- $B \rightarrow c\beta$  production in  $G$



# Proof: Induction Step, $\Leftarrow$

- $(q, zy, A) \xrightarrow[n+1]{\mathcal{A}} (q, y, \gamma)$
- assume  $((q, c, B), (q, \beta)) \in \Delta$  last transition taken
- $\Rightarrow z = uc, u \in \Sigma^*, \gamma = \beta\alpha, \alpha \in \Gamma^*$
- $\Rightarrow (q, ucy, A) \xrightarrow[n]{\mathcal{A}} (q, cy, B\alpha) \xrightarrow[1]{\mathcal{A}} (q, y, \beta\alpha)$
- IH  $\Rightarrow A \xrightarrow[n]{G, L} uB\alpha$
- $B \rightarrow c\beta$  production in  $G$
- $\Rightarrow A \xrightarrow[n]{G} uB\alpha \xrightarrow[1]{G} uc\beta\alpha = zy$



# Proof: last step

Thus we proved

## Theorem

$$L(\mathcal{A}) = L(G)$$



## SIMULATING PDAS BY CFGs

---

# Idea of the Construction

Two steps:





# Idea of the Construction

Two steps:

1. every PDA can be simulated by PDA with one state



# Idea of the Construction

Two steps:

1. every PDA can be simulated by PDA with one state
2. every PDA with one state is equivalent to CFG



## ad Step (2)

- Construction from CFG  $\rightarrow$  PDA is invertible:



## ad Step (2)

- Construction from  $\text{CFG} \rightarrow \text{PDA}$  is invertible:
  - given  $\mathcal{A} = (\{q\}, \Sigma, \Gamma, \Delta, q, \perp, \emptyset)$



## ad Step (2)

- Construction from  $\text{CFG} \rightarrow \text{PDA}$  is invertible:
  - given  $\mathcal{A} = (\{q\}, \Sigma, \Gamma, \Delta, q, \perp, \emptyset)$
  - set  $G = (\Gamma, \Sigma, P, \perp)$  where  $P$  contains production



- Construction from  $\text{CFG} \rightarrow \text{PDA}$  is invertible:
  - given  $\mathcal{A} = (\{q\}, \Sigma, \Gamma, \Delta, q, \perp, \emptyset)$
  - set  $G = (\Gamma, \Sigma, P, \perp)$  where  $P$  contains production
  - $A \rightarrow cB_1 \dots B_k$  for all  $((q, c, A), (q, B_1 \dots B_k)) \in \Delta$



## ad Step (2)

- Construction from  $\text{CFG} \rightarrow \text{PDA}$  is invertible:
  - given  $\mathcal{A} = (\{q\}, \Sigma, \Gamma, \Delta, q, \perp, \emptyset)$
  - set  $G = (\Gamma, \Sigma, P, \perp)$  where  $P$  contains production
  - $A \rightarrow cB_1 \dots B_k$  for all  $((q, c, A), (q, B_1 \dots B_k)) \in \Delta$
- Proof is analogous



# ad Step (1)

Idea: keep some state-information on the stack





# ad Step (1)

Idea: keep some state-information on the stack

- w.l.o.g.  $\mathcal{A} = (Q, \Sigma, \Gamma, \Delta, q_0, \perp, \{q_f\})$



# ad Step (1)

Idea: keep some state-information on the stack

- w.l.o.g.  $\mathcal{A} = (Q, \Sigma, \Gamma, \Delta, q_0, \perp, \{q_f\})$
- $\Gamma' := Q \times \Gamma \times Q$



# ad Step (1)

Idea: keep some state-information on the stack

- w.l.o.g.  $\mathcal{A} = (Q, \Sigma, \Gamma, \Delta, q_0, \perp, \{q_f\})$
- $\Gamma' := Q \times \Gamma \times Q$
- $\mathcal{A}' = (\{q\}, \Sigma, \Gamma', \Delta', q, (q_0, \perp, t), \emptyset)$



## ad Step (1): Defining $\Delta'$

$$\bigcirc ((p_1, c, A), (p_2, \varepsilon)) \in \Delta \Rightarrow$$

$$((q, c, (p_1, A, p_2)), (q, \varepsilon)) \in \Delta'.$$



## ad Step (1): Defining $\Delta'$

○  $((p_1, c, A), (p_2, \varepsilon)) \in \Delta \Rightarrow$

$$((q, c, (p_1, A, p_2)), (q, \varepsilon)) \in \Delta'.$$

○  $((p_1, c, A), (p_2, B_1 \dots B_k)) \in \Delta \Rightarrow$

$$((q, c, (p_1, A, q_{k+1})), (q, (q_1, B_1, q_2) \dots (q_k B_k q_{k+1}))) \in \Delta'$$



## ad Step (1): Defining $\Delta'$

$$\bigcirc ((p_1, c, A), (p_2, \varepsilon)) \in \Delta \Rightarrow$$

$$((q, c, (p_1, A, p_2)), (q, \varepsilon)) \in \Delta'.$$

$$\bigcirc ((p_1, c, A), (p_2, B_1 \dots B_k)) \in \Delta \Rightarrow$$

$$((q, c, (p_1, A, q_{k+1})), (q, (q_1, B_1, q_2) \dots (q_k B_k q_{k+1}))) \in \Delta'$$

Intuition:  $\mathcal{A}'$  simulates  $\mathcal{A}$  by guessing in what state  $\mathcal{A}$  will be and saving those guesses on the stack



## Lemma

$$\begin{aligned}(p_1, x, B_1 \dots B_k) &\xrightarrow[\mathcal{A}]{n} (p_2, \varepsilon, \varepsilon) \Leftrightarrow \\ &\exists q_1, \dots, q_k : p_1 = q_1, p_2 = q_k \wedge \\ &\quad (q, x, (q_1, B_1, q_2) \dots (q_k, B_k, q_k)) \xrightarrow[\mathcal{A}']{n} (q, \varepsilon, \varepsilon)\end{aligned}$$



## Theorem

$$L(\mathcal{A}') = L(\mathcal{A})$$





## Theorem

$$L(\mathcal{A}') = L(\mathcal{A})$$

Proof:  $\forall x \in \Sigma^*$  :

$$\begin{aligned}x \in L(\mathcal{A}') &\Leftrightarrow (q, x, (q_0, \perp, q_f)) \xrightarrow[\mathcal{A}']{n} (q, \varepsilon, \varepsilon) \\&\Leftrightarrow (q_0, x, \perp) \xrightarrow[\mathcal{A}]{*} (q_f, \varepsilon, \varepsilon) \\&\Leftrightarrow x \in L(\mathcal{A})\end{aligned}$$



# DETERMINISTIC PUSHDOWN AUTOMATA

---

# Deterministic Pushdown Automata

## Definition

$\mathcal{A} = (Q, \Sigma, \Gamma, \delta, \perp, \vdash, q_0, F)$  **DPDA** iff

- $Q, \Sigma, \Gamma, \perp, q_0, F$  as in PDA
- $\vdash$  right endmarker (end of the word)
- $\delta : Q \times (\Sigma \cup \{\vdash, \varepsilon\}) \times \Gamma \rightarrow Q \times \Gamma^*$
- $\perp$  has to remain at the bottom of the stack (deadlock prevention)
- acceptance only by final state



# Configuration, Acceptance by DPDA

## Definition

- start configuration:  $(q_0, x \vdash, \perp)$
- $\mathcal{A}$  accepts  $x$ :  $(q_0, x \vdash, \perp) \xrightarrow[\mathcal{A}]{}^* (q_f, \varepsilon, \beta)$
- language **deterministic context-free**: accepted by DPDA



# DPDAs are closed under complement

## Lemma

*If  $L$  is a deterministic context-free language, then  $\Sigma^* \setminus L$  is as well.*



# DPDAs are closed under complement

## Lemma

*If  $L$  is a deterministic context-free language, then  $\Sigma^* \setminus L$  is as well.*

Proof:



# DPDAs are closed under complement

## Lemma

*If  $L$  is a deterministic context-free language, then  $\Sigma^* \setminus L$  is as well.*

Proof:

- $\mathcal{A}$  DPDA for  $L$



# DPDAs are closed under complement

## Lemma

*If  $L$  is a deterministic context-free language, then  $\Sigma^* \setminus L$  is as well.*

Proof:

- $\mathcal{A}$  DPDA for  $L$
- we have to construct  $\mathcal{A}'$  for  $\Sigma^* \setminus L$





# DPDAs are closed under complement

## Lemma

*If  $L$  is a deterministic context-free language, then  $\Sigma^* \setminus L$  is as well.*

Proof:

- $\mathcal{A}$  DPDA for  $L$
- we have to construct  $\mathcal{A}'$  for  $\Sigma^* \setminus L$
- problem: switching  $F$  and  $Q \setminus F$  is not possible



# DPDAs are closed under complement

## Lemma

*If  $L$  is a deterministic context-free language, then  $\Sigma^* \setminus L$  is as well.*

Proof:

- $\mathcal{A}$  DPDA for  $L$
- we have to construct  $\mathcal{A}'$  for  $\Sigma^* \setminus L$
- problem: switching  $F$  and  $Q \setminus F$  is not possible
  - DPDAs have to scan the complete input



# DPDAs are closed under complement

## Lemma

*If  $L$  is a deterministic context-free language, then  $\Sigma^* \setminus L$  is as well.*

Proof:

- $\mathcal{A}$  DPDA for  $L$
- we have to construct  $\mathcal{A}'$  for  $\Sigma^* \setminus L$
- problem: switching  $F$  and  $Q \setminus F$  is not possible
  - DPDAs have to scan the complete input
  - $\Rightarrow$  may loop infinitely on not accepted inputs



Trick: modify  $\mathcal{A}$  such that we know exactly if we have already seen  $\perp$



Trick: modify  $\mathcal{A}$  such that we know exactly if we have already seen  $\dashv$

- $Q' = \{q' \mid q \in Q\}$  (disjoint duplication of  $Q$ )



Trick: modify  $\mathcal{A}$  such that we know exactly if we have already seen  $\dashv$

- $Q' = \{q' \mid q \in Q\}$  (disjoint duplication of  $Q$ )
- new transitions:
  - $\delta(p', a, A) = (q', \beta)$  for  $\delta(p, a, A) = (q, \beta)$



Trick: modify  $\mathcal{A}$  such that we know exactly if we have already seen  $\neg$

- $Q' = \{q' \mid q \in Q\}$  (disjoint duplication of  $Q$ )
- new transitions:
  - $\delta(p', a, A) = (q', \beta)$  for  $\delta(p, a, A) = (q, \beta)$
  - replace  $\delta(p, \neg, A) = (q, \beta)$  by  $\delta(p, \neg, A) = (q', \beta)$



Trick: modify  $\mathcal{A}$  such that we know exactly if we have already seen  $\dashv$

- $Q' = \{q' \mid q \in Q\}$  (disjoint duplication of  $Q$ )
- new transitions:
  - $\delta(p', a, A) = (q', \beta)$  for  $\delta(p, a, A) = (q, \beta)$
  - replace  $\delta(p, \dashv, A) = (q, \beta)$  by  $\delta(p, \dashv, A) = (q', \beta)$
- we switch to the primed version if we saw the endmarker





Trick: modify  $\mathcal{A}$  such that we know exactly if we have already seen  $\dashv$

- $Q' = \{q' \mid q \in Q\}$  (disjoint duplication of  $Q$ )
- new transitions:
  - $\delta(p', a, A) = (q', \beta)$  for  $\delta(p, a, A) = (q, \beta)$
  - replace  $\delta(p, \dashv, A) = (q, \beta)$  by  $\delta(p, \dashv, A) = (q', \beta)$
- we switch to the primed version if we saw the endmarker
- $F' = \{q' \mid q \in F\}$



Trick: modify  $\mathcal{A}$  such that we know exactly if we have already seen  $\perp$

- $Q' = \{q' \mid q \in Q\}$  (disjoint duplication of  $Q$ )
- new transitions:
  - $\delta(p', a, A) = (q', \beta)$  for  $\delta(p, a, A) = (q, \beta)$
  - replace  $\delta(p, \perp, A) = (q, \beta)$  by  $\delta(p, \perp, A) = (q', \beta)$
- we switch to the primed version if we saw the endmarker
- $F' = \{q' \mid q \in F\}$
- $\mathcal{A}' = (Q \cup Q', \Sigma, \Gamma, \delta', \perp, \perp, q_0, F')$



Trick: modify  $\mathcal{A}$  such that we know exactly if we have already seen  $\perp$

- $Q' = \{q' \mid q \in Q\}$  (disjoint duplication of  $Q$ )
- new transitions:
  - $\delta(p', a, A) = (q', \beta)$  for  $\delta(p, a, A) = (q, \beta)$
  - replace  $\delta(p, \perp, A) = (q, \beta)$  by  $\delta(p, \perp, A) = (q', \beta)$
- we switch to the primed version if we saw the endmarker
- $F' = \{q' \mid q \in F\}$
- $\mathcal{A}' = (Q \cup Q', \Sigma, \Gamma, \delta', \perp, \perp, q_0, F')$
- $L(\mathcal{A}') = \Sigma^* \setminus L$  and  $\mathcal{A}'$  is DPDA



Stopping the machine:



Stopping the machine:

- we are only in primed states if we saw  $\neg$



Stopping the machine:

- we are only in primed states if we saw  $\neg$
- $\Rightarrow$  we can rest in a final state and stop doing funny things



Stopping the machine:

- we are only in primed states if we saw  $\neg$
- $\Rightarrow$  we can rest in a final state and stop doing funny things
- redefine  $\delta(p', \varepsilon, A) = (p', A)$  if the image was  $(q', \beta)$  for  $p' \in F'$



# Proof: Getting rid of Spurious Loops

- new states
  - $r \in Q' \setminus F'$ : move to the end, don't change the stack





# Proof: Getting rid of Spurious Loops

- new states
  - $r \in Q' \setminus F'$ : move to the end, don't change the stack
  - $r' \in Q' \setminus F'$ : reject



# Proof: Getting rid of Spurious Loops

- new states
  - $r \in Q' \setminus F'$ : move to the end, don't change the stack
  - $r' \in Q' \setminus F'$ : reject
  - $\delta(r, a, A) = (r, A)$  for  $a \in \Sigma, A \in \Gamma$



# Proof: Getting rid of Spurious Loops

- new states
  - $r \in Q' \setminus F'$ : move to the end, don't change the stack
  - $r' \in Q' \setminus F'$ : reject
  - $\delta(r, a, A) = (r, A)$  for  $a \in \Sigma, A \in \Gamma$
  - $\delta(r, \vdash, A) = (r', A)$  for  $A \in \Gamma$



# Proof: Getting rid of Spurious Loops

## ○ new states

- $r \in Q' \setminus F'$ : move to the end, don't change the stack
- $r' \in Q' \setminus F'$ : reject
- $\delta(r, a, A) = (r, A)$  for  $a \in \Sigma, A \in \Gamma$
- $\delta(r, \vdash, A) = (r', A)$  for  $A \in \Gamma$
- $\delta(r', \varepsilon, A) = (r', A)$  for  $A \in \Gamma$



# Proof: Getting rid of Spurious Loops

- new states
  - $r \in Q' \setminus F'$ : move to the end, don't change the stack
  - $r' \in Q' \setminus F'$ : reject
  - $\delta(r, a, A) = (r, A)$  for  $a \in \Sigma, A \in \Gamma$
  - $\delta(r, \vdash, A) = (r', A)$  for  $A \in \Gamma$
  - $\delta(r', \varepsilon, A) = (r', A)$  for  $A \in \Gamma$
- replace  $\delta(p, \varepsilon, A) = (q, \beta)$  by  $\delta(p, \varepsilon, A) = (r, A)$



# Proof: Getting rid of Spurious Loops

- new states
  - $r \in Q' \setminus F'$ : move to the end, don't change the stack
  - $r' \in Q' \setminus F'$ : reject
  - $\delta(r, a, A) = (r, A)$  for  $a \in \Sigma, A \in \Gamma$
  - $\delta(r, \vdash, A) = (r', A)$  for  $A \in \Gamma$
  - $\delta(r', \varepsilon, A) = (r', A)$  for  $A \in \Gamma$
- replace  $\delta(p, \varepsilon, A) = (q, \beta)$  by  $\delta(p, \varepsilon, A) = (r, A)$
- replace  $\delta(p', \varepsilon, A) = (q, \beta)$  by  $\delta(p, \varepsilon, A) = (r', A)$



- DFAs and NFAs are equivalent, have the same power



# DPDA - (N)PDA

- DFAs and NFAs are equivalent, have the same power
- does this hold for pushdown automata as well?





# PDAs are more powerful than DPDAs

## Theorem

*There exists languages recognizable by a PDA but not by a DPDA.*



# PDAs are more powerful than DPDAs

## Theorem

*There exists languages recognizable by a PDA but not by a DPDA.*

Proof:



# PDAs are more powerful than DPDAs

## Theorem

*There exists languages recognizable by a PDA but not by a DPDA.*

Proof:

- $L = \{ww \mid w \in \Sigma^*\}$  not context-free.



# PDAs are more powerful than DPDAs

## Theorem

*There exists languages recognizable by a PDA but not by a DPDA.*

Proof:

- $L = \{ww \mid w \in \Sigma^*\}$  not context-free.
- $\overline{L} = \Sigma^* \setminus L$  context-free



# PDAs are more powerful than DPDAs

## Theorem

*There exists languages recognizable by a PDA but not by a DPDA.*

Proof:

- $L = \{ww \mid w \in \Sigma^*\}$  not context-free.
- $\bar{L} = \Sigma^* \setminus L$  context-free
- DPDA closed under complement  $\Rightarrow L$  recognizable by DPDA  $\Rightarrow$  Contradiction



# THE COCKE-YOUNGER-KASAMI ALGORITHM

---

# Membership-Problem

## Definition

Given a language  $L$  over  $\Sigma^*$  and a word  $w \in \Sigma^*$ , decide whether  $w \in L$  or not.



# Membership-Problem

## Definition

Given a language  $L$  over  $\Sigma^*$  and a word  $w \in \Sigma^*$ , decide whether  $w \in L$  or not.

- problem is in general hard to solve
- we can't build all paths in an automaton or all derivations in a grammar





# CYK-Algorithm

Given context-free grammar  $G$  (w.l.o.g. in CNF) the CYK-algorithm decides *efficiently* whether a word is producible or not.



# CYK-Algorithm

Given context-free grammar  $G$  (w.l.o.g. in CNF) the CYK-algorithm decides *efficiently* whether a word is producible or not.

Some Preliminaries:



# CYK-Algorithm

Given context-free grammar  $G$  (w.l.o.g. in CNF) the CYK-algorithm decides *efficiently* whether a word is producible or not.

Some Preliminaries:

- $w \langle i, j \rangle = w[i + 1 \dots j]$   
 $(aabbab \langle 1, 4 \rangle = aabbab[2, \dots, 4] = abb)$



# CYK-Algorithm

Given context-free grammar  $G$  (w.l.o.g. in CNF) the CYK-algorithm decides *efficiently* whether a word is producible or not.

Some Preliminaries:

- $w \langle i, j \rangle = w[i + 1 \dots j]$   
( $aabbab \langle 1, 4 \rangle = aabbab[2, \dots, 4] = abb$ )
- $T_{ij} \subseteq V$  generating  $w \langle i, j \rangle$



# CYK-Algorithm

Given context-free grammar  $G$  (w.l.o.g. in CNF) the CYK-algorithm decides *efficiently* whether a word is producible or not.

Some Preliminaries:

- $w \langle i, j \rangle = w[i + 1 \dots j]$   
( $aabbab \langle 1, 4 \rangle = aabbab[2, \dots, 4] = abb$ )
- $T_{ij} \subseteq V$  generating  $w \langle i, j \rangle$ 
  - $A \rightarrow a \in P \Rightarrow aabbab \langle 0, 1 \rangle, aabbab \langle 1, 2 \rangle, aabbab \langle 4, 5 \rangle$   
producible  
 $\Rightarrow T_{01} = T_{12} = T_{45} = \{A\}$



# CYK-Algorithm

Given context-free grammar  $G$  (w.l.o.g. in CNF) the CYK-algorithm decides *efficiently* whether a word is producible or not.

Some Preliminaries:

- $w \langle i, j \rangle = w[i + 1 \dots j]$   
( $aabbab \langle 1, 4 \rangle = aabbab[2, \dots, 4] = abb$ )
- $T_{ij} \subseteq V$  generating  $w \langle i, j \rangle$ 
  - $A \rightarrow a \in P \Rightarrow aabbab \langle 0, 1 \rangle, aabbab \langle 1, 2 \rangle, aabbab \langle 4, 5 \rangle$   
producible  
 $\Rightarrow T_{01} = T_{12} = T_{45} = \{A\}$
- by this we get easily all factors of length 1



- consider  $w$ 's factors of length 2



- consider  $w$ 's factors of length 2
- $w[i \dots i + 1] = w[i]w[i + 1] = w \langle i - 1, i \rangle w \langle i, i + 1 \rangle$





- consider  $w$ 's factors of length 2
- $w[i \dots i + 1] = w[i]w[i + 1] = w \langle i - 1, i \rangle w \langle i, i + 1 \rangle$
- look-up productions for  $w \langle i - 1, i \rangle$  and  $w \langle i, i + 1 \rangle$  in  $T_{i-1,i}$  resp.  $T_{i,i+1}$



- consider  $w$ 's factors of length 2
- $w[i \dots i + 1] = w[i]w[i + 1] = w \langle i - 1, i \rangle w \langle i, i + 1 \rangle$
- look-up productions for  $w \langle i - 1, i \rangle$  and  $w \langle i, i + 1 \rangle$  in  $T_{i-1,i}$  resp.  $T_{i,i+1}$
- for all  $X \in T_{i-1,i}$  and for all  $Y \in T_{i,i+1}$  check if there is a production with right-hand side  $XY$



- consider  $w$ 's factors of length 2
- $w[i \dots i + 1] = w[i]w[i + 1] = w \langle i - 1, i \rangle w \langle i, i + 1 \rangle$
- look-up productions for  $w \langle i - 1, i \rangle$  and  $w \langle i, i + 1 \rangle$  in  $T_{i-1,i}$  resp.  $T_{i,i+1}$
- for all  $X \in T_{i-1,i}$  and for all  $Y \in T_{i,i+1}$  check if there is a production with right-hand side  $XY$
- update  $T_{i-1,i+1}$  by the corresponding left-hand side



in general:

- given a factor  $x$  of  $w$  of length  $k$



in general:

- given a factor  $x$  of  $w$  of length  $k$
- decompose  $x$  into two parts in all possible ways



in general:

- given a factor  $x$  of  $w$  of length  $k$
- decompose  $x$  into two parts in all possible ways
- lookup the corresponding sets and see if a combination gives the right-hand side of a production



in general:

- given a factor  $x$  of  $w$  of length  $k$
- decompose  $x$  into two parts in all possible ways
- lookup the corresponding sets and see if a combination gives the right-hand side of a production
- if so, take the left-hand side into the set corresponding to  $x$



in general:

- given a factor  $x$  of  $w$  of length  $k$
- decompose  $x$  into two parts in all possible ways
- lookup the corresponding sets and see if a combination gives the right-hand side of a production
- if so, take the left-hand side into the set corresponding to  $x$
- if  $S$  is in  $T_{0,n}$  for  $|w| = n$  then  $w \in L$





# Closure-Properties for CFLs

CFLs are closed under

- union



# Closure-Properties for CFLs

CFLs are closed under

- union
- concatenation



# Closure-Properties for CFLs

CFLs are closed under

- union
- concatenation
- star



# Closure-Properties for CFLs

CFLs are closed under

- union
- concatenation
- star

CFLs are not closed under intersection!

- But... the intersection of a regular language and a context-free one is context-free



# Closure-Properties for DCFLs

DCFLs are closed under intersection.



# Closure-Properties for DCFLs

DCFLs are closed under intersection.

DCFLs are not closed under

- union



# Closure-Properties for DCFLs

DCFLs are closed under intersection.

DCFLs are not closed under

- union
- reversal



# THE CHOMSKY-SCHÜTZENBERGER THEOREM

---



# The Language $\text{PAREN}_n$

## Definition

$\text{PAREN}_n$  (Dyck language) is generated by the grammar

$$S \rightarrow [{}_1S]_1 \mid \dots \mid [{}_nS]_n \mid SS \mid \varepsilon$$

( $n$  different kinds of parenthesis)



# The Chomsky-Schützenberger-Theorem

## Theorem (Chomsky-Schützenberger)

*For every CFL  $\mathcal{A}$  there exists an  $n \in \mathbb{N}_0$ , a regular language  $R$ , and a homomorphism  $h$  with*

$$\mathcal{A} = h(\text{PAREN}_n \cap R).$$

