



navigation

- [Main Page](#)
- [Documentation](#)
- [FAQ](#)
- [Downloads](#)
- [Glossary](#)
- [Index](#)
- [Recent changes](#)
- [Random page](#)
- [Help](#)

search

tools

- [What links here](#)
- [Related changes](#)
- [Special pages](#)
- [Printable version](#)
- [Permanent link](#)
- [Page information](#)

IF

| [English \(en\)](#) | [français \(fr\)](#) | [日本語 \(ja\)](#) | [中文 \(中國大陸\) \(zh_CN\)](#) |



3Ca - IF (author: Tao Yue, state: unchanged)

The IF statement allows you to branch based on the result of a Boolean operation. The one-way branch format is:

```
if BooleanExpression then
    StatementIfTrue;
```

If the Boolean expression evaluates to `true`, the statement executes. Otherwise, it is skipped.

The IF statement accepts only one statement. If you would like to branch to a compound statement, you must use a `begin-end` **block** to enclose the statements:

```
if BooleanExpression then
begin
    Statement1;
    Statement2
end;
```

There is also a two-way selection:

```
if BooleanExpression then
    StatementIfTrue
else
    StatementIfFalse;
```

If the Boolean expression evaluates to `FALSE`, the statement following the `else` will be performed. Note that you may not use a semicolon after the statement preceding the `else`. That causes the computer to treat it as a one-way selection, leaving it to wonder where the `else` came from.

If you need multi-way selection, simply nest `if` statements:

```
if Condition1 then
    Statement1
else
    if Condition2 then
        Statement2
    else
        Statement3;
```

Be careful with nesting. Sometimes the computer won't do what you want it to do:

```
if Condition1 then
    if Condition2 then
        Statement2
else
    Statement1;
```

The `else` is always matched with the most recent `if`, so the computer interprets the preceding block of code as:

```
if Condition1 then
    if Condition2 then
        Statement2
    else
        Statement1;
```

You can get by with a null statement:

```
if Condition1 then
    if Condition2 then
        Statement2
    else
else
    Statement1;
```

Or you could use a `begin-end` block. But the best way to clean up the code would be to rewrite the condition.

```
if not Condition1 then
    Statement1
else
    if Condition2 then
        Statement2;
```

This example illustrates where the `not` operator comes in very handy. If `Condition1` had been a Boolean like: `(not(a < b) or (c + 3 > 6))` and `g`, reversing the expression would be more difficult than NOTting it.

Also notice how important indentation is to convey the logic of program code to a human, but the compiler ignores the indentation.



Category: [Object Pascal Introduction](#)