

Charging Best Practices

1. Overview

These best practices help you charge the vehicle battery safely, maintain long-term performance, and avoid damage caused by improper charging methods. Whether you're using a workshop charger, a portable maintainer, or the vehicle's own charging system, the goal is steady and controlled charging.

2. Preparing for Charging

Safety First

- Switch off the ignition and remove the key.
- Keep open flames, sparks, and smoking materials away from the battery area.
- Wear gloves and eye protection.
- Make sure the charging area is dry and well ventilated.

Initial Checks

Before connecting any charger:

- Inspect the battery for cracks, swelling, or leakage.
 - Check the terminals for corrosion or loose clamps.
 - Confirm the charger type matches the battery chemistry (AGM, EFB, or standard lead-acid).
 - Avoid charging severely damaged or frozen batteries.
-

3. Connecting the Charger

Correct Sequence

1. Connect the positive charger lead to the positive battery terminal.
2. Connect the negative charger lead to a suitable chassis ground point.
3. Ensure all cables are secure and not touching moving components.
4. Switch on the charger only after the leads are connected.

Disconnecting

- Turn off the charger first.

- Remove the negative lead.
- Remove the positive lead last.

This order reduces the chance of sparks and accidental shorting.

4. Charging Modes and When to Use Them

Standard Charging

- Ideal for routine top-ups.
- Provides slow and steady current.
- Best for preserving battery health over time.

Fast Charging

- Only use when absolutely necessary, such as recovering a deeply discharged battery.
- High current can shorten overall battery life if used repeatedly.
- Avoid using fast charge on older or weakened batteries.

Maintenance or Trickle Charging

- Designed for long-term storage or infrequently used vehicles.
 - Prevents deep discharge without overcharging.
 - Recommended for vehicles parked for more than two weeks.
-

5. Charging Duration and Monitoring

How Long Should It Take

- A mild top-up can take one to two hours.
- A low battery may require several hours.
- Deep discharge recovery can take overnight depending on charger output.

Monitor Progress

- Check battery temperature; it should stay cool or only slightly warm.
- Watch for any unusual smells, hissing, or deformation.
- Stop charging immediately if anything appears abnormal.

Avoid Overcharging

- Use chargers with automatic cut-off or smart control.
 - Manual chargers must be supervised; leaving them connected for too long can cause overheating and reduced battery life.
-

6. Temperature Considerations

Cold Weather

- Cold temperatures slow the charging process.
- Allow the battery to warm slightly before charging if it's extremely cold.
- Charging a frozen battery can cause internal damage.

Hot Weather

- High heat speeds up chemical reactions and can lead to overcharging.
 - Charge in shaded or temperature-controlled areas when possible.
-

7. After Charging

Final Checks

- Ensure terminals are clean and fully tightened.
- Confirm voltage is within normal range (typically above 12.6 volts when rested).
- Start the vehicle and verify stable operation of lights, electronics, and dashboard systems.

Driving After Charging

- A short drive helps the alternator stabilise battery chemistry.
 - Avoid heavy electrical loads immediately after reconnecting a previously discharged battery.
-

8. Quick Do's and Don'ts

Do

- Use the correct charger type for your battery
- Keep terminals clean and dry

- Charge slowly whenever possible
- Use a maintainer for long-term parking

Don't

- Fast-charge repeatedly
- Charge a visibly damaged battery
- Mix charger types or improvised adapters
- Leave a manual charger unattended