

## 4a-b formal specification exercises

2.1

P: System Software is in debug mode

Q: Users have database access.

R: Users can save new records.

$$1.1) \quad P \rightarrow \neg Q \quad \text{is not} \quad \neg P \vee \neg Q$$

$$1.2) \quad Q \rightarrow R \quad \text{is} \quad \neg Q \vee R$$

$$1.3) \quad \neg R \rightarrow \neg P \quad \text{is} \quad R \vee \neg P$$

2.2) Consistency :-

	P	Q	R	$\neg P \vee \neg Q$	$\neg Q \vee R$	$R \vee \neg P$
	T	T	T	F	T	T
	T	T	F	T	F	F
	T	F	T	<del>T</del> T	T	T
	T	F	F	T	T	F
→	F	T	T	T	T	T
	F	T	F	T	F	T
→	F	F	T	T	T	T
→	F	F	F	T	T	T

$$\therefore (F_1 \wedge F_2 \wedge F_3) \rightarrow G \rightarrow \text{Tautology}$$

$\therefore$  all the requirements are consistent.

3)

3.1

1)

### AddMeeting

$\exists$  MeetingPlanner

name? : NAME

dateTime? : DATETIME

meetingId? : MEETINGID.

meetingId?  $\notin$  scheduled

when' = when  $\cup$  {meetingId?  $\rightarrow$  dateTime?}

participant' = participant  $\cup$  {name?  $\rightarrow$  meetingId?}

2)

### FindMeeting

$\exists$  MeetingPlanner

meetingId? : MEETINGID

datetime? : DATETIME

name! : ~~PNAME~~ PNAME

meetingId? :  $\in$  scheduled

datetime? : when (meetingId?)

name! = {  $x$  : participant | participant (n) = meetingId? }

3.2

1)  $RAddMeeting = (AddMeeting \wedge Success) \vee AlreadyKnown$

2)

AddMeeting  $\wedge$  Success

$\Delta$  MeetingPlanner

name? : NAME

meetingid? : MEETINGID

datetime? : DATE TIME

result! : REPORT

meetingid?  $\neq$  scheduled

participant' = participant  $\cup$  {name?  $\rightarrow$  meetingid?}

when' = when  $\cup$  {meetingid?  $\rightarrow$  datetime?}

result! : ok