Supplementary Material: Adversarial Contingency Auctions for Decentralized Multi-Robot Task Allocation under Strategic Blockages

Anonymous Authors

I. Overview

This supplementary document provides extended statistical visualizations and diagnostics supporting the primary manuscript. All evaluations correspond to the pre-registered benchmark sweep ($N = 250$ matched independent instances, $13,800$ total simulation trials) conducted across 5 graph families, 4 adversary behavioral profiles, and 3 communication regimes.

II. Extended Performance Distributions

Fig. 1 illustrates the full sample distribution across all primary metrics via raincloud plots combining half-violin kernel density estimates, boxplots with interquartile ranges, and jittered instance points.

III. Non-Parametric Effect Size Heatmap

Fig. 2 details pairwise effect sizes evaluated via Cliff's δ non-parametric metric across all algorithm pairings.

IV. Confidence Interval Width Scaling

Fig. 3 validates statistical sample size adequacy by evaluating empirical 95% bootstrap confidence interval half-widths as a function of sample instance count $N \in [25, 250]$.

V. Rollout Execution Keyframes

Fig. 4 provides synchronized execution keyframes on the Downtown Boston road network comparing ACA against CTP Replan and standard CBBA under identical adversarial interdictions.

VI. Paired Differences vs. ACA Baseline

Fig. 5 details Hodges–Lehmann median paired differences with 95% bootstrap confidence intervals across benchmark algorithms.

VII. Interdiction Budget Sensitivity Analysis

Fig. 6 illustrates the scaling of completion across simultaneous blockage budgets $\kappa \in \{2, 4, 6\}$ ($N = 750$ instances, 3,300 trials, hypothesis H_6).

VIII. Stratified Benchmark Performance

Table I details performance stratified across map classes (Real vs. Synthetic) and adversarial regimes (Benign vs. Adversarial).

TABLE I
Task Completion (%) Stratified by Map Class and Adversarial Regime (Mean ± 95% Bootstrap CI).

Method	Real (Benign)	Real (Adv.)	Synth (Benign)	Synth (Adv.)	Overall (%)
ACA (Ours)	97.7 ± 0.6	97.9 ± 0.4	90.3 ± 1.4	93.1 ± 0.9	95.4 ± 0.4
ACA (No Margin Ablation)	97.9 ± 1.0	98.0 ± 0.7	93.3 ± 2.1	90.4 ± 1.8	95.5 ± 0.7
ACA (Depth-0 Ablation)	97.1 ± 1.2	97.4 ± 0.7	93.5 ± 1.9	91.2 ± 1.6	95.3 ± 0.6
ACA (Depth-2)	98.2 ± 0.8	98.2 ± 0.6	93.5 ± 1.9	91.0 ± 1.7	95.7 ± 0.6
ACA (No Inference)	97.6 ± 1.2	97.9 ± 0.8	93.6 ± 1.9	92.1 ± 1.6	95.9 ± 0.6
CBBA [1]	89.7 ± 2.2	87.0 ± 1.9	87.8 ± 2.4	84.3 ± 2.2	87.0 ± 1.0
CBBA (+LR)	91.4 ± 2.1	89.1 ± 1.3	87.8 ± 2.4	84.5 ± 1.5	88.2 ± 0.8
CBBA-PR (Adapted) [2]	92.5 ± 2.0	91.6 ± 1.6	88.0 ± 2.4	87.7 ± 1.9	90.9 ± 0.9
CBBA-PR (+LR)	89.7 ± 1.6	90.4 ± 1.0	83.6 ± 1.8	88.3 ± 1.2	89.1 ± 0.6
SSI [3]	90.1 ± 2.9	89.0 ± 2.2	85.5 ± 3.5	83.3 ± 2.6	87.1 ± 1.2
SSI (+LR)	90.4 ± 2.9	89.4 ± 2.2	85.5 ± 3.6	82.7 ± 2.7	87.2 ± 1.2
CTP Replan	98.1 ± 0.5	96.6 ± 0.8	94.6 ± 1.0	92.1 ± 1.2	95.4 ± 0.5
Implicit (No Consensus) [4]	99.2 ± 0.4	98.9 ± 0.5	94.7 ± 1.6	93.4 ± 1.5	97.1 ± 0.5
Clairvoyant greedy (reference, not a bound)	99.9 ± 0.2	99.8 ± 0.2	97.5 ± 1.1	96.7 ± 0.8	98.6 ± 0.3
Foresight Optimal (CP-SAT bound)	N/A	99.2 ± 1.2	N/A	96.0 ± 2.8	97.6 ± 1.6

IX. Confirmatory Evaluation Across Disjoint Evaluation Seeds

To evaluate generalizability and empirical consistency across the full benchmark universe, confirmatory evaluation was conducted across all 5 map topologies and 3 adversary regimes on strictly disjoint evaluation seeds $101 \ldots 130$ ($N = 450$ matched instances across 150 independent environments, 3,600 total paired trials). Table II details the confirmatory performance metrics.

TABLE II
Protocol v5 Confirmatory Held-Out Results Across 5 Benchmark Families and 3 Adversary Regimes ($N = 450$ Matched Instances, Seeds 101–130, Mean ± 95% Bootstrap CI).

Method	Completion (%)	Net Welfare	Total Conf.	Messages
ACA (Static Pinsker, $\kappa = 1.0$, Ours)	92.4 ± 1.1	937 ± 25	39.7 ± 3.0	218 ± 13
ACA+ (Heuristic, Adaptive + Pruning)	92.4 ± 1.0	936 ± 25	38.6 ± 2.9	221 ± 13
ACA-Adaptive (Heuristic)	91.3 ± 1.1	920 ± 25	39.0 ± 3.0	232 ± 14
ACA (No Margin)	93.5 ± 1.0	939 ± 23	49.9 ± 3.3	213 ± 12
CBBA (+LR) [1]	94.7 ± 0.9	959 ± 22	25.5 ± 1.8	243 ± 11
CBBA-PR (+LR) [2]	93.4 ± 1.0	953 ± 22	40.6 ± 2.8	239 ± 12
CTP Replan [5]	92.3 ± 1.1	540 ± 42	0.0 ± 0.0	56 ± 3
SSI (+LR) [3]	80.5 ± 2.0	666 ± 41	0.0 ± 0.0	146 ± 10

X. Benchmark System and Algorithm Parameters

Table III lists operational parameters across all benchmark environments.

References

[1] H.-L. Choi, L. Brunet, and J. P. How, "Consensus-based bundle algorithms for multi-agent task allocation," *IEEE Trans. Robot.*, vol. 25, no. 4, pp. 957–968, 2009.

[2] L. Buckman, H.-L. Choi, and J. P. How, "Partial replanning for decentralized dynamic task allocation," in *AIAA Scitech 2019 Forum*, 2019, p. 0418.

[3] S. Koenig *et al.*, "The power of sequential single-item auctions for agent coordination," in *Proc. AAAI Conf. Artif. Intell.*, vol. 21, no. 2, 2006, pp. 1625–1629.




Fig. 1. Raincloud Performance Distributions ($N = 250$ matched instances per method across 5 graph topologies): Panels depict mission completion rate (%), net team welfare, distinct task conflict counts, and total communication message volume. Boxplots show median and interquartile ranges; half-violins illustrate kernel probability densities; points indicate individual instance evaluations.




Fig. 2. Pairwise Non-Parametric Effect Size Heatmap (Cliff's δ, $N = 250$ matched instances per comparison): Color gradient indicates magnitude and direction of difference (warm: ACA advantage; cool: baseline advantage). Significance evaluated via Mann–Whitney U test with Holm–Bonferroni correction.




Fig. 3. Confidence Interval Width Scaling ($10,000$ bootstrap resamples across subsample sizes $N \in [25, 250]$): Shaded regions depict empirical 95% bootstrap CI bounds on mission completion rate, demonstrating asymptotic error reduction consistent with $O(1/\sqrt{N})$ central limit convergence.

TABLE III
BENCHMARK SYSTEM AND ALGORITHM PARAMETERS

Category	Parameter	Default Value
Blockage Process	Baseline onset rate (p_0)	0.15 (θ_1), 0.05 (θ_2)
	Reactive traffic scaling (α)	0.35 (θ_2)
	Corridor clearance rate (μ)	0.15
	Interdiction budget (k)	4
	Risky edge fraction ($\lvert E_{\text{risk}}\rvert/\lvert E\rvert$)	0.25
Fleet & Comms	Fleet size (R)	4
	Tasks per mission (M)	15
	Maximum bundle capacity (L_b)	4
	Robot speed / Sensor range	5.0 / 25.0
	Comm range / Packet drop	45.0 / $p_{\text{drop}} = 0.05$
ACA Algorithm	Contingency recourse depth (d)	1
	ToM estimation error bound (η)	0.05
	Age inflation (λ_{age}) / δ_{map}	0.005 / 0.0

[4] M. Alighanbari and J. P. How, "Decentralized task assignment for unmanned aerial vehicles with inconsistent world views," in *Proc. Amer. Control Conf. (ACC)*, 2005, pp. 2658–2663.
[5] C. H. Papadimitriou and M. Yannakakis, "Shortest paths without a map," *Theor. Comput. Sci.*, vol. 84, no. 1, pp. 127–150, 1991.




Fig. 4. Synchronized Rollout Execution Keyframes on Downtown Boston Road Network ($n = 216, |E| = 323$) under Identical Adversarial Blockage Stream: Columns depict ACA (Ours, Left), CTP Replan (Center), and Standard CBBA (Right) across time steps $t \in \{0, 4, 8, 14\}$. When corridors are blocked (orange markers), standard CBBA drops entire bundles and incurs market re-auction delays, whereas ACA executes zero-message local recourse detours.




Fig. 5. Paired differences in task completion rate (%) vs. ACA across benchmark algorithms ($N = 750$ matched independent instances across 5 graph families, hypotheses H_1, H_2, H_3). Markers denote Hodges–Lehmann median paired differences with 95% bootstrap confidence intervals; p-values computed via two-sided paired Wilcoxon signed-rank tests with Holm–Bonferroni correction.




Fig. 6. Sensitivity of fleet completion to interdiction budget $\kappa \in \{2, 4, 6\}$ across 5 benchmark graph families ($N = 750$ matched independent instances, 3,300 total trials, hypothesis H_6). Non-parametric Jonckheere–Terpstra trend test evaluates monotonic completion degradation under escalating adversary resource bounds.