

```
mysql> INSERT INTO DEPT VALUES
-> (10, 'ACCOUNTING', 'NEW YORK'),
-> (20, 'RESEARCH', 'DALLAS'),
-> (30, 'SALES', 'CHICAGO'),
-> (40, 'OPERATIONS', 'BOSTON');
Query OK, 4 rows affected (0.02 sec)
Records: 4  Duplicates: 0  Warnings: 0
```

```
mysql> select * from dept;
```

DEPTNO	DNAME	LOC
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO
40	OPERATIONS	BOSTON

```
4 rows in set (0.00 sec)
```

```
mysql> INSERT INTO EMP VALUES
-> (7369, 'SMITH', 'CLERK', 7902, '1980-12-17', 800.00, NULL, 20),
-> (7499, 'ALLEN', 'SALESMAN', 7698, '1981-02-20', 1600.00, 300.00, 30),
-> (7521, 'WARD', 'SALESMAN', 7698, '1981-02-22', 1250.00, 500.00, 30),
-> (7566, 'JONES', 'MANAGER', 7839, '1981-04-02', 2975.00, NULL, 20),
-> (7654, 'MARTIN', 'SALESMAN', 7698, '1981-09-28', 1250.00, 1400.00, 30),
-> (7782, 'CLARK', 'MANAGER', 7839, '1981-06-09', 2450.00, NULL, 10),
-> (7839, 'KING', 'PRESIDENT', NULL, '1981-11-17', 5000.00, NULL, 10),
-> (7844, 'TURNER', 'SALESMAN', 7698, '1981-09-08', 1500.00, 0.00, 30),
-> (7900, 'JAMES', 'CLERK', 7698, '1981-12-03', 950.00, NULL, 30),
-> (7902, 'FORD', 'ANALYST', 7566, '1981-12-03', 3000.00, NULL, 20),
-> (7934, 'MILLER', 'CLERK', 7782, '1982-01-23', 1300.00, NULL, 10),
-> (8000, 'ABI', 'CLERK', NULL, '2026-07-30', 1500.00, NULL, 50);
Query OK, 12 rows affected (0.02 sec)
Records: 12  Duplicates: 0  Warnings: 0
```

```
mysql> select * from emp;
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7369	SMITH	CLERK	7902	1980-12-17	800.00	NULL	20
7499	ALLEN	SALESMAN	7698	1981-02-20	1600.00	300.00	30
7521	WARD	SALESMAN	7698	1981-02-22	1250.00	500.00	30
7566	JONES	MANAGER	7839	1981-04-02	2975.00	NULL	20
7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
7782	CLARK	MANAGER	7839	1981-06-09	2450.00	NULL	10
7839	KING	PRESIDENT	NULL	1981-11-17	5000.00	NULL	10
7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30
7900	JAMES	CLERK	7698	1981-12-03	950.00	NULL	30

7902	FORD	ANALYST	7566	1981-12-03	3000.00	NULL	20
7934	MILLER	CLERK	7782	1982-01-23	1300.00	NULL	10
8000	ABJ	CLERK	NULL	2026-07-30	1500.00	NULL	50

12 rows in set (0.00 sec)

```
mysql> SELECT DEPTNO, 'DEPT' AS TABLE_NAME
-> FROM DEPT
->
-> UNION
->
-> SELECT DEPTNO, 'EMP' AS TABLE_NAME
-> FROM EMP;
```

DEPTNO	TABLE_NAME
10	DEPT
20	DEPT
30	DEPT
40	DEPT
20	EMP
30	EMP
10	EMP
50	EMP

8 rows in set (0.00 sec)

```
mysql> SELECT DEPTNO, 'DEPT' AS TABLE_NAME
-> FROM DEPT
->
-> UNION ALL
->
-> SELECT DEPTNO, 'EMP' AS TABLE_NAME
-> FROM EMP;
```

DEPTNO	TABLE_NAME
10	DEPT
20	DEPT
30	DEPT
40	DEPT
20	EMP
30	EMP
30	EMP
20	EMP
30	EMP
10	EMP
10	EMP
30	EMP

	30	EMP	
	20	EMP	
	10	EMP	
	50	EMP	

+-----+
16 rows in set (0.00 sec)

```
mysql> SELECT DEPTNO, 'Only in EMP' AS STATUS
-> FROM EMP
-> WHERE DEPTNO NOT IN (SELECT DEPTNO FROM DEPT)
->
-> UNION
->
-> SELECT DEPTNO, 'Only in DEPT' AS STATUS
-> FROM DEPT
-> WHERE DEPTNO NOT IN (SELECT DEPTNO FROM EMP);
```

+-----+	+-----+	+-----+
DEPTNO	STATUS	
+-----+	+-----+	+-----+
50	Only in EMP	
40	Only in DEPT	
+-----+	+-----+	+-----+

2 rows in set (0.02 sec)

mysql>