



PIMPRI CHINCHWAD EDUCATION TRUST'S.  
**PIMPRI CHINCHWAD COLLEGE OF ENGINEERING**  
(An Autonomous Institute)  
Affiliated to Savitribai Phule Pune University (SPPU)  
ISO 21001:2018 Certified by TUV SUD

**T.Y. B. TECH**

**Year:** 2025 – 26

**Semester:** 6

**Name of the Student:** Mrinmayee Pramod  
Kulkarni

**PRN:** 124B2B025

**Branch:** Computer Engineering

**Division:** C

**Date:** 6/2/2026

## Assignment 1

**Assignment Title:** Create a static web page which defines all text formatting tags of HTML in tabular format.

### Objectives:

- To understand different HTML text formatting tags
- To learn how text can be styled and emphasized using HTML
- To represent information in a clear tabular format
- To design a basic static web page using HTML only

### Outcomes:

- Identify various HTML text formatting tags
- Explain the purpose of each formatting tag
- Use formatting tags to enhance text appearance
- Create a simple static HTML webpage
- Present technical information in a structured table

### Theory Concept in brief

HTML (HyperText Markup Language) provides several text formatting tags that help in improving the readability and presentation of content on a webpage.

These tags allow developers to make text bold, italic, underlined, highlighted, small, deleted, inserted, and more.

**Text formatting tags are mainly used to:**

- Emphasize important text
- Improve visual clarity
- Convey meaning to users
- Structure content professionally

**Program code with output screenshot**

**Code:**

```
<!DOCTYPE html>

<html lang="en">

<head>

    <meta charset="UTF-8">

    <meta name="viewport" content="width=device-width, initial-scale=1.0">

    <title>Document</title>

<style>    body{        background-
color: antiquewhite;        color:black;
    }    td,th{        border:
2px solid black;
    }    table{        border-
collapse: collapse;
width:80%

    }    tr:nth-
child(even)
    {
        background-color: rgb(208, 239, 244);
```

```

    }    tr:nth-
child(odd)
    {
        background-color: rgb(222, 170, 243);
    }
</style>
</head>
<body>

<h1 align=center>Assignment 1</h1>
<br>
<br>
<table border="1" align="center" >
    <tr>
        <th>Tag</th>
        <th>description</th>
        <th>example output</th>
        <th>links</th>
    </tr>
    <tr>
        <td>&lt;b&gt;</td>
        <td>Bold text</td>
        <td><b>Bold description</b></td>
        <td><a
href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/b">Bold</a></td>
    </tr>
    <tr>

```

<td>&lt;strong&gt;</td>

<td>important text</td>

<td><strong>important description</strong></td>

<td><a

href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/strong">strong</a></td>

</tr>

<tr>

<td>&lt;i&gt;</td>

<td>italic text</td>

<td><i>italic description</i></td>

<td><a

href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/italic">italic</a></td>

</tr>

<tr>

<td>&lt;em&gt;</td>

<td>emphasized text</td>

<td><em>emphasized description</em></td>

<td><a

href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/em">em</a></td>

</tr>

<tr>

<td>&lt;u&gt;</td>

<td>underline text</td>

<td><u>underline description</u></td>

```
    <td><a
href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/u">underline</a></td>
>
```

```
</tr>
```

```
<tr>
```

```
    <td>&lt;mark&gt;</td>
```

```
    <td>highlight text</td>
```

```
    <td><mark>mark description</mark></td>
```

```
    <td><a
```

```
href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/mark">mark</a></td>
>
```

```
</tr>
```

```
<tr>
```

```
    <td>&lt;small&gt;</td>
```

```
    <td>smaller text</td>
```

```
    <td><small>smaller description</small></td>
```

```
    <td><a
```

```
href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/small">small</a></td>
>
```

```
</tr>
```

```
<tr>
```

```
    <td>&lt;del&gt;</td>
```

```
    <td>deleted text</td>
```

```
    <td><del>deleted description</del></td>
```

```
    <td><a
```

```
href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/del">del</a></td>
```

</tr>

<tr>

<td>&lt;ins&gt;</td>

<td>inserted text</td>

<td><ins>inserted description</ins></td>

<td><a

href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/ins">ins</a></td>

</tr>

<tr>

<td>&lt;sub&gt;</td>

<td>subscripted text</td>

<td>H<sub>2</sub>O</td>

<td><a

href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/sub">sub</a></td>

</tr>

<tr>

<td>&lt;sup&gt;</td>

<td>superscript text</td>

<td>x<sub>2</sub></td>

<td><a

href="https://developer.mozilla.org/docs/Web/HTML/Reference/Elements/sup">sup</a></td>

</tr>

</table>

</body>

</html>

Output:

Title of my first html pageheaderDocument

File C:/Users/lenovo/Downloads/6th%20sem/fullstacklab/Assignment1.htmlSign inChat

Assignment 1

| Tag      | description      | example output                 | links                     |
|----------|------------------|--------------------------------|---------------------------|
| <b>      | Bold text        | <b>Bold description</b>        | <a href="#">Bold</a>      |
| <strong> | important text   | <b>important description</b>   | <a href="#">strong</a>    |
| <i>      | italic text      | <i>italic description</i>      | <a href="#">italic</a>    |
| <em>     | emphasized text  | <i>emphasized description</i>  | <a href="#">em</a>        |
| <u>      | underline text   | <u>underline description</u>   | <a href="#">underline</a> |
| <mark>   | highlight text   | <b>mark description</b>        | <a href="#">mark</a>      |
| <small>  | smaller text     | smaller description            | <a href="#">small</a>     |
| <del>    | deleted text     | <del>deleted description</del> | <a href="#">del</a>       |
| <ins>    | inserted text    | <u>inserted description</u>    | <a href="#">ins</a>       |
| <sub>    | subscripted text | H <sub>2</sub> O               | <a href="#">sub</a>       |
| <sup>    | superscript text | x <sub>2</sub>                 | <a href="#">sup</a>       |