

METHODS OF COLLECTION

Collection framework classes and interfaces all of them are present in java.util package.

Method of Collection interface

Collection Framework

A	B	C	D	E	F	
---	---	---	---	---	---	--

F	G	H
---	---	---


interface Collection

- add(E e)
- addAll(Collection<E> c)
- remove(Object o)
- removeAll(Collection<E> c)
- retainAll(Collection<E> c)
- clear()
- isEmpty()
- contains(Object o)
- containsAll(Collection<E> c)
- equals(Object o)
- size()
- iterator()
- toArray()

These collection classes and interfaces are Generic. They support the object of any class.

- add(E e) – It will add one object to the collection.

- `addAll(collection<E>c)`



`C1.addAll(C2)`- So, it will add all collections from C2 to C1.

- `remove(Object o)`- It will remove the object and it will return Boolean result [TRUE / FALSE].
- `removeAll(Collection<E>c)` – I can remove all elements, It means that we have to mention a collection and it will remove that collection.

`C1.removeAll(C2)` – So, from C1 I want to remove all those objects, which are already there in C2. [E, F] will remove and [G, H] will not remove.

`C1.retainAll(C2)` – will remove everything and only left EF.


- `Clear()` – collection will get empty

- isEmpty()- returns true if there is nothing in the collection.
- contains(Object o)- If we want to search for a particular object.



Example – C1 does it contains A or not.. returns true.

- containsAll(Collection<E>c) – It will allow us to check whether this enter collection present or not.



Ex – c1.containsAll(C2)- It will now check all C2 elements are present in C1 or not. But here (means in C1) H is not present in there. So, it will return FALSE.

- Equals(Object o)- If we have two collections we can compare them equal in size or not.
- Size- what is the size of collection?
- Iterator()- traversing – scanning- in simple words it will visiting all the objects in a collection.
- toArray()- you can convert a collection to an array.