

analyticsedge

Mridul Jain

7/2/23

Table of contents

The Analytics Edge: Introduction	3
The Analytics Edge: Assignment 1	4
An Analytical Detective	4
Stock Dynamics	14
Demographics and Employment in the United States	22
Internet Privacy Poll (OPTIONAL)	49
The Analytics Edge: Assignment 2	60
Climate Change	60

The Analytics Edge: Introduction

The Analytics Edge: Assignment 1

The following link will lead you to the assignment on the edX website: <https://learning.edx.org/course/course-v1:MITx+15.071x+2T2020/block-v1:MITx+15.071x+2T2020+type@sequential+block@a5915d0492804dada5feb1926ba5be7a>

An Analytical Detective

There are two main types of crimes: violent crimes, and property crimes. In this problem, we'll focus on one specific type of property crime, called "motor vehicle theft" (sometimes referred to as grand theft auto). This is the act of stealing, or attempting to steal, a car. In this problem, we'll use some basic data analysis in R to understand the motor vehicle thefts in Chicago.

Please download the file [mvtWeek1.csv](#) for this problem (do not open this file in any spreadsheet software before completing this problem because it might change the format of the Date field).

Start:

Read the dataset `mvtWeek1.csv` into R, using the `read.csv` function, and call the data frame "mvt".

```
mvt <- read.csv("/cloud/project/analyticsedge/Datasets/DatasetsUnit1/mvtWeek1.csv")
```

1.1: How many rows of data (observations) are in this dataset?

Answer: 191641

```
nrow(mvt)
```

```
[1] 191641
```

1.2: How many variables are in this dataset?

Answer: 11

```
ncol(mvt)
```

```
[1] 11
```

1.3: Using the “max” function, what is the maximum value of the variable “ID”?

Answer: 9181151

```
max(mvt$ID)
```

```
[1] 9181151
```

1.4: What is the minimum value of the variable “Beat”?

Answer: 111

```
min(mvt$Beat)
```

```
[1] 111
```

1.5: How many observations have value TRUE in the Arrest variable (this is the number of crimes for which an arrest was made)?

Answer: 15536

```
sum(mvt$Arrest)
```

```
[1] 15536
```

1.6: How many observations have a LocationDescription value of ALLEY?

Answer: 2308

```
sum(mvt$LocationDescription == "ALLEY")
```

```
[1] 2308
```

2.1: In what format are the entries in the variable Date?

Answer: Month/Day/Year Hour:Minute

```
mvt$Date[1]
```

```
[1] "12/31/12 23:15"
```

2.2: What is the month and year of the median date in our dataset? Enter your answer as “Month Year”, without the quotes.

Answer: May 2006

```
DateConvert = as.Date(strptime(mvt$Date, "%m/%d/%y %H:%M"))
#summary(DateConvert)
median(DateConvert)
```

```
[1] "2006-05-21"
```

2.3: In which month did the fewest motor vehicle thefts occur?

Answer: February

```
mvt$Month = months(DateConvert)
mvt$Weekday = weekdays(DateConvert)
mvt$Date = DateConvert
table(mvt$Month)
```

April	August	December	February	January	July	June	March
15280	16572	16426	13511	16047	16801	16002	15758
May	November	October	September				
16035	16063	17086	16060				

2.4: On which weekday did the most motor vehicle thefts occur?

Answer: Friday

```
table(mvt$Weekday)
```

Friday	Monday	Saturday	Sunday	Thursday	Tuesday	Wednesday
29284	27397	27118	26316	27319	26791	27416

2.5: Which month has the largest number of motor vehicle thefts for which an arrest was made?

Answer: January

```
table(mvt$Month, mvt$Arrest)
```

	FALSE	TRUE
April	14028	1252
August	15243	1329
December	15029	1397
February	12273	1238
January	14612	1435
July	15477	1324
June	14772	1230
March	14460	1298
May	14848	1187
November	14807	1256
October	15744	1342
September	14812	1248

3.1.1: In general, does it look like crime increases or decreases from 2002 - 2012?

Answer: Decreases

3.1.2: In general, does it look like crime increases or decreases from 2005 - 2008?


Answer: Decreases

3.1.3: In general, does it look like crime increases or decreases from 2009 - 2011?

Answer: Increases

```
hist(mvt$Date, breaks=100)
```


Histogram of mvt\$Date



3.2: Does it look like there were more crimes for which arrests were made in the first half of the time period or the second half of the time period?

Answer: First half

```
boxplot(Date ~ Arrest, data = mvt)
```



3.3: For what proportion of motor vehicle thefts in 2001 was an arrest made?

Answer: 0.1041173

```
tapply(mvt$Arrest, mvt$Year, mean)
```

2001	2002	2003	2004	2005	2006	2007
0.10411728	0.11278195	0.10794261	0.10040327	0.09269595	0.08087961	0.08487395
2008	2009	2010	2011	2012		
0.07061267	0.06903920	0.04523456	0.03996930	0.03902924		

3.4: For what proportion of motor vehicle thefts in 2007 was an arrest made?

Answer: 0.08487395

```
tapply(mvt$Arrest, mvt$Year, mean)
```

2001	2002	2003	2004	2005	2006	2007
0.10411728	0.11278195	0.10794261	0.10040327	0.09269595	0.08087961	0.08487395
2008	2009	2010	2011	2012		
0.07061267	0.06903920	0.04523456	0.03996930	0.03902924		

3.5: For what proportion of motor vehicle thefts in 2012 was an arrest made?

Answer: 0.03902924

```
tapply(mvt$Arrest, mvt$Year, mean)
```

2001	2002	2003	2004	2005	2006	2007
0.10411728	0.11278195	0.10794261	0.10040327	0.09269595	0.08087961	0.08487395
2008	2009	2010	2011	2012		
0.07061267	0.06903920	0.04523456	0.03996930	0.03902924		

4.1: Which locations are the top five locations for motor vehicle thefts, excluding the “Other” category?

Answer: STREET, PARKING LOT/GARAGE(NON.RESID.), ALLEY, GAS STATION, DRIVEWAY - RESIDENTIAL

```
sort(table(mvt$LocationDescription), decreasing = TRUE)
```

STREET	156564
PARKING LOT/GARAGE(NON.RESID.)	14852
OTHER	4573
ALLEY	2308
GAS STATION	2111
DRIVEWAY - RESIDENTIAL	1675
RESIDENTIAL YARD (FRONT/BACK)	1536
RESIDENCE	1302
RESIDENCE-GARAGE	1176
VACANT LOT/LAND	985
VEHICLE NON-COMMERCIAL	817
SIDEWALK	462

CHA PARKING LOT/GROUNDS	405
AIRPORT/AIRCRAFT	363
POLICE FACILITY/VEH PARKING LOT	266
PARK PROPERTY	255
SCHOOL, PUBLIC, GROUNDS	206
APARTMENT	184
SPORTS ARENA/STADIUM	166
CTA GARAGE / OTHER PROPERTY	148
COMMERCIAL / BUSINESS OFFICE	126
HOTEL/MOTEL	124
SCHOOL, PUBLIC, BUILDING	114
HOSPITAL BUILDING/GROUNDS	101
GROCERY FOOD STORE	80
CHURCH/SYNAGOGUE/PLACE OF WORSHIP	56
RESTAURANT	49
GOVERNMENT BUILDING/PROPERTY	48
COLLEGE/UNIVERSITY GROUNDS	47
CAR WASH	44
CONSTRUCTION SITE	35
SMALL RETAIL STORE	33
OTHER RAILROAD PROP / TRAIN DEPOT	28
AIRPORT EXTERIOR - NON-SECURE AREA	

	24
SCHOOL, PRIVATE, GROUNDS	
	23
VEHICLE-COMMERCIAL	
	23
DEPARTMENT STORE	
	22
HIGHWAY/EXPRESSWAY	
	22
NURSING HOME/RETIREMENT HOME	
	21
TAXICAB	
	21
MOVIE HOUSE/THEATER	
	18
RESIDENCE PORCH/HALLWAY	
	18
BAR OR TAVERN	
	17
WAREHOUSE	
	17
FACTORY/MANUFACTURING BUILDING	
	16
SCHOOL, PRIVATE, BUILDING	
	14
TAVERN/LIQUOR STORE	
	14
AIRPORT PARKING LOT	
	11
AIRPORT VENDING ESTABLISHMENT	
	10
ATHLETIC CLUB	
	9
DRUG STORE	
	8
OTHER COMMERCIAL TRANSPORTATION	
	8
BANK	
	7
CONVENIENCE STORE	
	7
FOREST PRESERVE	
	6

AIRPORT TERMINAL UPPER LEVEL - NON-SECURE AREA	5
CHA APARTMENT	5
DAY CARE CENTER	5
FIRE STATION	5
ABANDONED BUILDING	4
AIRPORT BUILDING NON-TERMINAL - NON-SECURE AREA	4
BARBERSHOP	4
LAKEFRONT/WATERFRONT/RIVERBANK	4
LIBRARY	4
SAVINGS AND LOAN	4
BOWLING ALLEY	3
CLEANING STORE	3
MEDICAL/DENTAL OFFICE	3
BRIDGE	2
COLLEGE/UNIVERSITY RESIDENCE HALL	2
CURRENCY EXCHANGE	2
AIRPORT BUILDING NON-TERMINAL - SECURE AREA	1
AIRPORT EXTERIOR - SECURE AREA	1
ANIMAL HOSPITAL	1
APPLIANCE STORE	1
CTA TRAIN	1
JAIL / LOCK-UP FACILITY	

1
NEWSSTAND
1

Create a subset of your data, only taking observations for which the theft happened in one of these five locations, and call this new data set “Top5”.

```
Top5 <- subset(mvt, mvt$LocationDescription == "STREET"  
  | mvt$LocationDescription == "PARKING LOT/GARAGE(NON.RESID.)"  
  | mvt$LocationDescription == "ALLEY"  
  | mvt$LocationDescription == "GAS STATION"  
  | mvt$LocationDescription == "DRIVEWAY - RESIDENTIAL")
```

4.2: How many observations are in Top5?

Answer: 177510

```
nrow(Top5)
```

```
[1] 177510
```

4.3: One of the locations has a much higher arrest rate than the other locations. Which is it?

Answer: Gas Station (Check percentages)

```
Top5$LocationDescription = factor(Top5$LocationDescription)  
table(Top5$LocationDescription, Top5$Arrest)
```

	FALSE	TRUE
ALLEY	2059	249
DRIVEWAY - RESIDENTIAL	1543	132
GAS STATION	1672	439
PARKING LOT/GARAGE(NON.RESID.)	13249	1603
STREET	144969	11595

4.4: On which day of the week do the most motor vehicle thefts at gas stations happen?

Answer: Saturday

```
table(Top5$LocationDescription == "GAS STATION", Top5$Weekday)
```

	Friday	Monday	Saturday	Sunday	Thursday	Tuesday	Wednesday
FALSE	26746	25008	24917	24220	24956	24527	25025
TRUE	332	280	338	336	282	270	273

4.5: On which day of the week do the fewest motor vehicle thefts in residential driveways happen?

Answer: Saturday

```
table(Top5$LocationDescription == "DRIVEWAY - RESIDENTIAL", Top5$Weekday)
```

	Friday	Monday	Saturday	Sunday	Thursday	Tuesday	Wednesday
FALSE	26821	25033	25053	24335	24975	24554	25064
TRUE	257	255	202	221	263	243	234

Stock Dynamics

A stock market is where buyers and sellers trade shares of a company, and is one of the most popular ways for individuals and companies to invest money. The size of the world stock market is now estimated to be in the trillions. The largest stock market in the world is the New York Stock Exchange (NYSE), located in New York City. About 2,800 companies are listed on the NYSE. In this problem, we'll look at the monthly stock prices of five of these companies: IBM, General Electric (GE), Procter and Gamble, Coca Cola, and Boeing. The data used in this problem comes from Infochimps.

Please download the following files: [IBMStock.csv](#), [GESTock.csv](#), [ProcterGambleStock.csv](#), [CocaColaStock.csv](#), [BoeingStock.csv](#) (do not open these files in any spreadsheet software before completing this problem because it might change the format of the Date field).

Start:

1. Read the datasets into R, using the read.csv function, and call the data frames "IBM", "GE", "ProcterGamble", "CocaCola", and "Boeing", respectively.

```
IBM <- read.csv("/cloud/project/analyticsege/Datasets/DatasetsUnit1/IBMStock.csv")
GE <- read.csv("/cloud/project/analyticsege/Datasets/DatasetsUnit1/GESTock.csv")
ProcterGamble <- read.csv("/cloud/project/analyticsege/Datasets/DatasetsUnit1/ProcterGamb
CocaCola <- read.csv("/cloud/project/analyticsege/Datasets/DatasetsUnit1/CocaColaStock.cs
Boeing <- read.csv("/cloud/project/analyticsege/Datasets/DatasetsUnit1/BoeingStock.csv")
```

2. Before working with these data sets, we need to convert the dates into a format that R can understand. Take a look at the structure of one of the datasets using the str function. Right

now, the date variable is stored as a factor. We can convert this to a “Date” object in R by using the following five commands (one for each data set):

```
IBM$Date = as.Date(IBM$Date, "%m/%d/%y")
GE$Date = as.Date(GE$Date, "%m/%d/%y")
CocaCola$Date = as.Date(CocaCola$Date, "%m/%d/%y")
ProcterGamble$Date = as.Date(ProcterGamble$Date, "%m/%d/%y")
Boeing$Date = as.Date(Boeing$Date, "%m/%d/%y")
```

1.1: Our five datasets all have the same number of observations. How many observations are there in each data set?

Answer: 480

```
nrow(IBM)
```

```
[1] 480
```

```
# According to the assignment, use: str(IBM)
# We only need to use the command for one of the datasets, since they all have the same nu
```

1.2: What is the earliest year in our datasets?

Answer: 1970

```
min(IBM$Date)
```

```
[1] "1970-01-01"
```

```
# According to the assignment, use: summary(IBM$Date)
# Again, we only need to use the command for one of the datasets, since the observations st
```

1.3: What is the latest year in our datasets?

Answer: 2009

```
max(IBM$Date)
```

```
[1] "2009-12-01"
```

```
# According to the assignment, use: summary(IBM$Date)
# Again, we only need to use the command for one of the datasets, since the observations en
```

1.4: What is the mean stock price of IBM over this time period?

Answer: 144.375

```
mean(IBM$StockPrice)
```

```
[1] 144.375
```

```
# According to the assignment, use: summary(IBM$StockPrice)
```

1.5: What is the minimum stock price of General Electric (GE) over this time period?

Answer: 9.293636

```
min(GE$StockPrice)
```

```
[1] 9.293636
```

```
# According to the assignment, use: summary(GE$StockPrice)
```

1.6: What is the maximum stock price of Coca-Cola over this time period?

Answer: 146.5843

```
max(CocaCola$StockPrice)
```

```
[1] 146.5843
```

```
# According to the assignment, use: summary(CocaCola$StockPrice)
```

1.7: What is the median stock price of Boeing over this time period?

Answer:

```
median(Boeing$StockPrice)
```

```
[1] 44.8834
```



```
# According to the assignment, use: summary(Boeing$StockPrice)
```

1.8: What is the standard deviation of the stock price of Procter & Gamble over this time period?

Answer: 18.19414

```
sd(ProcterGamble$StockPrice)
```

```
[1] 18.19414
```

Side note: According to the assignment, questions 1.2 - 1.7 should've been solved using the summary function. However, I used commands that would give more accurate answer. Along with the commands I used, I also wrote how the assignment could be solved using the summary function.


2.1.1: Around what year did Coca-Cola has its highest stock price in this time period?

Answer: 1973

2.1.2: Around what year did Coca-Cola has its lowest stock price in this time period?

Answer: 1980


```
plot(CocaCola$Date, CocaCola$StockPrice, "l")
```



2.2: In March of 2000, the technology bubble burst, and a stock market crash occurred. According to this plot, which company's stock dropped more?

Answer: Procter and Gamble

```
plot(CocaCola$Date, CocaCola$StockPrice, "l", col = "red")
lines(ProcterGamble$Date, ProcterGamble$StockPrice, col = "blue")
abline(v=as.Date(c("2000-03-01")), lwd=2)
```




2.3.1: Around 1983, the stock for one of these companies (Coca-Cola or Procter and Gamble) was going up, while the other was going down. Which one was going up?

Answer: CocaCola

2.3.1: In the time period shown in the plot, which stock generally has lower values?


Answer: CocaCola

```
plot(CocaCola$Date, CocaCola$StockPrice, "l", col = "red")
lines(ProcterGamble$Date, ProcterGamble$StockPrice, col = "blue")
abline(v=as.Date(c("1983-01-01")))
```



Plot to answer the following questions:

```
plot(CocaCola$Date[301:432], CocaCola$StockPrice[301:432], type="l", col="red", ylim=c(0,200))
lines(ProcterGamble$Date[301:432], ProcterGamble$StockPrice[301:432], col = "blue")
lines(IBM$Date[301:432], IBM$StockPrice[301:432], col = "green")
lines(GE$Date[301:432], GE$StockPrice[301:432], col = "purple")
lines(Boeing$Date[301:432], Boeing$StockPrice[301:432], col = "orange")
```




3.1: Which stock fell the most right after the technology bubble burst in March 2000?

Answer: General Electric (GE)

```

plot(CocaCola$Date[301:432], CocaCola$StockPrice[301:432], type="l", col="red", ylim=c(0,200))
lines(ProcterGamble$Date[301:432], ProcterGamble$StockPrice[301:432], col = "blue")
lines(IBM$Date[301:432], IBM$StockPrice[301:432], col = "green")
lines(GE$Date[301:432], GE$StockPrice[301:432], col = "purple")
lines(Boeing$Date[301:432], Boeing$StockPrice[301:432], col = "orange")
abline(v = as.Date(c("2000-03-01")))

```



3.2: Which stock reaches the highest value in the time period 1995-2005?

Answer: IBM


3.3: Comparing September 1997 to November 1997, which companies saw a decreasing trend in their stock price?

Answer: Procter and Gamble, Boeing

```

plot(CocaCola$Date[301:432], CocaCola$StockPrice[301:432], type="l", col="red", ylim=c(0,200))
lines(ProcterGamble$Date[301:432], ProcterGamble$StockPrice[301:432], col = "blue")
lines(IBM$Date[301:432], IBM$StockPrice[301:432], col = "green")
lines(GE$Date[301:432], GE$StockPrice[301:432], col = "purple")
lines(Boeing$Date[301:432], Boeing$StockPrice[301:432], col = "orange")
abline(v = as.Date(c("1997-09-1")))
abline(v = as.Date(c("1997-11-1")))

```



3.4: In the last two years of this time period (2004 and 2005) which stock seems to be performing the best, in terms of increasing stock price?

Answer: Boeing

4.1: In which months has IBM historically had a higher stock price (on average)?

Answer: January, February, March, April, May

```
tapply(IBM$StockPrice, months(IBM$Date), mean) > mean(IBM$StockPrice)
```

April	August	December	February	January	July	June	March
TRUE	FALSE	FALSE	TRUE	TRUE	FALSE	FALSE	TRUE
May	November	October	September				
TRUE	FALSE	FALSE	FALSE				

4.2: General Electric and Coca-Cola both have their highest average stock price in the same month. Which month is this?

Answer: April

```
tapply(GE$StockPrice, months(GE$Date), mean) == max(tapply(GE$StockPrice, months(GE$Date),
```

April	August	December	February	January	July	June	March
TRUE	FALSE	FALSE	FALSE	FALSE	FALSE	FALSE	FALSE
May	November	October	September				
FALSE	FALSE	FALSE	FALSE				

4.3: For the months of December and January, every company's average stock is higher in one month and lower in the other. In which month are the stock prices lower?

Answer: December

```
tapply(GE$StockPrice, months(GE$Date), mean)
```

April	August	December	February	January	July	June	March
64.48009	56.50315	59.10217	62.52080	62.04511	56.73349	56.46844	63.15055
May	November	October	September				
60.87135	57.28879	56.23897	56.23913				

Demographics and Employment in the United States

In the wake of the Great Recession of 2009, there has been a good deal of focus on employment statistics, one of the most important metrics policymakers use to gauge the overall strength of the economy. In the United States, the government measures unemployment using the Current Population Survey (CPS), which collects demographic and employment information from a wide range of Americans each month. In this exercise, we will employ the topics reviewed in the lectures as well as a few new techniques using the September 2013 version of this rich, nationally representative dataset (available online).

The observations in the dataset represent people surveyed in the September 2013 CPS who actually completed a survey. While the full dataset has 385 variables, in this exercise we will use a more compact version of the dataset.

Please download the following file: [CPSPData.csv](#)

Start:

Load the dataset from CPSPData.csv into a data frame called CPS.

```
CPS <- read.csv("/cloud/project/analyticsedge/Datasets/DatasetsUnit1/CPSPData.csv")
```

1.1: How many interviewees are in the dataset?

Answer: 131302

```
nrow(CPS)
```

```
[1] 131302
```

1.2: Among the interviewees with a value reported for the Industry variable, what is the most common industry of employment?

Answer: Educational and health services

```
head(sort(table(CPS$Industry), decreasing = TRUE), 1)
```

```
Educational and health services
15017
```

1.3.1: Which state has the fewest interviewees?

Answer: New Mexico

```
tail(sort(table(CPS$State), decreasing = TRUE), 1)
```

```
New Mexico
1102
```

1.3.2: Which state has the largest number of interviewees?

Answer: California

```
head(sort(table(CPS$State), decreasing = TRUE), 1)
```

```
California
11570
```

1.4: What proportion of interviewees are citizens of the United States?

Answer: 0.9421943

```
table(CPS$Citizenship)
```

Citizen, Native Citizen, Naturalized	Non-Citizen
116639	7590

```
(116639+7590)/nrow(CPS)
```

```
[1] 0.9421943
```

1.5: For which races are there at least 250 interviewees in the CPS dataset of Hispanic ethnicity?

Answer: American Indian, Black, Multiracial, White

```
table(CPS$Race, CPS$Hispanic) > 250
```

	0	1
American Indian	TRUE	TRUE
Asian	TRUE	FALSE
Black	TRUE	TRUE
Multiracial	TRUE	TRUE
Pacific Islander	TRUE	FALSE
White	TRUE	TRUE

2.1: Which variables have at least one interviewee with a missing (NA) value?

Answer: MetroAreaCode, Married, Education, EmploymentStatus, Industry

```
sum(is.na(CPS$PeopleInHousehold)) > 0
```

```
[1] FALSE
```

```
sum(is.na(CPS$Region)) > 0
```

```
[1] FALSE
```

```
sum(is.na(CPS$State)) > 0
```

```
[1] FALSE
```

```
sum(is.na(CPS$MetroAreaCode)) > 0
```

```
[1] TRUE
```

```
sum(is.na(CPS$Age)) > 0
```

```
[1] FALSE
```



```
sum(is.na(CPS$Married)) > 0
```

```
[1] TRUE
```

```
sum(is.na(CPS$Sex)) > 0
```

```
[1] FALSE
```

```
sum(is.na(CPS$Education)) > 0
```

```
[1] TRUE
```

```
sum(is.na(CPS$Race)) > 0
```

```
[1] FALSE
```

```
sum(is.na(CPS$Hispanic)) > 0
```

```
[1] FALSE
```

```
sum(is.na(CPS$CountryOfBirthCode)) > 0
```

```
[1] FALSE
```

```
sum(is.na(CPS$Citizenship)) > 0
```

```
[1] FALSE
```

```
sum(is.na(CPS$EmploymentStatus)) > 0
```

```
[1] TRUE
```

```
sum(is.na(CPS$Industry)) > 0
```

```
[1] TRUE
```

2.2: We will try to determine if there is a pattern in the missing values of the Married variable.

Answer: The Married variable being missing is related to the Age value for the interviewee.

```
table(CPS$Region, is.na(CPS$Married))
```

	FALSE	TRUE
Midwest	24609	6075
Northeast	21432	4507
South	33535	7967
West	26388	6789

```
table(CPS$Sex, is.na(CPS$Married))
```

	FALSE	TRUE
Female	55264	12217
Male	50700	13121

```
table(CPS$Age, is.na(CPS$Married))
```

	FALSE	TRUE
0	0	1283
1	0	1559
2	0	1574
3	0	1693
4	0	1695
5	0	1795
6	0	1721
7	0	1681
8	0	1729
9	0	1748
10	0	1750

11	0	1721
12	0	1797
13	0	1802
14	0	1790
15	1795	0
16	1751	0
17	1764	0
18	1596	0
19	1517	0
20	1398	0
21	1525	0
22	1536	0
23	1638	0
24	1627	0
25	1604	0
26	1643	0
27	1657	0
28	1736	0
29	1645	0
30	1854	0
31	1762	0
32	1790	0
33	1804	0
34	1653	0
35	1716	0
36	1663	0
37	1531	0
38	1530	0
39	1542	0
40	1571	0
41	1673	0
42	1711	0
43	1819	0
44	1764	0
45	1749	0
46	1665	0
47	1647	0
48	1791	0
49	1989	0
50	1966	0
51	1931	0
52	1935	0
53	1994	0

```

54 1912 0
55 1895 0
56 1935 0
57 1827 0
58 1874 0
59 1758 0
60 1746 0
61 1735 0
62 1595 0
63 1596 0
64 1519 0
65 1569 0
66 1577 0
67 1227 0
68 1130 0
69 1062 0
70 1195 0
71 1031 0
72 941 0
73 896 0
74 842 0
75 763 0
76 729 0
77 698 0
78 659 0
79 661 0
80 2664 0
85 2446 0

```

```
table(CPS$Citizenship, is.na(CPS$Married))
```

	FALSE	TRUE
Citizen, Native	91956	24683
Citizen, Naturalized	6910	163
Non-Citizen	7098	492

2.3.1: How many states had all interviewees living in a non-metropolitan area (aka they have a missing MetroAreaCode value)? For this question, treat the District of Columbia as a state (even though it is not technically a state).

Answer: 2

2.3.2: How many states had all interviewees living in a metropolitan area? Again, treat the District of Columbia as a state.

Answer: 3

```
table(CPS$State, is.na(CPS$MetroAreaCode))
```

	FALSE	TRUE
Alabama	1020	356
Alaska	0	1590
Arizona	1327	201
Arkansas	724	697
California	11333	237
Colorado	2545	380
Connecticut	2593	243
Delaware	1696	518
District of Columbia	1791	0
Florida	4947	202
Georgia	2250	557
Hawaii	1576	523
Idaho	761	757
Illinois	3473	439
Indiana	1420	584
Iowa	1297	1231
Kansas	1234	701
Kentucky	908	933
Louisiana	1216	234
Maine	909	1354
Maryland	2978	222
Massachusetts	1858	129
Michigan	2517	546
Minnesota	2150	989
Mississippi	376	854
Missouri	1440	705
Montana	199	1015
Nebraska	816	1133
Nevada	1609	247
New Hampshire	1148	1514
New Jersey	2567	0
New Mexico	832	270
New York	5144	451
North Carolina	1642	977
North Dakota	432	1213

Ohio	2754	924
Oklahoma	1024	499
Oregon	1519	424
Pennsylvania	3245	685
Rhode Island	2209	0
South Carolina	1139	519
South Dakota	595	1405
Tennessee	1149	635
Texas	6060	1017
Utah	1455	387
Vermont	657	1233
Virginia	2367	586
Washington	1937	429
West Virginia	344	1065
Wisconsin	1882	804
Wyoming	0	1624

2.4: Which region of the United States has the largest proportion of interviewees living in a non-metropolitan area?

Answer: Midwest

```
table(CPS$Region, is.na(CPS$MetroAreaCode))
```

	FALSE	TRUE
Midwest	20010	10674
Northeast	20330	5609
South	31631	9871
West	25093	8084

2.5.1:

Answer: Wisconsin

2.5.2:

Answer: Montana

```
sort(tapply(is.na(CPS$MetroAreaCode), CPS$State, mean))
```

District of Columbia	New Jersey	Rhode Island
0.00000000	0.00000000	0.00000000
California	Florida	Massachusetts
0.02048401	0.03923092	0.06492199

Maryland	New York	Connecticut
0.06937500	0.08060769	0.08568406
Illinois	Colorado	Arizona
0.11221881	0.12991453	0.13154450
Nevada	Texas	Louisiana
0.13308190	0.14370496	0.16137931
Pennsylvania	Michigan	Washington
0.17430025	0.17825661	0.18131868
Georgia	Virginia	Utah
0.19843249	0.19844226	0.21009772
Oregon	Delaware	New Mexico
0.21821925	0.23396567	0.24500907
Hawaii	Ohio	Alabama
0.24916627	0.25122349	0.25872093
Indiana	Wisconsin	South Carolina
0.29141717	0.29932986	0.31302774
Minnesota	Oklahoma	Missouri
0.31506849	0.32764281	0.32867133
Tennessee	Kansas	North Carolina
0.35594170	0.36227390	0.37304315
Iowa	Arkansas	Idaho
0.48694620	0.49049965	0.49868248
Kentucky	New Hampshire	Nebraska
0.50678979	0.56874530	0.58132376
Maine	Vermont	Mississippi
0.59832081	0.65238095	0.69430894
South Dakota	North Dakota	West Virginia
0.70250000	0.73738602	0.75585522
Montana	Alaska	Wyoming
0.83607908	1.00000000	1.00000000

Codes like `MetroAreaCode` and `CountryOfBirthCode` are a compact way to encode factor variables with text as their possible values, and they are therefore quite common in survey datasets. In fact, all but one of the variables in this dataset were actually stored by a numeric code in the original CPS datafile.

When analyzing a variable stored by a numeric code, we will often want to convert it into the values the codes represent. To do this, we will use a dictionary, which maps the the code to the actual value of the variable. We have provided dictionaries [MetroAreaCodes.csv](#) and [CountryCodes.csv](#), which respectively map `MetroAreaCode` and `CountryOfBirthCode` into their true values. Read these two dictionaries into data frames `MetroAreaMap` and `CountryMap`.

```
MetroAreaMap <- read.csv("/cloud/project/analyticsege/Datasets/DatasetsUnit1/MetroAreaCod
CountryMap <- read.csv("/cloud/project/analyticsege/Datasets/DatasetsUnit1/CountryCodes.c
```

3.1.1: How many observations (codes for metropolitan areas) are there in MetroAreaMap?

Answer: 271

```
nrow(MetroAreaMap)
```

```
[1] 271
```

3.1.2: How many observations (codes for countries) are there in CountryMap?

Answer: 149

```
nrow(CountryMap)
```

```
[1] 149
```

To merge in the metropolitan areas, we want to connect the field MetroAreaCode from the CPS data frame with the field Code in MetroAreaMap. The following command merges the two data frames on these columns, overwriting the CPS data frame with the result:

```
CPS = merge(CPS, MetroAreaMap, by.x = "MetroAreaCode", by.y = "Code", all.x = TRUE)
```

3.2.1: hat is the name of the variable that was added to the data frame by the merge() operation?

Answer: MetroArea

```
str(CPS)
```

```
'data.frame':  131302 obs. of  15 variables:
 $ MetroAreaCode      : int  10420 10420 10420 10420 10420 10420 10420 10420 10420 10420 ...
 $ PeopleInHousehold  : int   4 4 2 4 1 3 4 4 2 3 ...
 $ Region             : chr  "Midwest" "Midwest" "Midwest" "Midwest" ...
 $ State              : chr  "Ohio" "Ohio" "Ohio" "Ohio" ...
 $ Age                : int   2 9 73 40 63 19 30 6 60 32 ...
 $ Married            : chr   NA NA "Married" "Married" ...
 $ Sex                : chr  "Male" "Male" "Female" "Female" ...
```



```

$ Education      : chr  NA NA "Some college, no degree" "High school" ...
$ Race           : chr  "White" "White" "White" "White" ...
$ Hispanic       : int   0 0 0 0 0 0 0 1 0 0 ...
$ CountryOfBirthCode: int  57 57 57 362 57 57 203 57 57 57 ...
$ Citizenship    : chr  "Citizen, Native" "Citizen, Native" "Citizen, Native" "Citizen, Native" ...
$ EmploymentStatus : chr  NA NA "Retired" "Not in Labor Force" ...
$ Industry       : chr  NA NA NA NA ...
$ MetroArea      : chr  "Akron, OH" "Akron, OH" "Akron, OH" "Akron, OH" ...

```

3.2.2: How many interviewees have a missing value for the new metropolitan area variable?

Answer: 34238

```
sum(is.na(CPS$MetroArea))
```

```
[1] 34238
```

3.3: Which of the following metropolitan areas has the largest number of interviewees?

Answer: Boston-Cambridge-Quincy, MA-NH

```
sort(table(CPS$MetroArea), decreasing = TRUE)
```

```

New York-Northern New Jersey-Long Island, NY-NJ-PA
                    5409
Washington-Arlington-Alexandria, DC-VA-MD-WV
                    4177
Los Angeles-Long Beach-Santa Ana, CA
                    4102
Philadelphia-Camden-Wilmington, PA-NJ-DE
                    2855
Chicago-Naperville-Joliet, IN-IN-WI
                    2772
Providence-Fall River-Warwick, MA-RI
                    2284
Boston-Cambridge-Quincy, MA-NH
                    2229
Minneapolis-St Paul-Bloomington, MN-WI
                    1942
Dallas-Fort Worth-Arlington, TX

```

	1863
Houston-Baytown-Sugar Land, TX	
	1649
Honolulu, HI	
	1576
Miami-Fort Lauderdale-Miami Beach, FL	
	1554
Atlanta-Sandy Springs-Marietta, GA	
	1552
Denver-Aurora, CO	
	1504
Baltimore-Towson, MD	
	1483
San Francisco-Oakland-Fremont, CA	
	1386
Detroit-Warren-Livonia, MI	
	1354
Las Vegas-Paradise, NV	
	1299
Riverside-San Bernardino, CA	
	1290
Seattle-Tacoma-Bellevue, WA	
	1255
Portland-Vancouver-Beaverton, OR-WA	
	1089
Phoenix-Mesa-Scottsdale, AZ	
	971
Kansas City, MO-KS	
	962
Omaha-Council Bluffs, NE-IA	
	957
St. Louis, MO-IL	
	956
San Diego-Carlsbad-San Marcos, CA	
	907
Hartford-West Hartford-East Hartford, CT	
	885
Tampa-St. Petersburg-Clearwater, FL	
	842
Pittsburgh, PA	
	732
Bridgeport-Stamford-Norwalk, CT	
	730

Salt Lake City, UT
 723
 Cincinnati-Middletown, OH-KY-IN
 719
 Milwaukee-Waukesha-West Allis, WI
 714
 Portland-South Portland, ME
 701
 Cleveland-Elyria-Mentor, OH
 681
 San Jose-Sunnyvale-Santa Clara, CA
 670
 Sacramento-Arden-Arcade-Roseville, CA
 667
 Burlington-South Burlington, VT
 657
 Boise City-Nampa, ID
 644
 Orlando, FL
 610
 Albuquerque, NM
 609
 San Antonio, TX
 607
 Oklahoma City, OK
 604
 Virginia Beach-Norfolk-Newport News, VA-NC
 597
 Sioux Falls, SD
 595
 Indianapolis, IN
 570
 Columbus, OH
 551
 Louisville, KY-IN
 519
 Charlotte-Gastonia-Concord, NC-SC
 517
 Austin-Round Rock, TX
 516
 New Haven, CT
 506
 Nashville-Davidson-Murfreesboro, TN

	505
Des Moines, IA	
	501
Richmond, VA	
	490
Dover, DE	
	456
Fargo, ND-MN	
	432
Wichita, KS	
	427
Ogden-Clearfield, UT	
	423
Little Rock-North Little Rock, AR	
	404
Jacksonville, FL	
	393
Birmingham-Hoover, AL	
	392
Colorado Springs, CO	
	372
New Orleans-Metairie-Kenner, LA	
	367
Memphis, TN-MS-AR	
	348
Buffalo-Niagara Falls, NY	
	344
Raleigh-Cary, NC	
	336
Allentown-Bethlehem-Easton, PA-NJ	
	334
Tulsa, OK	
	323
Reno-Sparks, NV	
	310
Provo-Orem, UT	
	309
Rochester, NY	
	307
Grand Rapids-Wyoming, MI	
	304
Fresno, CA	
	303

Tucson, AZ	302
Columbia, SC	291
Madison, WI	284
Albany-Schenectady-Troy, NY	268
Dayton, OH	268
Oxnard-Thousand Oaks-Ventura, CA	267
Baton Rouge, LA	262
Charleston, WV	262
Rochester-Dover, NH-ME	262
Greensboro-High Point, NC	251
Bakersfield, CA	245
El Paso, TX	244
Davenport-Moline-Rock Island, IA-IL	240
Toledo, OH	235
Charleston-North Charleston, SC	232
Akron, OH	231
Syracuse, NY	223
Jackson, MS	222
Fayetteville-Springdale-Rogers, AR-MO	215
Bangor, ME	208
Fort Collins-Loveland, CO	206
Norwich-New London, CT-RI	

	203
Savannah, GA	
	202
Poughkeepsie-Newburgh-Middletown, NY	
	201
Billings, MT	
	199
Lexington-Fayette, KY	
	198
Cedar Rapids, IA	
	196
Eugene-Springfield, OR	
	196
McAllen-Edinburg-Pharr, TX	
	195
Stockton, CA	
	193
Sarasota-Bradenton-Venice, FL	
	192
Durham, NC	
	189
Greenville, SC	
	185
Topeka, KS	
	182
Lafayette, LA	
	181
Monroe, LA	
	179
Scranton-Wilkes Barre, PA	
	176
Harrisburg-Carlisle, PA	
	174
Boulder, CO	
	171
Salem, OR	
	170
Knoxville, TN	
	168
Palm Bay-Melbourne-Titusville, FL	
	168
Chattanooga, TN-GA	
	167

Greeley, CO
 162
 Augusta-Richmond County, GA-SC
 161
 Springfield, MO
 161
 Modesto, CA
 158
 Waterbury, CT
 157
 Lancaster, PA
 156
 Spokane, WA
 156
 Waterloo-Cedar Falls, IA
 156
 Springfield, MA-CT
 155
 Youngstown-Warren-Boardman, OH
 153
 Lakeland-Winter Haven, FL
 149
 Cape Coral-Fort Myers, FL
 146
 Shreveport-Bossier City, LA
 146
 Worcester, MA-CT
 144
 Reading, PA
 142
 Bend, OR
 140
 Deltona-Daytona Beach-Ormond Beach, FL
 140
 Fort Wayne, IN
 136
 Green Bay, WI
 136
 Vallejo-Fairfield, CA
 133
 Corpus Christi, TX
 132
 Santa Barbara-Santa Maria-Goleta, CA

	132
Iowa City, IA	
	131
Pueblo, CO	
	130
Santa Rosa-Petaluma, CA	
	129
Kalamazoo-Portage, MI	
	127
Winston-Salem, NC	
	127
Duluth, MN-WI	
	126
Appleton, WI	
	125
Beaumont-Port Author, TX	
	123
Champaign-Urbana, IL	
	122
Visalia-Porterville, CA	
	121
Lansing-East Lansing, MI	
	119
Racine, WI	
	119
Canton-Massillon, OH	
	118
Coeur d'Alene, ID	
	117
Huntsville, AL	
	117
York-Hanover, PA	
	117
Asheville, NC	
	116
Victoria, TX	
	116
La Crosse, WI	
	114
Rockford, IL	
	114
Danbury, CT	
	112

Peoria, IL	112
Yakima, WA	112
Atlantic City, NJ	111
Eau Claire, WI	110
Mobile, AL	110
Port St. Lucie-Fort Pierce, FL	109
Las Cruces, NM	107
Pensacola-Ferry Pass-Brent, FL	107
Merced, CA	106
Fort Smith, AR-OK	105
Bloomington, IN	104
Salinas, CA	104
Montgomery, AL	103
Flint, MI	102
Myrtle Beach-Conway-North Myrtle Beach, SC	102
Killeen-Temple-Fort Hood, TX	101
El Centro, CA	99
Evansville, IN-KY	99
Janesville, WI	99
Olympia, WA	99
Spartanburg, SC	99
Lawrence, KS	

	98
Lawton, OK	97
Decatur, AL	96
Wausau, WI	96
Trenton-Ewing, NJ	91
Harrisonburg, VA	90
Muskegon-Norton Shores, MI	90
Laredo, TX	89
Amarillo, TX	88
Bremerton-Silverdale, WA	87
Erie, PA	87
Kankakee-Bradley, IL	87
Kingston, NY	87
Hagerstown-Martinsburg, MD-WV	86
Ann Arbor, MI	85
Oshkosh-Neenah, WI	85
Altoona, PA	82
Huntington-Ashland, WV-KY-OH	82
Medford, OR	82
Naples-Marco Island, FL	82
St. Cloud, MN	82
Decatur, IL	81

Lake Charles, LA	81
South Bend-Mishawaka, IN-MI	81
Fort Walton Beach-Crestview-Destin, FL	80
Utica-Rome, NY	80
Brownsville-Harlingen, TX	79
Vero Beach, FL	79
Waco, TX	79
Holland-Grand Haven, MI	78
Tuscaloosa, AL	78
Fayetteville, NC	77
Michigan City-La Porte, IN	77
San Luis Obispo-Paso Robles, CA	77
Ocala, FL	76
Springfield, IL	76
Barnstable Town, MA	75
Saginaw-Saginaw Township North, MI	74
Salisbury, MD	74
Binghamton, NY	73
Lynchburg, VA	73
Bellingham, WA	70
Gainesville, FL	70
Jackson, MI	

	70
Albany, GA	
	68
Kingsport-Bristol, TN-VA	
	67
Leominster-Fitchburg-Gardner, MA	
	66
Roanoke, VA	
	66
Santa-Cruz-Watsonville, CA	
	66
Athens-Clark County, GA	
	65
Gulfport-Biloxi, MS	
	65
Longview, TX	
	65
Macon, GA	
	65
Anderson, SC	
	64
Farmington, NM	
	64
Florence, AL	
	63
Jacksonville, NC	
	63
Johnstown, PA	
	63
Lubbock, TX	
	63
Monroe, MI	
	63
Anderson, IN	
	62
Anniston-Oxford, AL	
	61
Napa, CA	
	61
Chico, CA	
	60
Columbus, GA-AL	
	59

Joplin, MO	59
Panama City-Lynn Haven, FL	59
Hickory-Morgantown-Lenoir, NC	57
Madera, CA	57
Prescott, AZ	54
Vineland-Millville-Bridgeton, NJ	54
Johnson City, TN	52
Santa Fe, NM	52
Midland, TX	51
Niles-Benton Harbor, MI	51
Punta Gorda, FL	48
Columbia, MO	47
Tallahassee, FL	43
Valdosta, GA	42
Warner Robins, GA	42
Bloomington-Normal IL	40
Springfield, OH	34
Ocean City, NJ	30
Bowling Green, KY	29

3.4: Which metropolitan area has the highest proportion of interviewees of Hispanic ethnicity?

Answer: Laredo, TX

```
head(sort(tapply(CPS$Hispanic, CPS$MetroArea, mean), decreasing = TRUE), 1)
```

```
Laredo, TX  
0.9662921
```

3.5: Determine the number of metropolitan areas in the United States from which at least 20% of interviewees are Asian.

Answer: 4

```
sum(sort(tapply(CPS$Race == "Asian", CPS$MetroArea, mean), decreasing = TRUE) > 0.2)
```

```
[1] 4
```

3.6: Determine which metropolitan area has the smallest proportion of interviewees who have received no high school diploma.

Answer: Iowa City, IA

```
head(sort(tapply(CPS$Education == "No high school diploma", CPS$MetroArea, mean, na.rm = T
```

```
Iowa City, IA  
0.02912621
```

Just as we did with the metropolitan area information, merge in the country of birth information from the CountryMap data frame, replacing the CPS data frame with the result.

```
CPS = merge(CPS, CountryMap, by.x = "CountryOfBirthCode", by.y = "Code", all.x = TRUE)
```

4.1.1: What is the name of the variable added to the CPS data frame by this merge operation?

Answer: Country

```
str(CPS)
```

```
'data.frame': 131302 obs. of 16 variables:
 $ CountryOfBirthCode: int  57 57 57 57 57 57 57 57 57 57 ...
 $ MetroAreaCode      : int  10420 71650 10420 10420 10420 10420 10420 10420 10420 10420 ...
 $ PeopleInHousehold  : int   2 4 5 2 2 3 1 3 4 4 ...
 $ Region             : chr   "Midwest" "Northeast" "Midwest" "Midwest" ...
 $ State              : chr   "Ohio" "New Hampshire" "Ohio" "Ohio" ...
 $ Age               : int   73 5 10 30 30 0 34 32 6 9 ...
 $ Married            : chr   "Married" NA NA "Married" ...
 $ Sex               : chr   "Female" "Female" "Female" "Female" ...
 $ Education          : chr   "Some college, no degree" NA NA "Associate degree" ...
 $ Race              : chr   "White" "White" "White" "White" ...
 $ Hispanic           : int   0 0 0 0 0 0 0 0 1 0 ...
 $ Citizenship        : chr   "Citizen, Native" "Citizen, Native" "Citizen, Native" "Citizen, Native" ...
 $ EmploymentStatus   : chr   "Retired" NA NA "Employed" ...
 $ Industry           : chr   NA NA NA "Trade" ...
 $ MetroArea          : chr   "Akron, OH" "Boston-Cambridge-Quincy, MA-NH" "Akron, OH" "Akron, OH" ...
 $ Country            : chr   "United States" "United States" "United States" "United States"
```

4.1.2: How many interviewees have a missing value for the new country of birth variable?

Answer: 176

```
sum(is.na(CPS$Country))
```

```
[1] 176
```

4.2: Among all interviewees born outside of North America, which country was the most common place of birth?

Answer: Philippines

```
head(sort(table(CPS$Country), decreasing = TRUE), 3)
```

United States	Mexico	Philippines
115063	3921	839

4.3: What proportion of the interviewees from the “New York-Northern New Jersey-Long Island, NY-NJ-PA” metropolitan area have a country of birth that is not the United States? For this computation, don’t include people from this metropolitan area who have a missing country of birth.

Answer: 0.3086603

```
tapply(CPS$Country != "United States", CPS$MetroArea == "New York-Northern New Jersey-Long
```

```
FALSE      TRUE  
0.1392772 0.3086603
```

4.4: Which metropolitan area has the largest number (note – not proportion) of interviewees with a country of birth... 4.4.1: ...in India?

Answer: New York-Northern New Jersey-Long Island, NY-NJ-PA

```
tail(sort(tapply(CPS$Country == "India", CPS$MetroArea, sum, na.rm = TRUE))), 1)
```

```
New York-Northern New Jersey-Long Island, NY-NJ-PA  
96
```

4.4.2: ...in Brazil?

Answer: Boston-Cambridge-Quincy, MA-NH

```
tail(sort(tapply(CPS$Country == "Brazil", CPS$MetroArea, sum, na.rm = TRUE))), 1)
```

```
Boston-Cambridge-Quincy, MA-NH  
18
```

4.4.3: ...in Somalia?

Answer: Minneapolis-St Paul-Bloomington, MN-WI

```
tail(sort(tapply(CPS$Country == "Somalia", CPS$MetroArea, sum, na.rm = TRUE))), 1)
```

```
Minneapolis-St Paul-Bloomington, MN-WI  
17
```


Internet Privacy Poll (OPTIONAL)

Internet privacy has gained widespread attention in recent years. To measure the degree to which people are concerned about hot-button issues like Internet privacy, social scientists conduct polls in which they interview a large number of people about the topic. In this assignment, we will analyze data from a July 2013 Pew Internet and American Life Project poll on Internet anonymity and privacy, which involved interviews across the United States. While the full polling data can be found [here](#), we will use a more limited version of the results, available in [AnonymityPoll.csv](#).

Start:

Using `read.csv()`, load the dataset from `AnonymityPoll.csv` into a data frame called `poll`.

```
poll <- read.csv("/cloud/project/analyticsedge/Datasets/DatasetsUnit1/AnonymityPoll.csv")
```

1.1: How many people participated in the poll?

Answer: 1002

```
nrow(poll)
```

```
[1] 1002
```

1.2.1: How many interviewees responded that they use a smartphone?

Answer: 487

```
sum(poll$Smartphone, na.rm = TRUE)
```

```
[1] 487
```

1.2.2: How many interviewees responded that they don't use a smartphone?

Answer: 472

```
table(poll$Smartphone)
```

```
 0    1  
472 487
```

1.2.3: How many interviewees did not respond to the question, resulting in a missing value, or NA, in the `summary()` output?

Answer: 43

```
sum(is.na(poll$Smartphone))
```

[1] 43

1.3.1: Which of the following are states in the Midwest census region?

Answer: Kansas, Missouri, Ohio

1.3.2: Which was the state in the South census region with the largest number of interviewees?

Answer: Texas

```
table(poll$Region, poll$State)
```

	Alabama	Arizona	Arkansas	California	Colorado	Connecticut	Delaware
Midwest	0	0	0	0	0	0	0
Northeast	0	0	0	0	0	8	0
South	11	0	10	0	0	0	6
West	0	24	0	103	19	0	0

	District of Columbia	Florida	Georgia	Idaho	Illinois	Indiana	Iowa
Midwest		0	0	0	32	27	14
Northeast		0	0	0	0	0	0
South		2	42	34	0	0	0
West		0	0	0	8	0	0

	Kansas	Kentucky	Louisiana	Maine	Maryland	Massachusetts	Michigan
Midwest	14	0	0	0	0	0	31
Northeast	0	0	0	4	0	19	0
South	0	25	17	0	18	0	0
West	0	0	0	0	0	0	0

	Minnesota	Mississippi	Missouri	Montana	Nebraska	Nevada
Midwest	15	0	26	0	11	0
Northeast	0	0	0	0	0	0
South	0	11	0	0	0	0
West	0	0	0	5	0	8

	New Hampshire	New Jersey	New Mexico	New York	North Carolina
Midwest	0	0	0	0	0
Northeast	7	16	0	60	0

South	0	0	0	0	32
West	0	0	5	0	0

	North Dakota	Ohio	Oklahoma	Oregon	Pennsylvania	Rhode Island
Midwest	5	38	0	0	0	0
Northeast	0	0	0	0	45	4
South	0	0	14	0	0	0
West	0	0	0	20	0	0

	South Carolina	South Dakota	Tennessee	Texas	Utah	Vermont	Virginia
Midwest	0	3	0	0	0	0	0
Northeast	0	0	0	0	0	3	0
South	12	0	17	72	0	0	31
West	0	0	0	0	11	0	0

	Washington	West Virginia	Wisconsin	Wyoming
Midwest	0	0	23	0
Northeast	0	0	0	0
South	0	5	0	0
West	28	0	0	7

2.1.1: How many interviewees reported not having used the Internet and not having used a smartphone?

Answer: 186

```
tapply(poll$Internet.Use == 0, poll$Smartphone == 0, sum, na.rm = TRUE)
```

```
FALSE  TRUE
    17   186
```

2.1.2: How many interviewees reported having used the Internet and having used a smartphone?

Answer: 470

```
tapply(poll$Internet.Use, poll$Smartphone, sum, na.rm = TRUE)
```

```
0    1
285 470
```

2.1.3: How many interviewees reported having used the Internet but not having used a smartphone?

Answer: 285

```
tapply(poll$Internet.Use == 1, poll$Smartphone == 0, sum, na.rm = TRUE)
```

```
FALSE  TRUE  
470    285
```

2.1.4: How many interviewees reported having used a smartphone but not having used the Internet?

Answer: 17

```
tapply(poll$Internet.Use == 0, poll$Smartphone == 1, sum, na.rm = TRUE)
```

```
FALSE  TRUE  
186    17
```

```
# Alternative to all 4 above questions: table(poll$Internet.Use, poll$Smartphone)
```

2.2.1: How many interviewees have a missing value for their Internet use?

Answer: 1

```
sum(is.na(poll$Internet.Use))
```

```
[1] 1
```

2.2.2: How many interviewees have a missing value for their smartphone use?

Answer: 43

```
sum(is.na(poll$Smartphone))
```

```
[1] 43
```

Use the subset function to obtain a data frame called “limited”, which is limited to interviewees who reported Internet use or who reported smartphone use.

```

limited <- subset(poll, poll$Internet.Use == 1
                 | poll$Smartphone == 1)
# Alternative: limited = subset(poll, Internet.Use == 1 | Smartphone == 1)

```

2.3: How many interviewees are in the new data frame?

Answer: 792

```
nrow(limited)
```

```
[1] 792
```

3.1: Which variables have missing values in the limited data frame?

Answer: Smartphone, Age, Conservativeness, Worry.About.Info, Privacy.Importance, Anonymity.Possible, Tried.Masking.Identity, Privacy.Laws.Effective

```
summary(limited)
```

Internet.Use	Smartphone	Sex	Age
Min. :0.0000	Min. :0.0000	Length:792	Min. :18.00
1st Qu.:1.0000	1st Qu.:0.0000	Class :character	1st Qu.:33.00
Median :1.0000	Median :1.0000	Mode :character	Median :51.00
Mean :0.9785	Mean :0.6308		Mean :48.57
3rd Qu.:1.0000	3rd Qu.:1.0000		3rd Qu.:62.00
Max. :1.0000	Max. :1.0000		Max. :93.00
	NA's :20		NA's :22
State	Region	Conservativeness	Info.On.Internet
Length:792	Length:792	Min. :1.000	Min. : 0.000
Class :character	Class :character	1st Qu.:3.000	1st Qu.: 2.000
Mode :character	Mode :character	Median :3.000	Median : 4.000
		Mean :3.237	Mean : 3.795
		3rd Qu.:4.000	3rd Qu.: 6.000
		Max. :5.000	Max. :11.000
		NA's :45	
Worry.About.Info	Privacy.Importance	Anonymity.Possible	Tried.Masking.Identity
Min. :0.0000	Min. : 0.00	Min. :0.0000	Min. :0.0000
1st Qu.:0.0000	1st Qu.: 41.43	1st Qu.:0.0000	1st Qu.:0.0000
Median :0.0000	Median : 68.75	Median :0.0000	Median :0.0000
Mean :0.4886	Mean : 62.85	Mean :0.3692	Mean :0.1633
3rd Qu.:1.0000	3rd Qu.: 88.89	3rd Qu.:1.0000	3rd Qu.:0.0000
Max. :1.0000	Max. :100.00	Max. :1.0000	Max. :1.0000

```
NA's :2      NA's :5      NA's :39      NA's :8
Privacy.Laws.Effective
Min. :0.0000
1st Qu.:0.0000
Median :0.0000
Mean :0.2559
3rd Qu.:1.0000
Max. :1.0000
NA's :65
```

```
sum(is.na(limited$Sex))
```

```
[1] 0
```

```
sum(is.na(limited$State))
```

```
[1] 0
```

```
sum(is.na(limited$Region))
```

```
[1] 0
```

3.2: What is the average number of pieces of personal information on the Internet, according to the Info.On.Internet variable?

Answer: 3.795455

```
mean(limited$Info.On.Internet)
```

```
[1] 3.795455
```

3.3.1: How many interviewees reported a value of 0 for Info.On.Internet?

Answer: 105

```
sum(limited$Info.On.Internet == 0)
```

```
[1] 105
```

3.3.2: How many interviewees reported the maximum value of 11 for Info.On.Internet?

Answer: 8

```
sum(limited$Info.On.Internet == 11)
```

```
[1] 8
```

3.4: What proportion of interviewees who answered the Worry>About.Info question worry about how much information is available about them on the Internet?

Answer: 0.4886076

```
table(limited$Worry>About.Info)
```

```
 0    1
404 386
```

```
386/(404+386)
```

```
[1] 0.4886076
```

3.5: What proportion of interviewees who answered the Anonymity.Possible question think it is possible to be completely anonymous on the Internet?

Answer: 0.3691899

```
table(limited$Anonymity.Possible)
```

```
 0    1
475 278
```

```
278/(475+278)
```

```
[1] 0.3691899
```

3.6: What proportion of interviewees who answered the Tried.Masking.Identity question have tried masking their identity on the Internet?

Answer: 0.1632653

```
table(limited$Tried.Masking.Identity)
```

```
  0    1  
656 128
```

```
128/(656+128)
```

```
[1] 0.1632653
```

3.7: What proportion of interviewees who answered the Privacy.Laws.Effective question find United States privacy laws effective?

Answer: 0.2558459

```
table(limited$Privacy.Laws.Effective)
```

```
  0    1  
541 186
```


```
186/(541+186)
```

```
[1] 0.2558459
```

4.1: Build a histogram of the age of interviewees. What is the best represented age group in the population?

Answer: People aged about 60 years old.


```
hist(limited$Age)
```

4.2: What is the largest number of interviewees that have exactly the same value in their Age variable AND the same value in their Info.On.Internet variable?

Answer: 6

```
plot(limited$Age, limited$Info.On.Internet)
```



```
max(table(limited$Age, limited$Info.On.Internet))
```

```
[1] 6
```

4.3: Experimenting with the command `jitter(c(1, 2, 3))`, what appears to be the functionality of the jitter command?

Answer: jitter adds or subtracts a small amount of random noise to the values passed to it, and two runs will yield different results.


```
jitter(c(1, 2, 3))
```

```
[1] 0.9459555 2.0188513 3.0673628
```

4.4: What relationship to you observe between Age and Info.On.Internet?

Answer: Older age seems moderately associated with a smaller value for Info.On.Internet.

```
plot(jitter(limited$Age), jitter(limited$Info.On.Internet))
```



4.5.1: What is the average Info.On.Internet value for smartphone users?

Answer: 4.367556

4.5.2:

Answer: 2.922807

```
tapply(limited$Info.On.Internet, limited$Smartphone, mean, na.rm = TRUE)
```

```
      0      1  
2.922807 4.367556
```

4.6.1: What proportion of smartphone users who answered the Tried.Masking.Identity question have tried masking their identity when using the Internet?

Answer: 0.1925466

4.6.2: What proportion of non-smartphone users who answered the Tried.Masking.Identity question have tried masking their identity when using the Internet?

Answer: 0.1174377

```
tapply(limited$Tried.Masking.Identity, limited$Smartphone, mean, na.rm = TRUE)
```

	0	1
	0.1174377	0.1925466

And we're done! That was all for Assignment 1!

The Analytics Edge: Assignment 2

The following link will lead you to the assignment on the edX website: <https://learning.edx.org/course/course-v1:MITx+15.071x+2T2020/block-v1:MITx+15.071x+2T2020+type@sequential+block@60d93a44280348d7a0a16663f92af0f7>

Climate Change

There have been many studies documenting that the average global temperature has been increasing over the last century. The consequences of a continued rise in global temperature will be dire. Rising sea levels and an increased frequency of extreme weather events will affect billions of people.

In this problem, we will attempt to study the relationship between average global temperature and several other factors.

The file `climate_change.csv` contains climate data from May 1983 to December 2008.

Start:

We are interested in how changes in these variables affect future temperatures, as well as how well these variables explain temperature changes so far. To do this, first read the dataset `climate_change.csv` into R.

```
climateChange <- read.csv("/cloud/project/analyticsedge/Datasets/DatasetsUnit2/climate_cha
```

Then, split the data into a *training set*, consisting of all the observations up to and including 2006, and a *testing set* consisting of the remaining years (hint: use `subset`). A training set refers to the data that will be used to build the model (this is the data we give to the `lm()` function), and a testing set refers to the data we will use to test our predictive ability.

```
climateTrain <- subset(climateChange, Year <= 2006)
climateTest <- subset(climateChange, Year > 2006)
```

Next, build a linear regression model to predict the dependent variable `Temp`, using `MEI`, `CO2`, `CH4`, `N2O`, `CFC.11`, `CFC.12`, `TSI`, and `Aerosols` as independent variables (`Year` and `Month` should NOT be used in the model). Use the training set to build the model.

```
climateModel1 <- lm(Temp ~ MEI + CO2 + CH4 + N2O + CFC.11 + CFC.12 + TSI + Aerosols, data
```

1.1: What is the model R2 (the “Multiple R-squared” value)?

Answer: 0.7509

1.2: Which variables are significant in the model?

Answer: MEI, CO2, CFC.11, CFC.12, TSI, Aerosols

```
summary(climateModel1)
```

Call:

```
lm(formula = Temp ~ MEI + CO2 + CH4 + N2O + CFC.11 + CFC.12 +  
    TSI + Aerosols, data = climateTrain)
```

Residuals:

	Min	1Q	Median	3Q	Max
	-0.25888	-0.05913	-0.00082	0.05649	0.32433

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)	
(Intercept)	-1.246e+02	1.989e+01	-6.265	1.43e-09	***
MEI	6.421e-02	6.470e-03	9.923	< 2e-16	***
CO2	6.457e-03	2.285e-03	2.826	0.00505	**
CH4	1.240e-04	5.158e-04	0.240	0.81015	
N2O	-1.653e-02	8.565e-03	-1.930	0.05467	.
CFC.11	-6.631e-03	1.626e-03	-4.078	5.96e-05	***
CFC.12	3.808e-03	1.014e-03	3.757	0.00021	***
TSI	9.314e-02	1.475e-02	6.313	1.10e-09	***
Aerosols	-1.538e+00	2.133e-01	-7.210	5.41e-12	***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 0.09171 on 275 degrees of freedom

Multiple R-squared: 0.7509, Adjusted R-squared: 0.7436

F-statistic: 103.6 on 8 and 275 DF, p-value: < 2.2e-16

Current scientific opinion is that nitrous oxide and CFC-11 are greenhouse gases: gases that are able to trap heat from the sun and contribute to the heating of the Earth. However, the regression coefficients of both the N2O and CFC-11 variables are *negative*, indicating that increasing atmospheric concentrations of either of these two compounds is associated with lower global temperatures.

2.1: Which of the following is the simplest correct explanation for this contradiction?

Answer: All of the gas concentration variables reflect human development - N2O and CFC.11 are correlated with other variables in the data set.

2.2.1: Which of the following independent variables is N2O highly correlated with (absolute correlation greater than 0.7)?

Answer: CO2, CH4, CFC.12

2.2.2: Which of the following independent variables is CFC.11 highly correlated with?

Answer: CH4, CFC.12

```
cor(climateTrain)
```

	Year	Month	MEI	CO2	CH4
Year	1.00000000	-0.0279419602	-0.0369876842	0.98274939	0.91565945
Month	-0.02794196	1.0000000000	0.0008846905	-0.10673246	0.01856866
MEI	-0.03698768	0.0008846905	1.0000000000	-0.04114717	-0.03341930
CO2	0.98274939	-0.1067324607	-0.0411471651	1.00000000	0.87727963
CH4	0.91565945	0.0185686624	-0.0334193014	0.87727963	1.00000000
N2O	0.99384523	0.0136315303	-0.0508197755	0.97671982	0.89983864
CFC.11	0.56910643	-0.0131112236	0.0690004387	0.51405975	0.77990402
CFC.12	0.89701166	0.0006751102	0.0082855443	0.85268963	0.96361625
TSI	0.17030201	-0.0346061935	-0.1544919227	0.17742893	0.24552844
Aerosols	-0.34524670	0.0148895406	0.3402377871	-0.35615480	-0.26780919
Temp	0.78679714	-0.0998567411	0.1724707512	0.78852921	0.70325502
	N2O	CFC.11	CFC.12	TSI	Aerosols
Year	0.99384523	0.56910643	0.8970116635	0.17030201	-0.34524670
Month	0.01363153	-0.01311122	0.0006751102	-0.03460619	0.01488954
MEI	-0.05081978	0.06900044	0.0082855443	-0.15449192	0.34023779
CO2	0.97671982	0.51405975	0.8526896272	0.17742893	-0.35615480
CH4	0.89983864	0.77990402	0.9636162478	0.24552844	-0.26780919
N2O	1.00000000	0.52247732	0.8679307757	0.19975668	-0.33705457
CFC.11	0.52247732	1.00000000	0.8689851828	0.27204596	-0.04392120
CFC.12	0.86793078	0.86898518	1.0000000000	0.25530281	-0.22513124
TSI	0.19975668	0.27204596	0.2553028138	1.00000000	0.05211651
Aerosols	-0.33705457	-0.04392120	-0.2251312440	0.05211651	1.00000000
Temp	0.77863893	0.40771029	0.6875575483	0.24338269	-0.38491375
	Temp				
Year	0.78679714				
Month	-0.09985674				
MEI	0.17247075				

```

CO2      0.78852921
CH4      0.70325502
N2O      0.77863893
CFC.11   0.40771029
CFC.12   0.68755755
TSI       0.24338269
Aerosols -0.38491375
Temp     1.00000000

```

Given that the correlations are so high, let us focus on the N2O variable and build a model with only MEI, TSI, Aerosols and N2O as independent variables. Remember to use the training set to build the model.

```
climateModel2 <- lm(Temp ~ MEI + N2O + TSI + Aerosols, data = climateTrain)
```

3.1: What is the coefficient of N2O in this reduced model?

Answer: 2.532e-02 (0.02532)

3.2: What is the model R^2 ?

Answer: 0.7261

```
summary(climateModel2)
```

Call:

```
lm(formula = Temp ~ MEI + N2O + TSI + Aerosols, data = climateTrain)
```

Residuals:

```

      Min       1Q   Median       3Q      Max
-0.27916 -0.05975 -0.00595  0.05672  0.34195

```

Coefficients:

```

              Estimate Std. Error t value Pr(>|t|)
(Intercept) -1.162e+02  2.022e+01  -5.747 2.37e-08 ***
MEI           6.419e-02  6.652e-03   9.649 < 2e-16 ***
N2O           2.532e-02  1.311e-03  19.307 < 2e-16 ***
TSI           7.949e-02  1.487e-02   5.344 1.89e-07 ***
Aerosols     -1.702e+00  2.180e-01  -7.806 1.19e-13 ***
---

```

```
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

Residual standard error: 0.09547 on 279 degrees of freedom

Multiple R-squared: 0.7261, Adjusted R-squared: 0.7222

F-statistic: 184.9 on 4 and 279 DF, p-value: < 2.2e-16

```
climateModel <- step(climateModel1)
```

Start: AIC=-1348.16

Temp ~ MEI + CO2 + CH4 + N2O + CFC.11 + CFC.12 + TSI + Aerosols

	Df	Sum of Sq	RSS	AIC
- CH4	1	0.00049	2.3135	-1350.1
<none>			2.3130	-1348.2
- N2O	1	0.03132	2.3443	-1346.3
- CO2	1	0.06719	2.3802	-1342.0
- CFC.12	1	0.11874	2.4318	-1335.9
- CFC.11	1	0.13986	2.4529	-1333.5
- TSI	1	0.33516	2.6482	-1311.7
- Aerosols	1	0.43727	2.7503	-1301.0
- MEI	1	0.82823	3.1412	-1263.2

Step: AIC=-1350.1

Temp ~ MEI + CO2 + N2O + CFC.11 + CFC.12 + TSI + Aerosols

	Df	Sum of Sq	RSS	AIC
<none>			2.3135	-1350.1
- N2O	1	0.03133	2.3448	-1348.3
- CO2	1	0.06672	2.3802	-1344.0
- CFC.12	1	0.13023	2.4437	-1336.5
- CFC.11	1	0.13938	2.4529	-1335.5
- TSI	1	0.33500	2.6485	-1313.7
- Aerosols	1	0.43987	2.7534	-1302.7
- MEI	1	0.83118	3.1447	-1264.9

4.1: What is the R^2 value of the model produced by the step function?

Answer: 0.7508

4.2: Which of the variable(s) were eliminated from the full model by the step function?

Answer: CH4

```
summary(climateModel)
```


Call:

```
lm(formula = Temp ~ MEI + CO2 + N2O + CFC.11 + CFC.12 + TSI +  
    Aerosols, data = climateTrain)
```

Residuals:

	Min	1Q	Median	3Q	Max
	-0.25770	-0.05994	-0.00104	0.05588	0.32203

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)	
(Intercept)	-1.245e+02	1.985e+01	-6.273	1.37e-09	***
MEI	6.407e-02	6.434e-03	9.958	< 2e-16	***
CO2	6.402e-03	2.269e-03	2.821	0.005129	**
N2O	-1.602e-02	8.287e-03	-1.933	0.054234	.
CFC.11	-6.609e-03	1.621e-03	-4.078	5.95e-05	***
CFC.12	3.868e-03	9.812e-04	3.942	0.000103	***
TSI	9.312e-02	1.473e-02	6.322	1.04e-09	***
Aerosols	-1.540e+00	2.126e-01	-7.244	4.36e-12	***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 0.09155 on 276 degrees of freedom

Multiple R-squared: 0.7508, Adjusted R-squared: 0.7445

F-statistic: 118.8 on 7 and 276 DF, p-value: < 2.2e-16

5: Using the model produced from the step function, calculate temperature predictions for the testing data set, using the predict function. What is the testing set R^2 ?

Answer: 0.6286051

```
predictTemp <- predict(climateModel, newdata = climateTest)
SSE = sum((predictTemp - climateTest$Temp)^2)
SST = sum((mean(climateTrain$Temp) - climateTest$Temp)^2)
R2 = 1 - SSE/SST
R2
```

[1] 0.6286051