BART Toolbox for Computational MRI

- For research use
- Available for Linux, MacOS X, (Windows), ...
- ► BSD license (free for commercial use)
- https://mrirecon.github.io/bart/

Contributors:

Jon Tamir, Christian Holme, Moritz Blumenthal, Nick Scholand, Philip Schaten, ... many more (see ACKNOWLEDGMENTS)

Research Support

American Heart Association Grant 12BGIA9660006, NIH Grant R41RR09784 and Grant R01EB009690, UC Discovery Grant 193037, Sloan Research Fellowship, GE Healthcare, DZHK (German Centre for Cardiovascular Research), and a personal donation from David Donoho's Shaw Prize, NIH Grant U24EB029240-01









Motivation

- Rapid prototyping (similar to Matlab, octave, ...)
- Reproducible research (i.e. scripts to reproduce experiments)
- Robustness and clinically feasible runtime (C/C++, OpenMP, GPU programming)
- Educational tool
- ► Platform for collaboration

Motivation

- Rapid prototyping (similar to Matlab, octave, ...)
- Reproducible research (i.e. scripts to reproduce experiments)
- Robustness and clinically feasible runtime (C/C++, OpenMP, GPU programming)
- Educational tool
- ► Platform for collaboration

Programming library

- ► Consistent API based on multi-dimensional arrays
- ► Fast transforms: FFT, nuFFT, wavelet
- ▶ Generic iterative (matrix-free) algorithms (conjugate gradients, FISTA, IRGNM, ADMM, iPALM, ...)
- ► Composable operators / algorithms
- ► Transparent GPU acceleration of most functions
- ► Neural networks

Command-line tools

- ► Simple file format
- ► Looping, parallelization, streaming
- Interoperability with Matlab, Python
- ▶ Basic operations: fft, resize, slice, . . .
- Sensitivity calibration and image reconstruction

Programming library

- ► Consistent API based on multi-dimensional arrays
- ► Fast transforms: FFT, nuFFT, wavelet
- ▶ Generic iterative (matrix-free) algorithms (conjugate gradients, FISTA, IRGNM, ADMM, iPALM, ...)
- ► Composable operators / algorithms
- ► Transparent GPU acceleration of most functions
- ► Neural networks

Command-line tools

- ► Simple file format
- ► Looping, parallelization, streaming
- ► Interoperability with Matlab, Python
- ▶ Basic operations: fft, resize, slice, . . .
- Sensitivity calibration and image reconstruction

Generic Tools		MRI Tools	
fft slice extract resize flip join zeros/ones circshift conv scale conj fmac saxpy sdot rss repmat	extract slice extract block crop / zeropad reverse dimensions merge files create files circular shift convolution scale complex ocnjugate fused multiply-add scalar mult. and add dot product root-sum-of-squares repmat	cc walsh caldir ecalib ncalib pics moba nlinv nufft pocsense fovshift pattern poisson signal	channel compression Walsh method Direct calibration ESPIRiT calibration non-linear calibration ℓ_1 -SENSE/ESPIRiT model-based recon non-linear inversion non-uniform FFT POCSENSE Retrospectively shift FO extract pattern Poisson-disc pattern create signal curves
svd	singular-value d.	Low field?	

Generic Tools		MRI Tools	
fft slice extract resize flip join zeros/ones circshift conv scale conj fmac saxpy sdot rss repmat	FFT extract slice extract slice extract block crop / zeropad reverse dimensions merge files create files circular shift convolution scale complex ocnjugate fused multiply-add scalar mult. and add dot product root-sum-of-squares repmat	cc walsh caldir ecalib ncalib pics moba nlinv nufft pocsense fovshift pattern poisson signal	channel compression Walsh method Direct calibration ESPIRiT calibration non-linear calibration ℓ₁-SENSE/ESPIRiT model-based recon non-linear inversion non-uniform FFT POCSENSE Retrospectively shift FO' extract pattern Poisson-disc pattern create signal curves
svd	singular-value d.	Low field?	

pics: Parallel Imaging Compressed Sensing

> bart pics -RA:B:C:D -R ... [-t trj] [-B basis] kspace sens image

- parallel imaging and compressed sensing
- non-Cartesian k-space trajectories
- subspace reconstruction
- multiple regularization terms
- A: different types of regularization: ℓ_2 , ℓ_1 , total variation, ℓ_1 -wavelet, (multi-scale) low-rank
- ► B: transforms along arbitrary dimensions (space, time, etc.)
- C: joint-thresholding along arbitrary dimensions
- D: regularization parameter

Note: Depending on the algorithm additional parameters (step size, number of iterations, etc.) must be set for optimal results.

moba: Model-Based Reconstruction

- > bart moba model -r ... [-t trj] kspace enc output [sens]
 - ▶ signal model $(T_1, T_2, T_2^{\star}, T_2^{\star} + \delta B_0, Bloch)$
 - parallel imaging and compressed sensing
 - non-Cartesian k-space trajectories
 - ► A, B, C, D: regularization

Note: Depending on the algorithm additional parameters (step size, number of iterations, etc.) must be set for optimal results.

Resources

- 1. README, doc/
- 2. Website: https://mrirecon.github.io/bart
- 3. Source code: https://github.com/mrirecon/bart
- 4. Mailing list with public archive (see website)
- 5. Workshops: https://github.com/mrirecon/bart-workshop
- 6. Webinars: https://github.com/mrirecon/bart-webinars
- 7. Help: Each command has '-h' option for a very brief help.

Resources

- 1. README, doc/
- 2. Website: https://mrirecon.github.io/bart
- 3. Source code: https://github.com/mrirecon/bart
- 4. Mailing list with public archive (see website)
- 5. Workshops: https://github.com/mrirecon/bart-workshop
- 6. Webinars: https://github.com/mrirecon/bart-webinars
- 7. Help: Each command has '-h' option for a very brief help.

Educational Track 2 (ET2): Reconstruction of Images and Parameter Maps

```
https:
```

```
//github.com/mritogether/ESMRMB2024_Hardware_to_Map
```

Schedule

- ► Image Reconstruction: Compressed Sensing, Model-Based Reconstruction, Machine Learning (Efrat Shimron)
- ► Introduction to the BART Toolbox (Martin Uecker)
- Parameter Mapping for Low-Field MRI (Julia Pfitzer)

Literature

Model-based reconstruction for T_2 mapping:

- Block, Uecker, Frahm. Model-based Iterative Reconstruction for Radial Fast Spin-Echo MRI. IEEE TMI 2009;28:1759-1769.
- ► Sumpf et al. Model-based Nonlinear Inverse Reconstruction for T2 Mapping Using Highly Undersampled Spin-Echo MRI. JMRI 2011;34:420-428. MARTINI (⇒ GRAPPATINI)
- Sumpf, Petrovic, Uecker, Knoll, Frahm. Fast T2 Mapping with Improved Accuracy Using Undersampled Spin-echo MRI and Model-based Reconstructions with a Generating Function. IEEE Transactions on Medical Imaging 2014;33:2213-2222. stimulated echos!
- ► Tamir et al. T2 Shuffling: Sharp, Multicontrast, Volumetric Fast Spin-Echo Imaging. MRM 2017;77:180-195 subspace
- Wang et al. Physics-based Reconstruction Methods for Magnetic Resonance Imaging. Philosophical Transactions of the Royal Society A. 2021;379:20200196. review with BART code!
- Scholand et al. Quantitative Magnetic Resonance Imaging by Nonlinear Inversion of the Bloch Equations. Magnetic Resonance in Medicine 2023;90:520-538. generic Bloch model, BART