Instalasi dan Konfigurasi DHCP Server Pada Debian 6 squeeze

1. Ketik **apt-get install dhcp3-server**. Kemudian enter.

```
root@mrizqiariadi:~# apt-get install dhcp3-server -y_
```

3. ketik **nano /etc/default/isc-dhcp-server**. Kemudian tekan enter.

```
 dhcp3-server isc-dhcp-server
0 upgraded, 2 newly installed, 0 to remove and 0 not upgraded.
Need to get 0 B/404 kB of archives.
After this operation, 954 kB of additional disk space will be used.
0% [Working]
Media change: please insert the disc labeled
 'Debian GNU/Linux 6.0.6 _Squeeze_ - Official i386 DVD Binary-1 20120929-15:56'
in the drive '/media/cdrom/' and press enter
0% [Working]
Prakonfigurasi paket ...
Memilih paket isc-dhcp-server yang sebelumnya tidak dipilih.
(Sedang membaca basis data ... 22440 berkas atau direktori telah terpasang.)
Sedang membuka paket isc-dhcp-server (dari .../isc-dhcp-server_4.1.1-P1-15+squee
ze6_i386.deb) ...
Memilih paket dhcp3-server yang sebelumnya tidak dipilih.
Sedang membuka paket dhcp3-server (dari .../dhcp3-server_4.1.1-P1-15+squeeze6_al
l.deb) ...
Sedang memproses pemicu untuk man-db ...
Sedang menata isc-dhcp-server (4.1.1-P1-15+squeeze6) ...
Generating /etc/default/isc-dhcp-server...
Starting ISC DHCP server: dhcpdcheck syslog for diagnostics. ... failed!
 failed!
invoke-rc.d: initscript isc-dhcp-server, action "start" failed.
Sedang menata dhcp3-server (4.1.1-P1-15+squeeze6) ...
root@mrizqiariadi:~# nano /etc/default/isc-dhcp-server _
```

4. Ketik **eth0** seperti pada gambar. Kemudian save dengan menekan **Ctrl+X**. Kemudian tekan **Y** dan enter.

5. Ketik perintah **nano /etc/dhcp/dhcpd.conf**. Kemudian tekan enter.

6. Hilangkan tanda pagar dan edit seperti pada gambar. Kemudian save dengan menekan **Ctrl+X**. Kemudian tekan **Y** dan enter.

7. Kemudian restart DHCP Server dengan mengetik **Service isc-dhcp-server restart**. Kemudian enter.

```
# A slightly different configuration for an internal subnet.
subnet 192.168.10.0 netmask 255.255.255.0 {
  range 192.168.10.2 192.168.10.22;
  option domain-name-servers 192.168.10.1;
  option domain-name "itservice-01.co.id";
  option routers 192.168.10.1;
  option broadcast-address 192.168.10.255;
  default-lease-time 600;
  max-lease-time 7200;
}

# Hosts which require special configuration options can be listed in
# host statements.   If no address is specified, the address will be
# allocated dynamically (if possible), but the host-specific information
# will still come from the host declaration.

#host passacaglia {
#   hardware ethernet 0:0:c0:5d:bd:95;
#   filename "vmunix.passacaglia";
                          [ Wrote 107 lines ]

root@mrizqiariadi:~# service isc-dhcp-server restart
Stopping ISC DHCP server: dhcpd failed!
Starting ISC DHCP server: dhcpd.
root@mrizqiariadi:~# service isc-dhcp-server restart _
```