Machine learning for gravitational-wave detector data: a literature review catalogue for the gravyflow model zoo

Michael Norman

Status: **Work in progress** October 2026

Abstract. We catalogue 313 machine-learning models for gravitational-wave detector data, 138 from the first catalogue (seeded by a thesis literature review) and 175 added by completeness sweeps, and extract 3160 reported metrics from the papers, 676 of them read from figures. For each model we place its headline results on a small set of comparison axes that the literature supports: efficiency at a false-alarm rate normalised per month and in hertz, sensitive distance or volume at a false-alarm rate, Gravity Spy accuracy and macro-F1 with the dataset release, waveform overlap for denoisers, calibration and bias for parameter estimation, and sensitivity depth for continuous waves. Only 26 models are directly comparable on a shared contract and 79 more conditionally; 208 report metrics that cannot be placed on a shared axis. We list 381 suspected errors or internal inconsistencies across 228 papers, record which models release code (106) and trained weights (29), and set out the programme for reproducing these models in gravyflow. Every model carries a placeholder for our reproduction, which is pending.

Contents

1 Scope and method 2
2 A short history and taxonomy 2
3 Compact-binary detection 3
4 Early warning 10
5 Burst and unmodelled transients 12
6 Anomaly and multi-signal detection 15
7 Continuous and long-duration waves 16
8 Glitch classification and data quality 18
9 Denoising and signal extraction 21
10 Parameter estimation 23
11 Space-based detectors 26
12 Other: alerts, generators, lensing, backgrounds 27
13 Code and reproducibility 28
14 Reproduction programme in gravyflow 32
15 Open questions 38
References 39

1 Scope and method

Sources. The starting point was the literature review of the owner's thesis, which contributed 46 of the original 138 entries; arXiv and web searches completed the first catalogue. The completeness sweeps then proposed 186 further papers. Four were dropped at the sweep (a review, a population-level classifier, a likely duplicate and an ID fix); of the remaining 182, 175 are kept and 7 are dropped here because they do not train on or apply to gravitational-wave detector data (Table 2). Duplicates in the first catalogue had been merged before.

Metric extraction. Each paper was read by an extraction agent from its PDF, with figures rendered as page images. For every reported metric the agent recorded the value, units, the conditions under which it was measured (noise, population, SNR range, test-set size), its location in the paper (table, figure or section) and whether it was stated in the text or read from a figure; read-from-figure values carry the reading uncertainty noted in the catalogue. The agents also recorded code repositories (checked on the hosting site for licence, last commit and trained weights) and every internal inconsistency they found, with its evidence.

Grading. The synthesiser then placed the headline metrics of each paper on the shared axes of Table 1, converted false-alarm rates to per month (30-day months, the MLGWSC-1 convention) and to hertz where the paper states a rate or a fraction over disjoint segments of stated length, and graded each model comparable, conditionally comparable or not comparable, saying what differs. Suspected errors highlighted in this review are a selection of the extracted inconsistencies, stated neutrally; they are reading notes, not verdicts, and each should be checked against the paper before it is relied on. All 381 extracted notes are kept in the machine-readable catalogue.

Archive. PDFs were downloaded from arXiv only; 276 of the 313 models have a paper in the private archive. The remaining 37 have no arXiv version: their dossiers rest on the publisher's or INSPIRE's abstract page, and they are marked as such. The archive is private and is not redistributed.

Numbers. Every number in the tables is the paper's, located by table, figure or section; "read-from-figure" marks values read from a plot. No value was invented or interpolated by the synthesiser beyond the unit conversions stated.

Table 1. Comparison axes and grades used throughout.

Axis	Meaning
eff@FAR	Detection efficiency (TPR) at a FAR that is a rate per unit time; far_hz and far_per_month given.
FAR@eff	FAR at fixed efficiency.
reach@FAR	Sensitive distance or volume (or hrss50 for bursts) at a stated FAR; the search-grade comparison.
eff@FAP	TPR at a per-window or per-sample false-alarm probability: not a rate; comparable only with the same window length, noise and SNR distribution.
AUC	Area under ROC; quoted only where noise and SNR distribution are stated, otherwise noted as such.
GS	Glitch classification on a Gravity Spy release: accuracy and macro-F1 with release, class count and split.
overlap	Denoising/extraction: overlap or match with the injected waveform.
range	Noise regression: BNS inspiral-range or VT gain on real data.
PE	Parameter estimation: calibration (P-P / coverage), bias or JSD against a sampler, sampling efficiency.
depth@pfa	Continuous waves: sensitivity depth at a false-alarm probability per frequency band.
events	Real catalogue events recovered (supplementary; never a substitute for efficiency at FAR).
other	A headline metric outside the shared axes.
comparable	Same contract as a published reference (MLGWSC-1, LVK injection sets, Gravity Spy split with re-trained baselines, CW depth at pfa), so numbers can be set side by side.
conditional	On a shared axis but with a stated difference (noise, population, detector count, dataset release, relative-only gain).
not comparable	No shared axis: per-window fractions, private toy sets, qualitative or unread.

Table 2. Added models dropped because they are not trained on or applied to gravitational-wave detector data.

Key	arXiv	Reason (dossier)
badaracco2020	2005.09289	Not applied to GW strain (uses seismic correlations; Virgo is not NN-limited so C_NN is modelled, not measured); one hour of data; universality of c(N)=a(1-1/bN) is unexplained; no real cancellation test.
baltus2022light	none	Thesis body not read. The ML content is a compilation of Baltus et al. 2021 (PRD 103, 102003; baltus2021), the CBMI 2021 paper (baltus2021b), Baltus et al. 2022 (PRD 106, 042002; baltus2022), plus a sub-solar-mass matched-filter search and a sky-localisation chapter whose papers are not in the catal
boudart2023	none	Thesis body not read. Its ML chapters correspond to catalogue entries boudart2022 (ALBUS, arXiv 2201.08727) and boudart2022glitch (arXiv 2210.04588).
khan2021	2112.07669	Trained and tested on noiseless NRHybSur3dq8 surrogate waveforms; no detector noise or detector data is used anywhere (PyCBC comparison uses a flat PSD only to set the likelihood). It is a waveform-manifold regression study. Flagged for the owner: keep only as a noise-free PE reference, not as a ...
mitra2023	2310.15649	No detector noise, no SNR/distance dependence, no detection stage; axisymmetric sims lack realistic prompt convection; one progenitor; classification of EOS labels not regression. Not an ML-on-detector-data model: the network is trained and tested on noise-free simulated waveforms, so is_ml_on_gw_de
puecher2024	2408.10678	Trained on NR simulation parameters, not on detector data; classifier outputs depend on NR physics and EoS coverage (authors state this is the dominant uncertainty).
whittaker2022	2201.06461	Not applied to detector data, noise, detection or parameter inference; the proof of principle is on a synthetic generator derived from the same 123 fits.

2 A short history and taxonomy

Detection on whitened windows (2017-2019). Two groups showed in 2017-2018 that a small convolutional network on one-second windows of whitened strain can approach matched-filter sensitivity for binary black holes at fixed per-window false-alarm probabilities [1], [2], and that the same networks run on real O1 noise [3]. A critique followed: per-window fractions are not search false-alarm rates, and networks must be judged on continuous data [4].

Search-grade evaluation (2020-2022). Schafer et al. reported sensitive distance against false-alarm rate on months of continuous simulated data and studied training strategies that keep the network usable at low false-alarm rates [5], [6], [7]. MLGWSC-1 made this contract a benchmark with four datasets, the last on real O3a noise, and found that the best entries came close to PyCBC on simulated noise but fell further behind on real noise [8].

Production searches (2023-2026). Networks then ran over full observing runs with time-slide backgrounds and the LVK injection campaigns: Aframe and its BNS extension [9], [10], [11], AresGW and Sage on MLGWSC-1 and O3 [12], [13], [14], SNR-series networks [15], [16] and anomaly pipelines [17]. Machine learning inside cWB followed a parallel route for bursts [18], [19].

Glitches, denoising and inference. Gravity Spy set the image format and labels for glitch classification [20], [21], later extended to O3 [22], [23]. Denoising began with recurrent autoencoders [24] and noise regression from witness channels [25]. Inference moved from point regressors to normalising-flow posteriors validated against samplers on real events [26], [27], [28].

Taxonomy. We organise the catalogue by task (compact-binary detection, early warning, bursts, anomalies, continuous waves, glitches, denoising, parameter estimation, space-based detectors, other) and, within each task, by family. A second axis cuts across tasks: the input representation (whitened strain, time-frequency images, matched-filter SNR series, pipeline triggers or alert products, auxiliary witness channels). The representation determines most of the adaptation work in gravyflow (Section Section 14).

Table 3. Models per section, with grades.

Section	Models	Added	Comparable	Conditional	Not comparable
Compact-binary detection	92	40	12	24	56
Early warning	9	3	0	3	6
Burst and unmodelled transients	33	12	5	10	18
Anomaly and multi-signal detection	11	7	2	1	8
Continuous and long-duration waves	18	14	5	5	8
Glitch classification and data quality	56	32	0	14	42
Denoising and signal extraction	32	19	0	13	19
Parameter estimation	33	28	2	9	22
Space-based detectors	14	12	0	0	14
Other: alerts, generators, lensing, backgrounds	15	8	0	0	15

3 Compact-binary detection

Compact-binary coalescence (CBC) detection is the largest category. The early papers asked whether a network could match matched filtering on short whitened windows of simulated noise; the later ones ask whether a network-based search, run over months of real data with a measured background, reaches the sensitive distance of the production pipelines. Only the second kind of result can be compared across papers.

3.1 Families and lineage

3.1.1 Deep Filtering and 1D classifiers on whitened strain

The first wave fed one-second windows of whitened strain to small 1D networks and compared them with matched filtering at fixed per-window false-alarm probabilities [1], [2] real O1 noise and two-detector coincidence followed [3], [29]. Later work varied the waveform space (binary neutron stars, [30], [31] precession, [32] eccentricity and higher modes, [33]), the architecture or training [34], [35], [36], and the output (Bayesian networks, [37] ensembles, [38] four classes, [39]).

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 37 models: [29], [2], [1], [3], [33], [40], [41], [42], [43], [44], [45], [35], [30], [46], [47], [48], [31], [37], [49], [34], [50], [51], [52], [38], [53], [39], [32], [54], [55], [56], [57], [58], [36], [59], [60], [61], [62]. Results will be placed on the shared axes of this section beside the published values.

3.1.2 Per-timestep (WaveNet) ensembles

Gebhard et al. argued that a detector must run on continuous data and be judged by its false positives per unit time [4]. The WaveNet-style ensembles of Huerta, Wei and collaborators label each time step and add coincidence across models and detectors [63], [64], [65], later with higher modes and graph layers [66], [67].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 7 models: [4], [68], [64], [63], [65], [66], [67]. Results will be placed on the shared axes of this section beside the published values.

3.1.3 Search-grade evaluation and the MLGWSC-1 benchmark

Schafer et al. measured sensitive distance against FAR on continuous simulated data [5], [6], [7], and the first Machine Learning Gravitational-Wave Search Mock Data Challenge (MLGWSC-1) fixed that contract for four datasets, the last on real O3a noise [8]. Entries and successors on the same datasets include AresGW [12], [13], the updated TPI FSU Jena search [69], Sage [14], a matched-filter hybrid [70] and the transformer pipelines GW-Whisper and CASTOR [71], [72].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 10 models: [5], [6], [7], [8], [12], [13], [69], [14], [70], [72]. Results will be placed on the shared axes of this section beside the published values.

3.1.4 Production-style searches on observing-run data

Aframe brought a 1D ResNet to real-time and offline O3 searches with year-long time-slide backgrounds and the LVK injection sets [9], [10], and was extended to binary neutron stars [11]. Other O3 searches with measured backgrounds include Q-transform ResNets [73], [74], [75], SNR-series networks [15], [16], [76], and lightweight or alternative-physics detectors [77], [78], [79], [80], [81].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 15 models: [73], [82], [74], [76], [80], [81], [9], [75], [15], [10], [16], [78], [77], [79], [11]. Results will be placed on the shared axes of this section beside the published values.

3.1.5 Matched-filter front ends

A template bank inside or in front of the network: learnable template layers [83], [84], matched filtering after denoising [85], SNR-map classifiers [86], and overlap statistics against reconstructed signals [87].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 6 models: [83], [84], [85], [87], [88], [86]. Results will be placed on the shared axes of this section beside the published values.

3.1.6 Time-frequency images

Spectrogram or Q-transform images fed to image backbones, often ImageNet-pretrained [89], [90], [91], [92], including Einstein Telescope studies [93], [94].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 11 models: [89], [95], [96], [97], [93], [90], [94], [98], [92], [91], [99]. Results will be placed on the shared axes of this section beside the published values.

3.1.7 Re-ranking inside existing pipelines

Classifiers or density estimators that re-rank the triggers of GstLAL, PyCBC or GRB-triggered searches rather than read strain [100], [101], [102], [103], [104], [105].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 6 models: [100], [101], [102], [103], [105], [104]. Results will be placed on the shared axes of this section beside the published values.

3.2 Comparison on the shared axes

Rows are the models graded comparable or conditionally comparable (36 of 92); each axis entry is one row. FAR is converted to per month (30 d) and to Hz where the paper states a rate.

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
`gabbard2018` [2]	eff@FAP	CNN vs matched filter TPR at FAP 0.1, rho_opt 4: ~0.44 vs ~0.31; at FAP 1e-3, rho_opt 6: ~0.49 (both) (Fig 3; read-from-figure)	-	conditional Per-SNR balanced test sets of 1 s windows in Gaussian aLIGO-design noise, non-spinning BBH; FAP is per window, so no rate. The paired matched-filter curve on identical data is the paper's comparison.	*pending*
`bresten2019` [40]	AUC	mixed-SNR (2.1-18) test: raw CNN 0.50, TDA 0.76, raw+TDA 0.79 (Fig 4; stated)	-	conditional White (uncoloured) Gaussian noise with a stated SNR range; AUC comparable only to other white-noise toy studies.	*pending*
`gebhard2019` [4]	eff@FAR	~89 % of injections (SNR 5-20) at one false positive per 19.5 min (Sec VII A; stated)	2.22e+03 /month; 0.000855 Hz	conditional Real O1 noise, clustered triggers on continuous data: a true rate, but at ~2.2e3 per month and over a uniform-SNR injection set rather than a population.	*pending*

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
	events	all GWTC-1 events except GW170817 (Sec VII C; stated)	-		*pending*
`jadhav2020` [102]	reach@FAR	VT ratio MLStat/base 1.32 / 1.27 / 1.30 / 1.29 at IFAR 0.1 / 1 / 10 / 100 yr (chirp mass 5-50 Msun) (Fig 3 bottom; read-from-figure)	0.0821 /month; 3.17e-08 Hz	conditional PyCBC re-ranking with a glitch classifier on O1/O2 chunks; VT ratios relative to the base statistic.	*pending*
	events	GW151012 IFAR 5.84 to 218.1 yr; GW170729 0.73 to 55.8 yr (Sec IV; stated)	-		*pending*
`schafer2020` [5]	reach@FAR	sensitive distance ~130 Mpc at 10 per month (BNS); PyCBC Live reconstructed ~245 Mpc at 0.5 per month (Abstract, Sec V, Fig 4; stated)	10 /month; 3.86e-06 Hz	comparable Continuous ~101 d of Gaussian aLIGO-design H1+L1 data with BNS injections, sensitive distance vs FAR: the template for the later MLGWSC-1 metric. Gaussian noise only.	*pending*
`menendezvazquez2021` [73]	eff@FAR	L1-H1 SNR for 50 / 80 / 99 % efficiency: 11 / 12 / 19 (low mass), 5 / 6 / 7 (high mass) at ~25 false positives per day (Table III; stated)	750 /month; 0.000289 Hz	conditional Threshold set for ~25 false positives per day on a test set; the real O2 scan gives 34-180 per day, so the rate is nominal.	*pending*
	events	8 of 11 O1-O2 catalogue events (Table IV; stated)	-		*pending*
`schafer2021a` [6]	reach@FAR	sensitive distance ~2150 Mpc vs matched filter ~2340 Mpc at 1 per month (single detector, BBH 10-50 Msun) (Sec IV A, Fig 5; stated)	1 /month; 3.86e-07 Hz	conditional Single detector, Gaussian design noise, with a matched-filter baseline on the same data; sensitive distance at a true FAR. Distances differ from MLGWSC-1 by detector count and population.	*pending*
	eff@FAP	efficiency 0.90-0.94 at SNR 9, FAP 1e-4 (Sec IV B; stated)	-		*pending*
`schafer2021b` [7]	reach@FAR	two-detector coincidence retains 92.4 % of the time-coincident matched-filter distance down to ~4e-4 per month; ~2200 Mpc at 4e-4/month (Sec II H, Fig 2; stated (ratio); read-from-figure (distance))	0.0004 /month; 1.54e-10 Hz	conditional Gaussian design noise, H1+L1, ~200 yr time-shift background; ML and matched filter on the same data.	*pending*
`wei2021ensemble` [63]	eff@FAR	no efficiency; 3 false positives in 200 h of August 2017 H1+L1 data (~1 per 2.7 d) (Abstract, Sec IV; stated)	10.8 /month; 4.17e-06 Hz	conditional A true FAR on real data but with no injection campaign, so no efficiency to pair it with.	*pending*
	events	GW170104, 0729, 0809, 0814, 0817, 0818, 0823, GW190412 (0608 and 190521 after fine-tuning) (Figs 4, 7; stated)	-		*pending*
`xia2021` [34]	AUC	ConvNet5 0.91 vs basic 0.86 (SNR 7-7.5); 0.98 vs 0.96 (SNR 7-15) (Table IV; stated)	-	conditional Gaussian noise, stated SNR ranges, 500-sample test sets (AUC uncertainty ~0.01-0.02).	*pending*
`andrews2022` [82]	eff@FAP	TAP ~0.86 at 3 sigma (FAP 1.3e-3) and ~0.81 at 4 sigma, H1+L1, real O1 noise (Fig 3 left; read-from-figure)	-	conditional Real O1 noise with a BBH injection population, but FAP is a fraction of background windows without time slides.	*pending*
`mcisaac2022` [103]	reach@FAR	VT gain of the tuned chi^2 at FAR 1/yr: ~4 % (100-300 Msun) to ~11 % (300-600 Msun); band labels +2 to +17 % (Fig 5, Sec V; stated)	0.0821 /month; 3.17e-08 Hz	conditional Relative VT gain inside a PyCBC IMBH search on 8 held-out days.	*pending*
`mlgwsc2022` [8]	reach@FAR	DS4 (real O3a): PyCBC 1544, Virgo-AUTh 1092, MFCNN 650, CNN-Coinc 0, TPI 0 Mpc at 1/month (Table IV; stated)	1 /month; 3.86e-07 Hz	comparable The reference contract: one month of H1+L1 test data per dataset, IMRPhenomXPHM injections, FAR per month from injection-free background, chirp-distance-weighted sensitive distance.	*pending*
	reach@FAR	DS1 (Gaussian): PyCBC 2492, TPI 2363, AUTh 2116 Mpc at 1/month (Table IV; stated)	1 /month; 3.86e-07 Hz		*pending*
`andrescarcasona2023` [74]	eff@FAR	network SNR for 80 / 90 / 95 % efficiency, H1-L1-V1: 17.3 / 21.1 / 25.8 (Table IV; stated)	-	conditional Real O3 search with time-slide FAR down to 1/152.6 yr, but the threshold behind Table IV is not clearly stated.	*pending*
	other	O3 merger-rate upper limits 560 to 3e6 Gpc^-3 yr^-1 (asymmetric, sub-solar) (Sec IV; stated)	-		*pending*
`beveridge2023` [76]	eff@FAR	TPR ~0.17 / ~0.48 at network SNR 8 / 10 at 1 per 2 months (1.9e-7 Hz) (Fig 8; read-from-figure)	0.5 /month; 1.93e-07 Hz	conditional Simulated coloured Gaussian noise with simulated glitches; a true FAR from 6e6 s of background, but the alert threshold lies in the extrapolated tail.	*pending*
	eff@FAR	34 % of 10,000 GWTC-3-like injections at FAR < 1 per 2 months (Sec III B 1; stated)	0.5 /month; 1.93e-07 Hz		*pending*
`jadhav2023` [80]	reach@FAR	sensitive distance at 1/month on 8.8 d of O3: 140 / 996 / 2173 Mpc for chirp mass 1-10 / 10-40 / 40-80 Msun (Sec VI B, Fig 16; stated)	1 /month; 3.86e-07 Hz	conditional Real O3 data with injections and a sensitive distance at a true FAR, but mass bins and the distance definition differ from MLGWSC-1.	*pending*
	AUC	CBC vs PyCBC background triggers 0.976 (0.989 after GAN training) (Fig 14b; stated)	-		*pending*
	events	GW190519 and GW190521_074359 at FAR < 1/20,350 yr (Sec VI; stated)	-		*pending*
`nousi2022` [12]	reach@FAR	MLGWSC-1 DS4: ~1575 Mpc at 1/month (PyCBC ~1540, cWB ~1255 on the same figure) (Fig 10; read-from-figure)	1 /month; 3.86e-07 Hz	comparable MLGWSC-1 DS4 with the challenge evaluation: directly comparable with the challenge entries.	*pending*
`tian2023` [66]	eff@FAR	TPR ~0.97 at SNR 8.4 and ~0.55-0.65 at SNR 6.2 for 2-3 false positives per year (coloured Gaussian HLV, O4/O5 PSDs) (Fig 2, Table 1; read-from-figure)	0.246 /month; 9.51e-08 Hz	conditional A year of synthetic coloured Gaussian HLV noise: a FAR, but for Gaussian noise only.	*pending*
`tian2024gnn` [67]	AUC	ROC AUC 0.982 / 0.973 / 0.965 (2 / 3 / 4 models) at network SNR 8.4 (Table 1; stated)	-	conditional Decade of synthetic coloured Gaussian noise; the real-data month is a tuned ensemble with manual vetting.	*pending*
	eff@FAR	TPR 0.45 / 0.33 / 0.27 at SNR 6.2 for 7 / 3 / 2 false positives per decade (synthetic HLV) (Fig 1 insets; read-from-figure)	0.0246 /month; 9.51e-09 Hz		*pending*

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
`trovato2023` [81]	eff@FAR	efficiency at FAR 1e-5 Hz: TCN/IT 0.49 / 0.75 / 0.91 at SNR 9.5 / 11.5 / 14.5; CNN 0.43 / 0.68 / 0.85 (Fig 5; read-from-figure)	25.9 /month; 1e-05 Hz	conditional Single-detector L1 O1 test segments; FAR is the test-set false-alarm count per second of segments, not time slides; model selected on the test set.	*pending*
	eff@FAR	TCN ~0.76 at 1e-6 Hz (averaged over SNR 8-20) (Fig 4; read-from-figure)	2.59 /month; 1e-06 Hz		*pending*
`badger2024` [87]	eff@FAR	overlap statistic TPR ~0.06 vs matched filter ~0.22 at 12/yr (astrophysical population, simulated A+ Gaussian, single detector) (Fig 4; read-from-figure)	0.986 /month; 3.8e-07 Hz	conditional Single-detector simulated A+ noise with FAR from one month of noise; a paired matched-filter baseline on the same injections.	*pending*
`koloniari2024` [13]	events	34 of 43 published O3 events in range at p_astro > 0.5; 28 at FAR < 1/yr; 8 new candidates (Sec VI A, Tables I, III; stated)	-	conditional Real O3 search with a 10 yr time-shifted background but no injection-based sensitivity: events recovered is the only efficiency.	*pending*
`marx2024` [9]	reach@FAR	sensitive volume at 1/yr: Aframe ~10.3 vs PyCBC-BBH ~9.7, GstLAL ~9.8 Gpc^3 (35+35 Msun); 20+10 Msun: ~0.7 vs ~1.55 (Fig 4; read-from-figure)	0.0821 /month; 3.17e-08 Hz	comparable O3 data with a year of time slides and the GWTC-3 pipelines' public injection sets: comparable with the LVK searches on sensitive volume at FAR.	*pending*
	events	9 of 9 GWTC-3 candidates in the test period (Table IV; stated)	-		*pending*
`menendez2024` [75]	eff@FAR	network SNR for 50 / 80 / 99 % efficiency at 1/week: 10 / 12 / 20 (high mass), 20 / 24 / 39 (low mass) (Table 2; stated)	4.29 /month; 1.65e-06 Hz	conditional Real O3 HLV data with time-slide FAR down to 1/152.6 yr; efficiency in network SNR rather than distance.	*pending*
	events	26 of 50 three-detector O3 events at 1/week (22 of 31 in range) (Sec 5; stated)	-		*pending*
`wang2023tf` [91]	reach@FAR	U-Net sensitive distance ~230 Mpc at 1/month, ~950 at 100/month (own O3a time-shifted background) (Fig 4; read-from-figure)	1 /month; 3.86e-07 Hz	conditional Sensitive distance in the MLGWSC-1 style but on 32.5 d of its own background from 10 shifts of 3.25 d, and MLGWSC-1 curves are overplotted from a different data set.	*pending*
	events	all O1/O2 BBH and 59 of 73 O3 BBH (union over detectors) (Sec III C; stated)	-		*pending*
`zelenka2024` [69]	reach@FAR	MLGWSC-1 DS4: updated TPI FSU Jena 1316 Mpc at 1/month (original submission 0) (Sec IV C 2, Fig 4; stated)	1 /month; 3.86e-07 Hz	comparable MLGWSC-1 DS4 with the challenge evaluation, but the update is selected as the best of six runs on the real-noise test data.	*pending*
`beveridge2025o3` [15]	reach@FAR	sensitive hyper-volume per mass pair vs GWTC-3 pipelines on 83,815 O3 injections (p_astro >= 0.5, FAR < 2/day): comparable above chirp mass ~25 Msun, lower below (Table I, Fig 5; stated)	60 /month; 2.31e-05 Hz	comparable Real O3 data with the GWTC-3 injection campaign and the LVK detection criterion: search-grade.	*pending*
	events	2,916 of 10,472 week-4/6/8 injections at FAR < 1 per 2 months (PyCBC-BBH 3,751) (Table III; stated)	0.5 /month; 1.93e-07 Hz		*pending*
`marx2025aframeO3` [10]	reach@FAR	sensitive volume at 1/yr, 35+35 Msun: Aframe ~10.8 vs GstLAL ~9.8, PyCBC-BBH ~9.5 Gpc^3; 35+20: ~4.8 vs ~5.8 / ~5.6 (Fig 2; read-from-figure)	0.0821 /month; 3.17e-08 Hz	comparable Offline O3 search over 202.4 d against GWTC-3 pipeline curves for the same four mass distributions.	*pending*
`mcleod2025` [16]	reach@FAR	BNS sensitive distance ~172 Mpc at 1 per 2 months (PyCBC ~175, MBTA ~172, GstLAL ~163) on the GWTC-3 O3 week-4 injections (Fig 7; read-from-figure)	0.5 /month; 1.93e-07 Hz	comparable Real O3 noise and the official GWTC-3 BNS injection set: directly comparable with the LVK pipelines on that set.	*pending*
	eff@FAR	34 % of 2,800 BNS injections at FAR < 1 per 2 months (Sec V A; stated)	0.5 /month; 1.93e-07 Hz		*pending*
`nagarajan2025` [14]	reach@FAR	MLGWSC-1 DS4: Sage-Broad 1638 Mpc at 1/month vs PyCBC 1539, AresGW 1574, Aframe 1441 (Table V; stated)	1 /month; 3.86e-07 Hz	comparable MLGWSC-1 DS4 with the challenge evaluation; best-of-three seeds reported.	*pending*
`tiki2025` [77]	reach@FAR	median sensitive volume 5.4 Gpc^3 at median FAR 20.5/yr; 4.6 Gpc^3 at the zero-FP threshold (O3b, 10,000 BBH) (Abstract, Sec 3; stated)	1.68 /month; 6.5e-07 Hz	conditional Real O3 noise with shifted-noise FAR and a fixed BBH population; population and FAR definition differ from MLGWSC-1 and Aframe.	*pending*
	events	8-9 of 13 O3b GWTC-3 events, 0-1 false triggers in 22.7 d (Sec 3; stated)	-		*pending*
`wang2025exotic` [79]	reach@FAR	sensitive distance ~750 Mpc at 10/yr (GR injections), real O1 noise, 4-day test (Fig 6; read-from-figure)	0.821 /month; 3.17e-07 Hz	conditional Volume-averaged distance in the MLGWSC-1 style but on a narrow chirp-mass and mass-ratio window and 21 d of background.	*pending*
`yamamoto2025` [70]	reach@FAR	MLGWSC-1 DS1: 2428 Mpc at 1/month (PyCBC 2492), 2743 at 100/month (PyCBC 2687) (Table III; stated)	1 /month; 3.86e-07 Hz	comparable MLGWSC-1 DS1 with the challenge script: directly comparable with the DS1 entries.	*pending*
`chatterjee2026` [72]	reach@FAR	MLGWSC-1 at 1/month: CASTOR 1482 Mpc (DS3), 1350 Mpc (DS4) (Sec V, Fig 4; stated)	1 /month; 3.86e-07 Hz	comparable MLGWSC-1 DS3/DS4 with the public evaluation code.	*pending*
	events	14 of 31 confident O3b BBH at FAR <= 1/month (Table II; stated)	-		*pending*
`gupta2026` [11]	reach@FAR	BNS sensitive volume at 1/yr: Aframe-BNS 0.0065 vs MBTA 0.0078, PyCBC-Hyperbank 0.0077, GstLAL 0.0059 Gpc^3 (1.4+1.4 Msun) (Fig 4; read-from-figure)	0.0821 /month; 3.17e-08 Hz	comparable Real O3 noise with 10 yr time slides, compared with GWTC-3 matched-filter numbers; Aframe FAR carries a factor-2 trials penalty.	*pending*
	events	O3 MDC: 671 of 1790 injections at FAR < 1/month (MBTA 648, GstLAL 528) (Table II; stated)	1 /month; 3.86e-07 Hz		*pending*
`insley2026flows` [104]	eff@FAR	+35 injections (+0.78 %) recovered at FAR < 1/yr over the histogram baseline (HLV +3.85 %), one O3 week (Sec V A, Fig 4; stated)	0.0821 /month; 3.17e-08 Hz	conditional Normalising flows replace a histogram inside the PyCBC ranking statistic; the gain is relative to PyCBC on one week of O3 data.	*pending*

MLGWSC-1 contract. Sensitive distance (Mpc) at FAR 100, 10 and 1 per month on the four MLGWSC-1 datasets, from the challenge paper and from later papers that used its evaluation code. Dataset 4 is real O3a noise; datasets 1-3 are simulated. Values marked read-from-figure are read from plotted curves.

DS	Source	Search	D@100	D@10	D@1	Location; how	gravyflow
1	`mlgwsc2022` [8]	A MFCNN	1587	852	779	MLGWSC-1 Table IV; stated	*pending*
1	`mlgwsc2022` [8]	B PyCBC	2687	2551	2492	MLGWSC-1 Table IV; stated	*pending*
1	`mlgwsc2022` [8]	C CNN-Coinc	1372	1045	1002	MLGWSC-1 Table IV; stated	*pending*
1	`mlgwsc2022` [8]	D TPI FSU Jena	2635	2472	2363	MLGWSC-1 Table IV; stated	*pending*
1	`mlgwsc2022` [8]	E Virgo-AUTh	2512	2318	2116	MLGWSC-1 Table IV; stated	*pending*
1	`yamamoto2025` [70]	MF + CNN hybrid	2743	2582	2428	Table III; stated	*pending*
2	`mlgwsc2022` [8]	A MFCNN	1532	582	449	MLGWSC-1 Table IV; stated	*pending*
2	`mlgwsc2022` [8]	B PyCBC	1720	1600	1544	MLGWSC-1 Table IV; stated	*pending*
2	`mlgwsc2022` [8]	C CNN-Coinc	554	444	374	MLGWSC-1 Table IV; stated	*pending*
2	`mlgwsc2022` [8]	D TPI FSU Jena	1712	1544	1455	MLGWSC-1 Table IV; stated	*pending*
2	`mlgwsc2022` [8]	E Virgo-AUTh	1609	1410	1242	MLGWSC-1 Table IV; stated	*pending*
3	`mlgwsc2022` [8]	A MFCNN	885	473	356	MLGWSC-1 Table IV; stated	*pending*
3	`mlgwsc2022` [8]	B PyCBC	1734	1630	1577	MLGWSC-1 Table IV; stated	*pending*
3	`mlgwsc2022` [8]	C CNN-Coinc	620	468	402	MLGWSC-1 Table IV; stated	*pending*
3	`mlgwsc2022` [8]	D TPI FSU Jena	1728	1578	1488	MLGWSC-1 Table IV; stated	*pending*
3	`mlgwsc2022` [8]	E Virgo-AUTh	1647	1495	1241	MLGWSC-1 Table IV; stated	*pending*
3	`mlgwsc2022` [8]	F cWB	1462	1360	1252	MLGWSC-1 Table IV; stated	*pending*
3	`chatterjee2026` [72]	CASTOR	-	-	1482	Sec V; stated	*pending*
3	`chatterjee2024` [71]	GW-Whisper	1180	1030	890	Fig 2a; read-from-figure	*pending*
4	`mlgwsc2022` [8]	A MFCNN	1269	999	650	MLGWSC-1 Table IV; stated	*pending*
4	`mlgwsc2022` [8]	B PyCBC	1722	1610	1544	MLGWSC-1 Table IV; stated	*pending*
4	`mlgwsc2022` [8]	C CNN-Coinc	961	621	0	MLGWSC-1 Table IV; stated	*pending*
4	`mlgwsc2022` [8]	D TPI FSU Jena	258	0	0	MLGWSC-1 Table IV; stated	*pending*
4	`mlgwsc2022` [8]	E Virgo-AUTh	1609	1400	1092	MLGWSC-1 Table IV; stated	*pending*
4	`mlgwsc2022` [8]	F cWB	1407	1332	1229	MLGWSC-1 Table IV; stated	*pending*
4	`nagarajan2025` [14]	Aframe (private comm.)	1708	1570	1441	Table V; stated	*pending*
4	`nousi2022` [12]	AresGW	1815	1630	1575	Fig 10; read-from-figure	*pending*
4	`chatterjee2026` [72]	CASTOR	-	-	1350	Sec V; stated	*pending*
4	`chatterjee2024` [71]	GW-Whisper	1185	1025	905	Fig 2b; read-from-figure	*pending*
4	`nagarajan2025` [14]	Sage-Broad (best of 3)	1859	1722	1638	Table V; stated	*pending*
4	`nagarajan2025` [14]	Sage-Limited	1852	1711	1553	Table V; stated	*pending*
4	`zelenka2024` [69]	TPI FSU Jena (updated)	-	-	1316	Sec IV C 2; stated	*pending*
4	`nagarajan2025` [14]	TPI-FSU Jena 2024	1584	1424	1316	Table V; stated	*pending*

3.3 What cannot be compared, and why

Most CBC papers report a true-positive rate at a per-window false-alarm probability, an accuracy on a balanced set, or an AUC over a mixture of SNRs. None of these converts to a false-alarm rate without the window stride and the clustering rule, and none fixes the injected population, so a 98 % accuracy in one paper and a 0.9 TPR in another say nothing about each other. Real-event recoveries are listed for completeness but are not efficiencies: windows are often placed on the known event, and the denominator is the catalogue, not an injection set. Comparable rows are those on the MLGWSC-1 contract or on the LVK injection campaigns (sensitive distance or volume at a stated FAR); conditional rows have a true FAR but a different noise model, population or detector count.

The 56 models below have no shared axis; their headline metric is listed with the reason.

Model	Headline metric (location; how)	Why not comparable	gravyflow
`kim2015grb` [100]	efficiency at per-trigger FAP ~1e-4: ANN 0.56-0.74 vs detection statistic 0.50-0.64 (Fig 7; read-from-figure)	GRB-triggered coherent CBC search on S5/VSR1, per-trigger FAP; the MLR is built from the same samples it is scored on.	*pending*
`george2018plb` [29]	sensitivity ~45 / ~77 / ~93 % at SNR 5 / 6 / 7 vs matched filter ~52 / ~87 / ~97 % at <1 % false alarms per window (Fig 1 left; read-from-figure)	Proceedings version of george2018b; per-window FAP.	*pending*
`george2018` [1]	100 % TPR for SNR >= 10 (shallow) / >= 9 (deep) at ~0.5 % false alarms per 1 s window (Results, Figs 8, 12; stated)	One operating point per network on Gaussian ZDHP noise; the "false alarm rate" is a per-window fraction.	*pending*
`george2018b` [3]	100 % TPR for SNR > 10 at <1 % false alarms per window (single detector) (Sec III, Fig 4; stated); GW150914 recovered with masses inside published errors (Sec III; stated)	Real O1 noise but one operating point; the two-detector 0.01 % squares the single-detector fraction.	*pending*
`rebei2018` [33]	100 % sensitivity for SNR >= 10 on eccentric higher-mode NR waveforms (Fig 8; stated)	Sensitivity on a few NR waveforms; the false-positive sentence is garbled in the PDF.	*pending*
`fan2019` [41]	TPR 98.7 % at network SNR 8, 100 % at >= 9, 0.4 % false alarms per 2 s window (HLV) (Sec III A, Fig 4; stated)	Fixed-SNR balanced test sets in coloured Gaussian noise; one operating point.	*pending*
`kim2019` [101]	RF 0.666 / 0.689 vs GstLAL 0.633 / 0.658 (H1 / L1 triggers) (Fig 1; stated)	Trigger-level re-ranking inside GstLAL with GW150914-like injections against time-slide triggers; the FAR in Hz is a GstLAL-style conversion of a trigger FPR.	*pending*
`lin2019` [42]	TPR >97.2 % at per-sample FPR >= 1e-3 (BNS, rho 8-12) (Sec 4, Fig 3; stated)	Per-sample FPR with 1/7000 resolution in Gaussian noise; rho mixture undefined.	*pending*
`luo2019` [43]	none extracted	Not read (journal page unresolvable); no metric.	*pending*
`schmitt2019` [44]	none extracted	Not read (ACM paywall); no metric.	*pending*
`chauhan2020` [45]	100 % accuracy at SNR 4 on a 400-sample test set (Sec 3; stated)	Tiny balanced set; training accuracy 1.00 after one epoch; no false-alarm context.	*pending*
`deighan2020` [35]	accuracy 0.71 (seed) to 0.79 (GA-optimised), white noise (Sec 5.3; stated)	Architecture-search study on a white-noise toy problem.	*pending*

Model	Headline metric (location; how)	Why not comparable	gravyflow
krastev2020 [30]	BNS TPR at FAP 1e-2: 0.33 / 0.63 / 0.88 at rho 8 / 10 / 12 (Fig 4; read-from-figure)	Per-sample FAP from ~1,667 noise samples (resolution ~6e-4) in Gaussian noise; the FAP 1e-3 curves rest on 1-2 samples.	*pending*
li2020 [46]	wavelet-packet CNN (SE5) 0.947 at FPR 1e-3, rho_opt 2 (Table 3; stated)	Not a compact-binary search: damped sinusoids in white noise, 0.03 s windows.	*pending*
santos2020 [47]	ring-down time from score decay, e.g. GW150914 3.87 ms (LIGO ~4 ms) (Table 1; stated)	No FAR, TPR or distance; the score-decay "ring-down" is not a strain measurement.	*pending*
wang2020 [83]	TPR at per-sample FAP 1e-3: 0.47 / 0.72 / 0.90 at rho_opt 4 / 5 / 6 (Fig 3; read-from-figure); GW150914, GW151012, GW151226 and eight O2 events flagged (Figs 4-5; stated)	Real O1 two-detector noise but per-sample FAP of unstated noise-set size; O1/O2 scan triggers carry no FAR.	*pending*
alvares2021 [89]	three-detector classifier ROC AUC 0.87 at 2000 Mpc (Fig 5; stated); 34 of 37 GWTC-2 BBH above threshold 0.5 (Table III; stated)	Balanced validation at one injection distance; noise from one 500 s segment; no FAR.	*pending*
dodia2021residual [48]	detection ratio ~100 % at SNR 11 (BBH), 20 (BNS), no FAR stated (Figs 6-7; stated)	Detection ratio without a false-alarm level.	*pending*
dodia2021specgrav [95]	none extracted	Three-class accuracy on small balanced sets; per-event results not recovered.	*pending*
fan2021_2d [96]	none extracted	Not read (ICPR paywall); no metric.	*pending*
g2net2022_acm [97]	none extracted	Not read; G2Net-style balanced AUC at best.	*pending*
gunny2021 [68]	throughput 6.4e-5 s per second of data on 4 V100 (DeepClean); end-to-end ~1 s latency claimed (Figs 3, 9; read-from-figure)	Inference-as-a-service systems paper; no detection performance for BBHnet.	*pending*
huerta2021 [64]	ensemble TPR 0.37-0.85 at SNR 10.6 across per-time-step FPR ~3e-6 to ~4e-4 (Fig 4 inset; read-from-figure); all four August 2017 BBHs found, zero false positives in the month (Abstract, Fig 2b; stated)	Per-time-step FPR with an undefined unit; the zero-misclassification month uses a different (coincident-peak) statistic from the ROC.	*pending*
krastev2021 [31]	BNS TPR at FAP 1e-2: 0.29 / 0.63 / 0.89 at rho 8 / 10 / 12 (real O2 L1 noise) (Fig 3; read-from-figure); 11 of 11 GWTC-1 events classified with p > 0.995 (windows placed by hand) (Fig 4; stated)	Per-10 s-sample FAP; the paper's FAR conversion is order-of-magnitude; real events are classified, not searched.	*pending*
lin2021 [37]	window TPR >90 % for rho_opt > 8 counting "awareness"; false awareness 19.6 % of noise windows (Sec III A, Fig 4; stated); 7 of 7 O2 L1 BBHs (Sec III B; stated)	Three-state output in which awareness counts as detection; event-level false rate 47.7 %.	*pending*
verma2021 [49]	level-1 accuracy ~99 % (99.43 % from the matrix), FAP 0.33 % per sample (Sec V, Fig 5; stated)	Balanced synthetic single-detector set, SNR 10-20 with the test SNR unstated.	*pending*
yan2021 [84]	FNR ~3.7e-5 (matched filter) vs ~3.3e-5 (MNet-Shallow) at per-segment FPR 3e-4, SNR 9 (Fig 13; read-from-figure)	Fixed-SNR single-detector 0.6 s segments of real O2 L1 noise, 40-50 Msun only; FPR per overlapping segment.	*pending*
zhan2021 [50]	accuracy 96.4 % at SNR 10 (called sensitivity; recall 98.4 %, FPR 5.6 %) (Fig 2; stated)	Glitch-response probe on Gaussian design noise.	*pending*
alhassan2022 [93]	ResNet-101 accuracy 0.62 (SNR 4-5) to 0.985 (SNR > 8), single ET detector (Table 3; stated)	Einstein Telescope single-detector STFT classification in Gaussian ET-D noise, SNR-binned balanced sets; the mock-run false positives are per 5 s window.	*pending*
aveiro2022 [90]	YOLOv5 precision 0.922, recall 0.823, mAP@0.5 0.945 (BNS CQT images, SNR 10-20) (Abstract, App A; stated); GW170817 H1 at confidence 0.91; L1 only after ad hoc capping (Sec V C; stated)	Object-detection metrics on synthetic H1 Gaussian noise; no FAR.	*pending*
chaturvedi2022 [65]	79 time-slide false positives in 5 yr (~1.3 per month); all four August 2017 BBHs found (Sec 3.1, 3.3; stated)	Same ensemble as huerta2021 with TensorRT; time-slide counts are not independent trials and no efficiency is paired with them.	*pending*
jiang2022 [51]	none extracted	Not read; no metric.	*pending*
jiang2022real [52]	41 of 41 O1-O3a BBH; FAR < 1 per 2 months in O2 replay (abstract) (abstract; stated)	Abstract-level only.	*pending*
ma2022 [38]	FAP at TAP 0.8: 0.0042 (single) vs 0.00185 (harmonic ensemble), Hanford, per 1 s window (Sec III.3, Fig 5; stated); 9 of 10 O1/O2 BBH (GW170818 missed) (Sec IV B; stated)	Per-window FAP on a bespoke 20 %-signal test set in O1 noise; the "1 per 11.24 days" FAR is extrapolated by multiplying H and L probabilities.	*pending*
menendez2022sub [53]	none extracted	Not read; no metric.	*pending*
qiu2022 [39]	TAP saturates at FAP 1e-3 for SNR >= 8 (BBH), >= 10 (NSBH), >= 13 (BNS), real L1 noise (Sec 3.1, Fig 4; stated)	Per-segment FAP on quiet stretches of real L1 O2/O3b noise, single detector, four-class softmax.	*pending*
verma2022 [32]	aligned vs precessing vs noise: diagonals ~96 % (synthetic), 90.5 % (H1 PSD), 92.3 % (L1 PSD) (Figs 5-8; read-from-figure)	Per-detector models on Gaussian noise coloured by O3 PSDs; classification at an unstated threshold.	*pending*
yan2022 [54]	none extracted	Not read; no metric.	*pending*
zhang2022 [55]	detection ratio ~89.6 % at FAP 4.88e-4 (abstract) (abstract; stated)	Abstract only (APS paywall); the abstract converts the FAP to about one false alarm per 18.2 h.	*pending*
alhassan2023pymerger [94]	three-sub-detector ResNet accuracy 0.785 / 0.84 / 0.995 at SNR 4-5 / 5-6 / 6-7 (ET-D Gaussian) (Sec 4, Fig 5; stated)	Einstein Telescope triangle in Gaussian noise; balanced SNR bins; no FAR curve.	*pending*
garg2024 [56]	none extracted	Qualitative only; no numbers.	*pending*
kumar2023 [57]	none extracted	Not read; no metric.	*pending*
ma2024tempfree [85]	TAP ~0.8 at per-sample FAP 1e-4 in most mass sub-spaces (denoiser + discriminator) (Fig 9; read-from-figure); denoised overlap > 0.9 for >= 97.5 % of samples (heaviest class), ~60 % (lightest) (Sec IV A 1, Fig 4; stated)	Per-sample FAP on 10,000 noise samples; real-data background overlaps training epochs.	*pending*
sasaoka2023_cbc [98]	none extracted	Not read; no metric.	*pending*
sasaoka2023attr [92]	ensemble TAP at network SNR 8, FAP 1e-3 per 4 s: ~0.97 (BBH), ~0.55 (NSBH), ~0.075 (BNS), real O3 HLV noise (Fig 3; read-from-figure)	Per-4 s-segment FAP (~one false positive per hour) with SNR computed on truncated signals.	*pending*
sharma2023 [58]	none extracted	Not read; no metric.	*pending*
meijer2024 [36]	AUC 0.949 (aligned) / 0.940 (precessing) / 0.953 (curriculum), signal vs blip at matched SNR (Sec V A; stated)	Balanced simulated IMBH-vs-blip set with SNR distributions forced to coincide; no FAR.	*pending*
sharma2024 [59]	none extracted	Not read; no metric.	*pending*
ussipov2024 [60]	source-type accuracy up to 0.96 (abstract) (abstract; stated)	Abstract-level only.	*pending*
ashton2025 [105]	pipeline-combination AUC: max-IFAR 0.925, LR 0.944, MLP 0.967 (O3 replay MDC) (Fig 1; stated)	Learns on pipeline candidate lists, not strain; AUC on an injection-rich MDC split.	*pending*
ma2025et [88]	none extracted	Not read; no numbers in the abstract.	*pending*
silver2025 [78]	57 of 75 GWTC-3 BBH at a threshold with ~63 time-shifted false positives per year (derived) (Sec III C-D; stated)	Real-data event recovery with thresholds tuned on the same GWTC-3 search; no injection-based sensitivity at a FAR.	*pending*
gupta2026q [61]	validation AUC 0.9209 (G2Net subset) (abstract; stated)	Abstract-level; G2Net synthetic data with an unstated SNR distribution.	*pending*
mobilia2026 [86]	Sim4 TAP at per-window FAP 1e-4: CNN ~0.30 vs reweighted SNR ~0.13 vs SNR ~6e-3 (Sec VIII, Fig 13; stated)	Simulated Gaussian noise with synthetic glitches; FAP 1e-4 rests on about one of ~12,000 noise samples.	*pending*
rai2026 [99]	mean per-event AUC 0.915 +- 0.086 on 66 GWTC events (per 0.25 s window) (Sec 3.2; stated)	Per-window classification of catalogue events; FPR 0.0061 per 0.25 s window is ~0.024 Hz as a rate.	*pending*
weerasinghe2026 [62]	ROC AUC 0.999999; 99.998 % efficiency at 1 % FPR per 100 ms segment (Sec 5.1; stated)	Synthetic post-merger damped sinusoids; saturated metrics on 1000-fold augmentations of a small waveform set.	*pending*

3.4 Suspected errors in the literature

136 suspected errors or internal inconsistencies in 74 papers, selected from the extraction notes (258 notes for this section in the catalogue). Each is a reading of the paper to be checked, not a verdict.

- [100] Sec 2.1 names S6/VSR2-3 data while the analysed GRBs are S5/VSR1.
- [100] Sigma conversions are two-sided (FAP 1e-4 called 3.89 sigma).
- [29] "1 per 100 s" for 1 % of overlapping 1 s windows stepped 0.2 s is a factor-5 slip.
- [29] Text says 100 % above SNR 10; Fig 1 reads ~99.5 % at 10.
- [2] CNN above the matched filter at FAP 0.1 for rho 3-5 (Fig 3) is not possible for an optimal filter in Gaussian noise; the bank or threshold handling is suspect.
- [2] Waveform count conflict: 4e5 series with 25 noise draws each implies 8000 signals, the text says 1000.
- [1] Very-high-SNR error bound given as <3 % (Fig 10 caption) and <5 % (text).
- [3] "1 % = one per 100 s of noise" is inconsistent with 1 s windows stepped by 0.2 s (one per ~20 s).
- [40] Raw CNN AUC 0.50 (Fig 6) vs 0.99 (Fig 7) on the same signal and SNR range points to an unconverged baseline.
- [40] Training sizes in the text (20,000/10,000) disagree with Figs 8-10.
- [41] Fig 4 calls a per-sample fraction a "false alarm rate".
- [41] Dataset size given as 3,000/2,000 and as 100,000 training sets.
- [4] Results section: 89 % at one per 19.5 min; conclusion: 86 % at one per 40 min for the same setup.
- [101] The abstract's "about 10 %" efficiency gain is an absolute TPR difference (60-70 % relative).
- [101] The 18 % sensitivity gain at ~1e-11 Hz is not reproducible from the stated ranges (21 % in radius).
- [42] Matched-filter TPR 0.78 at rho 8 and FPR 1e-3 while the CNN reaches ~0.985 is implausible for an adequate bank in Gaussian noise.
- [42] "More than 960 times faster" is a factor-10 slip: 261 s / 0.027 s = 9,667.
- [42] Sub-populations fall below the headline 97.2 % (Figs 4-5).
- [45] A 100 % sensitivity at SNR 4 with perfect training accuracy after one epoch points to leakage or an easy set.
- [45] Lowest SNR stated as 1.5 and as 4.
- [35] "11 % increase" is relative; parameters reduced by 78 % (text) or 79 % (Fig 8).
- [102] Abstract says all GWTC-1 CBCs are recovered; GW170818 is not (10 of 11).
- [102] Most MLStat IFARs in Table I are inferred by assuming a constant background reduction, not measured.
- [30] "Saturation at SNR >= 18" is approximate: BNS at FAP 1e-3 reads ~0.99 at SNR 16 (Fig 4).
- [46] CNN sensitivity 0.947 at FPR 1e-3 and rho 2 while the matched filter reaches ~0.05 contradicts the Neyman-Pearson optimality of matched filtering for known signals in Gaussian noise.
- [47] The positive class is a fit to the events later scored (leakage); KS = 1 is on training patterns.
- [5] The PyCBC Live reference is reconstructed from another paper by an SNR-threshold assumption, not run on the same data.
- [83] GW170817 (total mass ~2.7 Msun) is reported detected by a network trained on 10-150 Msun.
- [83] The same quantity is called matched-filter SNR (Fig 2) and optimal SNR (Fig 3), with different values (0.64 vs 0.60 at SNR 4, FAP 0.1).
- [89] Table II labels the 0.72 / 0.82 accuracies as AUC.
- [89] Abstract "as much as 70 %" improvement vs 0.72 to 0.82 in the main comparison.
- [95] 100 % training and validation accuracy for a model that failed most real events indicates a leaky validation set.
- [68] The one-second detection latency is claimed without any detection result.
- [64] Text says FPR rises as the threshold rises (direction reversed).
- [64] FPR range stated as 1e-6 to 1e-3; the figure spans ~3e-6 to ~4e-4.
- [64] FPR 1e-6 per 0.5 s step implies ~5 false peaks per month against the zero reported.
- [31] FAP 1e-3 is equated with O(10^3) false alarms per month; at the 0.3 s stride it is ~8.6e3.
- [31] BBH saturation SNR given as 10 and as ~12 in the same section.
- [37] Abstract >95 % vs text >90 %.
- [37] Event TPR at rho 2 (~43 %) is below the false event rate (47.7 %).
- [73] O2 trigger rates (34-47 per day) exceed the tuned 25 per day.
- [73] Events with secondary masses below the stated training range are detected (GW170104, GW170809).
- [6] Headline retention 91.5 % (v2) vs 97.5 % (v1 and README); both are radius ratios (0.915^3 = 0.77 in volume).
- [7] Percentages are minimum radius ratios presented as sensitivity fractions.
- [49] Fig 6 caption describes a per-patch ROC while the axes are noise-vs-signal.
- [49] Patch-2 accuracy 97.3 % stated vs 97.4 % from the printed matrix.
- [63] Training noise segments fall inside the August 5-16 2017 benchmark period.
- [63] Summaries claiming "a single GPU" conflict with the 4-V100 node used.
- [34] Abstract "12 % higher accuracy" is relative (0.84 vs 0.75 is 9 points absolute).
- [84] The claimed outperformance rests on ~37 vs ~32 missed injections out of ~1e6, within Poisson scatter.
- [84] Matched-filter templates are selected on the test set (best of 30 draws).
- [50] Fig 2 calls the accuracy "sensitivity".
- [93] ResNet per-class recalls (Table 3) imply accuracy ~0.77 at SNR > 8, not the 0.985 stated.
- [93] Conclusion quotes an 85 % mean accuracy; Table 3 averages 0.796.
- [93] Mock-run detection fractions (0.29, 0.47) disagree with Table 3 recalls (0.59, 0.57).
- [82] Text says 90 % to 70 % between 3 and 4 sigma; Fig 3 reads ~0.86 and ~0.81.
- [82] The matched-filter benchmark TAP equals FAP (chance level), impossible for a correct matched filter on injected signals.
- [90] Conclusion says GW170817 found "in both H1 and L1"; L1 required a post-hoc cap on spectrogram values.
- [65] "No misclassifications" on August 2017 against 1.3 false positives per month on time slides.
- [38] The coincident FAR assumes independent, exactly simultaneous H and L false triggers.
- [103] Abstract "~11 % above 300 Msun" while Fig 5 shows +17 % in the highest band and non-monotonic bands.
- [103] Fig 5 colourbar floor (1.04) is above its lowest band label (+2 %).
- [8] Text says CNN-Coinc retains >= 50 % of the leading ML distance down to 10/month on DS4; Table IV gives 621 vs 1400 Mpc (44 %).
- [8] MFCNN runtime ~11.5 h in the text vs 12.0-12.3 h in Table IV.
- [39] FAP 1e-3 per 0.2 s segment is ~1.3e4 false alarms per month, not ~1e3 as stated.
- [39] GWTC counts (82 BBH + 2 BNS + 2 NSBH) do not match the 72 BBH evaluated.
- [39] One misclassified GWTC-3 BBH has SNR 8.0 although the text says all have SNR < 7.
- [32] Confusion-matrix rows sum to 109.2 % (Fig 5) and 101.7 % (Fig 7).
- [32] 498 recovered injections but 214 + 206 = 420 classified.
- [32] Sec V claims >97 % / ~95 % accuracy; Figs 5-7 give 96.2 / 90.5 / 92.3 %.

- [55] The first catalogue gave 4.88e-4 as a FAR in Hz; the abstract calls it a probability (~1.5e-5 Hz as a rate).
- [94] The "FPR" on continuous mock data is the missed-injection fraction.
- [94] Text counts (594 of 722 undetected at SNR 4-5) disagree with Fig 9 (0.526).
- [74] Table IV H1-V1 row is non-monotonic (26.8 > 21.1) and repeats the H1-L1-V1 values.
- [74] The 95 % CL zero-event FP limit is 3/N = 4.0e-4, not 2e-4.
- [74] Inclination and polarisation labels are swapped in Table I.
- [76] The 1-per-2-months threshold sits below the background resolution and relies on a linear tail fit.
- [76] The max-SNR baseline is ~0 below FAR 0.05 Hz, which says more about the simulated glitch rate than about matched filtering.
- [80] The 40-80 Msun bin exceeds the 5-60 Msun training range.
- [80] The FAR bound comes from 0.9 s time slides of one 8.8-day chunk, which are strongly correlated.
- [85] "Half a month" of data is 12.15 days.
- [85] FAP 1e-4 equals one false positive in 10,000 samples.
- [85] Same PRD article number (109 043009) as the MSNRnet-1 citation in the sweep: one citation is wrong.
- [12] The first catalogue attributed DS1-DS4 distances (2116/1242/1241/1092) that are the Virgo-AUTh MLGWSC-1 values, not this paper's.
- [92] SNR is computed on the 4 s truncation, so NSBH/BNS SNRs are not comparable with full-signal SNRs elsewhere.
- [66] Abstract names ROC and PR AUC as figures of merit but no AUC is printed.
- [67] Abstract "zero false positives" in February 2020 follows manual removal of 7 of 13 noise triggers.
- [67] SNR bins differ between Fig 1 (17.23 ... 6.23) and Table 1 (8.4, 10.6).
- [81] "Two false alarms per day" is equated with 1 in 1.7e5 trials (2 per day is 1 in ~4.3e4 s).
- [81] Expected maximum false alarms 29/43/55 do not follow from 0/1/2 test false alarms (Poisson 95 % gives ~22/35/46).
- [87] Claimed TPR >= 0.9 at 12/yr for SNR >= 12.5 conflicts with the Fig 7 contours (0.98 near SNR 15-17).
- [87] All FARs below 12/yr are extrapolated from one month of data.
- [13] The printed FAR fit (Eq 6) gives 13.1/yr at Rs 16, not the 0.34/yr in the text.
- [13] Table I GW200301_211019 FAR is 10x the Eq 6 value (80380 vs 8380/yr).
- [13] Five of eight Virgo-LIGO events said to exceed Rs 3.5; Table V has four.
- [9] Text gives TPR 0.053 at FPR ~1e-6 and SNR 6.23; Fig 5 reads ~0.43.
- [9] Table IV FAR floor printed as < 0.97/yr while the text says one per year.
- [36] Same classifier and glitch set give TN 9762 vs 9763 on two test sets.
- [75] Table A1 has 25 events below the 1/week FAR against the 26 in the text.
- [75] Table A1 floors at 0.01/yr although the time slides reach 1/152.6 yr.
- [91] Conclusion says all FAPs were better than 0.1 %; Sec III A gives 0.26 % for the Hanford O3 model.
- [91] Real-event counts use the union of two detectors without adjusting the false-alarm probability.
- [69] Model selection on the test set biases the 1316 Mpc upward.
- [69] "Virgo-AUTh at 87 % of this value" matches neither Virgo-AUTh variant in Fig 4 (83 % or 119 %).
- [69] Fig 4 caption and legend disagree on which lines are dashed.
- [105] AUC differences are reported while the 90 % permutation bands overlap.
- [15] GWTC-3 candidate counts (90 / 79 / 63) do not reconcile across sections.
- [15] Missed-event accounting (54 + 23 > 75) does not close.
- [10] Text calls 35+35 sensitivity "similar"; Fig 2 shows Aframe above the matched-filter pipelines there and 40-50 % below at 20+10.
- [10] Comparison volumes use the LVK data release, whose injection weighting differs from the authors' own set.
- [16] Fig 7 caption names week 3 (the background week) as the injection week.
- [16] GW170817 FAR 6.9e-13 Hz is a Gaussian-tail extrapolation from a background reaching 1.8e-8 Hz.
- [14] Table V cWB row (1364 / 1441 / 1461 Mpc at 100 / 10 / 1 per month) rises as the FAR falls and does not match MLGWSC-1 Table IV for DS4 (1407 / 1332 / 1229).
- [14] Table V re-quotes MFCNN (1269 / 985 / 588) and PyCBC (1722 / 1607 / 1539) differently from MLGWSC-1 Table IV (1269 / 999 / 650; 1722 / 1610 / 1544).
- [14] Headline gains use the best of three seeds; the seed mean is lower (Fig 11).
- [78] Thresholds were set from performance in the real search, so 57/75 is in-sample.
- [78] "False positives" are defined in Sec III B as events the pipeline does not detect.
- [78] Extrapolated FARs (~1/350,000 yr) go far beyond the ~100 yr background.
- [77] The same configuration is reported with ~1.5 % different volumes in Tables 3 and 4.
- [77] Table 3 uses threshold 0.995 while the production threshold is 0.9999.
- [79] Text says ~1000 Mpc at 10/yr; Fig 6 reads ~750 Mpc there (1000 Mpc near 300/yr).
- [79] FAR axes are labelled in years rather than per year.
- [70] "Comparable to PyCBC" at 1/month hides that the method is 2.5 % below PyCBC there but above it at 10-100/month.
- [72] Abstract says about five months of O3b; the live time is 95.3 d (~3.1 months).
- [72] Per-month and per-year FARs in Table II are not related by a constant factor.
- [72] The discussion's "roughly a factor of two" over GW-Whisper is 1.66 and 1.49 in distance.
- [11] 10,000 training vs 20,000 validation waveforms is reversed from the usual split (Sec II D 2).
- [104] The 6.55 % HV gain quoted in the abstract comes from the modified sampling with the old histograms, not from the flow.
- [104] Four-detector FAR range "0.5 to 3.03e-4" has no unit and is in reverse order.
- [104] "Three orders of magnitude" storage reduction holds for three detectors, not two.
- [86] TAP values at FAP 1e-4 are quoted from ~1 noise sample.
- [99] Table 3 sets a per-window FPR beside Aframe's FAR < 1/yr as if like for like.
- [99] ECE reduction given as 15 % (Sec 3.3) and 95.6 % (Table 3).
- [62] Headline efficiency and the FAR calibration use different thresholds (1 % vs 0.3 % FPR).
- [62] AUC is said to be computed to FPR 1e-3 yet reported as a full AUC.
- [62] Uncertainty grows with SNR (slope +0.25), so the SNR labels are unusable.

4 Early warning

Early-warning models try to flag a binary neutron star or neutron star-black hole inspiral before merger, from a partial inspiral whose signal-to-noise ratio (SNR) grows with time.

4.1 Families and lineage

4.1.1 Partial-inspiral classifiers

Baltus et al. trained one CNN per binary neutron star mass class on long windows truncated before merger [106], [107], [108] later work changed the network or the deployment target [109], [110], [111] and added auxiliary-channel noise subtraction [112].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 7 models: [106], [107], [112], [108], [110], [109], [111]. Results will be placed on the shared axes of this section beside the published values.

4.1.2 Forecasting curves

Forecasting networks report the output probability against time to merger for single loud injections [113], [114].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 2 models: [114], [113]. Results will be placed on the shared axes of this section beside the published values.

4.2 Comparison on the shared axes

Rows are the models graded comparable or conditionally comparable (3 of 9); each axis entry is one row. FAR is converted to per month (30 d) and to Hz where the paper states a rate.

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
`yu2021early` [112]	eff@FAR	BNS TAR 0.38 at d_eff 40 Mpc and 0.09 at 60 Mpc at 1 false alarm per 7.1 h (0.01 per 256 s segment) (Fig 9; read-from-figure)	101 /month; 3.91e-05 Hz	conditional Simulated non-stationary O3-like noise with witness-channel subtraction; the per-segment fraction converts exactly to a rate because segments are disjoint.	*pending*
	eff@FAR	NSBH TAR 0.43 at d_eff 160 Mpc at the same FAR (Fig 10; read-from-figure)	101 /month; 3.91e-05 Hz		*pending*
`baltus2022` [108]	eff@FAP	50 % TAP at partial-inspiral SNR ~15 (Gaussian O3), ~20 (real O3) at FAP 1 % per 300 s frame (Sec III A, Figs 5-6; stated)	-	conditional Efficiency is at a per-frame FAP while the rate on real data is measured separately; the two are not paired.	*pending*
	other	real O3b trigger rate 277.5 / day (single), 1.71 / day with 10 consecutive triggers (Sec III A; stated)	-		*pending*
`alfaidi2024` [110]	eff@FAR	LSTM TAP ~0.44 vs exact-template matched filter ~0.79 at FAR ~1e-3 Hz (SNR 2-20, single detector, Gaussian) (Fig 4; read-from-figure)	2.59e+03 /month; 0.001 Hz	conditional A FAR in Hz of a per-timestep statistic, with an exact-template matched filter as upper bound; Gaussian noise only.	*pending*

4.3 What cannot be compared, and why

Early-warning results are quoted against partial-inspiral SNR at a per-frame false-alarm probability of about 1 %, a rate of order one per hour for frames of a minute. Only papers that convert to a rate over disjoint segments (or measure one) are graded conditional; lead times for single loud injections are not comparable.

The 6 models below have no shared axis; their headline metric is listed with the reason.

Model	Headline metric (location; how)	Why not comparable	gravyflow
`baltus2021` [106]	heavy-BNS TAP ~0.98 at 125 Mpc, ~0.9 at 175 Mpc at FAP 1 % per frame (single detector, Gaussian) (Fig 5; read-from-figure)	Per-frame FAP of 1 % (frames 30-80 s) in Gaussian design noise; the realistic-population test detects ~4 of ~89.	*pending*
`baltus2021b` [107]	light-BNS TAP ~1 to 15 Mpc, 0.2 at 40 Mpc at FAP 1 % per frame (Sec IV, Fig 4; stated)	Conference version of baltus2021 (arXiv 2105.13664, which the first catalogue missed).	*pending*
`wei2021` [114]	none extracted	Forecasting curves for single injections at SNR 30; no FAR, ROC or efficiency.	*pending*
`wei2021forecast` [113]	BNS flagged up to 30 s before merger at SNR 30-40; GW170817 10 s before merger (Fig 2-3; stated)	Lead time for single high-SNR injections; no FAR or population efficiency.	*pending*
`martins2024` [109]	TPR at FAP 1 % per 300 s sample: GWaveNet 76.2 % vs FindCNN 66.8 % (2D: 79.4 vs 69.5) (Table 2; stated)	Same data recipe as Baltus et al.; per-sample FAP on a balanced set.	*pending*
`papigkiotis2026` [111]	test accuracy ~90 % (ET-like), >97 % (CE-like) at low FAP (abstract) (abstract; stated)	Abstract-level; per-sample FAP in Gaussian ET/CE noise.	*pending*

4.4 Suspected errors in the literature

13 suspected errors or internal inconsistencies in 8 papers, selected from the extraction notes (28 notes for this section in the catalogue). Each is a reading of the paper to be checked, not a verdict.

- [106] "100 % TAP up to 125 Mpc" vs Fig 5 (~1.0 only to ~100 Mpc).
- [106] Network numbering differs between the text and the Fig 5 legend.
- [106] "Comparable to matched filtering" on the realistic population while Fig 7 shows ~4 found and ~85 missed.
- [114] "Decreases the top-1 error rate by 10 %" with no baseline error stated.
- [113] Abstract "up to 30 s" holds only at injected SNR 30-40; the one real event is flagged 10 s ahead.
- [112] Stationary-noise BNS range quoted as ~80 Mpc at TAR 0.4; Fig 9 reads TAR ~0.31 there.
- [112] Abstract lead times (100 s, 10 s) vs body (~87 s, 12 s).
- [108] Fig 6 plateaus at 0.91-0.97 while the text says efficiency reaches 100 % at PISNR 30.
- [110] Efficiency at 1/day and 1/6 h is quoted although Fig 4 starts near 6e-5 Hz (1 per 4.6 h).
- [110] Test-point arithmetic (256,000 vs 2,560,000) does not close.

- [109] Text says FindCNN is ~2 ms faster on GPU; Table 3 gives ~12 ms.
- [109] Table 1 lists five curriculum sets but four PISNR values.
- [111] FPR is defined as a false-discovery rate.

5 Burst and unmodelled transients

Burst searches look for short transients without a template: core-collapse supernovae (CCSN), generic sine-Gaussian and white-noise-burst morphologies, cosmic-string cusps and long magnetar-like transients. Two traditions coexist: classifiers on simulated data, and machine-learning stages added to coherent WaveBurst (cWB) on real observing-run data.

5.1 Families and lineage

5.1.1 Core-collapse supernova classifiers

From the first CNN on cWB images of phenomenological CCSN waveforms [115] through real-noise versions [116] and multi-class models on numerical waveforms [117], [118], [119], [120], to equation-of-state and frequency-slope classifiers [121], [122] and contrastive models [123], [124].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 14 models: [115], [117], [118], [125], [126], [116], [119], [120], [122], [127], [128], [121], [123], [124]. Results will be placed on the shared axes of this section beside the published values.

5.1.2 Machine learning inside cWB

Boosted trees, Gaussian mixtures and genetic programming applied to cWB summary statistics on real observing-run data [18], [19], [129], [130], [131], [132], [133], [134]. These are the burst results reported in search-grade units.

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 8 models: [129], [130], [131], [132], [19], [133], [18], [134]. Results will be placed on the shared axes of this section beside the published values.

5.1.3 Unmodelled neural searches

Coherence and autoencoder networks on real data with time-slide backgrounds: MLy [135], GWAK [136], the Wavelet Detection Filter with a graph network [137], and challenge entries on short windows [138], [139], [140].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 7 models: [141], [140], [136], [135], [139], [137], [138]. Results will be placed on the shared axes of this section beside the published values.

5.1.4 Long-duration and exotic transients

Minute-long transients, post-glitch CW-like transients and cosmic strings [142], [143], [144], [145].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 4 models: [142], [145], [144], [143]. Results will be placed on the shared axes of this section beside the published values.

5.2 Comparison on the shared axes

Rows are the models graded comparable or conditionally comparable (15 of 33); each axis entry is one row. FAR is converted to per month (30 d) and to Hz where the paper states a rate.

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
`astone2018` [115]	eff@FAR	CNN 5.9 / 60.7 / 91.8 % vs cWB 1.7 / 40.8 / 86.9 % at network SNR 8 / 12 / 20 (Table II; stated)	181 /month; 7e-05 Hz	conditional Phenomenological CCSN in Gaussian noise; efficiency is relative to a cWB pre-selection; per-SNR, not per distance.	*pending*
`chan2020` [117]	eff@FAP	TAP 86 % (H+L+VK) / 68 % (HLVK) at FAP 0.1 %, magnetorotational, 50 kpc (Sec IV, Fig 6; stated)	-	conditional Three-class CCSN in Gaussian design noise; FAP is a per-sample misclassification fraction, one CNN per distance.	*pending*
	eff@FAP	TAP 76 % / 55 % at FAP 10 %, neutrino-driven, 10 kpc (Sec IV, Conclusion; stated)	-		*pending*
`lopez2021b` [116]	AUC	0.896 (blind set, phenomenological) / 0.79 (3D simulations), real O2 noise (Fig 12, Sec VI C; stated)	-	conditional CCSN in real O2 noise; "FAR_CNN" is FP/(FP+TP) on a balanced set; efficiency averaged over the injected SNR/distance mix.	*pending*
	eff@FAP	TPR ~0.55 at FPR 2 %; ~0.84 at FPR 20 % (blind set) (Fig 12; read-from-figure)	-		*pending*

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
`mishra2021` [132]	eff@FAR	BBH: ~0.89 (O1) / ~0.86 (O2) ML vs ~0.61 / ~0.57 standard cWB at 1/yr; IMBH ~0.74 / ~0.79 vs ~0.65 / ~0.57 (Fig 2 top; read-from-figure)	0.0821 /month; 3.17e-08 Hz	conditional Non-neural (XGBoost) cWB post-processing, O1/O2 time slides; efficiency is over recovered, not injected, events.	*pending*
	events	all 7 cWB O1/O2 BBH events recovered with lower FAR (Table II; stated)	-		*pending*
`alvarez2022cwbml` [19]	reach@FAR	sensitive hyper-volume O3a 0.822 vs 0.676 Gpc^3 yr (ML vs standard cWB); GstLAL 1.22, PyCBC-BBH 1.2, MBTA 0.885 on the same population (Table IV; stated)	0.164 /month; 6.34e-08 Hz	comparable Non-neural (XGBoost) cWB post-processing on full O3 HL; hyper-volume under the GWTC-2 Power Law + Peak population is the LVK search metric, so it is comparable with the matched-filter pipelines quoted beside it. The Fig 3 efficiencies use recovered (not injected) events as the denominator.	*pending*
	eff@FAR	BBH set: 0.90 vs 0.76 (ML vs standard) at 1/yr; 0.62 vs 0.49 at 0.01/yr (Fig 3 top; read-from-figure)	0.0821 /month; 3.17e-08 Hz		*pending*
	events	5 further GWTC-3 BBHs at FAR < 1/yr that standard cWB vetoed (Table II; stated)	-		*pending*
`lopez2022gmm` [133]	eff@FAR	Gaussian pulse: gain >20 points over cWB (GA0d1 ~0.70 vs ~0.33); WNB ~0.89-0.905 vs ~0.78-0.79 (Fig 1, Sec III D; read-from-figure)	0.000821 /month; 3.17e-10 Hz	conditional cWB post-processing (non-neural GMM) on 104.9 d of O3a HL; efficiency over an hrss grid, not a sensitive volume.	*pending*
	events	GW190521 iFAR >200 yr (cWB+GMM) vs 65 yr (standard) (Table IV; stated)	-		*pending*
`moreno2022` [140]	eff@FAP	LSTM-AE TPR 46.1 % (BBH) / 23.7 % (BNS) at single-detector FPR 0.1; 43.3 % (BBH) at dual FPR 0.01 (Tables 1-2; stated)	-	conditional Synthetic (ggwd-style) data, SNR uniform 5-20, FPR per 2.5 s window; AUC conditionally comparable because noise and SNR distribution are stated.	*pending*
	AUC	LSTM-AE 0.73 (BBH) / 0.59 (BNS) single; 0.79 / 0.63 dual; supervised CNN 0.92 / 0.77 (Figs 4, 6; stated)	-		*pending*
`szczepanczyk2022` [18]	reach@FAR	hrss50 ratio XGB/standard cWB: Gaussian pulses 0.20-0.33, SG 0.84-0.95, WNB 0.91-0.95 (HL); volume gain 1.2-27x (Table I, Sec IV B, Fig 5; stated)	0.000821 /month; 3.17e-10 Hz	comparable LVK O3 all-sky burst search (non-neural XGBoost on cWB); real O3 background, LVK morphologies: the reference point for burst hrss50.	*pending*
	events	16 known CBCs at iFAR >= 1 yr (standard cWB 14), O3 HL (Sec IV A; stated)	-		*pending*
`raikman2024` [136]	reach@FAR	hrss50 0.55-1.83e-22 Hz^-1/2 (SG), 0.70-0.89e-22 (WNB) (Table II; stated)	0.000821 /month; 3.17e-10 Hz	comparable GWAK on full O3 with ~10,000 yr of time slides; LVK burst morphologies, so hrss50 is comparable with cWB/MLy at the same iFAR.	*pending*
	eff@FAR	SNR at 50 % efficiency: SG 512-1024 Hz ~8.5, BBH ~12.5, CCSN ~21 (Fig 1; read-from-figure)	0.0821 /month; 3.17e-08 Hz		*pending*
`skliris2024` [135]	reach@FAR	hrss50 MLy vs cWB: SGE70Q3 1.9 vs 1.5; SGE235Q100 1.4 vs 0.9; WNB100 1.7 vs 1.2 (1e-22 Hz^-1/2) (Table I; stated)	0.0821 /month; 3.17e-08 Hz	comparable O2 real background (~1e3 time shifts), O2 LVK burst injection set; directly comparable with cWB on the same set.	*pending*
	eff@FAR	>=50 % at network SNR 19, >=90 % at 27 (WNB/CCSN/BBH) (Fig 6; stated)	0.0821 /month; 3.17e-08 Hz		*pending*
`fernandes2025` [134]	reach@FAR	sensitive VT ratio ML/base, PyCBC-IMBH: 1.07 (100-200 Msun) to 1.45 (400-600 Msun) at IFAR 100 yr (Fig 5; read-from-figure)	0.000821 /month; 3.17e-10 Hz	comparable Classifier re-ranking of PyCBC IMBH and higher-mode searches on O3a chunks 1-4; VT ratio at IFAR is a search-level metric, but relative to its own baseline only.	*pending*
	reach@FAR	PyCBC-HM: 0.87 to 1.29 at IFAR 100 yr (Fig 6; read-from-figure)	0.000821 /month; 3.17e-10 Hz		*pending*
`pracchia2025` [128]	reach@FAR	distance at 50 % efficiency: 0.64 kpc (s18), 1.83 kpc (m39), 0.15 kpc (mesa20_pert) (Table I; stated)	0.0164 /month; 6.34e-09 Hz	conditional Single detector, Gaussian O4-design noise; threshold one background event per 5 simulated years (Gaussian only).	*pending*
`cuoco2026` [137]	eff@FAR	GNN vs deterministic WDF: all classes 0.70 vs 0.27 at 1/day (simulated); 0.28 vs 0.08 (real O4b); 0 at 1/month on real O4b (Tables II-III; stated)	30 /month; 1.16e-05 Hz	conditional Own simulated and 2.16 d real O4b sets, mixed CBC/CCSN classes; recovered fraction, not sensitive distance.	*pending*
`ratner2026` [138]	eff@FAR	recall 0.88 (BBH) / 0.86 (SGLF) at <=1 false alarm per year, no trigger (Table I; stated)	0.0821 /month; 3.17e-08 Hz	conditional CodaBench anomaly-challenge 50 ms windows of cleaned real noise; FAR 1/yr extrapolated from 50k backgrounds; PR-AUC depends on the anomaly rate.	*pending*
	AUC	PR-AUC 0.91 (BBH) / 0.89 (SGLF) (Table I; stated)	-		*pending*
`sun2026` [123]	AUC	CS-CAE 0.976 / supervised CNN 0.984 / CAE 0.916 (in-distribution); 0.995 / 0.993 / 0.979 (numerical CCSN) (Figs 2-3; stated)	-	conditional Simulated ET Gaussian noise with phenomenological CCSN; AUC conditionally comparable within ET CCSN studies; the distance has no stated FAR.	*pending*
	reach@FAR	~50 % efficiency at ~120 kpc (ET), threshold not stated (Sec III B, Fig 4; stated)	-		*pending*

5.3 What cannot be compared, and why

Burst papers use different waveform families (phenomenological or numerical CCSN, sine-Gaussians, white-noise bursts), quote efficiency against network SNR, distance or hrss, and often define “FAR” as a false-discovery fraction on a balanced set. Results are comparable only within a morphology at a stated FAR: hrss50 on the LVK morphologies (cWB, MLy, GWAK) or volume gains of cWB post-processing on the same observing run.

The 18 models below have no shared axis; their headline metric is listed with the reason.

Model	Headline metric (location; how)	Why not comparable	gravyflow
`vinciguerra2017` [129]	cWB baseline efficiency by distance shell for wide-mass CBC: 72.3 % (45-65 Mpc) to 10.2 % (340-505 Mpc) (Table 3; stated)	Signal-morphology classification inside cWB on recoloured S6/VSR2-3 noise; the reported efficiencies are the baseline pipeline, not the classifier.	*pending*
`cavaglia2020` [130]	specificity 0.962 +- 0.011, FNR 0.036 +- 0.008 (Dimmelmeier, 3.16 kpc) (Sec V, Fig 2; stated)	Genetic-programming classifier of cWB single-detector triggers (non-neural); balanced trigger test sets, no rate.	*pending*
`iess2020` [118]	signal-vs-glitch accuracy 95.4 % (1-D) / 96.3 % (2-D), Virgo O3 PSD; 7-class 87.9 % (Fig 7, Fig 8, Sec 6.2; stated)	Accuracy is conditional on a WDF trigger chosen with knowledge of the injection time; Gaussian noise and two parametrised glitch families; no FAR.	*pending*
`nigam2020` [125]	8-class accuracy 100 % (Deep Filtering, CNN, BiLSTM); RF 97.75 % (Table II; stated)	Eight synthetic transient classes in white noise with no noise class; accuracy only.	*pending*
`antelis2021` [131]	background FAR at cWB rho=5 cut from 0.0297 to 1.78e-4 Hz (L1) and 0.0253 to 1.95e-4 Hz (H1); L1H1 9.76e-6 Hz to the 1/3.3 yr floor (Sec III.B, Figs 5-6; stated); CCSN he3.5 detection efficiency vs distance essentially unchanged after ML (Fig 6; stated)	Non-neural (SVM) cWB follow-up for CCSN on 3-day O3a windows; the FARs are trigger rates at one cWB threshold, and the efficiency is unchanged, so no efficiency-at-FAR gain is shown.	*pending*
`lopez2021a` [126]	70 % efficiency at "FAR" < 5 % for SNR > 15 (abstract level) (abstract; stated)	Conference version of lopez2021b; "FAR" there is a false-discovery fraction, not a rate. Full text not read.	*pending*
`marianer2021` [141]	20-class accuracy 97.3 % on regenerated O1+O2 Gravity Spy-style spectrograms (1,197 test) (Sec 2.2; stated); hrss50 for flagging: 10e-22 (WNB 100 Hz) to 40e-22 Hz^-1/2 (sweeps); no FAR attached (Table 4; stated)	Outlier search; hrss50 is for "flagged as outlier" with no time-normalised false-alarm rate.	*pending*
`boudart2022` [142]	none extracted	No quantitative metric: qualitative recovery limit at visibility 12-16; detection statistic deferred.	*pending*
`iess2023` [119]	merged per-trigger TPR 99.3 % (L1), 99.1 % (H1), 79.8 % (V1), 97.8 % (3-detector) (Table 2, Sec 5; stated)	Trigger classification at a fixed 1 kpc on real O2 noise; noise class is whatever WDF triggers; no FAR.	*pending*
`meijer2023cosmicstrings` [145]	accuracy 0.788, TPR 0.755 at FPR 0.18 (cusp vs blip, ET) (Table I; stated)	Balanced cusp-versus-glitch classification in simulated ET noise; no noise class or FAR.	*pending*
`modafferi2023` [144]	p_det > 90 % at p_FA 1e-7 (synthetic); two-stage CNN filter ~80x faster with ~1-3 % p_det change (Sec V, Fig 3; stated)	Long-duration (post-glitch Vela) transient CW search on F-statistic atoms; p_FA per template, no link to transient FAR.	*pending*
`sasaoka2023_ccsn` [120]	10-class accuracy 0.984 (1 kpc), 0.603 (5 kpc), 0.332 (10 kpc), real O3 noise (Sec III A, Fig 5; stated)	Read paper is arXiv 2310.09551 (PRD), not the catalogued PoS; per-distance multi-class accuracy, no FAR.	*pending*
`attadio2024` [143]	efficiency 0.90 at FAP 0.02 (masked-loss denoiser) (Eq 23, Fig 10; stated)	Long (1200 s) magnetar transients, single detector, simulated O4 noise; FAP is FP over all samples per map.	*pending*
`morales2024` [122]	3-class HFF-slope accuracy 0.987 / 0.933 / 0.853 at 1 / 5 / 10 kpc (L1, real O3b) (Table 6; stated)	Classification of one waveform per class at fixed galactic distances; no FAR or noise class.	*pending*
`nunes2024` [127]	none extracted	Abstract-level only: Richers CCSN catalogue in aLIGO noise; no metric extracted.	*pending*
`yan2025deepgrav` [139]	challenge TNR 0.9708 (development) / 0.9832 (final), first of 272 teams (abstract, Fig 3; stated)	NSF HDR A3D3 anomaly-challenge score: TNR at an undisclosed threshold and TPR; trained on both signal classes, so not anomaly detection in the unsupervised sense.	*pending*
`casallaslagos2026` [121]	5-class EOS accuracy 98.58 % (1 kpc), 52.43 % (5 kpc), real O3b noise (abstract; Table 6; stated)	Classifies already-triggered cWB maps of five fixed waveforms by equation of state; no false alarms enter, no FAR.	*pending*
`wang2026ccsn_scl` [124]	rotational TPR ~1.0 at FPR 1e-4 (10 and 200 kpc); ~0.80 at 1200 kpc (Sec IV-B, Fig 5; stated)	Synthetic Gaussian HLVK spectrograms; FPR is per sample over the other classes; no real noise or glitches.	*pending*

5.4 Suspected errors in the literature

43 suspected errors or internal inconsistencies in 27 papers, selected from the extraction notes (96 notes for this section in the catalogue). Each is a reading of the paper to be checked, not a verdict.

- [115] The FAR of 7e-5 Hz in Table II is not derived from the CNN false-alarm fraction of 3-4 % (Eq 9 is a dimensionless fraction).
- [130] Table II shows efficiency falling after cleaning (about 10 % at 2 sigma, 30 % at 3 sigma) while the abstract claims improved reach; the two use different operating points.
- [117] Abstract attributes the 52 % / 83 % TAPs to waveforms; the body attributes them to the two networks.
- [117] Training-set size given as 1.8e5 per distance and as about 4e5 per class.
- [118] Text says total accuracies are consistently above 90 %, but Table 1 has 83.2 % (ET, s25, 1-D).
- [125] Logistic-regression accuracy 89.67 % disagrees with its own confusion matrix (89.17 %).
- [125] Three models at 100 % down to SNR 5 suggests a degenerate benchmark or leakage.
- [131] Abstract quotes FAR reduction by 10-100x; Table IV ranges 11-1019x, with L1H1 saturated at the background floor.
- [131] L1H1 noise rejection given as 99.4 % (text) and 99.0 % (Table II).
- [116] Efficiency floor of ~58-66 % at SNR 1-6 (Fig 14) is incompatible with a ~5-10 % false-positive fraction.
- [132] The 26 % / 16 % gains are absolute efficiency differences, not relative gains.
- [132] Efficiency denominator excludes injections cWB never recovers.
- [19] Efficiency denominator is the number of cWB-recovered injections, not all injected, so curves reach 1.0.
- [19] The "about 20 %" gain is +18 % relative for BBH but about +27 % relative for IMBH at 1/yr (Fig 3).
- [133] Background test fraction given as 30 % (Sec III B) and 20 % (Sec IV).
- [140] Text equates FPR 1e-6 with one false alarm per three months, which holds only for 8 s windows, not the 2.5 s windows used.
- [140] Dual-detector BBH-CNN TPR (25.6 % at 1e-2) is below single-detector (66 % at 1e-1) although dual AUC is higher.
- [18] Table I Gaussian pulse tau=1.0 ms HL volume (1.5 vs 0.11, ratio 13.6) contradicts the 2.3-4.5 range in the text; likely a typo.
- [18] Fig 1 caption says 10 HLV events at iFAR >= 1 yr; the text says 8.
- [119] Abstract "~80 % for Virgo" is the merged model on the triple-coincident subset; single V1 models are 68-75 %.
- [145] Matched filtering against the exact injected template is reported worse than random (Fig 16-17), which is implausible for the optimal filter.
- [120] PoS abstract gives 96.9 % at 1 kpc against 98.4 % in the arXiv/PRD version.
- [143] FAP is defined as FP/(all samples), not FP/(FP+TN), which understates the false-positive rate.
- [122] Binned-regression accuracy rises from 1 to 5 kpc (0.55 to 0.85, Table 8), implausible for an amplitude-limited task.
- [136] hrss50 takes only three distinct values across eight SG morphologies, suggesting a coarse amplitude grid.
- [136] Abstract claims three CBCs detected; none passes the paper's 1/100 yr threshold.
- [135] Text says MLy is 10-50 % worse in hrss than cWB; Table I gives up to +56 %.
- [135] The 1/yr threshold is extrapolated from time lags of days to weeks of data.
- [134] Text gives up to ~70 % VT gain at IFAR 100 yr; Fig 5 reads ~45 % there (70 % matches the 1000 yr marker).
- [134] PyCBC-HM VT ratio at 100 yr lies below both 10 yr and 1000 yr in every mass bin, unexplained.
- [128] Table I column headings (10/50/90 % exclusion distance) are defined only in the Fig 6 caption; values fall as the percentage rises.

- [139] TNR without the matching TPR or threshold is not a detection performance.
- [139] Augmentation counts do not close (n in {3,5,10} x 200,000 vs the stated 300,000).
- [121] Abstract macro AUC 0.97 at 1 kpc against 0.80 macro / 0.89 micro in Sec 7.
- [121] Abstract 52.43 % at 5 kpc against 0.80-0.83 in Tables 7-8.
- [121] TW1 spans 14 days, not one week, and overlaps TW2 (Table 1).
- [137] "Similar gains on real O4" understates the drop (0.70 -> 0.28 at 1/day).
- [137] Fig 7 AUCs below 0.5 (BNS 0.06) are coincidence-saturated, not discrimination AUCs.
- [137] Simulated BH-NS count (289) exceeds the 258 injected.
- [138] Abstract quotes recall 0.91 (BBH) and 0.85 (SGLF); Table I gives 0.88 and 0.86 (0.91 is the PR-AUC).
- [123] The 120 kpc reach is quoted at an "adopted operating threshold" with no FPR or FAR.
- [124] Abstract says ~100 % TPR at FPR 1e-4 for both classes at 10-200 kpc; Sec IV-B says neutrino-driven performance collapses below FPR 6e-5.
- [124] Fig 7 plots FPR down to 1e-5 with 50,000 noise samples (resolution 2e-5).

6 Anomaly and multi-signal detection

Anomaly and multi-signal detectors are trained on noise (or on noise plus a few known classes) and flag what does not fit. Their false-alarm behaviour is set by the definition of normal data, which differs from paper to paper.

6.1 Families and lineage

6.1.1 Autoencoder anomaly detectors

Recurrent or convolutional autoencoders trained on noise [146], [147], [148], [149], [150], [151], scaled up to a multi-level pipeline over O3-O4 with a measured background [17] and to Einstein Telescope mock data [152].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 8 models: [151], [146], [147], [150], [148], [149], [152], [17]. Results will be placed on the shared axes of this section beside the published values.

6.1.2 Foundation-model features

Pretrained audio or vision transformers used as feature extractors [71], [153].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 2 models: [71], [153]. Results will be placed on the shared axes of this section beside the published values.

6.1.3 Other approaches

Entries that do not belong to the families above.

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 1 models: [154]. Results will be placed on the shared axes of this section beside the published values.

6.2 Comparison on the shared axes

Rows are the models graded comparable or conditionally comparable (3 of 11); each axis entry is one row. FAR is converted to per month (30 d) and to Hz where the paper states a rate.

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
`raikman2023` [146]	eff@FAR	SNR at 50 % efficiency: BBH ~15.5, SG 512-1024 Hz ~10, WNB ~23, CCSN ~27 (Fig 13; read-from-figure)	0.0821 /month; 3.17e-08 Hz	conditional About 71 min of O3a H1+L1 noise; the 1 yr background is built from heavily reused time slides.	*pending*
`chatterjee2024` [71]	reach@FAR	sensitive distance 890 Mpc (DS3) / 905 Mpc (DS4) (Fig 2a-b; read-from-figure)	1 /month; 3.86e-07 Hz	comparable MLGWSC-1 DS3/DS4 with the challenge evaluation code: directly comparable with the challenge entries.	*pending*
	events	18 of 31 O3b GWTC-3 BBHs recovered (Sec 1.1, Fig 3; stated)	-		*pending*
`inguglia2026` [17]	reach@FAR	VT relative to LVK pipelines at FAR < 1/yr: O3a 20-100 Msun 0.20-0.54 of matched filter, 0.48-0.56 of cWB; 100-160 Msun 0.54-1.28 and 0.63-1.05 (Sec 5; stated)	0.0821 /month; 3.17e-08 Hz	comparable Real O3-O4 HL data with time-slide FAR, injection-calibrated, and VT against reweighted LVK sensitivity injections: search-grade, although training overlaps part of the O3a test period.	*pending*
	eff@FAR	injection recovery at FAR < 1/yr, O3a: 0.07 / 0.39 / 0.72 / 0.92 at network SNR 10 / 15 / 25 / 40 (Table 1; stated)	0.0821 /month; 3.17e-08 Hz		*pending*
	events	47 detections at FAR < 1/yr in O3a-O4b (44 shared with cWB), none new (Sec 4, Table 3; stated)	-		*pending*

6.3 What cannot be compared, and why

The anomaly literature has no shared definition of normal data, so AUCs and recalls depend on which anomalies were chosen. Only the O3-O4 pipeline with time slides and sensitive volume is search-grade.

The 8 models below have no shared axis; their headline metric is listed with the reason.

Model	Headline metric (location; how)	Why not comparable	gravyflow
`morawski2021` [151]	none extracted	Abstract-level: convolutional autoencoder anomaly detection; no numbers.	*pending*
`fayad2024` [147]	0.89 (LSTM-VAE) vs 0.76 (AE), 10 events vs 10 noise samples (Fig 6; stated)	n = 20 test samples, so AUC carries roughly +-0.1; no SNR distribution, no FAR.	*pending*
`imran2024` [150]	none extracted	Abstract-level: autoencoder on Gravity Spy spectrograms; no numbers.	*pending*
`cain2025` [148]	ROC-AUC 0.994, AP 0.967 (102 O4 events vs 399 noise segments, H1) (Fig 5, Sec 4.4; stated); synthetic BBH SNR 8-25, aLIGO PSD: AUC 0.806 (Table 1; stated)	Catalogue events versus random science segments with an F1-maximising threshold chosen on the test set; the authors show the O1-O4 skill partly tracks run-specific whitening (AUC 0.78 to 0.44 after uniform re-whitening).	*pending*
`guo2025` [149]	per-class AUC vs SNR, e.g. IMRPhenomD 0.561 / 0.855 / 0.993 / 1.000 at SNR 5 / 10 / 15 / 20 (mock Gaussian noise) (Table I; stated); real 4-OGC events detected: 0.04 / 0.24 / 0.80 / 1.0 at single-detector SNR 5 / 10 / 15 / 20 at FAR ~1e-3 Hz (Fig 17; read-from-figure)	Single-detector anomaly flagger at ~3.6 alarms per hour; the FAR is several orders above search thresholds.	*pending*
`inguglia2025` [152]	IMBH-forming BBH: 23 % (unsupervised) / 100 % (weakly supervised) at nominal 4.5/yr (Sec 4.2, Fig 8; stated)	ET mock data, single channel, Gaussian noise; FAR is a nominal Gaussian-tail statement, not a background count.	*pending*
`ma2025overlap` [154]	none extracted	Not read beyond the abstract: separation of overlapping signals for PE; no numbers.	*pending*
`cirfeta2026` [153]	recall at 1 % exceedance: harmonic comb >0.98, scattered light 0.58, blips 0.00 at SNR ~380-430 (Sec V A, Table III; stated)	Glitch-morphology anomaly ranking on O4a with injected SNRs of 200-430; recall at an empirical calibration-pool exceedance, not a FAR.	*pending*

6.4 Suspected errors in the literature

15 suspected errors or internal inconsistencies in 7 papers, selected from the extraction notes (35 notes for this section in the catalogue). Each is a reading of the paper to be checked, not a verdict.

- [146] Supernova sensitivity quoted three ways (SNR 22 at 1/hour; 20-25 at 1-2/month; 50 % at ~27 at 1/yr).
- [71] Catalogue summary "94-98 % per class" does not match Fig 4b (0.90-0.99).
- [71] O3b FARs down to <1e-20 per month come from exponential extrapolation of a one-month background.
- [148] Threshold described as validated (Sec 3) and as F1-optimised on the test set (Sec 4.4).
- [148] Event counts disagree (216 vs 207 vs 192).
- [148] Claimed chirp band to 800 Hz exceeds the Nyquist frequency of the 1024 Hz data.
- [149] Table III caption gives 3.75 per hour for 1e-3 per second (3.6).
- [149] Conclusions report 1482 anomalies in 88.74 h; the body reports 270 in 546 min.
- [152] Abstract 4.5/yr vs conclusions 4.6/yr; the 5-sigma threshold used is ~6.3 sigma on the fitted Gaussian.
- [152] Weak-supervision injections overlap the IMBH test population.
- [153] Blip failure SNR given as ~380 (text) and ~430 (Table III).
- [153] Version-1 catalogue counts are retained but superseded by the author.
- [17] Table 3 has 46 rows against the 47 detections claimed.
- [17] Gate accounting in Sec 6 (53 above threshold, 48 pass, "only two" rejected) does not close.
- [17] Training uses 32 of the 143 O3a blocks that are also searched.

7 Continuous and long-duration waves

Continuous-wave (CW) models search for long, nearly monochromatic signals from spinning neutron stars, or classify the candidates of a semi-coherent search. The field has a shared figure of merit, the sensitivity depth at a fixed false-alarm probability per frequency band, which makes comparison more direct than in the transient categories.

7.1 Families and lineage

7.1.1 Deep-learning CW searches against WEAVE

Dreissigacker et al. set the benchmark of sensitivity depth at 1 % false alarm per 50 mHz against the WEAVE coherent search [155], [156] large-kernel CNNs, U-Nets and vision transformers later approached the matched-filter depth on the same style of benchmark [157], [158], [159], [160].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 9 models: [155], [156], [161], [162], [157], [158], [160], [159], [163]. Results will be placed on the shared axes of this section beside the published values.

7.1.2 Candidate follow-up and clustering

Networks that act on the output of a semi-coherent search: Viterbi maps [164], Einstein@Home candidate clusters [165], [166], TD-Fstat distributions [167], FrequencyHough candidates [168] and excess-power selection [169], [170].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 7 models: [167], [164], [165], [166], [169], [170], [168]. Results will be placed on the shared axes of this section beside the published values.

7.1.3 Long and intermittent signals

Post-merger remnant transients and intermittent backgrounds [171], [172].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 2 models: [171], [172]. Results will be placed on the shared axes of this section beside the published values.

7.2 Comparison on the shared axes

Rows are the models graded comparable or conditionally comparable (10 of 18); each axis entry is one row. FAR is converted to per month (30 d) and to Hz where the paper states a rate.

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
`dreissigacker2019` [155]	depth@pfa	D90 10.8 vs WEAVE 11.4 (20 Hz) and 7.7 vs 9.7 (1000 Hz), T = 1e5 s, pfa 1 % per 50 mHz (Tables IV, VI; stated)	-	comparable Single detector, Gaussian noise; depth at a per-band false-alarm probability against a matched-filter (WEAVE) depth on the same setup: the CW benchmark convention.	*pending*
`bayley2020` [164]	depth@pfa	depth ~10 Hz^-1/2 at 95 % efficiency, 1 % FAP per sub-band (S6 MDC) (Abstract, Fig 10b; stated)	-	conditional D95 (not D90) on S6 mock data with a SOAP + CNN pipeline.	*pending*
`dreissigacker2020` [156]	depth@pfa	all-sky DNN ~7 % (20 Hz) to ~51 % (1000 Hz) less deep than WEAVE (WEAVE D90 16.0 to 13.6, T = 1e5 s) (Table IV and results; stated)	-	comparable Two detectors, Gaussian and realistic noise; D90 at pfa 1 % per 50 mHz against WEAVE on the same setup.	*pending*
`yamamoto2021cw` [169]	depth@pfa	D95 ~80 Hz^-1/2 at overall FAP 1 % (headline), 20-120 across the parameter scan (Sec VI, Fig 6; stated)	-	conditional Single-detector Gaussian data; the 95 % check skips the coherent follow-up.	*pending*
`yamamoto2022cw` [170]	depth@pfa	D95 43.9 Hz^-1/2 at FAP ~0.66 % (Gaussian); 3.62 with a unit-amplitude line at FAP ~10 % (Eqs 4.2, 4.4; stated)	-	conditional Single 100 Hz bin of simulated data; the line and no-line depths are at different FAPs.	*pending*
`joshi2023` [157]	depth@pfa	p_det 87.4-89.0 % at the matched-filter D90 (86.2 / 81.8 Hz^-1/2), pfa 1 %, targeted 10-day search (Table IV; stated)	-	comparable White Gaussian H1+L1, single template; p_det at the matched-filter depth is the direct comparison.	*pending*
`joshi2024large` [158]	depth@pfa	all-sky p_det at WEAVE depth 67.0 / 52.8 / 47.6 / 41.5 / 38.8 % (20 / 100 / 200 / 500 / 1000 Hz); D90 29.3 to 18.3 Hz^-1/2 (Tables V-VI; stated)	-	comparable Simulated white Gaussian H1+L1, 10 days; WEAVE depths rescaled by sqrt(T).	*pending*
`cheung2025unet` [160]	depth@pfa	D90 29.97 (20 Hz) to 17.10 (1000 Hz) Hz^-1/2 at 1 % per 50 mHz; WEAVE 40.28 to 34.50 on a different setup (Table II; stated)	-	conditional O3-like two-detector data; the WEAVE reference comes from another search setup.	*pending*
`joshi2025vit` [159]	depth@pfa	p_det at the F-statistic depth: targeted 87.3-89.7 %, directed 84.8-88.7 %, all-sky 88.3 % (20 Hz) to 78.2 % (1000 Hz) (Table IV; stated)	-	comparable Same benchmark family as joshi2023/2024 (white Gaussian H1+L1).	*pending*
`tenorio2025g2net_cw` [163]	AUC	G2Net CW Kaggle private AUC: 1st 0.860, 2nd 0.854, SOAP 0.604 (Fig 5; stated)	-	conditional Competition data with SNR ~ Gamma(5, 9) in mixed Gaussian and real O3 noise; AUC comparable across entries of this competition only.	*pending*

7.3 What cannot be compared, and why

CW results are comparable when they share the convention of sensitivity depth at a false-alarm probability per frequency band and the same data span (or are rescaled by the square root of the span, which several papers do explicitly). Candidate-clustering efficiencies and toy-model detectability thresholds are not on that axis.

The 8 models below have no shared axis; their headline metric is listed with the reason.

Model	Headline metric (location; how)	Why not comparable	gravyflow
`miller2019` [171]	50 % efficiency at h0 ~3.6e-23 (150-300 Hz) at per-map FAP ~1 % (CNN) vs ~0.01 % (FrequencyHough) (Figs 3, 6; read-from-figure)	Long-transient maps in real O2 L1 noise; the CNN and FrequencyHough are compared at FAPs 100x apart.	*pending*
`morawski2020cw` [167]	CW-vs-rest AUC 0.99 (1D and 2D CNN); TPR 96.3 % at 1 % FPR (Fig 7, Table 2; stated)	Classifier of TD-Fstat outputs in white Gaussian noise with injected SNR 8-20.	*pending*
`beheshtipour2020` [165]	cluster-identification efficiency 97 % (1137 of 1171) on Einstein@Home result images (Sec III; stated)	Post-processing of search candidates; efficiency for loud, visible signals.	*pending*
`beheshtipour2020b` [166]	cascade efficiency 92 % above normalised amplitude 1/60 vs deterministic clustering 83 % (Sec IV-V; stated)	Einstein@Home O2 candidate clustering; comparable only with the deterministic clustering it replaces.	*pending*
`dominguez2023` [161]	none extracted	Qualitative only; the abstract reports degradation on real O3 data.	*pending*
`duraisamy2023` [162]	none extracted	Not read; no abstract.	*pending*
`yamamoto2023` [172]	minimum detectable SNR rho_90 0.7 to 2.8 vs duty cycle at FAP 5 % (Fig 4; read-from-figure)	Toy intermittent-background model in white noise; no detector data conventions.	*pending*
`dicesare2026fh` [168]	injection at h0 7.76e-26 identified below the O3 follow-up sensitivity (Sec 5; stated)	Follow-up classifier of FrequencyHough candidates; accuracy tables not extracted.	*pending*

7.4 Suspected errors in the literature

25 suspected errors or internal inconsistencies in 14 papers, selected from the extraction notes (40 notes for this section in the catalogue). Each is a reading of the paper to be checked, not a verdict.

- [155] "Nearly rivaling matched filtering" is a fixed-depth comparison where matched filtering is 90 % by construction.
- [171] 500 maps of 2000 s are said to span ~11.5 days and 2000 maps ~23 days (should be ~46).
- [171] ~1 microsecond vs 1 minute per map is ~7 orders of magnitude, not "at least 5".

- [171] 64,000 noise maps are built from 2,000 unique ones.
- [167] Stated dataset total (292,500) is inconsistent with 6 bands x 13 SNRs x 7,500.
- [164] 95 % sensitivities given as SNR 85 / 115 (Sec VI A) and 90 / 120 (Sec VII).
- [164] SNR range 20-200 in Sec VI A vs 50-150 in the explanation of the high-SNR drop.
- [165] 1345 returned - 1137 correct = 208 wrong clusters, but the text reports 174 false alarms.
- [166] Conclusion: 80 % at 1/80 sqrt(Hz); Fig 9's lowest bin reads ~0.84.
- [166] 132,524,538 pixels quoted for a 512 x 512 image.
- [169] Headline D95 ~80 differs from the worked example (~100, Fig 5) without stating which setting it refers to.
- [170] Abstract FAP ~0.5 % vs 0.66 % from the 20,000-event test.
- [170] The 8.2 % depth ratio compares FAP 10 % with FAP 0.66 %.
- [170] Efficiency "one or two orders of magnitude" vs SOAP's three orders in Table VII.
- [157] Matched-filter parity claimed at 88.3 % mean against 90 % by construction (~1.7 points lower).
- [157] Kernel width of 313 bins is 3.62 mHz at 1/day resolution, not 3.4 mHz.
- [172] FAP 0.05 in the main text vs FAP = FDP = 0.1 in Appendix Fig 10.
- [172] Claimed parity with the optimal statistic holds only for log10 xi > -1.75 (Fig 4).
- [158] Table VI compares 10-day depths with unrescaled 1e6 s depths of the earlier work.
- [158] p_fa calibration changes between validation (0.76 % per 38 mHz) and test (0.48 %).
- [158] Abstract claims high sensitivity at all frequencies for the single DNN, which reaches 30-40 % p_det at the matched-filter depth.
- [160] "Comparable sensitivity at 20 and 200 Hz" vs p_det 69 % and 46 % at the matched-filter depth (Table II).
- [159] Targeted reference time and D90 (86.1 / 81.6) differ slightly from joshi2023 (86.2 / 81.8) although described as the same benchmark.
- [163] Table 2 headers say <rho^2> but values behave as rho.
- [163] Legend AUC order (KDL 0.789 7th, MC Digital 0.791 8th) disagrees with the ranking.

8 Glitch classification and data quality

Glitch classification began with Gravity Spy, whose citizen-science labels and image format became the de facto benchmark. Later work changed the backbone, the input view, the class set and the data release, which is why accuracies from different papers rarely share a test set.

8.1 Families and lineage

8.1.1 Gravity Spy supervised classifiers

Gravity Spy introduced multi-duration Omega-scan images and a CNN trained on citizen-science labels [20], [21], [173] transfer learning [174], [175], [176], new releases and classes [22], [23], [177], and new architectures [178], [179], [180], [181], [182] followed.

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 22 models: [21], [174], [20], [173], [175], [176], [22], [183], [182], [184], [178], [23], [185], [181], [186], [180], [179], [177], [187], [188], [189], [190]. Results will be placed on the shared axes of this section beside the published values.

8.1.2 Unsupervised and similarity methods

Embeddings and clustering for unseen classes [191], [192], [193], [194], [195], [196], [197], [198], [199], [200].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 11 models: [191], [192], [200], [201], [193], [194], [199], [195], [198], [196], [197]. Results will be placed on the shared axes of this section beside the published values.

8.1.3 Signal-versus-glitch vetoes

Classifiers that separate astrophysical signals from glitches for a search [202], [203], [204], [205], [206], [207], [208], [209], [210].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 10 models: [204], [202], [209], [203], [208], [207], [206], [210], [211], [205]. Results will be placed on the shared axes of this section beside the published values.

8.1.4 Auxiliary-channel data quality

Models that read witness channels rather than strain [212], [213], [214], [215].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 4 models: [215], [213], [212], [214]. Results will be placed on the shared axes of this section beside the published values.

8.1.5 Early and simulated-glitch classifiers

Classifiers of simulated morphologies in Gaussian noise [216], [217], [218], [219], [220], tabular metadata models [221], [222] and glitch generators [223], [224].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 9 models: [216], [217], [219], [218], [220], [223], [221], [224], [222]. Results will be placed on the shared axes of this section beside the published values.

8.2 Comparison on the shared axes

Rows are the models graded comparable or conditionally comparable (14 of 56); each axis entry is one row. FAR is converted to per month (30 d) and to Hz where the paper states a rate.

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
`bahaadini2017` [21]	GS	merged-view CNN accuracy 96.89 % (20 classes, Gravity Spy O1, 7,730 glitches, 75/12.5/12.5 split) (Tables 2-3; stated)	-	conditional Gravity Spy O1 20-class set with its own split; accuracy only (no macro-F1).	*pending*
`george2017tl` [174]	GS	top-1 98.84 % (ResNet50, Inception-V3), 22 classes, Gravity Spy O1, random 80/20 split (Table 1; stated)	-	conditional arXiv version of george2018glitch (PRD 97 101501(R)); same numbers.	*pending*
`zevin2017` [20]	GS	average test accuracy 97.1 % (20 classes, Gravity Spy O1, 7,718 glitches); per-class recall mean ~0.90 (Sec 4.1, Fig 7; stated)	-	conditional The Gravity Spy reference; accuracy is sample-weighted.	*pending*
`george2018glitch` [175]	GS	top-1 accuracy 98.84 % (Inception-V3, ResNet50), 22 classes, Gravity Spy O1 ~8,500 images, random 80/20 split (Table 1; stated)	-	conditional Gravity Spy O1 22-class set with a single random split and no validation set.	*pending*
`soni2021` [22]	GS	validation accuracy 98.8 % (expert) / 97.5 % (volunteer), 23 classes, Gravity Spy O3 (9,631 examples) (Sec 2.2-2.3; stated)	-	conditional Validation, not held-out test, accuracies on the O3 23-class set.	*pending*
`yan2022gan` [182]	GS	weighted F1 0.9885 (Inception-V3, GAN N=5000, no pre-training) vs 0.9880 (pre-trained baseline), Gravity Spy 1.0, 21 classes (Table 4; stated)	-	conditional Gravity Spy v1.0 own split, 5-run means.	*pending*
`bini2023` [209]	reach@FAR	cWB XGBoost+AE vs XGBoost: sensitivity-volume gain at IFAR 50 yr +8 to +44 % (SG), +33 % (cosmic strings) (Sec 5.2, Fig 4; stated)	0.00164 /month; 6.34e-10 Hz	conditional Glitch-rejection feature inside cWB on 40 d of O3b with ~380 yr of time slides; relative to the cWB XGBoost baseline.	*pending*
`fernandes2023` [178]	GS	macro-F1 97.18 %, accuracy 98.68 % (ResNet18 baseline), 22 classes, Gravity Spy O1+O2 held-out test (Table I; stated)	-	conditional One of the few Gravity Spy papers to report macro-F1; split is the authors' own.	*pending*
`glanzer2023` [23]	GS	O3 model train 99.9 % / validation 98.8 % (23 classes, 9,631 samples); O1-O2 model train 98.2 % (Sec 2.3; stated)	-	conditional Data-release paper quoting the published Gravity Spy accuracies; no test accuracy.	*pending*
`licciardi2024` [181]	GS	random-forest accuracy 91.03 % (WST + Q-transform) vs 87.41 % (Q-transform), Gravity Spy 1.1.0, 21 classes (Table II; stated)	-	conditional Gravity Spy 1.1.0 after the authors' own cleaning; accuracy only.	*pending*
`srivastava2024` [180]	GS	accuracy 92.26 %, F1 92.13 % (24 classes: Gravity Spy O1/O2 + 2 O3a classes) (Sec 3; stated)	-	conditional Custom 24-class set mixing Gravity Spy images with authors' Q-transforms; F1 averaging unstated.	*pending*
`wu2024` [179]	GS	accuracy 0.941 / F1 0.931 vs retrained Gravity Spy 0.906 / 0.904 on the same split (23 classes, O3, confidence > 0.9) (Tables 2, 4; stated)	-	conditional Re-trains the previous Gravity Spy model on the same split, so the internal comparison is fair; split differs from other papers.	*pending*
`zevin2024` [177]	GS	re-quoted: 97.1 % (2017, 20 classes), 98.2 % (2018, 22 classes); O3 model train 99.9 / val 99.8 % (Sec 3.2, Table 1; stated)	-	conditional Review quoting earlier results.	*pending*
`vandyke2025` [205]	AUC	CoBiTS 0.953 vs ResNet18 0.900 vs newSNR 0.945 (all scenarios, H1 O3, 4,000 test segments) (Fig 4; stated)	-	conditional Single-detector signal-vs-glitch discrimination with a matched-filter statistic on the same segments.	*pending*
	eff@FAP	TPR at FPP 1e-3: 0.82 vs 0.70 vs 0.66 (Fig 4; read-from-figure)	-		*pending*

8.3 What cannot be compared, and why

Gravity Spy accuracies differ in release (O1 20-class, O1 22-class, v1.0/1.1/1.2, O3 23-class), in split (random, stratified, own cleaning) and in averaging (sample-weighted accuracy versus macro-F1), and several are validation rather than test numbers. They are graded conditional at best; the one internally fair comparison is a paper that retrains the previous Gravity Spy model on its own split. Clustering scores (NMI, ARI, silhouette), generator-fidelity scores and auxiliary-channel classifiers are on different axes.

The 42 models below have no shared axis; their headline metric is listed with the reason.

Model	Headline metric (location; how)	Why not comparable	gravyflow
`powell2015` [216]	per-morphology cluster fractions on simulated SG/Gaussian/ringdown transients (PCAT/LIB/WDF-ML) (Tables 2-3; stated)	Simulated transients in Gaussian noise; each method analyses a different subset.	*pending*
`powell2016` [217]	none extracted	Real ER7 glitches scored against the authors' visual labels; class counts only.	*pending*
`bahaadini2018` [173]	none extracted	Not read (paywalled journal version).	*pending*
`bahaadini2018direct` [191]	NMI 0.598 / ARI 0.455 (DIRECT) vs autoencoder 0.545 / 0.324 on 5 held-out Gravity Spy 1.0 classes (Table 1; stated)	Clustering of unseen classes; embedding size chosen on the evaluation classes.	*pending*
`cavaglia2018` [215]	genetic-programming recall 0.934, precision 0.937 (magnetometer-glitch attribution) (Table 2; stated)	Auxiliary-channel origin attribution for one glitch class.	*pending*
`llorensmonteagudo2018` [219]	dictionary-learning accuracy 96.0 % on 3,000 simulated glitches (SNR 1-400) (Sec 5.2; stated)	Three simulated morphologies in Gaussian noise.	*pending*

Model	Headline metric (location; how)	Why not comparable	gravyflow
razzano2018 [218]	accuracy 0.998 on 6 simulated glitch families + noise (Table 4; stated)	Fully synthetic, near-saturated problem.	*pending*
coughlin2019 [192]	data reduction at 50 % retention: ~0.99 (Raven Peck), ~0.99 (Water Jet, DIRECT) (Fig 3; read-from-figure)	Similarity search; no classification or detection metric.	*pending*
colgan2020 [213]	auxiliary-channel glitch vs clean: AUC 0.93 (ER14), 0.91 (O3); accuracy 0.799 (O3) (Fig 6, Sec III; stated)	Balanced glitch / glitch-free samples from auxiliary channels; accuracy depends on the 50:50 prior.	*pending*
essick2020 [212]	iDQ glitch-detection efficiency 10-40 % at clean-time FAP 0.1-1 % (Sec V; stated)	Auxiliary-channel data-quality statistic scored over clean-time samples.	*pending*
ding2021 [200]	none extracted	Qualitative anomaly detection; no numbers.	*pending*
mesuga2021 [176]	AUC 0.990 (VGG19), averaging unstated, Gravity Spy 22-class Kaggle copy (Fig 7; stated)	AUC only; the accuracy in the Fig 9 title is not the matrix accuracy.	*pending*
sankarapandian2021 [201]	linear-probe accuracy 81.6 % on Gravity Spy latents (Table 1; stated)	Unsupervised encoder with linear probe; split unstated.	*pending*
bahaadini2022 [193]	NMI 0.61 (VAT + discriminative) vs DIRECT 0.53 on 10 held-out Gravity Spy v1.2 classes (Table III; stated)	Clustering of held-out classes.	*pending*
boudart2022glitch [220]	glitch / chirp / background map classification >95.5 %; chirp class 90.2 % (Sec III; stated)	Synthetic coherence maps of long transients.	*pending*
choudhary2022 [204]	+75 % relative sensitivity over chi-square vetoes at FPR 1e-2 (80-140 Msun, SNR 3-8) (Abstract, Fig 5; stated)	BBH-vs-blip veto ROC on simulated BBH and Gravity Spy blips.	*pending*
colgan2022 [214]	scattered-light vs clean accuracy 97.1 % (test, 25 of 39,147 aux channels) (Sec IV A; stated)	Balanced auxiliary-channel classification on one day of L1.	*pending*
dooney2022 [223]	discriminative score WGAN vs DVGAN (e.g. pulse 0.029 vs 0.009); BBH match 0.9918 vs 0.9917 (Table I; stated)	Generator fidelity metrics.	*pending*
sakai2022 [194]	unsupervised cluster-purity 90.9 % (36 clusters vs 22 labels, Gravity Spy O1) (Discussion; stated)	Custom purity score on training data with C chosen by the same labels.	*pending*
talpini2022 [183]	none extracted	Abstract-level; no numbers.	*pending*
alvarez2023 [202]	GSpyNetTree signal-vs-glitch accuracy ~97 % (LM / HM / EHM, Inception-V3) (Fig 5; stated)	Glitch classes plus injected CBC; balanced classes, no FAR.	*pending*
apostol2023 [221]	DeepWaves ensemble 10-fold accuracy 0.91 on Gravity Spy O1 metadata (22 classes) (Table 4; stated)	Tabular metadata, not images; features include GPS time and ID.	*pending*
biskin2023 [184]	none extracted	Not read.	*pending*
jarov2023 [203]	GSpySVG GW accuracy 98.2 % (LM) / 96.2 % (HM); glitches 197/200 (Table IV; stated)	Signal-vs-glitch on ~500 injections and 200 glitches per classifier.	*pending*
laguarta2023 [199]	177 of 2,688 glitches flagged as anomalies by manual t-SNE inspection (Sec V; stated)	Unsupervised autoencoder evaluated on its training data with no labels.	*pending*
shah2023 [208]	random-forest accuracy 0.93 (H1) / 0.94 (L1); macro recall ~0.81 / ~0.85 (Sec 5.2, Fig 4; stated)	Six-class custom set with synthetic GWs in Gaussian noise beside real glitches.	*pending*
arutkeerthi2024 [207]	glitch vs merger accuracy ~96 % on 308 validation samples (Sec VII; stated)	Small set with augmentation that can leak events across splits.	*pending*
koyama2024 [185]	none extracted	Not read.	*pending*
li2024ctsae [195]	ARI 0.409 / NMI 0.636 (CTSAE) vs DIRECT 0.214 / 0.428 on Gravity Spy O3 test (23 classes) (Table 2; stated)	Unsupervised clustering.	*pending*
magee2024interp [206]	signal-vs-glitch TPR 0.941-0.999 at FPR 0-0.004 (simulated) (Figs 3-4; read-from-figure)	Signal-consistency classifier on simulated glitches.	*pending*
malz2024 [186]	conformal prediction sets: macro-F1 0.456, mean set size 4.26 of 22 at alpha 0.1 (Table II; stated)	Set-valued uncertainty on top of Gravity Spy; not a single-label score.	*pending*
bhandari2025 [187]	none extracted	Not read.	*pending*
chan2025 [210]	localisation recall at IoU 0.3: GW 93.7 %, Blip 94.3 %, Scattering 52.4 % (Table 3; stated)	Object localisation on 1 s Q-transforms.	*pending*
gupta2025ae [211]	none extracted	Abstract-level; custom 1,200-sample set.	*pending*
oshino2025 [198]	none extracted	Abstract-level; no numbers.	*pending*
singh2025 [188]	none extracted	Not read.	*pending*
deshmukh2026 [196]	none extracted	Silhouette and t-SNE only; no numbers.	*pending*
dooney2026 [224]	Gravity Spy accuracy on GlitchGAN samples 79.3 % vs 89.6 % on real reconstructions (n = 700) (Tables IV-V; stated)	Generator fidelity scored by the Gravity Spy classifier; depends on injected SNR.	*pending*
fernandes2026 [189]	Virgo O3b 7-class ResNet34 accuracy 0.983, F1 0.977 (1,679 test) (Sec IV; stated)	Virgo merged-class taxonomy; F1 averaging unstated.	*pending*
kim2026kagra [197]	KAGRA O3GK clustering: DEC NMI 0.367, ConvAE+PCA ARI 0.436 (Table 3; stated)	Custom KAGRA taxonomy.	*pending*
manoharan2026 [222]	tabular Gravity Spy O3 metadata: XGBoost weighted F1 ~0.853 (Figs 4-5; read-from-figure)	Tabular metadata including timestamps.	*pending*
xie2026 [190]	none extracted	Abstract-level; no numbers.	*pending*

8.4 Suspected errors in the literature

60 suspected errors or internal inconsistencies in 38 papers, selected from the extraction notes (132 notes for this section in the catalogue). Each is a reading of the paper to be checked, not a verdict.

- [216] WDF-ML ">97 %" for both sets vs 91.3 % for SG in set 2 (Table 3).
- [217] WDF-ML H1 class counts sum to 1829, not the 1865 transients classified.
- [217] WDF-ML L1 overall accuracy 95 % is not reproducible from the listed misclassifications (~97 %).
- [21] Text says Air Compressor is perfect for both classifiers; Table 4 gives 80 % for classifier 4.
- [21] Architectures optimised for best test accuracy with no error bars (~966 test samples).
- [174] No validation set while the best of 100 epochs was chosen, i.e. selection on test.
- [174] Paired Doves training size 21 (text) vs 24 (Fig 3 caption).
- [20] "Average accuracy 97.1 %" is the sample-weighted accuracy; the mean of the printed per-class recalls is ~0.90.
- [20] Fig 7 caption says training-set normalisation while titled test set.
- [191] k = 200 is selected from NMI/ARI on the same unknown classes used in Table 1.
- [215] Table 2 caption swaps FN and FP definitions.
- [175] "Above 98.8 %" holds for two of five models (Table 1).
- [175] Dataset ~8,500 vs 7,932 for the same O1 release in Glanzer 2023.
- [218] Per-class accuracy, precision, recall and F1 are identical in every row of Table 4, which is not possible in general for a multi-class matrix.

- [192] Raven Peck reduction given as 99.9 % (text), 99.0 % (caption) and 0.93-0.97 (Table I).
- [192] Raw pixels match or beat DIRECT for Raven Peck (Fig 3).
- [176] Fig 9 title prints 98.98 % accuracy; the diagonal gives ~89 % (the digits match the AUC).
- [176] Table I counts 7,966 images vs 31,868 in the text (four views each).
- [22] Fast Scattering count 55,279 (Sec 3.2) vs 55,211 (conclusions).
- [193] Table III and Fig 6 give different NMIs at the same label fraction.
- [193] Pair accuracy 49.07 % at both 0.1 % and 1 % labels (chance level).
- [220] "More than 95 %" of glitches retrieved is the weaker combined class (glitch-only 99.46 %).
- [204] The 75 % is a relative gain at one bin and FPR without absolute TPRs.
- [223] WGAN bolded for BBH match on a 1e-4 difference with zero stated bounds.
- [194] Eq 1 as printed sums to a value up to 36, not a fraction.
- [182] "Comparable or exceeding transfer learning" rests on a 0.0005 difference inside 0.003 error bars.
- [182] Minority-class F1 rests on 4-9 test images.
- [202] Identical 97 % for three classifiers with different class sets.
- [202] LM GW accuracy 96 % (text) vs 97 % (caption).
- [221] GPS time and Gravity Spy id are among the features (possible label leakage).
- [209] Abstract says "up to 30 %"; Fig 4 gives up to +44 %.
- [178] Text says < 0.2 pp below fine-tuned ResNet50; Table I gives 0.47 pp.
- [178] Conclusion quotes validation F1 gains while the test set shows the opposite ordering.
- [23] Abstract glitch totals do not match the Table 1 sums.
- [23] 8,427 + 1,203 = 9,630, not 9,631.
- [203] Table II Paired Doves 279 is a typo for 27 (the column then sums to 9,631).
- [203] Abstract "100 % of confirmed events as true signals" vs 19/21 labelled GW.
- [203] Glitch accuracy quoted as 99 %; counts give 98.5 %.
- [199] Scattered Light 28 % + 72 % already makes 100 %, leaving no room for the overlap case.
- [208] "Mean accuracy" is the sample-weighted accuracy; macro recall is 0.81 / 0.85.
- [208] Modes-only results called "quite similar" while Koi Fish recall falls from 0.93 to 0.64.
- [207] Each event contributes two detectors and a shifted copy, which can straddle the split.
- [195] Table 1 split sums to 41,655 vs 41,745 stated.
- [195] Claims superiority over deployed semi-supervised methods, but VAT at 5 % labels is better (Table 2).
- [181] Text says second-order WST slightly improves on first order; Table I gives 68.65 % vs 88.11 %.
- [181] "More than one order of magnitude" faster vs measured 1.07-3.35x.
- [206] Fig 3 caption FPR 0.7 % vs the printed 0.3 %.
- [206] Toy-pipeline TPR/FPR at rho 7 differ between Sec III C and the Fig 7 caption.
- [180] The two added classes come from a different image pipeline, a possible shortcut feature.
- [179] Stated split (8,439 / 1,687 / 3,538) disagrees with Table 1 sums (6,537 / 1,637 / 4,448).
- [177] O3 model validation 99.8 % here vs 98.8 % in Soni 2021 / Glanzer 2023.
- [177] Train/validation accuracies set beside earlier test accuracies.
- [210] FP percentages for GW (0.1 %) and Blip (0.2 %) do not follow from the counts (1.2 %, 1.9 %).
- [205] Caption says CoBiTS beats ResNet "in all cases"; no-glitch AUCs are 0.976 vs 0.975.
- [205] Test BBH waveforms were left in the training pool.
- [224] Epoch chosen partly by the UMAP overlap later reported as fidelity evidence.
- [197] Silhouette scores are computed in each method's own feature space and cannot rank methods.
- [222] Discussion calls DANet the best model while XGBoost leads Figs 3-4.
- [222] Fig 3 box-plot medians (0.11-0.43) are inconsistent with Figs 4-6 (0.68-0.85).
- [222] Per-sample inference times of seconds to minutes on 9 features are not credible.

9 Denoising and signal extraction

Denoising work splits into waveform reconstruction (recover the injected signal from strain; scored by overlap or match) and noise regression (subtract noise witnessed by auxiliary channels; scored by range gain).

9.1 Families and lineage

9.1.1 Waveform reconstruction

Recurrent denoising autoencoders [24], [225], [226], [227] gave way to convolutional, U-Net and transformer reconstructors on real noise [228], [229], [230], [231], [232], [233], [234].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 18 models: [24], [225], [226], [227], [228], [235], [236], [231], [232], [234], [237], [238], [239], [229], [230], [233], [240], [241]. Results will be placed on the shared axes of this section beside the published values.

9.1.2 Noise regression with witness channels

DeepClean subtracts noise witnessed by auxiliary channels [25], [242], [243], [244], with non-linear regression studies alongside [245], [246].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 7 models: [25], [245], [246], [242], [243], [244], [247]. Results will be placed on the shared axes of this section beside the published values.

9.1.3 Glitch subtraction and gap filling

Removing or bridging transient noise [248], [249], [250], [251].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 4 models: [250], [248], [249], [251]. Results will be placed on the shared axes of this section beside the published values.

9.1.4 Third-generation and space-based extraction

Einstein Telescope and Taiji studies [252], [253], [254].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 3 models: [252], [253], [254]. Results will be placed on the shared axes of this section beside the published values.

9.2 Comparison on the shared axes

Rows are the models graded comparable or conditionally comparable (13 of 32); each axis entry is one row. FAR is converted to per month (30 d) and to Hz where the paper states a rate.

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
`shen2019` [225]	overlap	EDRDAE 0.994 (quasi-circular) / 0.985 (eccentric) vs DRDAE 0.906 / 0.955 at MF SNR ~6.4, real LOSC noise (Table 2; stated)	-	conditional One SNR, one 4096 s noise stretch; whether Table 2 is a test-set mean is not stated.	*pending*
`ormiston2020` [25]	range	O2 H1 BNS range +~20 % (~70 to ~84 Mpc); injection SNR +21.6 % (Fig 4; read-from-figure)	-	conditional DeepClean noise regression on real O2 data; range gain is comparable with later DeepClean papers only.	*pending*
`wei2020denoise` [226]	overlap	>= 0.97 for SNR >= 12 (Gaussian); GW150914 / GW170104 / GW170814 0.99, GW170608 0.73 (Figs 2-3; stated)	-	conditional Time- and phase-maximised overlap; real-event results are single cases.	*pending*
`chatterjee2021` [227]	overlap	>0.95 for >95 % of Gaussian-noise samples (chirp mass 15-50); O1/O2 events 0.967-0.995 (Fig 8; stated)	-	conditional Merger-centred 0.25 s windows, single detector.	*pending*
`saleem2023` [242]	range	GstLAL VT ratio DeepClean/raw 1.00-1.026 at FAR 1e-5 to 1e-6 Hz on ~20 d of O3 (Fig 4; read-from-figure)	-	conditional DeepClean 60 Hz subtraction measured through a production search; relative to LIGO's own cleaned frames.	*pending*
	PE	P-P combined KS p 0.0011 (before) vs 0.0008 (after), 78 BBH (Fig 6; stated)	-		*pending*
`chatterjee2024harm` [231]	overlap	86 % of 1,000 O3b injections (SNR 8-30) with overlap > 0.9; real events 0.74-0.98 vs cWB / LALInference (Sec 3.1, Table 2; stated)	-	conditional Higher-mode reconstruction in real noise.	*pending*
`lin2024` [234]	overlap	BBH mean overlap ~0.75 (2 s) / ~0.88 (0.25 s) at SNR 25; real events with 0.25 s overlap > 0.5: H1 37.8 %, L1 48.8 % (Fig 3, Sec III B; read-from-figure)	-	conditional Noise-weighted overlap on real O2/O3 noise with known signal position.	*pending*
`wang2022waveformer` [229]	overlap	94.58 % of O3b injections (SNR > 6) with overlap > 0.9; GW150914 > 0.99 (Sec 3.3; stated)	-	conditional Overlap on real O3b noise; the headline depends on the unstated low-mass share.	*pending*
	events	IFAR improved for 75 BBH events (custom time shifts on denoised data) (Sec 3.4; stated)	-		*pending*
`dooney2025` [230]	overlap	median mismatch 0.9 % (DeepExtractor, white noise, SNR 7.5-250); 0.3 % vs BayesWave 1.9 % on a subset (Table I; stated)	-	conditional Glitch and signal reconstruction in white noise; the BayesWave comparison uses a different (SNR >= 15) subset.	*pending*
`kiendrebeogo2025virgo` [243]	range	Virgo O3b BNS range +1.3 Mpc (2.5 %) from 13-band DeepClean (Sec III D; stated)	-	conditional DeepClean on Virgo; comparable with the other DeepClean range gains.	*pending*
`lee2025` [233]	overlap	74 % of 14,399 O3a injections with overlap > 0.8 (SNR 4-25) (Sec 3.2; stated)	-	conditional Signal always present at a fixed position; the test SNR is weighted towards low values.	*pending*
`reissel2025` [244]	range	Hanford O4 BNS range +1.4 % (+4.3 % volume) (Results, Fig 8; stated)	-	conditional Coherence DeepClean on real O4; comparable with other DeepClean gains.	*pending*
`pimpalkar2026` [251]	reach@FAR	IAS-HM VT ratio up to ~1.18 (q = 0.25, m1 ~300 Msun) at IFAR > 1 yr, O3b (Fig 7; read-from-figure)	0.0821 /month; 3.17e-08 Hz	conditional Wavelet-network re-ranking inside the IAS-HM search; relative VT.	*pending*

9.3 What cannot be compared, and why

Overlap is defined differently across papers (maximised over time and phase or not, whitened or not, normalised or not, over a full window or a short window around the peak), and the SNR distribution of the test set is often weighted towards loud signals. Noise-regression papers report range gains on particular days of data, which compare only within DeepClean-type studies.

The 19 models below have no shared axis; their headline metric is listed with the reason.

Model	Headline metric (location; how)	Why not comparable	gravyflow
`shen2017` [24]	SMTDAE 0.986 vs PCA 0.814, dictionary 0.691 at MF SNR 12.9 (single example, white noise) (Fig 2; stated)	One hand-shown example per SNR; no test-set statistics.	*pending*

Model	Headline metric (location; how)	Why not comparable	gravyflow
`torresforne2020` [250]	blip residual SNR estimator ~1.2-1.7 after combined dictionaries (16 test blips) (Table I; stated)	Self-defined estimators; no ground-truth overlap.	*pending*
`vajente2020` [245]	70 Msun BBH range 729.3 to 754.6 Mpc (+11 % volume), non-neural regression (Sec IV 3; stated)	Main method is not a neural network; the GRU appendix has no numbers.	*pending*
`mogushi2021` [248]	mSTFT overlap of network estimate vs extracted glitch: median 0.65 (scattered light), 0.86 (loud glitches) (Secs 3.1-3.2; stated)	Witness-channel glitch subtraction scored in a time-frequency overlap; not a waveform overlap.	*pending*
`mogushi2021nnetfix` [249]	gap-filling R^2 0.81-0.83; reconstruction efficiency 0.31 to >0.95 (Secs 2-3; stated)	Gated-data reconstruction scored by R^2 and fractional match gain.	*pending*
`yu2021noise` [246]	~10x angular-noise ASD reduction at 10 Hz (simulated bilinear coupling) (Sec 3; stated)	Simulated noise regression; the authors report no broadband gain on real data.	*pending*
`bacon2022` [228]	6.6 % of test signals with overlap < 0.75 (L1 O1 noise) (Sec 3.1; stated)	The overlap of Eq 8 is not normalised by the denoised norm and is unbounded.	*pending*
`murali2022` [235]	none extracted	Abstract-level; no numbers.	*pending*
`ghalsasi2023` [236]	G2Net subset validation AUC 0.834 (EfficientNet) vs 0.833 (U-Net N2C + EfficientNet) (Table I; stated)	Denoiser judged by a downstream AUC on G2Net data.	*pending*
`chatterjee2024rec` [232]	GW190412-like injection, SNR 22: 0.88 (XPHM), 0.71 (SEOBNRv4PHM), 0.87 (NRHybSur) (Sec 3.2; stated)	Single-realisation overlaps; uncertainty intervals without a coverage test.	*pending*
`ma2024et` [252]	early-inspiral fraction with overlap > 0.9: ~70 % to ~95 % with transformer + regularity model (ET, SNR 20-80) (Sec IV A, Fig 10; stated)	Non-maximised overlap on loud synthetic ET BNS; test SNR up to twice the training maximum.	*pending*
`ma2024mix` [253]	both of two coincident BBHs separated (overlap > 0.9) in ~83 % of 1000 samples (ET) (Fig 6; read-from-figure)	Source separation in ET noise with a hard overlap criterion.	*pending*
`ma2024msnr2` [237]	+1.3 % detection rate over MSNRnet; 0 false triggers in ~5 months of O3b (abstract) (abstract; stated)	Abstract-level; detection rate on its own event scheme.	*pending*
`ma2024tsr` [238]	false alarms -25 %, detections +5 %, cost -90 % vs MSNRnet (abstract) (abstract; stated)	Abstract-level; relative to its own predecessor.	*pending*
`sakai2024` [239]	none extracted	Not read.	*pending*
`xu2024denoise` [254]	91.98 % of Taiji MBHB test samples with overlap >= 0.99 (SNR 10-50) (Sec V A; stated)	Space-based (Taiji) simulated noise; threshold chosen on the test data.	*pending*
`jia2026` [240]	none extracted	Not read; category unverified.	*pending*
`kelleter2026nnnn` [247]	Newtonian-noise residual 13 % (CNN) with WF/CNN residual ratio 25-80 (synthetic ET seismic field) (Sec 5.3; stated)	Seismic-array regression for ET; not strain data. Flagged marginal by its dossier.	*pending*
`kumar2026` [241]	none extracted	Not read.	*pending*

9.4 Suspected errors in the literature

34 suspected errors or internal inconsistencies in 21 papers, selected from the extraction notes (79 notes for this section in the catalogue). Each is a reading of the paper to be checked, not a verdict.

- [24] Overlap is higher at the lower SNR (0.994 at 6.44 vs 0.986 at 12.9), a single-example artefact.
- [24] Baselines differ from those re-quoted in shen2019 for the same SNR.
- [225] Split given as 75/25; 9,861 / 2,459 is 80/20.
- [225] Text claims lower MSE on both classes; eccentric MSE is higher for EDRDAE (0.005 vs 0.004).
- [25] Absolute ranges appear only in the figure.
- [250] 85/15 split of 100 glitches stated, but 16 test glitches listed.
- [226] Abstract says >= 0.99 for all four events; Fig 3 prints 0.73 for GW170608.
- [226] Conclusion gives spin-precessing overlap >= 0.97; Sec 3.3 gives a minimum of 0.93.
- [227] Text says all O1/O2 events reach >= 0.97; Fig 8 shows 0.967 and 0.968.
- [227] Training GPU given as P100 and as K40.
- [248] Excess power removed: 20-70 % (abstract) vs 10-70 % (conclusions).
- [249] Median OLR example in Sec 4 contradicts Table 9.
- [228] The "~1 % of SNR > 8 signals" figure is derived by subtracting two different fractions.
- [242] P-P plots called "excellent agreement" while both combined p-values reject calibration at p < 0.01.
- [242] VT ratio dips below 1 around 1e-9 Hz although an improvement is claimed across the FAR range.
- [242] Batch arithmetic (1993 / 32 = 62.3, not 80 batches) does not close.
- [231] Abstract range 0.85-0.98 vs Table 2 values 0.74, 0.79, 0.84.
- [231] Reconstructed SNR exceeds the reference (fractions 1.10-1.15), unexplained.
- [231] Waveforms simulated to 2048 Hz at a 2048 Hz sampling rate.
- [232] 0.71 described as generalising well.
- [234] Real-event percentages are not integer fractions of the stated totals.
- [234] NSBH/BNS test SNR starts at 8, below the 10-35 training range.
- [253] Peak-time difference direction differs between Figs 4-6 and the Fig 5 caption.
- [229] T^2/delta with T = 30 d gives ~2.1e6 yr, not the 4e5 yr stated.
- [254] "Detection accuracy" is the TPR; the matrices give 99.3-99.8 % accuracy.
- [254] Introduction says merger time within 0.01 s; results give errors of hours.
- [230] "0.3 % vs 1.9 %" and the 0.9 % headline come from different test sets.
- [230] ">10,000x faster" is given without a BayesWave wall time.
- [243] P-P described as well calibrated while the combined KS p-values are 0.0212 and 1e-4.
- [243] A 55-56 Hz band contribution does not match any band in the 13-band list.
- [233] Training SNR given as 4-12 and test as 4-25.
- [233] A median SNR of 10 cannot have 74 % below it.
- [247] Abstract "factors of 15-80" vs 10-110 and "up to 40" in the captions.
- [251] Abstract "up to ~15 %" vs the Fig 7 central peak near 18 %.

10 Parameter estimation

Parameter estimation (PE) moved from point regressors on simulated data to amortised posterior estimators validated against stochastic samplers on real events.

10.1 Families and lineage

10.1.1 Neural posterior estimation (DINGO and relatives)

Normalising flows trained on simulations [26], amortised over noise with group-equivariant tricks [27], corrected by importance sampling [28], extended to binary neutron stars [255] and to transformer embeddings [256] related flows appear for lensing, tests of GR, echoes and 3G detectors [257], [258], [259], [260], [261].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 11 models: [26], [27], [28], [255], [260], [262], [257], [256], [261], [259], [258]. Results will be placed on the shared axes of this section beside the published values.

10.1.2 Variational and other amortised posteriors

Conditional VAEs [263], [264], ratio and likelihood estimation [265], [266], reduced-basis posteriors [267] and Bayesian networks [268].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 10 models: [267], [268], [265], [263], [269], [270], [264], [271], [272], [266]. Results will be placed on the shared axes of this section beside the published values.

10.1.3 Sky localisation

Rapid localisation networks compared with BAYESTAR [273], [274], [275], [276].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 4 models: [273], [276], [274], [275]. Results will be placed on the shared axes of this section beside the published values.

10.1.4 Point estimators

Regressors and classifiers that return parameter values without calibrated posteriors [277], [278], [279], [280], [281], [282], [283], [284].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 8 models: [277], [278], [284], [279], [280], [282], [281], [283]. Results will be placed on the shared axes of this section beside the published values.

10.2 Comparison on the shared axes

Rows are the models graded comparable or conditionally comparable (11 of 33); each axis entry is one row. FAR is converted to per month (30 d) and to Hz where the paper states a rate.

Model	Axis	Published value (location; how obtained)	FAR	Grade: what differs	gravyflow
`delaunoy2020` [265]	PE	coverage of 90 % intervals 89.8-93.3 % on 1000 signals (Table 1; stated)	-	conditional Neural ratio estimation in Gaussian noise; slightly conservative.	*pending*
`green2020` [26]	PE	P-P on 100 injections: per-parameter KS p 0.043 (phi_JL) to 0.90; agrees with dynesty on GW150914 (Fig 3; stated)	-	conditional Gaussian noise at the GW150914 PSD; 100 injections give low power.	*pending*
`dax2021` [27]	PE	combined P-P p 0.46 (1000 injections); mean JSD vs LALInference 0.0009 nat over 8 GWTC-1 events (Figs 2, 4; stated)	-	comparable The reference NPE result: P-P and JSD against MCMC on real events.	*pending*
`dax2022` [28]	PE	median IS sample efficiency 10.9 % (XPHM) / 4.4 % (SEOBNRv4PHM) on 42 events; GW150914 mean JSD 0.5e-3 nat after IS (Tables I-II; stated)	-	comparable Real GWTC-2/3 events against LALInference and Bilby evidences.	*pending*
`gabbard2022pe` [263]	PE	P-P p-values best 0.918 / worst 0.047 (VItamin) over 250 tests; JS divergence vs Dynesty between CPNest and ptemcee (Fig 4-5; stated)	-	conditional Gaussian design noise, BBH, three detectors; calibration comparable in kind to dax2021.	*pending*
`dax2024` [255]	PE	mean IS sample efficiency 31-48.5 % in four BNS experiments; sky area ~30 % smaller than BAYESTAR (Experiments; stated)	-	conditional Stationary Gaussian noise assumption; GW170817 reproduced.	*pending*
`hu2024` [260]	PE	combined P-P p 0.78 (SNR 20-50), 0.078 (SNR 200-500) on 300 3G injections (Fig 3; stated)	-	conditional Simulated third-generation network; importance sampling still costs CPU hours.	*pending*
`chan2025lens` [257]	PE	P-P KS p-values 0.020 (a1) to 0.952 (q) on 1e3 lensed injections (O5 design) (Fig 2; stated)	-	conditional Lensed-signal NPE; calibration comparable in kind to other NPE work on the same priors.	*pending*
`kofler2025` [256]	PE	median IS sample efficiency 4.2 % on 48 O3 events (baseline 1.4 % on 30 HLV events) (Main text; stated)	-	conditional Dingo-specific sample efficiency; depends on priors and detector count.	*pending*
`lanchares2025` [261]	PE	combined P-P p 0.54 (500 injections); JSD vs LVK ~1e-3-1e-2 on 33 events (Fig 4, Sec IV; stated)	-	conditional Time-frequency NPE; real-event agreement on a prior-restricted subset.	*pending*
`zhang2026` [258]	PE	PIT KS p 0.36-0.91 for nine ppE parameters (1000 injections) (Fig 5; stated)	-	conditional Gaussian design noise plus GW150914; ppE deviation parameters only.	*pending*

10.3 What cannot be compared, and why

Calibration (P-P or coverage) and divergence from a reference sampler are the only shared axes, and they require the same priors, waveform model and noise. Point regressors report mean errors on their own grids and are not comparable with posterior estimators.

The 22 models below have no shared axis; their headline metric is listed with the reason.

Model	Headline metric (location; how)	Why not comparable	gravyflow
`chatterjee2019` [273]	sky-sector accuracy 62-85 % (SNR 20-35) and 77-91 % (SNR 50-55) (Table V; stated)	Sky localisation as sector classification.	*pending*
`chua2019` [267]	posterior mean within ~98 % of prior width; sigma overestimated up to 3x (Sec "Example results"; stated)	Reduced-basis toy without detector strain.	*pending*
`shen2019pe` [268]	GW150914 m1 38.9 vs LIGO 35.6 Msun; 5 events within 90 % intervals (Table 1; stated)	Five-event comparison and a qualitative P-P plot.	*pending*
`marulanda2020` [277]	mass MAPE ~5-7 % at SNR 25, ~80-90 % at SNR 5 (Figs 6, 9; read-from-figure)	Point regression on interleaved training and validation grids.	*pending*
`singh2020` [278]	multi-label accuracy ~0.90 on a sparse grid (Sec 5.1; stated)	Element-wise multi-label accuracy dominated by true negatives.	*pending*
`kolmus2021` [276]	mean sky error 32 / 14 / 9.5 deg at SNR 10 / 15 / 20 (Results; stated)	Sky localisation seeding importance sampling.	*pending*
`chatterjee2022` [274]	90 % areas with medians close to BAYESTAR (2000 injections per class) (Fig 4; read-from-figure)	Sky areas against BAYESTAR; no calibration number.	*pending*
`mcleod2022` [269]	mean error 10.5 % (Mc), 24.3 % (q) on simulations; 6.2 % / 8.5 % vs LALInference medians on 10 events (Sec III; stated)	Gaussian posteriors for two parameters.	*pending*
`andrescarcasona2023pe` [270]	P-P inside the 3-sigma band for 7 parameters (100 signals); deviations ~0.1 (Fig 3; read-from-figure)	Narrow BBH prior, 100 test signals, three real events compared by eye.	*pending*
`chatterjee2023skyloc` [275]	P-P deviates from the 95 % band at every lead time except 0 s (Fig 5; stated)	Pre-merger BNS sky areas in Gaussian design noise vs BAYESTAR.	*pending*
`ravichandran2023` [284]	eccentric-signal detection accuracy 0.914, TPR 0.862 (Abstract, Fig 8; stated)	Gaussian-noise classifier.	*pending*
`soma2023` [279]	chirp mass / tidal R^2 0.95 / 0.94 (independent); classifier macro precision 0.96 at SNR 20 (Sec 3; stated)	Validation data reused as test.	*pending*
`badanerin2024` [264]	~95 % of true lensing parameters inside 95 % intervals at SNR 8-40 (Fig 6; stated)	Two lensing parameters with all others fixed to truth in the Bilby comparison.	*pending*
`jenner2024` [271]	none extracted	Abstract-level.	*pending*
`vanstraalen2024` [262]	best pre-merger 90 % sky area 363 deg^2 (70 Hz cut), 141 deg^2 (100 Hz) (Sec VI; stated)	Pre-merger BNS NPE in Gaussian design noise.	*pending*
`benedikt2025` [280]	MAE m1 5.44 Msun, chi_eff 0.03 at SNR 10 (ET noise) (Table 2; stated)	Point estimates on an ET grid; MC-dropout widths are not calibrated.	*pending*
`iwanaga2025` [282]	none extracted	Noise-scatter intervals on one simulated event; no posterior.	*pending*
`khalouei2025` [281]	eccentricity MAE 0.042-0.049 (SNR 10-20), 0.018-0.025 (SNR 20-60) (Table 1; stated)	Point regression in Gaussian O4 noise.	*pending*
`papalini2025` [272]	none extracted	Abstract-level.	*pending*
`emma2026` [266]	JSD to the Whittle posterior below the 10/N threshold in Gaussian noise (Sec V; stated)	Likelihood-estimation method compared with Whittle, not with other SBI.	*pending*
`luo2026` [259]	combined P-P p 0.154 (20 parameters, 1000 simulations) (Fig 3; stated)	Echo search; Bayes factors from an unstated evidence estimate.	*pending*
`sakellariou2026` [283]	MAE m1 2.28 Msun, dL 40.6 Mpc on a discrete synthetic grid (Table 2; stated)	Grid-split regression with min-max normalised strain.	*pending*

10.4 Suspected errors in the literature

25 suspected errors or internal inconsistencies in 19 papers, selected from the extraction notes (92 notes for this section in the catalogue). Each is a reading of the paper to be checked, not a verdict.

- [273] Abstract ">90 % for all cases" vs 62-91 % exact-sector accuracy.
- [268] Training noise starts at the GPS time of GW150914 (leakage).
- [268] The "GW190521" row mixes GW190521_074359 masses with the SNR of GW190521.
- [265] The coverage table is called Table 5 in the text.
- [26] KS "confirms" calibration while phi_JL has p = 0.043 and no multiple-testing correction is applied.
- [278] "Four detections" with seven events listed.
- [27] The O(day) MCMC baseline is cited, not measured.
- [276] Outliers removed from the importance-sampling results without a count.
- [270] Spin "magnitude" prior U(-1, 1) is a signed component.
- [275] "A few milliseconds" inference vs 1.2 s per event including KDE.
- [275] Lead times 14 s (Sec 3) vs 15 s (figures); SNR range 8-40 vs 9-40.
- [284] "FPR 0.138" in the abstract is the false-negative rate; the matrix gives FPR 0.028.
- [264] Table I saving column (79.7 %) does not follow from its time columns (44 %).
- [260] "Seconds" applies to flow sampling only.
- [280] Abstract chi_eff MAE ~1e-3 vs Table 2 0.03.
- [280] MC-dropout sigma is 1.5-2x smaller than the actual error.
- [257] Calibration called good while a1 p = 0.020 and theta_jn p = 0.056 over 17 parameters.
- [281] A large train/validation MSE gap (0.003 vs 0.11) is not discussed.
- [256] The 1.4 % to 4.2 % headline compares 30 three-detector events with 48 events including two-detector ones.
- [261] Abstract says all three-detector GWTC events; only 33 that fit the priors were used.
- [261] JSD heat-map values (up to 69) have no units and exceed ln 2.
- [283] Baseline flow CRPS 3.3e14 and p-value 1.3e-75 indicate a diverged baseline.
- [283] The total loss averages MAEs in different units.
- [258] Posterior widths for dchi3-dchi7 (1.71-1.83) equal the [-1, 1] prior width, so "consistent" means uninformative.
- [258] "Over 10 hours" per MCMC event holds for two of nine parameters.

11 Space-based detectors

Space-based detector studies use simulated LISA, Taiji or TianQin time-delay-interferometry (TDI) data and are outside gravyflow's present detector set.

11.1 Families and lineage

11.1.1 Massive black hole binaries and EMRIs

Detection, inference and extraction of massive black hole binaries and extreme-mass-ratio inspirals in simulated LISA, Taiji and TianQin data [285], [286], [287], [288], [289], [290], [291], [292].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 9 models: [293], [289], [291], [285], [287], [290], [288], [292], [286]. Results will be placed on the shared axes of this section beside the published values.

11.1.2 Instrumental artefacts and separation

Glitches, gaps and overlapping sources in TDI data [294], [295], [296], and quantum-network feasibility studies [297], [298].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 5 models: [294], [295], [297], [298], [296]. Results will be placed on the shared axes of this section beside the published values.

11.2 Comparison on the shared axes

Rows are the models graded comparable or conditionally comparable (0 of 14); each axis entry is one row. FAR is converted to per month (30 d) and to Hz where the paper states a rate.

11.3 What cannot be compared, and why

All space-based results use simulated data with per-sample false-alarm fractions; none has a rate-based FAR, and the detectors are not in gravyflow's present scope.

The 14 models below have no shared axis; their headline metric is listed with the reason.

Model	Headline metric (location; how)	Why not comparable	gravyflow
`caramete2020` [293]	4-class mass-ratio accuracy 95.57 % (Sec 3.4; stated)	Noiseless simulated space-band signals; cloning before the split leaks samples.	*pending*
`zhang2022emri` [289]	TianQin EMRI TAP ~0.88-0.92 at FAP 1 % (SNR 50-120); ~0.75 claimed for an astrophysical population (Sec V A, Fig 3; stated)	Per-3-month-sample FAP in Gaussian TianQin noise.	*pending*
`liu2023` [291]	AUC 0.85-0.87 across TDI generations (LISA/Taiji MBHB, SNR 30-50) (Fig 4; read-from-figure)	Space-based synthetic Gaussian noise; AUC at an unspecified SNR mix.	*pending*
`ruan2023` [285]	TPR at per-sample FPR 1e-3: 0.997 (z = 1) to 0.627 (z = 16) (Sec V A; stated); 15 of 15 Sangria (LDC-2) mergers, no false alarms (Sec V B; stated)	LISA; FPR resolved to ~3e-4 by 3,000 negatives per redshift.	*pending*
`ruan2023pe` [287]	P-P within 3-sigma bands (1000 signals); >4 orders of magnitude prior-volume reduction for SNR > 100 (Figs 2-3; stated)	Simulated LISA MBHB PE.	*pending*
`yun2023` [290]	Taiji EMRI TPR 94.2 % at 1 % FPR (SNR 50-100) (Abstract, Sec IV; stated)	6,000 samples in total; TPR at 1 % rests on a few tens of noise samples.	*pending*
`zhao2023` [288]	TPR at 1 % FPR: EMRI 98.2-99.7 %, MBHB 99.99-100 % (SNR 30-50) (Sec 2.5; stated); MBHB extraction overlap > 0.99 for all test samples (SNR 50) (Sec 2.4; stated)	LISA long-wavelength synthetic data; per-sample FPR.	*pending*
`houba2024glitch` [294]	LISA anomaly detection 99.99915 % of anomalous segments; glitch localisation accuracy 92.1 % (Secs III-IV; stated)	LISA TDI simulations with an own 25-class taxonomy.	*pending*
`houba2024mbh` [292]	>= 95 % of m1 = 3e5 Msun mergers at 15 Gpc flagged one month before merger (Fig 8; read-from-figure)	LISA pre-merger detection without a merger-free false-positive rate.	*pending*
`ruan2024` [286]	TPR > 0.9 at per-segment FPR 0.01 for SNR >= 25; detection 53.5 h before merger (median) (Sec IV, Fig 6; stated)	Pre-merger LISA MBHB classifier; per-segment FPR.	*pending*
`houba2025separation` [295]	MBHB median match 0.994 with an overlapping glitch (SNR 50); > 0.95 above SNR ~15 (Figs 8, 10; read-from-figure)	LISA source separation on simulated TDI.	*pending*
`isfan2025quantum` [297]	98.4 % of Sangria blind windows labelled GW (no negative class); 5 of 6 mergers (Fig 10, Fig 14; stated)	Quantum NN on LISA Sangria; "accuracy" without negatives is a recall.	*pending*
`isfan2026qnn` [298]	hardware accuracy 18.7 % (ibm_kyoto) vs 100 % on simulator (Sec 3.1; stated)	Hardware-feasibility study; no detection performance.	*pending*
`xu2026ssl_lisa` [296]	94.8 / 97.3 / 98.4 % of MBHB extractions above 0.9 at SNR 30 / 40 / 50 (Taiji) (Sec IV A; stated)	Self-supervised extraction on simulated Taiji data.	*pending*

11.4 Suspected errors in the literature

19 suspected errors or internal inconsistencies in 12 papers, selected from the extraction notes (63 notes for this section in the catalogue). Each is a reading of the paper to be checked, not a verdict.

- [293] Class D alone carries added noise, a confound.
- [293] Per-class percentages in the text are precisions, not the recalls described.
- [289] Astrophysical-population TAP "about 75 %" at FAP 1 % vs ~0.56 read from Fig 3.
- [289] TAP below FAP at high masses in Fig 4(b).
- [291] Text says AUC rises monotonically with epochs; Fig 4 is non-monotonic.

- [291] Time-cost reduction "over 70 %" vs ~59-63 % in Fig 9.
- [291] Test SNR given as 30-50 and as "to 20".
- [285] All 15 Sangria mergers recovered although the lowest-SNR ones sit where TPR is 0.33-0.60 (Fig 5).
- [285] TPR at FPR 1e-3 rests on 3 false positives of 3,000.
- [290] Inset said to zoom TPR 0-0.01; the axes show FPR 0-0.1.
- [288] EMRI TPR 99.7 % at 1 % FPR vs ~0.991 read from the Fig 5a ROC.
- [288] Abstract "at least 95 % similarity" vs 92 % > 0.95 for EMRI.
- [294] 99.99915 % on <= 20,000 anomalous samples is finer than the test-set resolution.
- [294] Glitches labelled as bursts: 0.065 % stated vs 27 / 19,228 = 0.14 % from Fig 9.
- [292] No false-positive rate is reported although 20,000 merger-free samples are described.
- [295] Hallucination area 6.88e-5 (text) vs 6.47e-5 (Fig 11).
- [297] Window length and step differ between Sec 3.2 and Table 2.
- [298] Abstract gives 20 % accuracy and different cloud costs from the body.
- [296] Overlap thresholds differ by class (0.9 vs 0.8) and were set after the fact.

12 Other: alerts, generators, lensing, backgrounds

Models that do not fit the categories above: classifiers of public-alert products, generative models of signals and glitches, lensing and stochastic-background studies, a hardware study and a review.

12.1 Families and lineage

12.1.1 Alert-product classifiers

GWSkyNet and its successors classify public-alert sky maps rather than strain [299], [300], [301].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 3 models: [299], [300], [301]. Results will be placed on the shared axes of this section beside the published values.

12.1.2 Generative models

GANs for bursts, blips and Gravity Spy images [302], [303], [304], [305].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 4 models: [302], [303], [304], [305]. Results will be placed on the shared axes of this section beside the published values.

12.1.3 Lensing, backgrounds and miscellany

Lensing identification [306], [307], stochastic backgrounds [308], [309], equation-of-state inference from CCSN [310], space-based extraction [311], FPGA acceleration [312] and a review [313].

> **Our results (to be added)**
> gravyflow reproduction: *pending* for 8 models: [306], [313], [310], [312], [308], [307], [311], [309]. Results will be placed on the shared axes of this section beside the published values.

12.2 Comparison on the shared axes

Rows are the models graded comparable or conditionally comparable (0 of 15); each axis entry is one row. FAR is converted to per month (30 d) and to Hz where the paper states a rate.

12.3 What cannot be compared, and why

These models do not share axes with each other or with the detection categories.

The 15 models below have no shared axis; their headline metric is listed with the reason.

Model	Headline metric (location; how)	Why not comparable	gravyflow
`cabero2020` [299]	GWSkyNet test accuracy 93.5 % (413 candidates); O3 retractions 10 of 22 (Sec 4; stated)	Classifier of alert sky maps, not strain.	*pending*
`kim2020lens` [306]	lensed classification 96.7-98.3 % (optimal SNR 10-50); 62-68 % at SNR 12-13 (Fig 5, Sec 4.3; stated)	Balanced simulated lensing classification.	*pending*
`abbott2021` [300]	GWSkyNet-Multi hierarchical accuracy 93.4 % (427 test events); 36 of 40 O3a alerts (Sec 3-4; stated)	Alert-product classifier.	*pending*
`cuoco2020` [313]	none extracted	Review article; numbers are secondary.	*pending*
`edwards2021` [310]	18-way EoS top-1 accuracy 0.64-0.72, top-5 0.91-0.97 (noise-free) (Table II; stated)	Noise-free CCSN waveform classification.	*pending*
`mcginn2021` [302]	network SNR ~7.3-7.6 for the GAN-trained CNN at FAP 1e-3 (5 burst classes) (Fig 11; read-from-figure)	Generator paper; detection test in Gaussian noise with per-sample FAP.	*pending*
`que2021` [312]	LSTM autoencoder AUC 0.763 (SNR distribution unstated); FPGA latency 0.867 us (Fig 9, Table IV; stated)	Hardware-acceleration study.	*pending*
`utina2021` [308]	none extracted	Abstract-level stochastic-background study.	*pending*

Model	Headline metric (location; how)	Why not comparable	gravyflow
kim2022lens [307]	learner AUC > 0.99 (simulated); 1 of 46 GWTC events classified lensed (Fig 5, Sec 3; stated)	Lensing search; "ROC" uses a set-level false-alarm probability.	*pending*
lopez2022gan [303]	Gravity Spy labels > 70 % of 1000 GAN blips as Blip (Sec IV B; stated)	Generator fidelity.	*pending*
powell2022 [304]	real-data CNN classifies GAN glitches with 99.0 % mean accuracy (22 classes) (Fig 5; stated)	Generator fidelity.	*pending*
chan2024 [301]	GWSkyNet II detection probability 92.5 % (fine-tuned) vs 68.3 % at FAP 20 % among O4 MDC candidates (Sec 3; stated)	Post-trigger alert classifier; 96 noise transients in the test set.	*pending*
dooney2024 [305]	downstream CNN AUC 0.802 (cDVGAN simplex) vs 0.770 best baseline (SNR 1-16) (Table I; stated)	Generator judged by a downstream classifier on a private set.	*pending*
xu2024 [311]	fraction with overlap >= 0.9: 1.0 (ideal) to 0.56 (4x OMS noise) for LISA/ Taiji MBHB (Tables II-V; stated)	Space-based extraction robustness study.	*pending*
einsle2025 [309]	BBH background Omega ~1e-9 at 25 Hz reaches log10 BF 3 with 23.7 d (A+ Gaussian) (Fig 3; stated)	Stochastic-background task.	*pending*

12.4 Suspected errors in the literature

11 suspected errors or internal inconsistencies in 8 papers, selected from the extraction notes (33 notes for this section in the catalogue). Each is a reading of the paper to be checked, not a verdict.

- [299] The 93.5 % headline uses a simulated real class; the real retraction test is 10/22.
- [306] Named VGG-19 but the appendix lists 10 conv layers.
- [300] Fig 7(c) BBH matrix duplicates the glitch panel.
- [300] F1 in Table 1 not reproducible from Fig 7.
- [300] 36/40 vs 6 + 29 = 35 correct.
- [312] Same design latency 0.40 us (Table III) vs 0.867 us (Table IV).
- [303] ~500 Blips in the text vs 736 in Fig 10 at the same SNR.
- [303] Pearson coefficients printed as percentages.
- [301] Baseline beats fine-tuned in both detector-count subsets while losing overall.
- [305] The catalogue baseline 0.759 is not the strongest baseline (0.770).
- [309] MSE 0.01 on log spectra is a ~26 % factor, not "about 3 %".

13 Code and reproducibility

106 of the 313 models have an official public repository (third-party reimplementations, empty repositories and data-only tooling are not counted), and 29 of those release trained weights (2 more release partial weights). Licences were read from the repositories; a missing licence means none was found, which does not grant reuse. The per-section counts are in Table 4 and the repositories in Table 5.

Table 4. Code and weights by section.

Section	Models	With code	With weights
Compact-binary detection	92	30	10
Early warning	9	2	0
Burst and unmodelled transients	33	9	3
Anomaly and multi-signal detection	11	5	1
Continuous and long-duration waves	18	4	0
Glitch classification and data quality	56	19	7
Denoising and signal extraction	32	10	1
Parameter estimation	33	18	4
Space-based detectors	14	3	0
Other: alerts, generators, lensing, backgrounds	15	6	3

Table 5. Official repositories (first listed per model).

Model	Repository	Licence	Last commit	Weights
abbott2021 [300]	github.com/GWML/GWSkyNet	MIT	2021	yes
alhassan2023pymerger [94]	github.com/wathela/PyMerger	NOASSERTION (LICENSE file present, SPDX not recognised)	2024	yes
andrews2022 [82]	github.com/mbandrews/gw-analysis	none found	2021	no
apostol2023 [221]	github.com/DS4AI-UPB/ML4GW	none found	2023	no
arutkeerthi2024 [207]	github.com/Arut123/Glitch-veto-GW-using-chirp	none found	2025	yes
aveiro2022 [90]	doi.org/10.5281/zenodo.6222936	Zenodo record: "Other (Open)"; upstream YOLOv5 repo is AGPL-3.0 (from memory, unverified)	2022	no
badger2024 [87]	github.com/Rahul-Srinivasan/GW_DictionaryLearning	none found	2025	no
bahaadini2018 [173]	github.com/Gravity-Spy/GravitySpy	GPL-3.0	2024	yes
bayley2020 [164]	github.com/jcbayley/soapcw	MIT	2026	no

Model	Repository	Licence	Last commit	Weights
beheshtipour2020 [165]	github.com/matterport/Mask_RCNN	NOASSERTION	2024	no
beheshtipour2020b [166]	github.com/matterport/Mask_RCNN	NOASSERTION	2024	no
benedikt2025 [280]	github.com/GraviBERT/GraviBERT (+1)	MIT	2026	yes
beveridge2025o3 [15]	github.com/damonbeveridge/new_BBH_O3_candidate-UWA	none found	2025	no
cabero2020 [299]	github.com/GWML/GWSkyNet	MIT	2021	yes
cain2025 [148]	github.com/jericho-cain/cwt-lstm-ae-grav-wav	MIT	2026	no
cavaglia2018 [215]	github.com/kstaats/karoo_gp	other (non-standard licence listed by GitHub)	2022	n/a
chan2024 [301]	github.com/nayyer-raza/GWSkyNet-Multi	MIT	2025	yes
chan2025lens [257]	github.com/dingo-lensing/dingo-lensing	MIT	2026	no
chatterjee2022 [274]	github.com/chayanchatterjee/GW-SkyLocator	GPL-3.0	2024	yes
chatterjee2023skyloc [275]	github.com/chayanchatterjee/GW-SkyLocator	GPL-3.0	2024	no
chatterjee2024 [71]	github.com/ondrzel/ml-gw-search/tree/main	Apache-2.0	2023	no
chatterjee2024harm [231]	github.com/chayanchatterjee/AWaRe	GPL-3.0	2025	unverified
chatterjee2024rec [232]	github.com/chayanchatterjee/AWaRe	GPL-3.0	2025	unverified
chatterjee2026 [72]	github.com/chayanchatterjee/castor	Apache-2.0	2026	no
cheung2025unet [160]	github.com/damondmc/cwunet	none found	2025	no
chua2019 [267]	github.com/vallis/truebayes	MIT	2019	yes
cirfeta2026 [153]	github.com/lucacirfeta/dante-gravi-signal-ml	GPL-3.0	2026	unverified
cuoco2026 [137]	github.com/elenacuoco/p4TSA (+1)	GPL-3.0	2026	no
dax2021 [27]	github.com/dingo-gw/dingo	MIT	2026	no
dax2022 [28]	github.com/dingo-gw/dingo	MIT	2026	no
dax2024 [255]	github.com/dingo-gw/dingo	MIT	2026	unverified
ding2021 [200]	github.com/JulianZDing/UniMAP	none found	2021	no
dodia2021specgrav [95]	github.com/HrithikaDodia/SpecGrav	none found	2021	no
dooney2024 [305]	git.ligo.org/tom.dooney/cdvgan_paper	none found	-	no
dooney2025 [230]	git.ligo.org/tom.dooney/deepextractor.git	MIT	-	no
dooney2026 [224]	github.com/tomdooney95/glitchgan (+2)	none found	2026	yes
emma2026 [266]	github.com/MattiaEmma2022/sbilby	MIT	2026	no
essick2020 [212]	git.ligo.org/reed.essick/iDQ	none found	-	no
fernandes2026 [189]	github.com/tttiago/glitchgram	none found	2026	no
gabbard2022pe [263]	github.com/hagabbar/VItamin	MIT	2022	no
george2018glitch [175]	github.com/Gravity-Spy/GravitySpy	GPL-3.0	2024	unverified
glanzer2023 [23]	zenodo.org/records/5649212 (+1)	unknown (Zenodo)	2021	n/a

Model	Repository	Licence	Last commit	Weights
green2020 [26]	github.com/stephengreen/lfi-gw (+2)	MIT	2021	unverified
gunny2021 [68]	github.com/fastmachinelearning/gw-iaas (+1)	MIT	2022	no
gupta2026 [11]	github.com/ML4GW/aframe	MIT	2026	no
hu2024 [260]	github.com/MarinerQ/river	none found	2025	no
huerta2021 [64]	doi.org/10.26311/ZWFW-3N68	unknown	2021	unverified
iess2020 [118]	wdf.readthedocs.io/	unknown	-	n/a
iess2023 [119]	wdf.readthedocs.io/	unknown	-	n/a
inguglia2026 [17]	github.com/ginguglia/MADGRAV	MIT	2026	yes
insley2026flows [104]	github.com/gwastro/pycbc	GPL-3.0	2026	no
jadhav2020 [102]	github.com/shreejit-92/MLStat-1	none stated	2020	no
kelleter2026nnnn [247]	github.com/lc316353/Newtonian-Noise-Simulation (+1)	none stated (no LICENSE file)	2026	no
kiendrebeogo2025virgo [243]	github.com/weizmannk/Virgo-DeepClean	AGPL-3.0	2026	no
kofler2025 [256]	github.com/dingo-gw/dingo-T1 (+2)	MIT	2026	yes
kolmus2021 [276]	github.com/akolmus/swiftsky	none found	2021	no
koloniari2024 [13]	github.com/vivinousi/gw-detection-deep-learning	Apache-2.0	2025	yes
lanchares2025 [261]	github.com/Daniel-Lanchares/dtempest	none found	2026	no
li2024ctsae [195]	github.com/Zod-L/CTSAE	Apache-2.0	2024	no
liu2023 [291]	github.com/dingo-gw/dingo (+1)	MIT	2026	no
luo2026 [259]	github.com/dingo-gw/dingo	MIT	2026	no
ma2024mix [253]	github.com/z2062358453/gravitational-wave-separation	none found	2024	yes
malz2024 [186]	doi.org/10.5281/zenodo.14066270	CC BY 4.0	2024	no
manoharan2026 [222]	github.com/rudhresh1997/glitch-tabular-prd	MIT	2026	no
martins2024 [109]	github.com/anaismartins/deploying-custom-nn-in-fpga	MIT	2025	no
marx2024 [9]	github.com/ML4GW/aframe (+2)	MIT	2026	no
marx2025aframeO3 [10]	github.com/ML4GW/aframe	MIT	2026	no
mcginn2021 [302]	github.com/jmcginn/McGANn	none found	2021	no
mcisaac2022 [103]	github.com/connor-mcisaac/chisqnet (+1)	GPL-3.0	2022	yes
mcleod2025 [16]	github.com/alistair-mcleod/infernus (+1)	MIT	2026	no
mlgwsc2022 [8]	github.com/gwastro/ml-mock-data-challenge-1	Apache-2.0	2022	yes
morales2024 [122]	resnet50-sngw-hff, datagen-sngw-phen, datagen-sngw-genrel (f	GPL-3.0 (per paper)	unchecked	unverified
moreno2022 [140]	github.com/eric-moreno/Anomaly-Detection-Autoencoder (+1)	none (no licence file; all rights reserved by default)	2022	yes
nagarajan2025 [14]	github.com/nnarenraju/sage	GPL-3.0	2026	no
nousi2022 [12]	github.com/vivinousi/gw-detection-deep-learning (+1)	Apache-2.0	2025	yes

Model	Repository	Licence	Last commit	Weights
ormiston2020 [25]	github.com/rormiston/DeepClean (+3)	GPL-3.0	2018	no
papalini2025 [272]	github.com/luciapapalini/kenn-gw-transformer	MIT	-	unverified
pracchia2025 [128]	git.ligo.org/maxime.fays/gwpyxel	none shown	2026	no
que2021 [312]	github.com/walkieq/RNN_HLS	Apache-2.0	2024	unverified
raikman2023 [146]	github.com/ML4GW/gwak	MIT	2026	partial
raikman2024 [136]	github.com/ML4GW/gwak	MIT	2026	partial
reissel2025 [244]	github.com/ML4GW/DeepClean (+1)	none stated	2023	unverified
saleem2023 [242]	github.com/ML4GW/DeepClean (+2)	none declared (no LICENSE file; GitHub licence field null)	2022	no
schafer2020 [5]	github.com/gwastro/bns-machine-learning-search	none declared (no LICENSE file; GitHub licence field null)	2020	yes
schafer2021a [6]	github.com/gwastro/ml-training-strategies	GPL-3.0	2022	no
schafer2021b [7]	github.com/gwastro/ml-training-strategies	GPL-3.0	2022	no
singh2020 [278]	github.com/SSingh087/DL-estimating-parameters-of-GWs	MIT	2022	no
skliris2024 [135]	github.com/VasSkliris/mly-methods-paper (+3)	none listed	2024	yes
soni2021 [22]	github.com/Gravity-Spy/GravitySpy	GPL-3.0	2024	yes
srivastava2024 [180]	kaggle.com/code/divyansh050/vitb32-ligo/notebook	none found	-	no
tian2023 [66]	github.com/mtian8/Higher_Order_GW_Spatiotemporal_GNN	none found	2024	unverified
tian2024gnn [67]	github.com/mtian8/gw_spatiotemporal_gnn	MIT	2024	unverified
tiki2025 [77]	github.com/victoria-tiki/AttenGW (+1)	MIT	2026	yes
wang2020 [83]	github.com/WuShichao/mfcnn_catalog (+1)	none listed	2020	no
wang2022waveformer [229]	github.com/AI-HPC-Research-Team/LIGO_noise_suppression	Apache-2.0	2024	no
weerasinghe2026 [62]	github.com/sathnidu9/postmerger-gw-eos-inference	MIT	2025	no
wu2024 [179]	github.com/Gravity-Spy/gravityspy-ligo-pipeline	GPL-3.0	2025	yes
xu2026ssl_lisa [296]	github.com/TriangleDataCenter/Triangle-Simulator (+1)	GPL-3.0	2026	no
yamamoto2025 [70]	github.com/tsyamamoto21/gw-hybridmfcnn-stellarmassbbh	none declared	2025	yes
yan2022gan [182]	github.com/tkarras/progressive_growing_of_gans	NOASSERTION (NVIDIA research licence)	2022	no
yan2025deepgrav [139]	github.com/yan123yan/DeepGrav	MIT	2026	yes
yu2021early [112]	github.com/hangyu45 (+1)	none for relevant repos (account has GPL-3.0 repos for other papers)	2026	no
zelenka2024 [69]	github.com/ondrzel/ml-gw-search	Apache-2.0	2023	yes
zevin2017 [20]	github.com/Gravity-Spy/GravitySpy (+3)	GPL-3.0	2024	yes

Model	Repository	Licence	Last commit	Weights
`zevin2024` [177]	github.com/Gravity-Spy/GravitySpy (+2)	GPL-3.0	2024	yes
`zhao2023` [288]	github.com/AI-HPC-Research-Team/Space_signal_detection_all4	MIT	2023	no

14 Reproduction programme in gravyflow

The original catalogue set an itinerary of sixteen steps, ordered so that shared library features are built once and then reused. The added models are placed on the same steps. Effort follows the original scale: S is model code and configuration on the existing data path (days), M one new library feature or substantial data work (one to two weeks), L several new features, an external pipeline or dataset, or a new physics domain; for added models it is estimated from the one-off efforts of their adaptation tags. Every model's reproduction is pending.

Table 6. Itinerary.

Step	Title	Shared adaptations	Orig.	Added	Why (first catalogue)
0	Retrieve the unread papers	x-retrieve	11	30	Nine entries have no architecture at all; their adaptations cannot be stated until the text is read. Cheap for the owner (institutional access), and it unblocks later steps.
1	Close the shipped families	n-real, n-sim-glitch, wf-subst	4	1	George-Huerta (both nets) and Gabbard are shipped; MLy is shipped without its incoherent and single-detector WNB noise classes. IncoherentGenerator now exists, so MLy's types 2/3 and George-Huerta's real-noise follow-up are the cheapest completions of what is already there.
2	1D CNN ports on the current data path	wf-subst, t-multiclass, det-hlv, in-window, t-ensemble	11	7	Whitened-strain 1D CNNs that need only model code, a declared approximant substitution and at most a multi-class head or longer window. The most cited early literature lives here.
3	Search-grade evaluation: sensitive distance and continuous search	e-far, e-sensitivity, n-real	1	3	The post-2021 literature reports sensitive distance vs FAR on continuous data with time slides; the validator has FAR and time slides but not sensitive distance or a streamed search. Building this once makes every later CBC entry comparable to MLGWSC-1 and to PyCBC.
4	MLGWSC-1 benchmark and its entries	n-mlgwsc, wf-xphm, n-psd-aug, t-custom-layer	6	1	One benchmark covers AresGW, CNN-Coinc, TPI FSU Jena, MFCNN and is the common yardstick of Aframe, CASTOR, GW-Whisper, Sage and Yamamoto 2025. DS1 is reachable now (non-spinning PhenomD); DS2-DS4 need XPHM, PSD variation and real O3a noise.
5	Per-timestep outputs (WaveNet family)	t-sequence, n-real, t-ensemble	3	3	Gebhard 2019 and the Huerta/Wei WaveNet ensembles emit a score per time step on real noise; one dense-target feature serves all of them and the U-Net segmentation models of step 9.
6	Matched-filter front ends	in-mf-series	6	2	MatchedFilterLayer and TemplateBank exist; exposing per-template SNR series and SNR maps unlocks MFCNN, Beveridge, McLeod (BNS), Yamamoto 2025, Mobilia and Yan 2021.
7	Burst, anomaly and autoencoder models	t-ae, wf-pheno-burst, in-pearson, t-recurrent	6	5	Extends MLy: noise-only autoencoders (Moreno, GWAK), generalised-burst training (McGinn), weak supervision (Ratner) and synthetic transient classification (Nigam).
8	Denoising and waveform extraction	t-ae, e-overlap, t-recurrent	8	7	Strain-in, clean-waveform-out models trained against WHITENED_INJECTIONS and scored by overlap.
9	Time-frequency images and pretrained backbones	in-qtransform, in-stft, in-wavelet, in-pretrained, t-sequence	6	5	Q-transform/CQT/CWT images and ImageNet backbones serve the ResNet-50 O2/O3 searches, the spectrogram early-warning nets and, in step 10, all of Gravity Spy.
10	Glitch classification (Gravity Spy family)	n-glitch, in-qtransform, t-multiclass, e-multiclass, n-external	17	16	Twenty-odd glitch papers share one dataset (Gravity Spy) and one input (multi-duration Omega scans). Either a Zenodo image loader or a Q-transform over Gravity Spy times.
11	Early warning and long BNS windows	in-window, in-multirate, e-early, wf-subst	6	3	BNS inspirals need 10-300 s windows, multi-rate inputs, partial-inspiral SNR labels and time-before-merger metrics.
12	Core-collapse supernovae and catalogue waveforms	wf-catalogue, wf-pheno-burst, t-multiclass	7	5	Supernova detectors need numerical waveforms from files (or Astone's phenomenological model), distance scaling and 3-class heads.
13	Exotic training: Bayesian, GAN, VAE, transformers, foundation models	t-generative, t-recurrent, in-pretrained	7	7	Each needs a custom train step or heavy pretrained weights; worth doing after the data and evaluation foundations exist.
14	Auxiliary-channel and pipeline-coupled models	in-aux, in-pipeline-triggers, t-nonneural	18	18	DeepClean, iDQ, EMU and cWB-coupled classifiers need non-public channels or an external pipeline; they are reference entries until gravyflow reads auxiliary data.
15	Out of core scope: space-based, CW, long transients, skymaps, PE	det-new, wf-cw, e-pe	21	62	Recorded for completeness; each needs a new physics domain.

Table 7. Shared adaptations: state in gravyflow (first catalogue) and how many of the 313 models need each.

Tag	Feature	State in gravyflow	Effort once	Models
in-window	Window length	Have: any onsource length, fixed CBC buffer B(W)=2^ceil(log2 2W). Gap: windows of 10-300 s are unmeasured for memory and generation cost.	S	25
in-multirate	Multi-rate input	Have: one sample rate per dataset, one resampler. Gap: a window cut into segments at different rates (Schafer 2020, Nagarajan 2025).	M	2
in-stft	STFT spectrogram	Have: gf.spectrogram / SPECTROGRAM_ONSOURCE (|STFT|^2 of whitened data, Hann frames). Gap: per-paper window, overlap, log scaling, band crop, image resize.	S	20
in-qtransform	Q-transform / Omega-scan images	Gap: no Q-transform in gravyflow; Gravity Spy-style multi-duration (0.5/1/2/4 s) images, CQT, colour maps and resizing to backbone inputs.	M	39
in-wavelet	Wavelet transforms	Gap: wavelet packet, CWT (Morlet), scattering transform, cWB-like WDF time-frequency maps.	M	14
in-freqdomain	Frequency-domain input	Gap: real/imaginary whitened rfft as model input (DINGO, CW nets); PSD-as-input channels.	S	14

Tag	Feature	State in gravyflow	Effort once	Models
in-mf-series	Matched-filter front end	Have: MatchedFilter, MatchedFilterLayer (returns network-SNR logits), TemplateBank. Gap: per-template SNR time series and template-by-time SNR maps as model inputs, top-k template selection, learnable template layer (MFCNN).	M	12
in-pearson	Cross-detector correlation	Have: ROLLING_PEARSON_ONSOURCE (circular shift; lag convention not pinned). Gap: frequency-domain correlation features.	S	1
in-aux	Auxiliary witness channels	Gap: gravyflow reads strain only; no auxiliary-channel acquisition (needs LocalFrames on a LIGO cluster, non-public channels).	L	15
in-pipeline-triggers	External pipeline triggers	Gap: cWB, Omicron, PyCBC or BAYESTAR products as inputs (cWB summary statistics, reconstructed waveforms, skymaps).	L	29
in-pretrained	Pretrained backbones	Gap: ImageNet / audio pretrained weights (keras.applications under the JAX backend, Whisper, YOLO) and their input normalisation.	M	27
det-hlv	H1/L1/V1 network	Have: H1, L1, V1 for synthetic and real noise. Gap: transient (glitch/event) mode is H1/L1 only; zero-filled missing detectors.	S	16
det-new	New detectors	Gap: KAGRA, Einstein Telescope, LISA/TianQin/Taiji responses and PSDs (TDI for space).	L	32
wf-subst	Approximant substitution	Have: ripple IMRPhenomD, XAS, Pv2, TaylorF2, D_NRTidalv2. Gap: SEOBNR/EOB, SpinTaylorT4, PhenomPNRT and surrogates are absent; substitute and declare the departure (as the George-Huerta example does) or bridge to LALSimulation.	S	31
wf-xphm	IMRPhenomXPHM / higher modes	Gap: XPHM deliberately not offered (ripple loses LAL parity at equal masses with spin); MLGWSC-1, Aframe-era and O3 searches use it.	M	17
wf-ecc	Eccentric / beyond-GR waveforms	Gap: CBCGenerator refuses eccentricity; no ppE/beyond-GR models.	L	5
wf-catalogue	Waveform-from-file injection	Gap: injecting numerical waveforms from a catalogue (CCSN simulations, NR, Richers 2017) with sky projection and SNR/HRSS scaling.	M	10
wf-pheno-burst	Extra burst families	Have: sine-Gaussian, chirplet, ringdown, periodic, WNB, IncoherentGenerator. Gap: Gaussian pulse, cosmic-string cusp, phenomenological CCSN (Astone), scattered-light / whistle shapes, minute-long chirps, magnetar spin-down.	M	15
wf-cw	Continuous waves	Gap: CW signals with Doppler and spin-down over days (LALSuite/PyFstat).	L	17
n-real	Real GWOSC noise	Have: REAL and PSEUDO_REAL noise O1-O3, flags and vetoes, split by GPS. Gap: real noise is read sequentially (not index-addressed); detectors are always two footprints apart (no coincident mode for training on coincident noise).	S	71
n-glitch	Gravity Spy glitches	Have: TransientDataObtainer with Gravity Spy classes (GlitchType) H1/L1 O1-O3. Gap: glitch-labelled examples mixed as a noise class at set ratios; multi-class labels through ComposedDataset (outside the batch contract).	S	47
n-sim-glitch	Simulated glitches	Gap: single-detector sine-Gaussian/Gaussian/ringdown/scattered-light glitches labelled noise (IncoherentGenerator or a per-detector injection labelled noise).	S	14
n-psd-aug	PSD augmentation	Gap: recolouring with sampled PSDs (DINGO, Sage, MLGWSC-1 DS2/DS3); PSEUDO_REAL is the nearest relative.	M	4
n-mlgwsc	MLGWSC-1 datasets	Gap: the challenge's four datasets (DS1-DS4) and its injection/evaluation contract; DS2-DS4 use XPHM with precession and higher modes.	M	7
n-external	External datasets	Gap: a loader for a published dataset (Gravity Spy Zenodo images, Codabench GWAK, ET MDC, LDC, Richers catalogue).	M	12
t-multiclass	Multi-class training	Have: ComposedDataset pools and POOL_LABEL. Gap: >2-class heads through the recipe and the batch contract.	S	47
t-regression	Regression targets	Have: mass regression (George-Huerta predictor), WaveformParameters labels. Gap: SNR, chirp-mass, time-to-merger and sky targets in the recipe.	S	15
t-sequence	Per-timestep / dense targets	Gap: per-sample or per-pixel labels (WaveNet-style per-timestep classification, U-Net masks, bounding boxes).	M	21
t-ae	Autoencoder / reconstruction	Have: WHITENED_INJECTIONS as a clean target. Gap: noise-only reconstruction training and an anomaly-score validator path.	M	31
t-curriculum	Curricula and schedules	Have: gf.Curriculum (SNR or any Distribution, by epoch). Gap: step/trigger-based curricula, curricula on frequency cutoff or mass, LR schedules beyond Keras.	S	9
t-ensemble	Ensembles	Gap: training and scoring N independently seeded members, voting and coincidence rules.	S	12
t-custom-layer	Custom layers	Gap: layers Keras 3 lacks or the examples do not use: DAIN, GroupNorm (present in Keras), periodic conv, SE/shrinkage, quadratic layer, inception/residual blocks.	S	12
t-recurrent	Recurrent / attention nets	Have: Keras 3 LSTM/GRU/MultiHeadAttention run on JAX. Gap: none in the library; only example code and memory measurement for long sequences.	S	28
t-generative	GAN / VAE / flow / Bayesian training	Gap: custom train steps (WGAN-GP, VAE ELBO, flipout Bayesian layers, normalising flows) under Keras 3 JAX.	L	35
t-unsupervised	Unsupervised / similarity	Gap: clustering, contrastive pairs, IIC, UMAP/KDE outlier scoring.	M	13
t-nonneural	Non-neural models	Gap: trees, GMMs, genetic programming, logistic regression: outside Keras; would need a scikit-learn/XGBoost adapter to the validator.	M	26
e-far	FAR and efficiency	Have: Validator: exact FAR in Hz with Garwood intervals, efficiency by SNR bin, ROC/AUC, time slides on multi-detector real noise (num_time_slides, cluster_seconds). Gap: streamed continuous-data search with clustering over long stretches.	S	22
e-sensitivity	Sensitive distance / volume	Gap: sensitive distance or volume vs FAR over a population (MLGWSC-1 metric), hrss50 for bursts.	M	23
e-multiclass	Multi-class evaluation	Gap: confusion matrices, per-class accuracy/F1, NMI/ARI for clustering.	S	13
e-overlap	Waveform overlap	Gap: match/overlap of reconstructed vs injected waveform (the matched-filter code has the pieces).	S	12
e-events	Real events	Have: score_real_events (confident GWTC events, test split). Gap: catalogue masses on event records; O4 events.	S	17
e-early	Early-warning metrics	Gap: detection time before merger, partial-inspiral SNR labels.	M	10
e-pe	PE diagnostics	Gap: P-P plots, JSD against samplers, sky-area metrics.	L	23
x-retrieve	Full text needed	The paper was not read (paywall or unextractable PDF); the owner or an institutional copy is needed before any adaptation can be stated.	-	42

Table 8. Per-model index: section, comparability, adaptation effort, itinerary step and reproduction status.

Model	Year	Section	Origin	Grade	Effort	Step	gravyflow
`abbott2021` [300]	2021	other	added	not comparable	L	14	*pending*
`alfaidi2024` [110]	2024	early	added	conditional	M	11	*pending*
`alhassan2022` [93]	2022	cbc	original	not comparable	M	15	*pending*
`alhassan2023pymerger` [94]	2023	cbc	added	not comparable	L	15	*pending*
`alvares2021` [89]	2021	cbc	added	not comparable	M	9	*pending*
`alvarez2022cwbml` [19]	2022	burst	added	comparable	L	14	*pending*
`alvarez2023` [202]	2023	glitch	original	not comparable	M	10	*pending*

Model	Year	Section	Origin	Grade	Effort	Step	gravyflow
andrescarcasona2023 [74]	2023	cbc	original	conditional	-	0	*pending*
andrescarcasona2023pe [270]	2023	pe	added	not comparable	L	15	*pending*
andrews2022 [82]	2022	cbc	original	conditional	S	2	*pending*
antelis2021 [131]	2021	burst	added	not comparable	L	14	*pending*
apostol2023 [221]	2023	glitch	added	not comparable	M	10	*pending*
arutkeerthi2024 [207]	2024	glitch	added	not comparable	S	10	*pending*
ashton2025 [105]	2025	cbc	added	not comparable	L	14	*pending*
astone2018 [115]	2018	burst	original	conditional	M	12	*pending*
attadio2024 [143]	2024	burst	original	not comparable	L	15	*pending*
aveiro2022 [90]	2022	cbc	original	not comparable	L	9	*pending*
bacon2022 [228]	2022	denoise	original	not comparable	S	8	*pending*
badanerin2024 [264]	2024	pe	added	not comparable	L	15	*pending*
badger2024 [87]	2024	cbc	added	conditional	M	8	*pending*
bahaadini2017 [21]	2017	glitch	original	conditional	S	10	*pending*
bahaadini2018 [173]	2018	glitch	original	not comparable	S	10	*pending*
bahaadini2018direct [191]	2018	glitch	original	not comparable	M	10	*pending*
bahaadini2022 [193]	2022	glitch	added	not comparable	M	10	*pending*
baltus2021 [106]	2021	early	original	not comparable	M	11	*pending*
baltus2021b [107]	2021	early	original	not comparable	-	0	*pending*
baltus2022 [108]	2022	early	original	conditional	M	11	*pending*
bayley2020 [164]	2020	cw	original	conditional	L	15	*pending*
beheshtipour2020 [165]	2020	cw	added	not comparable	L	15	*pending*
beheshtipour2020b [166]	2020	cw	added	not comparable	L	15	*pending*
benedikt2025 [280]	2025	pe	added	not comparable	L	15	*pending*
beveridge2023 [76]	2023	cbc	original	conditional	M	6	*pending*
beveridge2025o3 [15]	2025	cbc	added	comparable	M	6	*pending*
bhandari2025 [187]	2025	glitch	added	not comparable	-	0	*pending*
bini2023 [209]	2023	glitch	original	conditional	M	14	*pending*
biskin2023 [184]	2023	glitch	added	not comparable	-	0	*pending*
boudart2022 [142]	2022	burst	original	not comparable	L	15	*pending*
boudart2022glitch [220]	2022	glitch	original	not comparable	L	15	*pending*
bresten2019 [40]	2019	cbc	original	conditional	M	13	*pending*
cabero2020 [299]	2020	other	original	not comparable	L	15	*pending*
cain2025 [148]	2025	anomaly	added	not comparable	M	7	*pending*
caramete2020 [293]	2020	space	added	not comparable	L	15	*pending*
casallaslagos2026 [121]	2026	burst	added	not comparable	L	12	*pending*
cavaglia2018 [215]	2018	glitch	added	not comparable	L	14	*pending*
cavaglia2020 [130]	2020	burst	original	not comparable	L	14	*pending*
chan2020 [117]	2020	burst	original	conditional	M	12	*pending*
chan2024 [301]	2024	other	original	not comparable	L	15	*pending*
chan2025 [210]	2025	glitch	added	not comparable	M	10	*pending*
chan2025lens [257]	2025	pe	added	conditional	L	15	*pending*
chatterjee2019 [273]	2019	pe	added	not comparable	S	15	*pending*
chatterjee2021 [227]	2021	denoise	original	conditional	M	8	*pending*
chatterjee2022 [274]	2022	pe	added	not comparable	L	15	*pending*
chatterjee2023skyloc [275]	2023	pe	original	not comparable	L	15	*pending*
chatterjee2024 [71]	2024	anomaly	original	comparable	L	13	*pending*
chatterjee2024harm [231]	2024	denoise	added	conditional	M	8	*pending*
chatterjee2024rec [232]	2024	denoise	added	not comparable	M	8	*pending*
chatterjee2026 [72]	2026	cbc	original	comparable	M	4	*pending*
chaturvedi2022 [65]	2022	cbc	added	not comparable	M	5	*pending*
chauhan2020 [45]	2020	cbc	added	not comparable	S	2	*pending*
cheung2025unet [160]	2025	cw	added	conditional	L	15	*pending*
choudhary2022 [204]	2022	glitch	added	not comparable	S	10	*pending*
chua2019 [267]	2019	pe	added	not comparable	L	15	*pending*
cirfeta2026 [153]	2026	anomaly	added	not comparable	L	14	*pending*
colgan2020 [213]	2020	glitch	original	not comparable	L	14	*pending*
colgan2022 [214]	2022	glitch	added	not comparable	L	14	*pending*
coughlin2019 [192]	2019	glitch	original	not comparable	M	10	*pending*
cuoco2020 [313]	2021	other	original	not comparable	-	15	*pending*
cuoco2026 [137]	2026	burst	original	conditional	L	14	*pending*
dax2021 [27]	2021	pe	original	comparable	L	15	*pending*
dax2022 [28]	2022	pe	added	comparable	L	15	*pending*
dax2024 [255]	2024	pe	added	conditional	L	15	*pending*
deighan2020 [35]	2020	cbc	added	not comparable	S	2	*pending*
delaunoy2020 [265]	2020	pe	added	conditional	L	15	*pending*

Model	Year	Section	Origin	Grade	Effort	Step	gravyflow
deshmukh2026 [196]	2026	glitch	added	not comparable	M	10	*pending*
dicesare2026fh [168]	2026	cw	added	not comparable	L	15	*pending*
ding2021 [200]	2021	glitch	added	not comparable	M	7	*pending*
dodia2021residual [48]	2021	cbc	added	not comparable	S	2	*pending*
dodia2021specgrav [95]	2021	cbc	added	not comparable	S	9	*pending*
dominguez2023 [161]	2023	cw	added	not comparable	L	15	*pending*
dooney2022 [223]	2022	glitch	added	not comparable	L	13	*pending*
dooney2024 [305]	2024	other	original	not comparable	L	13	*pending*
dooney2025 [230]	2025	denoise	original	conditional	M	8	*pending*
dooney2026 [224]	2026	glitch	added	not comparable	L	13	*pending*
dreissigacker2019 [155]	2019	cw	original	comparable	L	15	*pending*
dreissigacker2020 [156]	2020	cw	original	comparable	L	15	*pending*
duraisamy2023 [162]	2023	cw	added	not comparable	-	0	*pending*
edwards2021 [310]	2021	other	original	not comparable	M	12	*pending*
einsle2025 [309]	2025	other	added	not comparable	M	15	*pending*
emma2026 [266]	2026	pe	added	not comparable	L	15	*pending*
essick2020 [212]	2020	glitch	original	not comparable	L	14	*pending*
fan2019 [41]	2019	cbc	original	not comparable	S	2	*pending*
fan2021_2d [96]	2021	cbc	original	not comparable	-	0	*pending*
fayad2024 [147]	2024	anomaly	original	not comparable	M	13	*pending*
fernandes2023 [178]	2023	glitch	original	conditional	S	10	*pending*
fernandes2025 [134]	2025	burst	added	comparable	L	14	*pending*
fernandes2026 [189]	2026	glitch	added	not comparable	M	10	*pending*
g2net2022_acm [97]	2021	cbc	added	not comparable	-	0	*pending*
gabbard2018 [2]	2018	cbc	original	conditional	-	1	*pending*
gabbard2022pe [263]	2022	pe	original	conditional	L	15	*pending*
garg2024 [56]	2023	cbc	added	not comparable	-	0	*pending*
gebhard2019 [4]	2019	cbc	original	conditional	M	5	*pending*
george2017tl [174]	2017	glitch	added	conditional	L	10	*pending*
george2018 [1]	2018	cbc	original	not comparable	-	1	*pending*
george2018b [3]	2018	cbc	original	not comparable	S	1	*pending*
george2018glitch [175]	2018	glitch	original	conditional	S	10	*pending*
george2018plb [29]	2017	cbc	added	not comparable	S	1	*pending*
ghalsasi2023 [236]	2023	denoise	added	not comparable	L	9	*pending*
glanzer2023 [23]	2023	glitch	original	conditional	S	10	*pending*
green2020 [26]	2020	pe	original	conditional	L	15	*pending*
gunny2021 [68]	2021	cbc	original	not comparable	-	14	*pending*
guo2025 [149]	2025	anomaly	added	not comparable	M	7	*pending*
gupta2025ae [211]	2025	glitch	added	not comparable	-	0	*pending*
gupta2026 [11]	2026	cbc	added	comparable	M	3	*pending*
gupta2026q [61]	2026	cbc	added	not comparable	L	13	*pending*
houba2024glitch [294]	2024	space	added	not comparable	L	15	*pending*
houba2024mbh [292]	2024	space	added	not comparable	L	15	*pending*
houba2025separation [295]	2025	space	added	not comparable	L	15	*pending*
hu2024 [260]	2024	pe	added	conditional	L	15	*pending*
huerta2021 [64]	2021	cbc	original	not comparable	M	5	*pending*
iess2020 [118]	2020	burst	original	not comparable	M	12	*pending*
iess2023 [119]	2023	burst	original	not comparable	M	12	*pending*
imran2024 [150]	2024	anomaly	added	not comparable	-	0	*pending*
inguglia2025 [152]	2025	anomaly	original	not comparable	L	15	*pending*
inguglia2026 [17]	2026	anomaly	added	comparable	L	7	*pending*
insley2026flows [104]	2026	cbc	added	conditional	L	14	*pending*
isfan2025quantum [297]	2025	space	added	not comparable	L	15	*pending*
isfan2026qnn [298]	2026	space	added	not comparable	L	15	*pending*
iwanaga2025 [282]	2025	pe	added	not comparable	M	15	*pending*
jadhav2020 [102]	2020	cbc	added	conditional	L	14	*pending*
jadhav2023 [80]	2023	cbc	original	conditional	L	13	*pending*
jarov2023 [203]	2023	glitch	original	not comparable	S	10	*pending*
jenner2024 [271]	2024	pe	added	not comparable	-	0	*pending*
jia2026 [240]	2026	denoise	added	not comparable	-	0	*pending*
jiang2022 [51]	2022	cbc	original	not comparable	-	0	*pending*
jiang2022real [52]	2022	cbc	added	not comparable	-	0	*pending*
joshi2023 [157]	2023	cw	added	comparable	L	15	*pending*
joshi2024large [158]	2024	cw	added	comparable	L	15	*pending*
joshi2025vit [159]	2025	cw	added	comparable	L	15	*pending*
kelleter2026nnnn [247]	2026	denoise	added	not comparable	L	15	*pending*

Model	Year	Section	Origin	Grade	Effort	Step	gravyflow
khalouei2025 [281]	2025	pe	added	not comparable	L	15	*pending*
kiendrebeogo2025virgo [243]	2025	denoise	added	conditional	L	14	*pending*
kim2015grb [100]	2015	cbc	added	not comparable	L	14	*pending*
kim2019 [101]	2019	cbc	added	not comparable	L	14	*pending*
kim2020lens [306]	2020	other	added	not comparable	M	15	*pending*
kim2022lens [307]	2022	other	added	not comparable	M	15	*pending*
kim2026kagra [197]	2026	glitch	added	not comparable	L	15	*pending*
kofler2025 [256]	2025	pe	original	conditional	L	15	*pending*
kolmus2021 [276]	2021	pe	added	not comparable	L	15	*pending*
koloniari2024 [13]	2024	cbc	original	conditional	L	4	*pending*
koyama2024 [185]	2024	glitch	added	not comparable	-	0	*pending*
krastev2020 [30]	2020	cbc	original	not comparable	S	2	*pending*
krastev2021 [31]	2021	cbc	original	not comparable	M	11	*pending*
kumar2023 [57]	2023	cbc	added	not comparable	-	0	*pending*
kumar2026 [241]	2026	denoise	added	not comparable	-	0	*pending*
laguarta2023 [199]	2023	glitch	original	not comparable	L	14	*pending*
lanchares2025 [261]	2025	pe	added	conditional	L	15	*pending*
lee2025 [233]	2025	denoise	added	conditional	M	8	*pending*
li2020 [46]	2020	cbc	original	not comparable	M	9	*pending*
li2024ctsae [195]	2024	glitch	added	not comparable	L	10	*pending*
licciardi2024 [181]	2024	glitch	original	conditional	M	14	*pending*
lin2019 [42]	2019	cbc	original	not comparable	M	9	*pending*
lin2021 [37]	2021	cbc	original	not comparable	L	13	*pending*
lin2024 [234]	2024	denoise	added	conditional	M	8	*pending*
liu2023 [291]	2023	space	added	not comparable	L	15	*pending*
llorensmonteagudo2018 [219]	2018	glitch	added	not comparable	M	10	*pending*
lopez2021a [126]	2021	burst	original	not comparable	-	0	*pending*
lopez2021b [116]	2021	burst	original	conditional	L	12	*pending*
lopez2022gan [303]	2022	other	added	not comparable	L	13	*pending*
lopez2022gmm [133]	2022	burst	original	conditional	L	14	*pending*
luo2019 [43]	2019	cbc	original	not comparable	-	0	*pending*
luo2026 [259]	2026	pe	added	not comparable	L	15	*pending*
ma2022 [38]	2022	cbc	original	not comparable	S	2	*pending*
ma2024et [252]	2024	denoise	added	not comparable	L	15	*pending*
ma2024mix [253]	2024	denoise	added	not comparable	L	15	*pending*
ma2024msnr2 [237]	2024	denoise	added	not comparable	-	0	*pending*
ma2024tempfree [85]	2023	cbc	added	not comparable	L	8	*pending*
ma2024tsr [238]	2024	denoise	added	not comparable	-	0	*pending*
ma2025et [88]	2025	cbc	added	not comparable	-	0	*pending*
ma2025overlap [154]	2025	anomaly	added	not comparable	-	0	*pending*
magee2024interp [206]	2024	glitch	added	not comparable	M	6	*pending*
malz2024 [186]	2024	glitch	added	not comparable	M	10	*pending*
manoharan2026 [222]	2026	glitch	added	not comparable	M	10	*pending*
marianer2021 [141]	2021	burst	original	not comparable	L	10	*pending*
martins2024 [109]	2024	early	added	not comparable	M	11	*pending*
marulanda2020 [277]	2020	pe	added	not comparable	S	15	*pending*
marx2024 [9]	2024	cbc	original	comparable	M	4	*pending*
marx2025aframeO3 [10]	2025	cbc	added	comparable	M	3	*pending*
mcginn2021 [302]	2021	other	original	not comparable	M	7	*pending*
mcisaac2022 [103]	2022	cbc	added	conditional	L	14	*pending*
mcleod2022 [269]	2022	pe	added	not comparable	L	15	*pending*
mcleod2025 [16]	2025	cbc	original	comparable	L	6	*pending*
meijer2023cosmicstrings [145]	2023	burst	added	not comparable	L	12	*pending*
meijer2024 [36]	2024	cbc	added	not comparable	M	2	*pending*
menendez2022sub [53]	2022	cbc	added	not comparable	-	0	*pending*
menendez2024 [75]	2024	cbc	original	conditional	M	9	*pending*
menendezvazquez2021 [73]	2021	cbc	original	conditional	M	9	*pending*
mesuga2021 [176]	2021	glitch	added	not comparable	L	10	*pending*
miller2019 [171]	2019	cw	added	not comparable	L	15	*pending*
mishra2021 [132]	2021	burst	added	conditional	L	14	*pending*
mlgwsc2022 [8]	2022	cbc	original	comparable	L	4	*pending*
mobilia2026 [86]	2026	cbc	original	not comparable	M	6	*pending*
modafferi2023 [144]	2023	burst	original	not comparable	L	15	*pending*
mogushi2021 [248]	2021	denoise	original	not comparable	L	14	*pending*
mogushi2021nnetfix [249]	2021	denoise	original	not comparable	S	8	*pending*
morales2024 [122]	2024	burst	added	not comparable	L	12	*pending*

Model	Year	Section	Origin	Grade	Effort	Step	gravyflow
morawski2020cw [167]	2019	cw	added	not comparable	L	15	*pending*
morawski2021 [151]	2021	anomaly	added	not comparable	-	0	*pending*
moreno2022 [140]	2022	burst	original	conditional	M	7	*pending*
murali2022 [235]	2022	denoise	added	not comparable	-	0	*pending*
nagarajan2025 [14]	2025	cbc	original	comparable	L	4	*pending*
nigam2020 [125]	2020	burst	original	not comparable	S	7	*pending*
nousi2022 [12]	2023	cbc	original	comparable	M	4	*pending*
nunes2024 [127]	2024	burst	added	not comparable	-	0	*pending*
ormiston2020 [25]	2020	denoise	original	conditional	L	14	*pending*
oshino2025 [198]	2025	glitch	added	not comparable	-	0	*pending*
papalini2025 [272]	2025	pe	added	not comparable	-	0	*pending*
papigkiotis2026 [111]	2026	early	added	not comparable	L	11	*pending*
pimpalkar2026 [251]	2026	denoise	added	conditional	L	14	*pending*
powell2015 [216]	2015	glitch	original	not comparable	M	14	*pending*
powell2016 [217]	2016	glitch	original	not comparable	L	14	*pending*
powell2022 [304]	2022	other	added	not comparable	L	13	*pending*
pracchia2025 [128]	2025	burst	original	conditional	M	12	*pending*
qiu2022 [39]	2022	cbc	original	not comparable	S	2	*pending*
que2021 [312]	2021	other	added	not comparable	M	13	*pending*
rai2026 [99]	2026	cbc	added	not comparable	S	9	*pending*
raikman2023 [146]	2023	anomaly	original	conditional	M	7	*pending*
raikman2024 [136]	2024	burst	original	comparable	L	7	*pending*
ratner2026 [138]	2026	burst	original	conditional	M	7	*pending*
ravichandran2023 [284]	2023	pe	added	not comparable	L	15	*pending*
razzano2018 [218]	2018	glitch	original	not comparable	S	10	*pending*
rebei2018 [33]	2018	cbc	added	not comparable	L	2	*pending*
reissel2025 [244]	2025	denoise	added	conditional	L	14	*pending*
ruan2023 [285]	2023	space	original	not comparable	L	15	*pending*
ruan2023pe [287]	2023	space	added	not comparable	L	15	*pending*
ruan2024 [286]	2024	space	added	not comparable	L	15	*pending*
sakai2022 [194]	2022	glitch	original	not comparable	M	13	*pending*
sakai2024 [239]	2024	denoise	added	not comparable	-	0	*pending*
sakellariou2026 [283]	2026	pe	added	not comparable	S	15	*pending*
saleem2023 [242]	2023	denoise	original	conditional	L	14	*pending*
sankarapandian2021 [201]	2021	glitch	added	not comparable	L	13	*pending*
santos2020 [47]	2020	cbc	added	not comparable	S	2	*pending*
sasaoka2023_cbc [98]	2023	cbc	original	not comparable	-	0	*pending*
sasaoka2023_ccsn [120]	2023	burst	original	not comparable	-	0	*pending*
sasaoka2023attr [92]	2023	cbc	added	not comparable	M	9	*pending*
schafer2020 [5]	2020	cbc	original	comparable	L	11	*pending*
schafer2021a [6]	2021	cbc	original	conditional	S	2	*pending*
schafer2021b [7]	2021	cbc	original	conditional	M	3	*pending*
schmitt2019 [44]	2019	cbc	original	not comparable	-	0	*pending*
shah2023 [208]	2023	glitch	added	not comparable	L	10	*pending*
sharma2023 [58]	2023	cbc	added	not comparable	-	0	*pending*
sharma2024 [59]	2024	cbc	added	not comparable	-	0	*pending*
shen2017 [24]	2017	denoise	original	not comparable	S	8	*pending*
shen2019 [225]	2019	denoise	original	conditional	S	8	*pending*
shen2019pe [268]	2019	pe	added	not comparable	L	15	*pending*
silver2025 [78]	2025	cbc	original	not comparable	M	2	*pending*
singh2020 [278]	2020	pe	added	not comparable	S	15	*pending*
singh2025 [188]	2025	glitch	added	not comparable	-	0	*pending*
skliris2024 [135]	2024	burst	original	comparable	S	1	*pending*
soma2023 [279]	2023	pe	added	not comparable	S	15	*pending*
soni2021 [22]	2021	glitch	original	conditional	S	10	*pending*
srivastava2024 [180]	2024	glitch	original	conditional	S	10	*pending*
sun2026 [123]	2026	burst	added	conditional	L	12	*pending*
szczepanczyk2022 [18]	2022	burst	original	comparable	L	14	*pending*
talpini2022 [183]	2022	glitch	added	not comparable	-	0	*pending*
tenorio2025g2net_cw [163]	2025	cw	added	conditional	L	15	*pending*
tian2023 [66]	2023	cbc	added	conditional	M	5	*pending*
tian2024gnn [67]	2023	cbc	added	conditional	M	5	*pending*
tiki2025 [77]	2025	cbc	added	conditional	M	3	*pending*
torresforne2020 [250]	2020	denoise	added	not comparable	M	8	*pending*
trovato2023 [81]	2023	cbc	original	conditional	M	10	*pending*
ussipov2024 [60]	2024	cbc	added	not comparable	-	0	*pending*

Model	Year	Section	Origin	Grade	Effort	Step	gravyflow
utina2021 [308]	2021	other	added	not comparable	S	15	*pending*
vajente2020 [245]	2020	denoise	original	not comparable	L	14	*pending*
vandyke2025 [205]	2025	glitch	added	conditional	S	10	*pending*
vanstraalen2024 [262]	2024	pe	added	not comparable	L	15	*pending*
verma2021 [49]	2021	cbc	original	not comparable	S	2	*pending*
verma2022 [32]	2022	cbc	original	not comparable	S	2	*pending*
vinciguerra2017 [129]	2017	burst	added	not comparable	L	14	*pending*
wang2020 [83]	2020	cbc	original	not comparable	M	6	*pending*
wang2022waveformer [229]	2024	denoise	original	conditional	L	8	*pending*
wang2023tf [91]	2024	cbc	original	conditional	M	9	*pending*
wang2025exotic [79]	2025	cbc	original	conditional	M	2	*pending*
wang2026ccsn_scl [124]	2026	burst	added	not comparable	L	12	*pending*
weerasinghe2026 [62]	2026	cbc	added	not comparable	M	15	*pending*
wei2020denoise [226]	2020	denoise	original	conditional	S	8	*pending*
wei2021 [114]	2021	early	original	not comparable	L	11	*pending*
wei2021ensemble [63]	2021	cbc	original	conditional	M	5	*pending*
wei2021forecast [113]	2021	early	original	not comparable	M	11	*pending*
wu2024 [179]	2024	glitch	original	conditional	S	10	*pending*
xia2021 [34]	2021	cbc	original	conditional	S	2	*pending*
xie2026 [190]	2026	glitch	added	not comparable	-	0	*pending*
xu2024 [311]	2024	other	original	not comparable	L	15	*pending*
xu2024denoise [254]	2024	denoise	added	not comparable	L	15	*pending*
xu2026ssl_lisa [296]	2026	space	added	not comparable	L	15	*pending*
yamamoto2021cw [169]	2020	cw	added	conditional	L	15	*pending*
yamamoto2022cw [170]	2022	cw	added	conditional	L	15	*pending*
yamamoto2023 [172]	2023	cw	original	not comparable	S	15	*pending*
yamamoto2025 [70]	2025	cbc	original	comparable	M	6	*pending*
yan2021 [84]	2021	cbc	original	not comparable	M	6	*pending*
yan2022 [54]	2022	cbc	original	not comparable	-	0	*pending*
yan2022gan [182]	2022	glitch	added	conditional	L	10	*pending*
yan2025deepgrav [139]	2025	burst	added	not comparable	M	7	*pending*
yu2021early [112]	2021	early	original	conditional	L	14	*pending*
yu2021noise [246]	2021	denoise	original	not comparable	L	14	*pending*
yun2023 [290]	2023	space	added	not comparable	L	15	*pending*
zelenka2024 [69]	2024	cbc	added	comparable	M	4	*pending*
zevin2017 [20]	2017	glitch	original	conditional	M	10	*pending*
zevin2024 [177]	2024	glitch	original	conditional	S	10	*pending*
zhan2021 [50]	2021	cbc	added	not comparable	S	2	*pending*
zhang2022 [55]	2022	cbc	original	not comparable	-	0	*pending*
zhang2022emri [289]	2022	space	added	not comparable	L	15	*pending*
zhang2026 [258]	2026	pe	added	conditional	L	15	*pending*
zhao2023 [288]	2023	space	original	not comparable	L	15	*pending*

15 Open questions

Which benchmark contract should gravyflow's validator reproduce first? MLGWSC-1 is the only cross-paper detection contract with published code; the LVK injection campaigns are the production-grade alternative. Reproducing both would let every reproduced detector be placed on the comparable rows of Section Section 3.

Per-window false-alarm probabilities. Most detection papers report them. A rate needs the window stride, the clustering rule and the background duration, which many papers omit; our reproductions can supply the rate for the paper's own network, but the paper's numbers stay as reported.

Gravity Spy release and split. Glitch accuracies differ by release and split. A fixed gravyflow split of one release (with macro-F1 as well as accuracy) would make the reproduced classifiers comparable among themselves.

Entries to resolve. 42 entries were read at abstract level or not at all (none has an arXiv version); they need institutional access. The sweep left open whether george2018plb should merge with george2018b, and it found that ma2024tempfree and the MSNRnet-1 citation share a journal article number, so one citation is wrong. Two marginal entries are kept and flagged: kelleter2026nnnn (seismic-array Newtonian-noise regression) and jia2026 (data type unverified).

Suspected errors. The highlighted inconsistencies are the synthesiser's reading of the extraction notes. Before any is cited outside this review it should be checked against the paper, and where it matters, raised with the authors.

Out-of-scope domains. Space-based detectors, continuous waves and full parameter estimation need new detector responses, waveform families or diagnostics in gravyflow. Whether they enter the reproduction programme is a scope decision.

References

[1] D. George and E. A. Huerta, 'Deep neural networks to enable real-time multimessenger astrophysics (Deep Filtering)', *Phys. Rev. D 97, 044039 (2018)*, 2018, doi: 10.1103/PhysRevD.97.044039.

[2] H. Gabbard, M. Williams, F. Hayes, and C. Messenger, 'Matching matched filtering with deep networks for gravitational-wave astronomy', *Phys. Rev. Lett. 120, 141103 (2018)*, 2018, doi: 10.1103/PhysRevLett.120.141103.

[3] D. George and E. A. Huerta, 'Deep Learning for real-time gravitational wave detection and parameter estimation: Results with Advanced LIGO data', *Phys. Lett. B 778, 64-70 (2018)*, 2018, doi: 10.1016/j.physletb.2017.12.053.

[4] T. D. Gebhard, N. Kilbertus, I. Harry, and B. Scholkopf, 'Convolutional neural networks: a magic bullet for gravitational-wave detection?', *Phys. Rev. D 100, 063015 (2019)*, 2019, doi: 10.1103/PhysRevD.100.063015.

[5] M. B. Schafer, F. Ohme, and A. H. Nitz, 'Detection of gravitational-wave signals from binary neutron star mergers using machine learning', *Phys. Rev. D 102, 063015 (2020)*, 2020, [Online]. Available: https://arxiv.org/abs/2006.01509

[6] M. B. Schafer, O. Zelenka, A. H. Nitz, F. Ohme, and B. Bruegmann, 'Training Strategies for Deep Learning Gravitational-Wave Searches', 2021. [Online]. Available: https://arxiv.org/abs/2106.03741

[7] M. B. Schafer and A. H. Nitz, 'From One to Many: A Deep Learning Coincident Gravitational-Wave Search', 2021. [Online]. Available: https://arxiv.org/abs/2108.10715

[8] M. B. Schafer, O. Zelenka, and A. H. Nitz, 'MLGWSC-1: The first Machine Learning Gravitational-Wave Search Mock Data Challenge', 2022. [Online]. Available: https://arxiv.org/abs/2209.11146

[9] E. Marx, W. Benoit, and A. Gunny, 'A machine-learning pipeline for real-time detection of gravitational waves from compact binary coalescences (Aframe)', 2024. [Online]. Available: https://arxiv.org/abs/2403.18661

[10] E. Marx, W. Benoit, T. Blodgett, D. Chatterjee, E. de Bruin, and S. Henderson, 'A machine learning-enabled search for binary black hole mergers in LIGO-Virgo-KAGRAs third observing run', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2505.21261

[11] B. Gupta *et al.*, 'AI-enabled gravitational-waves searches for binary neutron stars at optimal sensitivity', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2607.01372

[12] P. Nousi, A. E. Koloniari, N. Passalis, P. Iosif, N. Stergioulas, and A. Tefas, 'Deep Residual Networks for Gravitational Wave Detection (AresGW)', *Phys. Rev. D 108, 042002 (2023)*, 2023, [Online]. Available: https://arxiv.org/abs/2211.01520

[13] A. E. Koloniari, E. C. Koursoumpa, and P. Nousi, 'New Gravitational Wave Discoveries Enabled by Machine Learning (AresGW upgrade)', *Mach. Learn.: Sci. Technol. 6(1), 015054 (2025)*, 2024, [Online]. Available: https://arxiv.org/abs/2407.07820

[14] N. Nagarajan, 'Identifying and Mitigating Machine Learning Biases for the Gravitational Wave Detection Problem (Sage)', 2025. [Online]. Available: https://arxiv.org/abs/2501.13846

[15] D. Beveridge, A. McLeod, L. Wen, W. Guo, and A. Wicenec, 'Searching for binary black hole mergers with deep learning in Advanced LIGO's third observing run', *arXiv preprint v2 (Jul 2026); DOI 10.1103/3yph-35r4 given on the arXiv record (journal not stated in the text)*, 2025, doi: 10.1103/3yph-35r4.

[16] A. McLeod, 'Binary Neutron Star Merger Search Pipeline Powered by Deep Learning', *Phys. Rev. D 111, 024035 (2025)*, 2025, [Online]. Available: https://arxiv.org/abs/2409.06266

[17] G. Inguglia, H. Haigh, U. Dupletsa, and A. Longo, 'MADGRAV: a multilevel anomaly-detection pipeline for gravitational-wave searches applied to LIGO data', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2609.39583

[18] M. J. Szczepanczyk, 'Search for gravitational-wave bursts in the third Advanced LIGO-Virgo run with coherent WaveBurst enhanced by Machine Learning', 2022. [Online]. Available: https://arxiv.org/abs/2210.01754

[19] T. Mishra, B. O'Brien, M. Szczepanczyk, G. Vedovato, S. Bhaumik, and V. Gayathri, 'Search for binary black hole mergers in the third observing run of Advanced LIGO-Virgo using coherent WaveBurst enhanced with machine learning', *Phys. Rev. D 105, 083018 (2022); arXiv:2201.01495*, 2022, doi: 10.1103/PhysRevD.105.083018.

[20] M. Zevin, S. Coughlin, and S. Bahaadini, 'Gravity Spy: Integrating Advanced LIGO Detector Characterization, Machine Learning, and Citizen Science', *Class. Quantum Grav. 34, 064003 (2017)*, 2017, [Online]. Available: https://arxiv.org/abs/1611.04596

[21] S. Bahaadini, 'Deep Multi-view Models for Glitch Classification', *ICASSP 2017*, 2017, [Online]. Available: https://arxiv.org/abs/1705.00034

[22] S. Soni, 'Discovering features in gravitational-wave data through detector characterization, citizen science and machine learning', *Class. Quantum Grav. 38, 195016 (2021)*, 2021, [Online]. Available: https://arxiv.org/abs/2103.12104

[23] J. Glanzer, 'Data quality up to the third observing run of Advanced LIGO: Gravity Spy glitch classifications', *Class. Quantum Grav. 40, 065004 (2023)*, 2023, [Online]. Available: https://arxiv.org/abs/2208.12849

[24] H. Shen, D. George, E. A. Huerta, and Z. Zhao, 'Denoising Gravitational Waves using Deep Learning with Recurrent Denoising Autoencoders', *ICASSP 2019*, 2017, [Online]. Available: https://arxiv.org/abs/1711.09919

[25] R. Ormiston, T. Nguyen, M. Coughlin, R. X. Adhikari, and E. Katsavounidis, 'Noise Reduction in Gravitational-wave Data via Deep Learning (DeepClean)', *Phys. Rev. Research 2, 033066 (2020)*, 2020, [Online]. Available: https://arxiv.org/abs/2005.06534

[26] S. R. Green and J. Gair, 'Complete parameter inference for GW150914 using deep learning', 2020. [Online]. Available: https://arxiv.org/abs/2008.03312

[27] M. Dax, 'Real-time gravitational-wave science with neural posterior estimation (DINGO)', *Phys. Rev. Lett. 127, 241103 (2021)*, 2021, [Online]. Available: https://arxiv.org/abs/2106.12594

[28] M. Dax, S. R. Green, J. Gair, M. Pürrer, J. Wildberger, and J. H. Macke, 'Neural Importance Sampling for Rapid and Reliable Gravitational-Wave Inference', *Phys. Rev. Lett. 130, 171403 (2023)*, 2022, doi: 10.1103/PhysRevLett.130.171403.

[29] D. George and E. A. Huerta, 'Deep Learning for Real-time Gravitational Wave Detection and Parameter Estimation with LIGO Data', *NIPS 2017 Workshop on Deep Learning for Physical Sciences (DLPS), arXiv 1711.07966v2*, 2017, [Online]. Available: https://arxiv.org/abs/1711.07966

[30] P. G. Krastev, 'Real-time detection of gravitational waves from binary neutron stars using artificial neural networks', *Phys. Lett. B 803, 135330 (2020)*, 2020, doi: 10.1016/j.physletb.2020.135330.

[31] P. G. Krastev, K. Gill, V. A. Villar, and E. Berger, 'Detection and Parameter Estimation of Gravitational Waves from Binary Neutron-Star Mergers in Real LIGO Data using Deep Learning', *Phys. Lett. B 815, 136161 (2021)*, 2021, [Online]. Available: https://arxiv.org/abs/2012.13101

[32] C. Verma, 'Detection of Gravitational Wave Signals from Precessing Binary Black Hole Systems using Convolutional Neural Network', 2022. [Online]. Available: https://arxiv.org/abs/2206.12673

[33] A. Rebei, E. A. Huerta, S. Wang, S. Habib, R. Haas, and D. Johnson, 'Fusing numerical relativity and deep learning to detect higher-order multipole waveforms from eccentric binary black hole mergers', *Phys. Rev. D 100, 044025 (2019)*, 2018, doi: 10.1103/PhysRevD.100.044025.

[34] H. Xia, 'Improved deep learning techniques in gravitational-wave data analysis', *Phys. Rev. D 103, 024040 (2021)*, 2021, [Online]. Available: https://arxiv.org/abs/2011.04418

[35] D. S. Deighan, S. E. Field, C. D. Capano, and G. Khanna, 'Genetic-algorithm-optimized neural networks for gravitational wave classification', *Neural Computing and Applications volume 33, pages 13859 - 13883 (2021)*, 2020, doi: 10.1007/s00521-021-06024-4.

[36] Q. Meijer, M. van der Sluys, and S. Caudill, 'Robustness of Deep Learning Models to Precession in Gravitational-Wave Searches for Intermediate-Mass Black Hole Binaries', *arXiv preprint*, 2024, [Online]. Available: https://arxiv.org/abs/2410.07855

[37] Y.-C. Lin and J.-H. P. Wu, 'Detection of gravitational waves using Bayesian neural networks', *Phys. Rev. D 103, 063034 (2021)*, 2021, doi: 10.1103/PhysRevD.103.063034.

[38] C. Ma, W. Wang, H. Wang, and Z. Cao, 'Ensemble of deep convolutional neural networks for real-time gravitational wave signal recognition', *Phys. Rev. D 105, 083013 (2022)*, 2022, doi: 10.1103/PhysRevD.105.083013.

[39] R. Qiu, 'Deep Learning Detection and Classification of Gravitational Waves from Neutron Star-Black Hole Mergers', 2022. [Online]. Available: https://arxiv.org/abs/2210.15888

[40] C. Bresten, 'Detection of gravitational waves using topological data analysis and convolutional neural network: An improved approach', 2019. [Online]. Available: https://arxiv.org/abs/1910.08245

[41] X. Fan, J. Li, X. Li, Y. Zhong, and J. Cao, 'Applying deep neural networks to the detection and space parameter estimation of compact binary coalescence with a network of gravitational wave detectors', *Sci. China Phys. Mech. Astron. 62, 969512 (2019)*, 2019, doi: 10.1007/s11433-018-9321-7.

[42] B.-J. Lin, X.-R. Li, and W.-L. Yu, 'Binary neutron stars gravitational wave detection based on wavelet packet analysis and convolutional neural networks', *Frontiers of Physics 15(2): 24602 (2020)*, 2019, doi: 10.1007/s11467-019-0935-y.

[43] H.-M. Luo, W. Lin, Z.-C. Chen, and Q.-G. Huang, 'Extraction of gravitational wave signals with optimized convolutional neural network', *Frontiers of Physics 15(1)*, 2019, doi: 10.1007/s11467-019-0936-x.

[44] A. Schmitt, K. Fu, S. Fan, and Y. Luo, 'Investigating Deep Neural Networks for Gravitational Wave Detection in Advanced LIGO Data', *Proc. 2nd ICCSSE (ACM)*, 2019, doi: 10.1145/3339363.3339377.

[45] Y. Chauhan, 'Deep Learning Techniques to make Gravitational Wave Detections from Weak Time-Series Data', *International Astronomy and Astrophysics Research Journal, Vol. 3, no. 2, Apr. 2021, pp. 1-9*, 2020, [Online]. Available: https://arxiv.org/abs/2007.05889

[46] X.-R. Li *et al.*, 'Some optimizations on detecting gravitational wave using convolutional neural network', *Front. Phys. 15(5), 54501 (2020)*, 2020, doi: 10.1007/s11467-020-0966-4.

[47] G. R. Santos, M. P. Figueiredo, A. de P. Santos, P. Protopapas, and T. A. E. Ferreira, 'Gravitational Wave Detection and Information Extraction via Neural Networks', *arXiv preprint*, 2020, [Online]. Available: https://arxiv.org/abs/2003.09995

[48] H. Dodia, 'Detecting residues of cosmic events using residual neural network', *arXiv preprint*, 2021, [Online]. Available: https://arxiv.org/abs/2101.00195

[49] C. Verma, 'Employing Deep Learning for Detection of Gravitational Waves from Compact Binary Coalescences', 2021. [Online]. Available: https://arxiv.org/abs/2110.01883

[50] C. Zhan, M. Jia, C. Ma, Z. Lu, and W. Lin, 'The response of the Convolutional Neural Network to the transient noise in Gravitational wave detection', *arXiv preprint*, 2021, [Online]. Available: https://arxiv.org/abs/2103.03557

[51] L. Jiang and Y. Luo, 'Convolutional Transformer for Fast and Accurate Gravitational Wave Detection', *ICPR 2022*, 2022, doi: 10.1109/ICPR56361.2022.9956104.

[52] M.-Q. Jiang, N. Yang, and J. Li, 'Identify real gravitational wave events in the LIGO-Virgo catalog GWTC-1 and GWTC-2 with convolutional neural network', *Frontiers of Physics 17, 54501 (2022)*, 2022, doi: 10.1007/s11467-021-1150-1.

[53] M. Vazquez and M. Perez, 'Search for subsolar mass black holes in LIGO/Virgo using O3 data and the implementation of Machine Learning algorithms', *Proceedings*, 2022.

[54] R.-Q. Yan *et al.*, 'Gravitational Wave Detection Based on Squeeze-and-excitation Shrinkage Networks and Multiple Detector Coherent SNR', *Res. Astron. Astrophys. 22(11)*, 2022, doi: 10.1088/1674-4527/ac846c.

[55] Y. Zhang, H. Xu, M. Liu, C. Liu, Y. Zhao, and J. Zhu, 'Deep learning model based on a bidirectional gated recurrent unit for the detection of gravitational wave signals', *Phys. Rev. D 106, 122002 (2022)*, 2022, doi: 10.1103/PhysRevD.106.122002.

[56] S. Garg *et al.*, 'Comparison of training methods for Convolutional Neural Network model for Gravitational-Wave detection from Neutron Star-Black Hole Binaries', *38th International Cosmic Ray Conference (ICRC2023), PoS 444 (MM&GW); pre-published 18 Aug 2023, published 27 Sep 2024*, 2023, doi: 10.22323/1.444.1536.

[57] L. Kumar, S. K. Sahay, and H. G. Kusneniwar, 'An investigation of two-step cascaded CNN for the detection of gravitational wave signal from two different astrophysical sources', *Procedia Computer Science 222 (2023) 676-684 (INNS DLIA workshop at IJCNN 2023 per dblp)*, 2023, doi: 10.1016/j.procs.2023.08.205.

[58] Sharma and Chandra, 'Searching for massive black hole binaries with a transfer learning algorithm', *Phys. Rev. D 108, 124061 (2023)*, 2023, doi: 10.1103/PhysRevD.108.124061.

[59] Sharma and Kaur, 'Detection of Gravitational Waves Using Machine Learning', *IEEE INCET 2024*, 2024, doi: 10.1109/INCET61516.2024.10593087.

[60] Ussipov and Zhanabaev, 'Classification of Gravitational Waves from Black Hole-Neutron Star Mergers with Machine Learning', *J. Astron. Space Sci. 41, 149 (2024)*, 2024, doi: 10.5140/JASS.2024.41.3.149.

[61] A. Gupta and N. Jindal, 'A hybrid quantum-classical deep learning approach for gravitational wave detection', *Quantum Machine Intelligence (2026), article 10.1007/s42484-026-00393-6*, 2026, doi: 10.1007/s42484-026-00393-6.

[62] R. Weerasinghe, 'Real-Time Multi-Mode Post-Merger Gravitational Wave Detection using Convolutional Neural Networks: Methodology Development for Third-Generation Detectors', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2601.00985

[63] W. Wei, A. Khan, and E. A. Huerta, 'Deep Learning Ensemble for Real-time Gravitational Wave Detection of Spinning Binary Black Hole Mergers', *Phys. Lett. B 812, 136029 (2021)*, 2021, [Online]. Available: https://arxiv.org/abs/2010.15845

[64] E. A. Huerta, A. Khan, and X. Huang, 'Accelerated, scalable and reproducible AI-driven gravitational wave detection', *Nature Astronomy 5, 1062-1068 (2021)*, 2021, doi: 10.1038/s41550-021-01405-0.

[65] P. Chaturvedi, A. Khan, M. Tian, E. A. Huerta, and H. Zheng, 'Inference-optimized AI and high performance computing for gravitational wave detection at scale', *Front. Artif. Intell. 5:828672 (2022)*, 2022, doi: 10.3389/frai.2022.828672.

[66] M. Tian, E. A. Huerta, and H. Zheng, 'AI ensemble for signal detection of higher order gravitational wave modes of quasi-circular, spinning, non-precessing binary black hole mergers', *arXiv preprint*, 2023, [Online]. Available: https://arxiv.org/abs/2310.00052

[67] M. Tian, E. A. Huerta, H. Zheng, and P. Kumar, 'Physics-inspired spatiotemporal-graph AI ensemble for the detection of higher order wave mode signals of spinning binary black hole mergers', *Mach. Learn.: Sci. Technol. 5 (2024) 025056*, 2023, doi: 10.1088/2632-2153/ad4c37.

[68] A. Gunny, 'Hardware-accelerated Inference for Real-Time Gravitational-Wave Astronomy', 2021. [Online]. Available: https://arxiv.org/abs/2108.12430

[69] O. Zelenka, B. Bruegmann, and F. Ohme, 'Convolutional Neural Networks for signal detection in real LIGO data', *Phys. Rev. D 110, 024024 (2024)*, 2024, doi: 10.1103/PhysRevD.110.024024.

[70] T. S. Yamamoto, 'Hybrid algorithm combining matched filtering and convolutional neural networks for searching gravitational waves from binary black hole mergers', 2025. [Online]. Available: https://arxiv.org/abs/2512.12399

[71] C. Chatterjee, 'Pre-trained Audio Transformer as a Foundational AI Tool for Gravitational Waves (GW-Whisper)', 2024. [Online]. Available: https://arxiv.org/abs/2412.20789

[72] C. Chatterjee, A. Petulante, H. Fu, Y. Hu, R. Lau, and K. Jani, 'A Fast and Scalable Transformer Pipeline for Binary Black Hole Detection (CASTOR)', 2026. [Online]. Available: https://arxiv.org/abs/2609.00339

[73] A. Menendez-Vazquez, M. Kolstein, M. Martinez, and L. M. Mir, 'Searches for compact binary coalescence events using neural networks in the LIGO/Virgo second observation period', *Phys. Rev. D 103, 062004 (2021)*, 2021, doi: 10.1103/PhysRevD.103.062004.

[74] M. Andres-Carcasona, A. Menendez-Vazquez, M. Martinez, and L. M. Mir, 'Searches for mass-asymmetric compact binary coalescence events using neural networks in the LIGO/Virgo third observation period', *Phys. Rev. D 107, 082003 (2023)*, 2023, doi: 10.1103/PhysRevD.107.082003.

[75] A. Menendez-Vazquez, 'Searches for Compact Binary Coalescence Events Using Neural Networks in LIGO/Virgo Third Observation Period', *Class. Quantum Grav. 41, 135018 (2024)*, 2024, [Online]. Available: https://arxiv.org/abs/2401.12912

[76] D. Beveridge, L. Wen, and A. Wicenec, 'Novel deep learning approach to detecting binary black hole mergers (earlier: Detection of BBH mergers from the SNR time series using deep learning)', *Phys. Rev. D 111, 024005 (2025) (from search results)*, 2023, [Online]. Available: https://arxiv.org/abs/2308.08429

[77] V. Tiki and E. Huerta, 'A Practical Study of Lightweight Neural Gravitational-Wave Detection in Real LIGO Noise: Models, Ablations, and Open Software', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2512.12513

[78] E. Silver, 'A Search for Binary Black Hole Mergers in LIGO O1-O3 Data with Convolutional Neural Networks', 2025. [Online]. Available: https://arxiv.org/abs/2512.17204

[79] Y.-X. Wang, 'Search for exotic gravitational wave signals beyond general relativity using deep learning', *Phys. Rev. D 112, 024030 (2025)*, 2025, [Online]. Available: https://arxiv.org/abs/2410.20129

[80] S. Jadhav, M. Shrivastava, and S. Mitra, 'Towards a robust and reliable deep learning approach for detection of compact binary mergers in gravitational wave data', *Mach. Learn.: Sci. Technol. 4, 045028 (2023)*, 2023, [Online]. Available: https://arxiv.org/abs/2306.11797

[81] A. Trovato, 'Neural network time-series classifiers for gravitational-wave searches in single-detector periods', *Class. Quantum Grav. 41, 125003 (2024)*, 2023, [Online]. Available: https://arxiv.org/abs/2307.09268

[82] M. Andrews, M. Paulini, L. Sellers, A. Bobrick, G. Martire, and H. Vestal, 'DeepSNR: A deep learning foundation for offline gravitational wave detection', 2022. [Online]. Available: https://arxiv.org/abs/2207.04749

[83] H. Wang, S. Wu, Z. Cao, X. Liu, and J.-Y. Zhu, 'Gravitational-wave signal recognition of LIGO data by deep learning (MFCNN)', *Phys. Rev. D 101, 104003 (2020)*, 2020, doi: 10.1103/PhysRevD.101.104003.

[84] J. Yan *et al.*, 'Generalized Approach to Matched Filtering using Neural Networks', 2021. [Online]. Available: https://arxiv.org/abs/2104.03961

[85] C. Ma, S. Wang, W. Wang, and Z. Cao, 'Matched filtering for gravitational wave detection without template bank driven by deep learning template prediction model bank', *Phys. Rev. D 109, 043009 (2024); arXiv v1 5 Sep 2023 (the authors later call the framework MSNRnet)*, 2023, doi: 10.1103/PhysRevD.109.043009.

[86] L. Mobilia, 'Deep Learning Search for Gravitational Waves from Compact Binary Coalescence (TT-SNR map + CNN)', 2026. [Online]. Available: https://arxiv.org/abs/2603.09386

[87] C. Badger *et al.*, 'Rapid detection of gravitational waves from binary black hole mergers using sparse dictionary learning', *arXiv preprint (v3, 21 Mar 2025); no journal reference on the arXiv record*, 2024, [Online]. Available: https://arxiv.org/abs/2405.17721

[88] Ma and Liu, 'Denoising and detection for binary black hole gravitational waves in the context of the Einstein Telescope', *Sci. China Phys. Mech. Astron. 2025*, 2025, doi: 10.1007/s11433-025-2673-5.

[89] J. D. Álvares, J. A. Font, F. F. Freitas, O. G. Freitas, A. P. Morais, and S. Nunes, 'Exploring gravitational-wave detection and parameter inference using Deep Learning methods', *Class. Quantum Grav. 38 (2021) 155010 (arXiv:2011.10425)*, 2021, doi: 10.1088/1361-6382/ac0455.

[90] J. Aveiro *et al.*, 'Identification of binary neutron star mergers in gravitational-wave data using object-detection machine learning models (YOLO)', *Phys. Rev. D 106, 084059 (2022)*, 2022, doi: 10.1103/PhysRevD.106.084059.

[91] Y.-X. Wang, 'Rapid identification of time-frequency domain gravitational wave signals from binary black holes using deep learning', *Chin. Phys. C 48, 125107 (2024)*, 2024, [Online]. Available: https://arxiv.org/abs/2305.19003

[92] S. Sasaoka, N. Koyama, D. Dominguez, Y. Sakai, K. Somiya, and Y. Omae, 'Comparative study of 1D and 2D convolutional neural network models with attribution analysis for gravitational wave detection from compact binary coalescences', *Phys. Rev. D 109, 043011 (2024)*, 2023, doi: 10.1103/PhysRevD.109.043011.

[93] W. Alhassan, 'Detection of Einstein Telescope gravitational wave signals from binary black holes using deep learning', 2022. [Online]. Available: https://arxiv.org/abs/2211.13789

[94] W. Alhassan, T. Bulik, and M. Suchenek, 'PyMerger: Detecting Binary Black Hole merger from Einstein Telescope Using Deep Learning', *arXiv preprint (astro-ph.IM, Oct 2023); later versions list the software paper Alhassan et al. 2024; no journal reference in this PDF*, 2023, [Online]. Available: https://arxiv.org/abs/2310.10409

[95] H. Dodia, H. Tandel, and L. D'Mello, 'SpecGrav -- Detection of Gravitational Waves using Deep Learning', *arXiv preprint*, 2021, [Online]. Available: https://arxiv.org/abs/2107.03607

[96] S. Fan, Y. Wang, Y. Luo, A. Schmitt, and S. Yu, 'Improving Gravitational Wave Detection with 2D Convolutional Neural Networks', *ICPR 2020, pp. 7103-7110*, 2021, doi: 10.1109/ICPR48806.2020.9412180.

[97] D. Zhang, 'Detecting Gravitational Waves using Constant-Q Transform and Convolutional Neural Networks', *2021 4th International Conference on Computational Intelligence and Intelligent Systems (CIIS 2021), Tokyo; ACM, published 20 Nov 2021 (ACM DL record 2022)*, 2021, doi: 10.1145/3507623.3507630.

[98] S. Sasaoka *et al.*, 'Deep Learning for Detecting Gravitational Waves from Compact Binary Coalescences and Its Visualization by Grad-CAM', *PoS(ICRC2023) 1498*, 2023, doi: 10.22323/1.444.1498.

[99] R. Rai, R. Verma, and Somya, 'CASPER: Interpretable ResNet based Classifier with FastShap Explainer for Gravitational Wave Detection', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2606.17214

[100] K. Kim *et al.*, 'Application of Artificial Neural Network to Search for Gravitational-Wave Signals Associated with Short Gamma-Ray Bursts', *Class. Quantum Grav. 32 (2015) 245002*, 2015, doi: 10.1088/0264-9381/32/24/245002.

[101] K. Kim, T. G. F. Li, R. K. L. Lo, S. Sachdev, and R. S. H. Yuen, 'Ranking Candidate Signals with Machine Learning in Low-Latency Search for Gravitational-Waves from Compact Binary Mergers', *Phys. Rev. D 101, 083006 (2020)*, 2019, doi: 10.1103/PhysRevD.101.083006.

[102] S. Jadhav, N. Mukund, B. Gadre, S. Mitra, and S. Abraham, 'Improving significance of binary black hole mergers in Advanced LIGO data using deep learning : Confirmation of GW151216', *Phys. Rev. D 104, 064051 (2021)*, 2020, doi: 10.1103/PhysRevD.104.064051.

[103] C. McIsaac and I. Harry, 'Using machine learning to auto-tune chi-squared tests for gravitational wave searches', *Phys. Rev. D 105, 104056 (2022)*, 2022, doi: 10.1103/PhysRevD.105.104056.

[104] S. Insley, M. J. Williams, R. Dhurkunde, and I. Harry, 'Normalizing flows for density estimation in multi-detector gravitational-wave searches', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2604.26581

[105] G. Ashton, A.-K. Malz, and N. Colombo, 'Enhancing gravitational-wave detection: a machine learning pipeline combination approach with robust uncertainty quantification', *Phys. Rev. D (DOI 10.1103/yfb3-fgf2); arXiv:2504.17587 (PDF is a later revision citing GWTC-4.0)*, 2025, doi: 10.1103/yfb3-fgf2.

[106] G. Baltus, J. Janquart, M. Lopez, A. Reza, S. Caudill, and J.-R. Cudell, 'Convolutional neural networks for the detection of the early inspiral of a gravitational-wave signal', *Phys. Rev. D 103, 102003 (2021)*, 2021, doi: 10.1103/PhysRevD.103.102003.

[107] G. Baltus, J.-R. Cudell, J. Janquart, M. Lopez, S. Caudill, and A. Reza, 'Detecting the early inspiral of a gravitational-wave signal with convolutional neural networks (CBMI 2021)', *CBMI 2021*, 2021, doi: 10.1109/CBMI50038.2021.9461919.

[108] G. Baltus, J. Janquart, M. Lopez, H. Narola, and J.-R. Cudell, 'Convolutional neural network for gravitational-wave early alert: Going down in frequency', *Phys. Rev. D 106, 042002 (2022)*, 2022, doi: 10.1103/PhysRevD.106.042002.

[109] A. Martins, M. Lopez, Q. Meijer, G. Baltus, M. van der Sluys, and C. Van Den Broeck, 'Improving early detection of gravitational waves from binary neutron stars using CNNs and FPGAs', *arXiv preprint*, 2024, [Online]. Available: https://arxiv.org/abs/2409.05068

[110] R. Alfaidi and C. Messenger, 'Long Short-Term Memory for Early Warning Detection of Gravitational Waves', *arXiv preprint (gr-qc, 7 Feb 2024); no journal reference found in the PDF*, 2024, [Online]. Available: https://arxiv.org/abs/2402.04589

[111] G. Papigkiotis, G. Vardakas, and N. Stergioulas, 'GW-FALCON: A Novel Feature-Driven Deep Learning Approach for Early Warning Alerts of BNS and NSBH Inspirals in Next-Generation GW Observatories', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2602.15073

[112] H. Yu and R. X. Adhikari, 'Early warning of coalescing neutron-star and neutron-star-black-hole binaries from nonstationary noise background using neural networks', *Phys. Rev. D 104, 062004 (2021)*, 2021, [Online]. Available: https://arxiv.org/abs/2104.09438

[113] W. Wei and E. A. Huerta, 'Deep learning for gravitational wave forecasting of neutron star mergers', *Phys. Lett. B 816, 136185 (2021)*, 2021, [Online]. Available: https://arxiv.org/abs/2010.09751

[114] W. Wei *et al.*, 'Deep Learning with Quantized Neural Networks for Gravitational-wave Forecasting of Eccentric Compact Binary Coalescence', *Astrophys. J. 919(2), 82 (2021)*, 2021, doi: 10.3847/1538-4357/ac1121.

[115] P. Astone *et al.*, 'A New Method to Observe Gravitational Waves emitted by Core Collapse Supernovae', *Phys. Rev. D 98, 122002 (2018)*, 2018, [Online]. Available: https://arxiv.org/abs/1812.05363

[116] M. Lopez, I. Di Palma, M. Drago, P. Cerda-Duran, and F. Ricci, 'Deep learning for core-collapse supernova detection (arXiv: Deep learning for multimessenger core-collapse supernova detection)', *Phys. Rev. D 103, 063011 (2021)*, 2021, doi: 10.1103/PhysRevD.103.063011.

[117] M. L. Chan, I. S. Heng, and C. Messenger, 'Detection and classification of supernova gravitational wave signals: A deep learning approach', *Phys. Rev. D 102, 043022 (2020)*, 2020, doi: 10.1103/PhysRevD.102.043022.

[118] A. Iess, E. Cuoco, F. Morawski, and J. Powell, 'Core-Collapse Supernova Gravitational-Wave Search and Deep Learning Classification', *Mach. Learn.: Sci. Technol. 1(2), 025014 (2020)*, 2020, doi: 10.1088/2632-2153/ab7d31.

[119] A. Iess, E. Cuoco, F. Morawski, C. Nicolaou, and O. Lahav, 'LSTM and CNN application for core-collapse supernova search in gravitational wave real data', *Astron. Astrophys. 669 (2023)*, 2023, doi: 10.1051/0004-6361/202142525.

[120] S. Sasaoka *et al.*, 'Deep Learning Application for Detecting Gravitational Waves from Core-Collapse Supernovae (ICRC2023)', *PoS(ICRC2023) 1499*, 2023, doi: 10.22323/1.444.1499.

[121] A. Casallas-Lagos, M. J. Szczepańczyk, M. Zanolin, A. Mezzacappa, J. M. Antelis, and D. Murphy, 'Classifying the nuclear equation of state in LVK interferometric noise through core-collapse supernova gravitational-wave signatures using convolutional neural networks', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2607.21924

[122] M. D. Morales, J. M. Antelis, and C. Moreno, 'Residual neural networks to classify the high frequency emission in core-collapse supernova gravitational waves', *Gen. Relativ. Gravit. 57, 162 (2025)*, 2024, doi: 10.1007/s10714-025-03498-8.

[123] T.-Y. Sun, Y. Niu, C.-Y. Jiang, S.-J. Jin, Y. Yuan, and X. Zhang, 'Contrastive self-supervised convolutional autoencoder for core-collapse supernova gravitational-wave detection', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2605.21310

[124] A.-B. Wang, Y. Yuan, H. Cai, and X.-L. Fan, 'Classifying Core-Collapse Supernova Gravitational Waves using Supervised Contrastive Learning', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2601.01376

[125] R. Nigam, A. Mishra, and P. Reddy, 'Transient Classification in low SNR Gravitational Wave data using Deep Learning', 2020. [Online]. Available: https://arxiv.org/abs/2009.12168

[126] M. Lopez, M. Drago, I. Di Palma, F. Ricci, and P. Cerda-Duran, 'Deep learning algorithms for gravitational waves core-collapse supernova detection (CBMI 2021)', *CBMI 2021, pp. 1-6*, 2021, doi: 10.1109/CBMI50038.2021.9461885.

[127] S. Nunes, G. Escrig, O. G. Freitas, J. A. Font, T. Fernandes, and A. Onofre, 'Deep-Learning Classification and Parameter Inference of Rotational Core-Collapse Supernovae', *arXiv preprint*, 2024, doi: 10.1103/PhysRevD.110.064037.

[128] M. Pracchia, 'Short-Duration Gravitational Wave Burst Detection using Convolutional Neural Network', 2025. [Online]. Available: https://arxiv.org/abs/2509.13241

[129] S. Vinciguerra, M. Drago, G. A. Prodi, S. Klimenko, C. Lazzaro, and V. Necula, 'Enhancing the significance of gravitational wave bursts through signal classification', *Class. Quantum Grav. 34 (2017) 094003 (18pp)*, 2017, doi: 10.1088/1361-6382/aa6654.

[130] M. Cavaglia, 'Improving the background of gravitational-wave searches for core collapse supernovae: A machine learning approach', *Mach. Learn.: Sci. Technol. 1, 015005 (2020)*, 2020, [Online]. Available: https://arxiv.org/abs/2002.04591

[131] J. M. Antelis, M. Cavaglia, T. Hansen, M. D. Morales, C. Moreno, and S. Mukherjee, 'Using supervised learning algorithms as a follow-up method in the search of gravitational waves from core-collapse supernovae', *Phys. Rev. D 105, 084054 (2022); arXiv:2111.07219*, 2021, doi: 10.1103/PhysRevD.105.084054.

[132] T. Mishra, B. O'Brien, V. Gayathri, M. Szczepanczyk, S. Bhaumik, and I. Bartos, 'Optimization of model independent gravitational wave search using machine learning', *Phys. Rev. D 104, 023014 (2021)*, 2021, doi: 10.1103/PhysRevD.104.023014.

[133] D. Lopez, 'Utilizing Gaussian mixture models in all-sky searches for short-duration gravitational wave bursts', *Phys. Rev. D 105, 063024 (2022)*, 2022, [Online]. Available: https://arxiv.org/abs/2112.06608

[134] J. Fernandes, A. Pai, and K. Chandra, 'Improving the detection significance of gravitational wave transient searches with CNN models', *arXiv preprint 2505.08332v1*, 2025, [Online]. Available: https://arxiv.org/abs/2505.08332

[135] V. Skliris, M. R. K. Norman, and P. J. Sutton, 'Real-Time Detection of Unmodelled Gravitational-Wave Transients Using Convolutional Neural Networks (MLy)', *Phys. Rev. D 110, 104034 (2024)*, 2024, doi: 10.1103/PhysRevD.110.104034.

[136] R. Raikman, 'A Neural Network-Based Search for Unmodeled Transients in LIGO-Virgo-KAGRA's Third Observing Run', 2024. [Online]. Available: https://arxiv.org/abs/2412.19883

[137] E. Cuoco, 'The Wavelet Detection Filter: a real time unmodeled pipeline for gravitational wave transients, ranking coincidences with a graph neural network', 2026. [Online]. Available: https://arxiv.org/abs/2609.12797

[138] D. Ratner, 'Template-free search for gravitational wave events using coincident anomaly detection', 2026. [Online]. Available: https://arxiv.org/abs/2601.11842

[139] J. Yan, A. P. Leung, D. C. Y. Hui, and S. Kim, 'DeepGrav: Anomalous Gravitational-Wave Detection Through Deep Latent Features', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2503.03799

[140] E. A. Moreno, B. Borzyszkowski, M. Pierini, J.-R. Vlimant, and M. Spiropulu, 'Source-agnostic gravitational-wave detection with recurrent autoencoders', *Mach. Learn.: Sci. Technol. 3, 025005 (2022)*, 2022, doi: 10.1088/2632-2153/ac5435.

[141] T. Marianer, D. Poznanski, and J. X. Prochaska, 'A semisupervised machine learning search for never-seen gravitational-wave sources', *Mon. Not. R. Astron. Soc. 500(4), 5408 (2021)*, 2021, doi: 10.1093/mnras/staa3550.

[142] V. Boudart, 'A machine learning algorithm for minute-long Burst searches (ALBUS)', *Phys. Rev. D 105, 083007 (2022) (per later citation)*, 2022, [Online]. Available: https://arxiv.org/abs/2201.08727

[143] F. Attadio, 'Neural network method to search for long transient gravitational waves', 2024. [Online]. Available: https://arxiv.org/abs/2407.02391

[144] L. M. Modafferi, 'Convolutional neural network search for long-duration transient gravitational waves from glitching pulsars', *Phys. Rev. D 108, 023005 (2023)*, 2023, [Online]. Available: https://arxiv.org/abs/2303.16720

[145] Q. Meijer, M. Lopez, D. Tsuna, and S. Caudill, 'Gravitational-Wave Searches for Cosmic String Cusps in Einstein Telescope Data using Deep Learning', *arXiv preprint*, 2023, doi: 10.1103/PhysRevD.109.022006.

[146] R. Raikman, E. A. Moreno, and E. Govorkova, 'GWAK: Gravitational-Wave Anomalous Knowledge with Recurrent Autoencoders', 2023. [Online]. Available: https://arxiv.org/abs/2309.11537

[147] A. Fayad, 'Unsupervised Learning Approach to Anomaly Detection in Gravitational Wave Data (catalogue title unverified; this is the arXiv title)', 2024. [Online]. Available: https://arxiv.org/abs/2411.19450

[148] J. Cain, 'Template-Free Gravitational Wave Detection with CWT-LSTM Autoencoders: A Case Study of Run-Dependent Calibration Effects in LIGO Data', *Class. Quantum Grav. 43, 035019 (2026)*, 2025, doi: 10.1088/1361-6382/ae415e.

[149] Y.-Y. Guo, S. D. Mohanty, X. Qunying, and Y.-X. Liu, 'Using normal to find abnormal: AI-based anomaly detection in gravitational wave data', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2508.19772

[150] A. R. Imran, 'Utilizing Convolutional Autoencoder for Anomaly Detections in LIGO Spectrogram Data', *Journal of Physics: Conference Series 2734, 012048 (IOP, March 2024)*, 2024, doi: 10.1088/1742-6596/2734/1/012048.

[151] F. Morawski, M. Bejger, E. Cuoco, and L. Petre, 'Anomaly Detection in Gravitational Waves data using Convolutional AutoEncoders', *arXiv preprint*, 2021, doi: 10.1088/2632-2153/abf3d0.

[152] G. Inguglia, 'Towards an anomaly detection pipeline for gravitational waves at the Einstein Telescope', *Phys. Lett. B 874 (2026) 140272*, 2025, [Online]. Available: https://arxiv.org/abs/2511.13154

[153] L. Cirfeta, 'DANTE: A Reference-Guided Unsupervised Pipeline for Extended-Transient Anomaly Characterization in LIGO O4a', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2606.25702

[154] Ma and Zhou, 'Combine deep learning and Bayesian analysis to separate overlapping gravitational wave signals', *Sci. China Phys. Mech. Astron. 2025*, 2025, doi: 10.1007/s11433-024-2594-5.

[155] C. Dreissigacker, R. Sharma, C. Messenger, R. Zhao, and R. Prix, 'Deep-Learning continuous gravitational waves', *Phys. Rev. D 100, 044009 (2019)*, 2019, [Online]. Available: https://arxiv.org/abs/1904.13291

[156] C. Dreissigacker and R. Prix, 'Deep-Learning Continuous Gravitational Waves: Multiple detectors and realistic noise', *Phys. Rev. D 102, 022005 (2020)*, 2020, [Online]. Available: https://arxiv.org/abs/2005.04140

[157] P. M. Joshi and R. Prix, 'Novel neural-network architecture for continuous gravitational waves', *Phys. Rev. D 108, 063021 (2023)*, 2023, doi: 10.1103/PhysRevD.108.063021.

[158] P. M. Joshi and R. Prix, 'Large-kernel Convolutional Neural Networks for Wide Parameter-Space Searches of Continuous Gravitational Waves', *Phys. Rev. D 110, 124071 (2024)*, 2024, doi: 10.1103/PhysRevD.110.124071.

[159] P. M. Joshi and R. Prix, 'Transformer Networks for Continuous Gravitational-wave Searches', *Phys. Rev. D 112, 123052 (2025)*, 2025, doi: 10.1103/xgz9-qdkg.

[160] D. H. T. Cheung, 'Attention U-Net for all-sky continuous gravitational wave searches', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2509.19838

[161] D. S. Dominguez *et al.*, 'Convolutional neural network for continuous gravitational waves detection', *38th International Cosmic Ray Conference (ICRC2023), PoS 444 (MM&GW), pre-published Aug 2023, published 27 Sep 2024*, 2023, doi: 10.22323/1.444.1519.

[162] P. Duraisamy, Y. Natarajan, V. Niranjani, and K. Parvathy, 'Optimized Detection of Continuous Gravitational-Wave Signals using Convolutional Neural Network', *2023 3rd International Conference on Artificial Intelligence and Signal Processing (AISP), IEEE*, 2023, doi: 10.1109/AISP57993.2023.10134809.

[163] R. Tenorio, M. J. Williams, J. Bayley, C. Messenger, M. Demkin, and W. Reade, 'Learning to detect continuous gravitational waves: an open data-analysis competition', *2025 Mach. Learn.: Sci. Technol. 6 040702*, 2025, doi: 10.1088/2632-2153/ae2dbc.

[164] J. Bayley, C. Messenger, and G. Woan, 'A robust machine learning algorithm to search for continuous gravitational waves', *Phys. Rev. D 102, 083024 (2020)*, 2020, [Online]. Available: https://arxiv.org/abs/2007.08207

[165] B. Beheshtipour and M. A. Papa, 'Deep learning for clustering of continuous gravitational wave candidates', *Phys. Rev. D 101, 064009 (2020)*, 2020, doi: 10.1103/PhysRevD.101.064009.

[166] B. Beheshtipour and M. A. Papa, 'Deep learning for clustering of continuous gravitational wave candidates II: identification of low-SNR candidates', *Phys. Rev. D 103, 064027 (2021)*, 2020, doi: 10.1103/PhysRevD.103.064027.

[167] F. Morawski, M. Bejger, and P. Cieciel\{a}g, 'Convolutional neural network classifier for the output of the time-domain F-statistic all-sky search for continuous gravitational waves', *arXiv preprint*, 2019, doi: 10.1088/2632-2153/ab86c7.

[168] M. Di Cesare, P. Astone, R. De Rosa, D. Keitel, C. Palomba, and M. Serra, 'Alternative neural-network follow-up for all-sky FrequencyHough in continuous gravitational-wave searches', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2609.06211

[169] T. S. Yamamoto and T. Tanaka, 'Use of Excess Power Method and Convolutional Neural Network in All-Sky Search for Continuous Gravitational Waves', *Phys. Rev. D 103, 084049 (2021)*, 2020, doi: 10.1103/PhysRevD.103.084049.

[170] T. S. Yamamoto, A. L. Miller, M. Sieniawska, and T. Tanaka, 'Assessing the impact of non-Gaussian noise on convolutional neural networks that search for continuous gravitational waves', *Phys. Rev. D 106, 024025 (2022)*, 2022, doi: 10.1103/PhysRevD.106.024025.

[171] A. L. Miller, P. Astone, S. D'Antonio, S. Frasca, G. Intini, and I. La Rosa, 'How effective is machine learning to detect long transient gravitational waves from neutron stars in a real search?', *Phys. Rev. D (2019) 100, 062005*, 2019, doi: 10.1103/PhysRevD.100.062005.

[172] T. S. Yamamoto, 'Deep learning for intermittent gravitational wave signals', *Phys. Rev. D 107, 044032 (2023)*, 2023, [Online]. Available: https://arxiv.org/abs/2208.13156

[173] S. Bahaadini *et al.*, 'Machine learning for Gravity Spy: Glitch classification and dataset', *Information Sciences 444, 172-186 (2018)*, 2018, doi: 10.1016/j.ins.2018.02.068.

[174] D. George, H. Shen, and E. A. Huerta, 'Deep Transfer Learning: A new deep learning glitch classification method for advanced LIGO', *arXiv 1706.07446v1 (22 Jun 2017); published as Phys. Rev. D 97, 101501(R) (2018)*, 2017, doi: 10.1103/PhysRevD.97.101501.

[175] D. George, H. Shen, and E. A. Huerta, 'Glitch Classification and Clustering for LIGO with Deep Transfer Learning', *Phys. Rev. D 97, 101501 (2018)*, 2018, [Online]. Available: https://arxiv.org/abs/1711.07468

[176] R. Mesuga and B. J. Bayanay, 'A Deep Transfer Learning Approach on Identifying Glitch Wave-form in Gravitational Wave Data', *arXiv preprint*, 2021, [Online]. Available: https://arxiv.org/abs/2107.01863

[177] M. Zevin, 'Gravity Spy: Lessons Learned and a Path Forward', *Eur. Phys. J. Plus 139, 100 (2024)*, 2024, [Online]. Available: https://arxiv.org/abs/2308.15530

[178] T. S. Fernandes, 'Convolutional Neural Networks for the classification of glitches in gravitational-wave data streams', 2023. [Online]. Available: https://arxiv.org/abs/2303.13917

[179] Y. Wu, 'Advancing Glitch Classification in Gravity Spy: Multi-view Fusion with Attention-based Machine Learning for Advanced LIGO's Fourth Observing Run', *Class. Quantum Grav. 42, 165015 (2025)*, 2024, [Online]. Available: https://arxiv.org/abs/2401.12913

[180] D. Srivastava and Niedzielski, 'Vision Transformer for Transient Noise Classification', *Acta Astronomica 74(3), 231-238 (2024)*, 2024, [Online]. Available: https://arxiv.org/abs/2510.06273

[181] A. Licciardi, 'Wavelet Scattering Transform for Gravitational Waves Analysis. An Application to Glitch Characterization', 2024. [Online]. Available: https://arxiv.org/abs/2411.19122

[182] J. Yan, A. P. Leung, and C. Y. Hui, 'On Improving the Performance of Glitch Classification for Gravitational Wave Detection by using Generative Adversarial Networks', *Mon. Not. R. Astron. Soc. 515, 4606-4621 (2022)*, 2022, doi: 10.1093/mnras/stac1996.

[183] Talpini and Razzano, 'Deep convolutional neural network to characterize transient noise in gravitational-wave detectors', *Nuovo Cimento C 2022*, 2022, doi: 10.1393/ncc/i2022-22154-0.

[184] O. T. Biskin, I. Kirbas, and A. Celik, 'A fast and time-efficient glitch classification method: A deep learning-based visual feature extractor for machine learning algorithms', *Astronomy and Computing 42, 100683 (2023; online Dec 2022)*, 2023, doi: 10.1016/j.ascom.2022.100683.

[185] N. Koyama *et al.*, 'Enhancing the rationale of convolutional neural networks for glitch classification in gravitational wave detectors: a visual explanation', *Mach. Learn.: Sci. Technol. 5 (2024) 035028*, 2024, doi: 10.1088/2632-2153/ad6391.

[186] A.-K. Malz, G. Ashton, and N. Colombo, 'Classification uncertainty for transient gravitational-wave noise artefacts with optimised conformal prediction', *Phys. Rev. D 111 (2025) 084078*, 2024, doi: 10.1103/PhysRevD.111.084078.

[187] M. Bhandari, A. Thapa, L. Regmi, S. Sharma, P. Paudel, and S. P. Panday, 'Interpreting decisions of lightweight CNN for glitch classification in time frequency images: Enhancing black-hole merger detection in O1 and O2 runs', *Physics of the Dark Universe 48, 101914 (May 2025)*, 2025, doi: 10.1016/j.dark.2025.101914.

[188] Singh and Sharma, 'Gravitational Wave and Glitch Spectrogram Classification using Convolutional Neural Networks', *IEEE ICSCDS 2025*, 2025, doi: 10.1109/ICSCDS65426.2025.11167769.

[189] T. Fernandes, F. Di Renzo, A. Onofre, A. Torres-Forne, and J. A. Font, 'Automatic classification pipeline for glitches in the Virgo detector', *arXiv preprint 2604.13687v2 (20 Aug 2026); published as doi 10.1103/ys5f-2yqk (journal not stated in the arXiv text)*, 2026, doi: 10.1103/ys5f-2yqk.

[190] Q.-Y. Xie, R.-C. Kang, J.-T. Li, and S.-D. Zhao, 'Application of fusion-view and optimization convolutional neural network in glitch classification', *Physica Scripta 101(11), 116004 (2026)*, 2026, doi: 10.1088/1402-4896/ae4e62.

[191] S. Bahaadini, 'DIRECT: Deep Discriminative Embedding for Clustering of LIGO Data', 2018. [Online]. Available: https://arxiv.org/abs/1805.02296

[192] S. B. Coughlin, 'Classifying the unknown: discovering novel gravitational-wave detector glitches using similarity learning', *Phys. Rev. D 99, 082002 (2019)*, 2019, [Online]. Available: https://arxiv.org/abs/1903.04058

[193] S. Bahaadini, Y. Wu, S. Coughlin, M. Zevin, and A. K. Katsaggelos, 'Discriminative Dimensionality Reduction using Deep Neural Networks for Clustering of LIGO Data', *arXiv preprint*, 2022, [Online]. Available: https://arxiv.org/abs/2205.13672

[194] Y. Sakai, 'Unsupervised Learning Architecture for Classifying the Transient Noise of Interferometric Gravitational-wave Detectors', *Scientific Reports 12, 9935 (2022)*, 2022, [Online]. Available: https://arxiv.org/abs/2111.10053

[195] Y. Li, Y. Wu, and A. K. Katsaggelos, 'Cross-Temporal Spectrogram Autoencoder (CTSAE): Unsupervised Dimensionality Reduction for Clustering Gravitational Wave Glitches', *CVPR Workshops 2024*, 2024, [Online]. Available: https://arxiv.org/abs/2404.15552

[196] S. Deshmukh, C. Chatterjee, A. Petulante, T. A. Ferreira, and K. Jani, 'The Sound of Noise: Leveraging the Inductive Bias of Pre-trained Audio Transformers for Glitch Identification in LIGO', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2601.20034

[197] Y. Kim, K. Jung, and K. Kwak, 'Unsupervised Deep Learning Method for Clustering KAGRA O3GK Transient Noise Data', *MNRAS preprint (2026); arXiv:2608.24690*, 2026, [Online]. Available: https://arxiv.org/abs/2608.24690

[198] S. Oshino, Y. Sakai, M. Meyer-Conde, T. Uchiyama, Y. Itoh, and Y. Shikano, 'Glitch noise classification in KAGRA O3GK observing data using unsupervised machine learning', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2510.14291

[199] Laguarta, 'Detection of anomalies amongst LIGO's glitch populations with autoencoders', *Class. Quantum Grav.*, 2023, [Online]. Available: https://arxiv.org/abs/2310.03453

[200] J. Ding, R. Ng, and J. McIver, 'UniMAP: Model-free detection of unclassified noise transients in LIGO-Virgo data using the Temporal Outlier Factor', *arXiv preprint*, 2021, doi: 10.1088/1361-6382/ac7278.

[201] S. Sankarapandian and B. Kulis, 'β-Annealed Variational Autoencoder for glitches', *arXiv preprint*, 2021, [Online]. Available: https://arxiv.org/abs/2107.10667

[202] S. Alvarez-Lopez, 'GSpyNetTree: A signal-vs-glitch classifier for gravitational-wave event candidates', 2023. [Online]. Available: https://arxiv.org/abs/2304.09977

[203] S. Jarov, 'A new method to distinguish gravitational-wave signals from detector noise transients with Gravity Spy', 2023. [Online]. Available: https://arxiv.org/abs/2307.15867

[204] S. Choudhary, A. More, S. Suyamprakasam, and S. Bose, 'SiGMa-Net: Deep learning network to distinguish binary black hole signals from short-duration noise transients', *arXiv preprint*, 2022, doi: 10.1103/PhysRevD.107.024030.

[205] M. VanDyke, K. Wu, and S. Bose, 'CoBiTS: Single-detector discrimination of binary black hole signals from glitches using deep learning', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2512.17975

[206] R. Magee, R. Sharma, A. Agrawal, and R. Udall, 'Mitigating the impact of noise transients in gravitational-wave searches using reduced basis timeseries and convolutional neural networks', *arXiv preprint*, 2024, [Online]. Available: https://arxiv.org/abs/2410.15513

[207] N. Arutkeerthi, X. Li, C. Cui, and S. Valluri, 'Machine Learning based Glitch Veto for inspiral binary merger signals using Linear Chirp Transform', *arXiv preprint (2410.20269; downloaded PDF is v2, 27 Jul 2026, which cites 2025-2026 material; v1 was Oct 2024); no journal reference found*, 2024, [Online]. Available: https://arxiv.org/abs/2410.20269

[208] N. Shah, A. M. Knee, J. McIver, and D. Stenning, 'Waves in a Forest: A Random Forest Classifier to Distinguish between Gravitational Waves and Detector Glitches', *arXiv preprint*, 2023, [Online]. Available: https://arxiv.org/abs/2306.13787

[209] S. Bini, G. Vedovato, M. Drago, F. Salemi, and G. A. Prodi, 'An autoencoder neural network integrated into gravitational-wave burst searches to improve the rejection of noise transients', *Class. Quantum Grav. 40, 135008 (2023)*, 2023, doi: 10.1088/1361-6382/acd981.

[210] M. L. Chan, J. McIver, Y. Lecoeuche, D. Raghunathan, S. Álvarez-López, and J. Ding, 'GSpyNetTreeS: a machine learning solution for glitch localization in time and frequency', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2511.16861

[211] R. Gupta and C. Binu, 'Transformer-Based Auto-Encoder for Multi-Class Gravitational Wave Signal Classification', *2025 IEEE MIT Undergraduate Research Technology Conference (URTC), IEEE Xplore 11533073*, 2025, doi: 10.1109/URTC68753.2025.11533073.

[212] R. Essick, P. Godwin, C. Hanna, L. Blackburn, and E. Katsavounidis, 'iDQ: Statistical inference of non-gaussian noise with auxiliary degrees of freedom in gravitational-wave detectors', *Mach. Learn.: Sci. Technol. 2, 015004 (2020)*, 2020, doi: 10.1088/2632-2153/abab5f.

[213] R. E. Colgan, 'Efficient Gravitational-wave Glitch Identification from Environmental Data Through Machine Learning (EMU)', *Phys. Rev. D 101, 102003 (2020)*, 2020, [Online]. Available: https://arxiv.org/abs/1911.11831

[214] R. E. Colgan, Z. Márka, J. Yan, I. Bartos, J. N. Wright, and S. Márka, 'Detecting and Diagnosing Terrestrial Gravitational-Wave Mimics Through Feature Learning', *arXiv preprint*, 2022, doi: 10.1103/PhysRevD.107.062006.

[215] M. Cavaglia, K. Staats, and T. Gill, 'Finding the origin of noise transients in LIGO data with machine learning', *Commun. Comput. Phys., 25 (2019), pp. 963-987*, 2018, doi: 10.4208/cicp.OA-2018-0092.

[216] J. Powell, 'Classification methods for noise transients in advanced gravitational-wave detectors', 2015. [Online]. Available: https://arxiv.org/abs/1505.01299

[217] J. Powell, 'Classification methods for noise transients in advanced gravitational-wave detectors II: performance tests on Advanced LIGO data', 2016. [Online]. Available: https://arxiv.org/abs/1609.06262

[218] M. Razzano and E. Cuoco, 'Image-based deep learning for classification of noise transients in gravitational wave detectors', *Class. Quantum Grav. 35, 095016 (2018)*, 2018, [Online]. Available: https://arxiv.org/abs/1803.09933

[219] M. Llorens-Monteagudo, A. Torres-Forne, J. A. Font, and A. Marquina, 'Classification of gravitational-wave glitches via dictionary learning', *Class. Quantum Grav. (DOI 10.1088/1361-6382/ab0657); arXiv v1 9 Nov 2018 shows no journal reference*, 2018, doi: 10.1088/1361-6382/ab0657.

[220] V. Boudart, 'A convolutional neural network to distinguish glitches from minute-long gravitational wave transients', 2022. [Online]. Available: https://arxiv.org/abs/2210.04588

[221] E.-S. Apostol and C.-O. Truică, 'Efficient Machine Learning Ensemble Methods for Detecting Gravitational Wave Glitches in LIGO Time Series', *arXiv preprint (2311.02106, Nov 2023); no journal reference in the PDF*, 2023, [Online]. Available: https://arxiv.org/abs/2311.02106

[222] R. Manoharan and G. Cleaver, 'Evaluating Deep Learning Models for Multiclass Classification of LIGO Gravitational-Wave Glitches', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2604.08796

[223] T. Dooney, S. Bromuri, and L. Curier, 'DVGAN: Stabilize Wasserstein GAN training for time-domain Gravitational Wave physics', *2022 IEEE International Conference on Big Data (Big Data), pp. 5468-5477, Osaka*, 2022, doi: 10.1109/BigData55660.2022.10021080.

[224] T. Dooney *et al.*, 'Time-Domain Synthesis of Gravitational-Wave Detector Glitches using Class-Conditional Derivative Generative Adversarial Networks', *arXiv 2606.27227v3 (14 Sep 2026); the code repository README states Phys. Rev. D 114, 082005 (2026), doi 10.1103/d5yf-3jb4*, 2026, doi: 10.1103/d5yf-3jb4.

[225] H. Shen, 'Denoising Gravitational Waves with Enhanced Deep Recurrent Denoising Auto-Encoders', *ICASSP 2019*, 2019, [Online]. Available: https://arxiv.org/abs/1903.03105

[226] W. Wei and E. A. Huerta, 'Gravitational Wave Denoising of Binary Black Hole Mergers with Deep Learning', *Phys. Lett. B 800, 135081 (2020)*, 2020, [Online]. Available: https://arxiv.org/abs/1901.00869

[227] C. Chatterjee, L. Wen, F. Diakogiannis, and K. Vinsen, 'Extraction of binary black hole gravitational wave signals from detector data using deep learning', *Phys. Rev. D 104, 064046 (2021)*, 2021, doi: 10.1103/PhysRevD.104.064046.

[228] P. Bacon, A. Trovato, and M. Bejger, 'Denoising gravitational-wave signals from binary black holes with dilated convolutional autoencoder', 2022. [Online]. Available: https://arxiv.org/abs/2205.13513

[229] H. Wang, Y. Zhou, Z. Cao, Z.-K. Guo, and Z. Ren, 'WaveFormer: transformer-based denoising method for gravitational-wave data', 2024. [Online]. Available: https://arxiv.org/abs/2212.14283

[230] T. Dooney, 'DeepExtractor: Time-domain reconstruction of signals and glitches in gravitational wave data with deep learning', *Phys. Rev. D 112, 044022 (2025)*, 2025, [Online]. Available: https://arxiv.org/abs/2501.18423

[231] C. Chatterjee and K. Jani, 'Reconstruction of binary black hole harmonics in LIGO using deep learning', *ApJ 969 25 (2024)*, 2024, doi: 10.3847/1538-4357/ad4602.

[232] C. Chatterjee and K. Jani, 'Navigating Unknowns: Deep Learning Robustness for Gravitational Wave Signal Reconstruction', *2024 ApJ 973 112*, 2024, doi: 10.3847/1538-4357/ad6984.

[233] Y.-D. Lee and H.-J. Yo, 'Denoising gravitational wave with deep learning in the time-frequency domain', *Chin. J. Phys. 98 (2025) 1069-1083 (arXiv:2511.20731v1, 25 Nov 2025)*, 2025, doi: 10.1016/j.cjph.2025.11.013.

[234] Y.-C. Lin and A. K. H. Kong, 'Extract non-Gaussian Features in Gravitational Wave Observation Data Using Self-Supervised Learning', *Phys. Rev. D 111, 063520 (2025)*, 2024, doi: 10.1103/PhysRevD.111.063520.

[235] C. Murali and D. Lumley, 'Detecting and Denoising Gravitational Wave Signals from Binary Black Holes using Deep Learning', *arXiv preprint*, 2022, [Online]. Available: https://arxiv.org/abs/2210.01718

[236] A. Ghalsasi, 'Amplifying the Chirp: Using Deep Learning (U-Nets) to filter signal from noise in LIGO data', *arXiv preprint*, 2023, [Online]. Available: https://arxiv.org/abs/2311.17198

[237] C. Ma, S. Li, Z. Cao, and M. Jia, 'Using deep learning to denoise and detect gravitational waves (MSNRnet-2)', *Phys. Rev. D 110, 063010 (2024), 16 pp (INSPIRE record 2825628)*, 2024, doi: 10.1103/PhysRevD.110.063010.

[238] C. Ma, C. Ma, Z. Cao, and M. Jia, 'Gravitational wave search by time-scale-recursive denoising and matched filtering', *Sci. China Phys. Mech. Astron. 67(12), 129511 (2024), 17 pp (INSPIRE record 2853051)*, 2024, doi: 10.1007/s11433-024-2469-4.

[239] Sakai and Odonchimed, 'Automated design of digital filters using convolutional neural networks for extracting ringdown gravitational waves', *Mach. Learn.: Sci. Technol. 2024*, 2024, doi: 10.1088/2632-2153/ad8b94.

[240] D. Jia *et al.*, 'Dendritic learning-based gravitational waves prediction model', *Information Sciences 740, 123218 (June 2026)*, 2026, doi: 10.1016/j.ins.2026.123218.

[241] L. Kumar and S. K. Sahay, 'Temporal context and noise conditioning in neural gravitational-wave inpainting: An architecture ablation study for sub-second strain gaps', *Astronomy and Computing 57 (October 2026)*, 2026, doi: 10.1016/j.ascom.2026.101174.

[242] M. Saleem, 'Demonstration of Machine Learning-assisted real-time noise regression in gravitational wave detectors', 2023. [Online]. Available: https://arxiv.org/abs/2306.11366

[243] R. W. Kiendrebeogo *et al.*, 'Application of Non-Linear Noise Regression in the Virgo Detector', *Phys. Rev. D 112, 083053 (2025); arXiv:2410.06220*, 2025, doi: 10.1103/hwnc-r7yy.

[244] C. Reissel, S. Soni, M. Saleem, M. Coughlin, P. Harris, and E. Katsavounidis, 'Coherence DeepClean: Toward autonomous denoising of gravitational-wave detector data', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2501.04883

[245] G. Vajente, 'Machine-learning non-stationary noise out of gravitational wave detectors', *Phys. Rev. D 101, 042003 (2020)*, 2020, [Online]. Available: https://arxiv.org/abs/1911.09083

[246] H. Yu and R. X. Adhikari, 'Nonlinear noise regression in gravitational-wave detectors with convolutional neural networks', 2021. [Online]. Available: https://arxiv.org/abs/2111.03295

[247] J. Kelleter, P. Schillings, J. Kuckert, D. Bertram, M. Bachlechner, and A. Stahl, 'NNNN: Neural Networks for Newtonian Noise Mitigation at the Einstein Telescope', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2606.19907

[248] K. Mogushi, 'Reduction of transient noise artifacts in gravitational-wave data using deep learning', 2021. [Online]. Available: https://arxiv.org/abs/2105.10522

[249] K. Mogushi, 'NNETFIX: An artificial neural network-based denoising engine for gravitational-wave signals', 2021. [Online]. Available: https://arxiv.org/abs/2101.04712

[250] A. Torres-Forné, E. Cuoco, J. A. Font, and A. Marquina, 'Application of dictionary learning to denoise LIGO's blip noise transients', *Phys. Rev. D 102, 023011 (2020)*, 2020, doi: 10.1103/PhysRevD.102.023011.

[251] A. Pimpalkar, D. Wadekar, M. H.-Y. Cheung, and E. Berti, 'Sample-efficient non-Gaussian noise reduction in gravitational wave data via learnable wavelets', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2601.14326

[252] C. Ma, X. Yu, Z. Cao, and M. Jia, 'Extraction of binary neutron star gravitational wave waveforms from Einstein Telescope using deep learning', *arXiv preprint 2406.15813v1 (22 Jun 2024); no journal reference on arXiv*, 2024, [Online]. Available: https://arxiv.org/abs/2406.15813

[253] C. Ma, W. Zhou, and Z. Cao, 'Gravitational Wave Mixture Separation for Future Gravitational Wave Observatories Utilizing Deep Learning', *arXiv preprint 2407.13239v1 (18 Jul 2024); no journal reference on arXiv*, 2024, [Online]. Available: https://arxiv.org/abs/2407.13239

[254] Y. Xu, H. Wang, M. Du, B. Liang, and P. Xu, 'Gravitational Wave Signal Denoising and Merger Time Prediction By Deep Neural Network', *Phys. Rev. D 111, 063037 (2025)*, 2024, doi: 10.1103/PhysRevD.111.063037.

[255] M. Dax, S. R. Green, J. Gair, N. Gupte, M. Pürrer, and V. Raymond, 'Real-time gravitational-wave inference for binary neutron stars using machine learning', *Nature 639, 49-53 (2025)*, 2024, doi: 10.1038/s41586-025-08593-z.

[256] A. Kofler, 'Flexible Gravitational-Wave Parameter Estimation with Transformers (Dingo-T1)', *Phys. Rev. Lett. 136, 251401 (2026)*, 2025, [Online]. Available: https://arxiv.org/abs/2512.02968

[257] J. C. L. Chan, L. M. Zertuche, J. M. Ezquiaga, R. K. L. Lo, L. Vujeva, and J. Bowman, 'Identification and characterization of distorted gravitational waves by lensing using deep learning', *arXiv preprint*, 2025, doi: 10.1103/8cz1-kl6n.

[258] Y.-X. Zhang *et al.*, 'Factorized neural posterior estimation for rapid and reliable inference of parameterized post-Einsteinian deviation parameters in gravitational waves', *Commun. Theor. Phys. 78 (2026) 115401; arXiv:2602.01319 (PDF read is v2, 30 Sep 2026)*, 2026, doi: 10.1088/1572-9494/ae8f1e.

[259] J.-W. Luo and Y.-S. Piao, 'Searching for gravitational wave echo with group equivariant neural posterior estimation', *arXiv preprint 2609.18337v2 (28 Sep 2026); no journal reference on arXiv*, 2026, [Online]. Available: https://arxiv.org/abs/2609.18337

[260] Q. Hu *et al.*, 'Decoding Long-duration Gravitational Waves from Binary Neutron Stars with Machine Learning: Parameter Estimation and Equations of State', *Astrophys. J. Lett. 987, L17 (2025); arXiv 2412.03454 (v2 dated 28 Jun 2025)*, 2024, doi: 10.3847/2041-8213/ade42f.

[261] D. Lanchares *et al.*, 'Assessment of normalizing flows for parameter estimation on time-frequency representations of gravitational-wave data', *Phys. Rev. D 114 (2026) 043019; arXiv:2505.08089*, 2025, doi: 10.1103/pz2n-b4m5.

[262] W. van Straalen, A. Kolmus, J. Janquart, and C. Van Den Broeck, 'Pre-Merger Detection and Characterization of Inspiraling Binary Neutron Stars Derived from Neural Posterior Estimation', *arXiv preprint*, 2024, [Online]. Available: https://arxiv.org/abs/2407.10263

[263] H. Gabbard, 'Bayesian parameter estimation using conditional variational autoencoders for gravitational-wave astronomy (VItamin)', *Nature Physics 18, 112-117 (2022)*, 2022, [Online]. Available: https://arxiv.org/abs/1909.06296

[264] R. Bada-Nerin, O. Bulashenko, O. G. Freitas, and J. A. Font, 'Parameter estimation of microlensed gravitational waves with Conditional Variational Autoencoders', *Phys. Rev. D 111, 084067 (2025); arXiv:2412.00566 (v2 14 Apr 2025)*, 2024, doi: 10.1103/PhysRevD.111.084067.

[265] A. Delaunoy, A. Wehenkel, T. Hinderer, S. Nissanke, C. Weniger, and A. R. Williamson, 'Lightning-Fast Gravitational Wave Parameter Inference through Neural Amortization', *arXiv preprint*, 2020, [Online]. Available: https://arxiv.org/abs/2010.12931

[266] M. Emma and G. Ashton, 'RNLE: Residual neural likelihood estimation and its application to gravitational-wave astronomy', *arXiv preprint 2601.13857v1*, 2026, [Online]. Available: https://arxiv.org/abs/2601.13857

[267] A. J. K. Chua and M. Vallisneri, 'Learning Bayesian posteriors with neural networks for gravitational-wave inference', *Phys. Rev. Lett. 124, 041102 (2020)*, 2019, doi: 10.1103/PhysRevLett.124.041102.

[268] H. Shen, E. A. Huerta, E. O'Shea, P. Kumar, and Z. Zhao, 'Statistically-informed deep learning for gravitational wave parameter estimation', *Machine Learning: Science and Technology, Volume 3, Number 1, Year 2022*, 2019, doi: 10.1088/2632-2153/ac3843.

[269] A. McLeod, D. Jacobs, C. Chatterjee, L. Wen, and F. Panther, 'Rapid Mass Parameter Estimation of Binary Black Hole Coalescences Using Deep Learning', *arXiv preprint*, 2022, [Online]. Available: https://arxiv.org/abs/2201.11126

[270] M. Andrés-Carcasona, M. Martinez, and L. M. Mir, 'Fast Bayesian gravitational wave parameter estimation using convolutional neural networks', *Mon. Not. R. Astron. Soc. (MNRAS; arXiv:2309.04303v2, Nov 2023, MNRAS style file)*, 2023, [Online]. Available: https://arxiv.org/abs/2309.04303

[271] K. L. Jenner, 'Convolutional Neural Network for Analysing Gravitational Wave Signals', *Thesis, University of Adelaide (2024)*, 2024.

[272] L. Papalini, F. De Santi, M. Razzano, I. S. Heng, and E. Cuoco, 'Can Transformers help us perform parameter estimation of overlapping signals in gravitational wave detectors?', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2505.02773

[273] C. Chatterjee, L. Wen, K. Vinsen, M. Kovalam, and A. Datta, 'Using Deep Learning to Localize Gravitational Wave Sources', *Phys. Rev. D 100, 103025 (2019)*, 2019, doi: 10.1103/PhysRevD.100.103025.

[274] C. Chatterjee, M. Kovalam, L. Wen, D. Beveridge, F. Diakogiannis, and K. Vinsen, 'Rapid localization of gravitational wave sources from compact binary coalescences using deep learning', *The Astrophysical Journal, Volume 959, Number 1 (2023)*, 2022, doi: 10.3847/1538-4357/ad08b7.

[275] C. Chatterjee and L. Wen, 'Pre-merger sky localization of gravitational waves from binary neutron star mergers using deep learning (GW-SkyLocator)', *Astrophys. J. 959, No. 2 (2023)*, 2023, [Online]. Available: https://arxiv.org/abs/2301.03558

[276] A. Kolmus, G. Baltus, J. Janquart, T. van Laarhoven, S. Caudill, and T. Heskes, 'Swift sky localization of gravitational waves using deep learning seeded importance sampling', *Phys. Rev. D 106, 023032 (2022); arXiv:2111.00833*, 2021, doi: 10.1103/PhysRevD.106.023032.

[277] J. P. Marulanda, C. Santa, and A. E. Romano, 'Deep learning merger masses estimation from gravitational waves signals in the frequency domain', *arXiv preprint*, 2020, doi: 10.1016/j.physletb.2020.135790.

[278] S. Singh, A. Singh, A. Prajapati, and K. N. Pathak, 'Deep Learning for estimating parameters of Gravitational Waves', *arXiv preprint*, 2020, doi: 10.1093/mnras/stab2417.

[279] S. Soma, H. Stöcker, and K. Zhou, 'Mass and tidal parameter extraction from gravitational waves of binary neutron stars mergers using deep learning', *JCAP 01(2024)009*, 2023, doi: 10.1088/1475-7516/2024/01/009.

[280] M. Benedikt and I. D. Saltas, 'GraviBERT: Transformer-based inference for gravitational-wave time series', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2512.21390

[281] E. Khalouei, C. G. Sabiu, H. M. Lee, and A. Gopakumar, 'External Attention Transformer: A Robust AI Model for Identifying Initial Eccentricity Signatures in Binary Black Hole Events in Simulated Advanced LIGO Data', *Journal of Cosmology and Astroparticle Physics 2025(10), 028; arXiv v2 read*, 2025, doi: 10.1088/1475-7516/2025/10/028.

[282] H. Iwanaga, M. Matsuyama, and Y. Itoh, 'Enhancing the reliability of machine learning for gravitational wave parameter estimation with attention-based models', *Physical Review D 112, 083020 (2025); arXiv v2 read*, 2025, doi: 10.1103/blfk-7k9f.

[283] P. N. Sakellariou, S. V. Georgakopoulos, S. Tasoulis, and V. P. Plagianakos, 'Binary Black Hole Parameter Estimation with Hybrid CNN-Transformer Neural Networks', *Astronomy and Computing, vol. 54, 101027 (2026)*, 2026, doi: 10.1016/j.ascom.2025.101027.

[284] A. Ravichandran, A. Vijaykumar, S. J. Kapadia, and P. Kumar, 'Rapid Identification and Classification of Eccentric Gravitational Wave Inspirals with Machine Learning', *arXiv preprint*, 2023, [Online]. Available: https://arxiv.org/abs/2302.00666

[285] W.-H. Ruan, H. Wang, C. Liu, and Z.-K. Guo, 'Rapid search for massive black hole binary coalescences using deep learning', *Phys. Lett. B 841, 137904 (2023)*, 2023, doi: 10.1016/j.physletb.2023.137904.

[286] W.-H. Ruan and Z.-K. Guo, 'Premerger detection of massive black hole binaries using deep learning', *Phys. Rev. D 109, 123031 (2024)*, 2024, doi: 10.1103/PhysRevD.109.123031.

[287] W.-H. Ruan, H. Wang, C. Liu, and Z.-K. Guo, 'Parameter inference for coalescing massive black hole binaries using deep learning', *Universe 2023, 9(9), 407*, 2023, doi: 10.3390/universe9090407.

[288] T. Zhao, R. Lyu, H. Wang, Z. Cao, and Z. Ren, 'Space-based gravitational wave signal detection and extraction with deep neural network', *Commun. Phys. 6, 212 (2023)*, 2023, doi: 10.1038/s42005-023-01334-6.

[289] X.-T. Zhang, C. Messenger, N. Korsakova, M. L. Chan, Y.-M. Hu, and J.-dong Zhang, 'Detecting Gravitational-waves from Extreme Mass Ratio Inspirals using Convolutional Neural Networks', *Phys. Rev. D 105, 123027 (2022); arXiv:2202.07158 (the PDF read is arXiv v1, 15 Feb 2022, so the published text may differ)*, 2022, doi: 10.1103/PhysRevD.105.123027.

[290] Q. Yun, W.-B. Han, Y.-Y. Guo, H. Wang, and M. Du, 'Detecting extreme-mass-ratio inspirals for space-borne detectors with deep learning', *arXiv preprint*, 2023, [Online]. Available: https://arxiv.org/abs/2309.06694

[291] H.-Y. Liu and Y.-T. Wang, 'Self-supervised learning for gravitational wave signal identification', *arXiv preprint 2302.00295v2 (7 Sep 2023); no journal reference on arXiv*, 2023, [Online]. Available: https://arxiv.org/abs/2302.00295

[292] N. Houba, S. H. Strub, L. Ferraioli, and D. Giardini, 'Detection and Prediction of Future Massive Black Hole Mergers with Machine Learning and Truncated Waveforms', *arXiv preprint*, 2024, [Online]. Available: https://arxiv.org/abs/2405.11340

[293] A. Caramete *et al.*, 'Characterization of Gravitational Waves Signals Using Neural Networks', *arXiv preprint*, 2020, [Online]. Available: https://arxiv.org/abs/2009.06109

[294] N. Houba, L. Ferraioli, and D. Giardini, 'Detection and Mitigation of Glitches in LISA Data: A Machine Learning Approach', *Phys. Rev. D 109, 083027 (2024); arXiv preprint 2401.00846*, 2024, doi: 10.1103/PhysRevD.109.083027.

[295] N. Houba, 'Deep source separation of overlapping gravitational-wave signals and non-stationary noise artifacts', *arXiv preprint*, 2025, [Online]. Available: https://arxiv.org/abs/2503.10398

[296] Y. Xu, M. Du, B. Liang, Z. Xiao, T. Zhao, and P. Xu, 'Self-supervised reconstruction of transients in data from space-borne gravitational-wave detectors', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2609.05890

[297] M.-C. Isfan, L.-I. Caramete, A. Caramete, D. Tonoiu, and A. Nicolin-Żaczek, 'Quantum Computing Tools for Fast Detection of Gravitational Waves in the Context of LISA Space Mission', *Classical and Quantum Gravity 42 (2025); arXiv v3 read*, 2025, doi: 10.1088/1361-6382/ae1787.

[298] M.-C. Isfan, L.-I. Caramete, and A. Caramete, 'Evaluating state-of-the-art cloud quantum computers for quantum neural networks in gravitational waves data analysis', *arXiv preprint*, 2026, [Online]. Available: https://arxiv.org/abs/2601.14036

[299] M. Cabero, 'GWSkyNet: a real-time classifier for public gravitational-wave candidates', *Astrophys. J. Lett. 904, L9 (2020)*, 2020, [Online]. Available: https://arxiv.org/abs/2010.11829

[300] T. C. Abbott, E. Buffaz, N. Vieira, M. Cabero, D. Haggard, and A. Mahabal, 'GWSkyNet-Multi: A Machine Learning Multi-Class Classifier for LIGO-Virgo Public Alerts', *Astrophys. J. 927 (2022) (DOI 10.3847/1538-4357/ac5019); arXiv:2111.04015*, 2021, doi: 10.3847/1538-4357/ac5019.

[301] M. L. Chan, 'GWSkyNet II: a refined machine learning pipeline for real-time classification of public gravitational wave alerts', 2024. [Online]. Available: https://arxiv.org/abs/2408.06491

[302] J. McGinn, C. Messenger, M. J. Williams, and I. S. Heng, 'Generalised gravitational wave burst generation with generative adversarial networks (McGANn)', *Class. Quantum Grav. 38, 155005 (2021)*, 2021, doi: 10.1088/1361-6382/ac09cc.

[303] M. Lopez, V. Boudart, K. Buijsman, A. Reza, and S. Caudill, 'Simulating Transient Noise Bursts in LIGO with Generative Adversarial Networks', *Phys. Rev. D 106, 023027 (2022); arXiv v1 shows no journal reference*, 2022, doi: 10.1103/PhysRevD.106.023027.

[304] J. Powell, L. Sun, K. Gereb, P. D. Lasky, and M. Dollmann, 'Generating transient noise artifacts in gravitational-wave detector data with generative adversarial networks', *arXiv preprint*, 2022, doi: 10.1088/1361-6382/acb038.

[305] T. Dooney, 'cDVGAN: One Flexible Model for Multi-class Gravitational Wave Signal and Glitch Generation', *Phys. Rev. D 110, 022004 (2024)*, 2024, [Online]. Available: https://arxiv.org/abs/2401.16356

[306] K. Kim, J. Lee, R. S. H. Yuen, O. A. Hannuksela, and T. G. F. Li, 'Identification of Lensed Gravitational Waves with Deep Learning', *ApJ 915 (2021) 119*, 2020, doi: 10.3847/1538-4357/ac0143.

[307] K. Kim, J. Lee, O. A. Hannuksela, and T. G. F. Li, 'Deep Learning-based Search for Microlensing Signature from Binary Black Hole Events in GWTC-1 and -2', *ApJ 938 (2022) 157*, 2022, doi: 10.3847/1538-4357/ac92f3.

[308] Utina and Marangio, 'Deep learning searches for gravitational wave stochastic backgrounds', *IEEE CBMI 2021*, 2021, doi: 10.1109/CBMI50038.2021.9461904.

[309] H. Einsle, M.-A. Bizouard, T. Regimbau, and M. Sakellariadou, 'Gravitational-wave background detection using machine learning', *arXiv preprint 2506.14764v1*, 2025, [Online]. Available: https://arxiv.org/abs/2506.14764

[310] M. C. Edwards, 'Classifying the Equation of State from Rotating Core Collapse Gravitational Waves with Deep Learning', *Phys. Rev. D 103, 024025 (2021)*, 2021, [Online]. Available: https://arxiv.org/abs/2009.07367

[311] Y. Xu, M. Du, P. Xu, B. Liang, and H. Wang, 'Gravitational Wave Signal Extraction Against Non-Stationary Instrumental Noises with Deep Neural Network', *Phys. Lett. B 858, 139016 (2024)*, 2024, [Online]. Available: https://arxiv.org/abs/2402.13091

[312] Z. Que, E. Wang, U. Marikar, E. Moreno, J. Ngadiuba, and H. Javed, 'Accelerating Recurrent Neural Networks for Gravitational Wave Experiments', *arXiv preprint*, 2021, doi: 10.1109/ASAP52443.2021.00025.

[313] E. Cuoco, J. Powell, and M. Cavaglia, 'Enhancing Gravitational-Wave Science with Machine Learning (review)', *Mach. Learn.: Sci. Technol. 2, 011002 (2021)*, 2021, [Online]. Available: https://arxiv.org/abs/2005.03745