



PERFORMANCE TROPHY DX

15W-40

High quality lubricant for diesel engines.

UTILISATION

All industrial vehicles

- Particularly suitable for the most modern Diesel engines, fitted on trucks, buses, construction or agricultural machinery, with or without turbocompressors, intercoolers or sophisticated injection systems.

All types of services

- Can handle the most demanding applications: transports, public works...

Environment

- Complies with the EURO 2 and EURO 3 technologies.

PERFORMANCES

Specifications

ACEA
API

E5/E3
CH-4/SJ

OEMs' approvals

MERCEDES
MAN
VOLVO
MTU OIL
RENAULT TRUCKS
MACK
CUMMINS
ZF
CATERPILLAR

MB-Approval 228.3
M 3275
VDS-2
Type 2
RD / RD-2
EOM
CES 20071/20072
TE-ML 04C
T0-2

CUSTOMER BENEFITS

Technical performances

- The advanced properties of this product have been validated in thousands of hours on construction sites and several million km on the roads in a variety of services.
- Very high protection against wear, in all conditions of services, thus guaranteeing an extended engine lifespan.
- Very high dispersancy and detergency levels: prevents clogging

CHARACTERISTICS

Performance Trophy DX	Units	SAE Grade 15W-40
Volumetric mass at 15°C	kg/m ³	883
Viscosity at 100°C	mm ² /s	14
Viscosity index	-	130
Flash point	°C	>200
Pour point	°C	-27
T.B.N	mgKOH/g	9.7

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS

Le SPAZIO

562 Avenue du Parc de l'Ile
92029 - NANTERRE CEDEX

PERFORMANCE TROPHY DX 15W-40

April 2010

N° MPR 09/07



This lubricant, used in accordance with our recommendations and for the application for which it is intended, does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.