

FIRE RATED UNINSULATED ACCESS DOOR

WITH PLASTER FLANGE

PFN-PLY

INSTALLATION: WALLS ONLY

[3 HOUR WALL APPLICATION]




Authorities Having Jurisdiction (AHJ) should be consulted in all cases as to the particular requirements covering the installation and use of fire rated access doors.

DIMENSIONS AND APPEARANCE

DOOR SIZE NUMBER

DOOR SIZE W x H inches (MM)	NUMBER OF LOCKS	WEIG LBS	KG
8 x 8 (203 x 203)	1	5	2.3
10 x 10 (254 x 254)	1	7	3.2
12 x 12 (304 x 304)	1	8	3.6
14 x 14 (355 x 355)	1	10	4.5
16 x 16 (406 x 406)	1	12	5.5
18 x 18 (457 x 457)	1	14	6.4
22 x 22 (558 x 558)	1	18	8.2
22 x 30 (558 x 762)	1	22	10
22 x 36 (558 x 914)	2	27	12.2
24 x 24 (609 x 609)	1	22	10
24 x 36 (609 x 914)	2	29	13.2
30 x 30 (762 x 762)	1	30	13.6
32 x 32 (812 x 812)	2	33	15
36 x 36 (914 x 914)	2	39	17.7
DESCRIPTION AND		ABEAIEIA	77.

2 3/4" H H + 5 1/2" W + 5 1/2" Rough wall opening is door size + 1/4" or + 6mm



DESCRIPTION AND MATERIAL SPECIFICATION

FIRE RATING: 2 hour fire barrier, rating 1½ hours. Access/Door Frame Assembly (uninsulated) for installation in vertical wall assemblies.

Maximum door size of: 36" x 36".

STANDARDS LISTED: NFPA 252-2003, UL 10b, UL-555, CAN/ULC S112 M90-R2001, CAN/ULC S104-10.

MEA # 507-06-M

Material: 16 gauge cold rolled steel Hinge: continuous piano hinge

Lock / latch: self latching tool-key operated latch

and/or ring operated latch, both included

Inside panel release: standard on all doors over 12" x 12"

PLY: 2 3/4" steel lath flange
Automatic panel closer: standard on all doors
Finish: high quality white powder coat primer

Packaging: individually wrapped, 1 per box

POPULAR
OPTIONS
Go to: www.cendrex.com
Material: stainless steel #4 (brushed finish),
Lock / latch: key operated cylinder cam latch,

handle operated slam latch, mortise preparation for cylinder (cylinder optional), hex head slam latch,

mortise deadbolt lock

Masonery anchor: available on all sizes







PROJECT DATA

PROJECT NAME:	QTY	W	Н	OPTIONS		
ARCHITECT:						
DEALER:						
CONTRACTOR:						
LOCATION:		SPECIAL INSTRUCTIONS:				
DATE:						
TAGGING INSTRUCTIONS:	SUBMITTAL APPROVAL: (signature or stamp)					

HEAD OFFICE: 11 303, 26th avenue, Montreal, Quebec, Canada H1E 6N6 **WAREHOUSES**: California, Colorado, Florida, Illinois, Pennsylvania, Texas

Tel.: 514 493-1489 - 1 800 479-1489 Fax: 514 493-1992 - 1 800 297-1489 www.cendrex.com info@cendrex.com