ROCSCIENCE

Case10
Slide2 - An Interactive Slope Stability Program
Date Created: 13/03/2026, 8:45:25 am
Software Version: 9.041

Table of Contents

Project Summary 3
General Settings 4
Analysis Options 5
Groundwater Analysis 6
Random Numbers 7
Surface Options 8
Seismic Loading 9
Loading 10
Materials 11
Global Minimums 12
Method: bishop simplified 12
Method: spencer 12
Valid and Invalid Surfaces 13
Method: bishop simplified 13
Method: spencer 13
Error Code Descriptions 13
Slice Data 14
Global Minimum Query (bishop simplified) - Safety Factor: 0.907907 14
Global Minimum Query (spencer) - Safety Factor: 0.918623 15
Interslice Data 16
Global Minimum Query (bishop simplified) - Safety Factor: 0.907907 16
Global Minimum Query (spencer) - Safety Factor: 0.918623 17
Entity Information 18
Group 1 18
Shared Entities 18
Scenario-based Entities 18

Slide2 Analysis Information

Case10

Project Summary

File Name:	Case10.slmd
Slide2 Modeler Version:	9.041
Compute Time:	00h:00m:01.135s
Project Title:	Slide2 - An Interactive Slope Stability Program
Date Created:	13/03/2026, 8:45:25 am

General Settings

Units of Measurement:	Metric Units
Time Units:	days
Permeability Units:	meters/second
Data Output:	Standard
Failure Direction:	Right to Left

Analysis Options

Slices Type:	Vertical
Analysis Methods Used	
	Bishop simplified
	Spencer
Number of slices:	50
Tolerance:	0.001
Maximum number of iterations:	75
Check malpha < 0.2:	Yes
Create Interslice boundaries at intersections with water tables and piezos:	Yes
Initial trial value of FS:	1
Steffensen Iteration:	Yes

Groundwater Analysis

Groundwater Method:	Water Surfaces
Pore Fluid Unit Weight [kN/m3]:	9.81
Advanced Groundwater Method:	None

Random Numbers

Pseudo-random Seed:	10116
Random Number Generation Method:	Park and Miller v.3

Surface Options

Surface Type:	Circular
Search Method:	Auto Refine Search
Divisions along slope:	20
Circles per division:	10
Number of iterations:	10
Divisions to use in next iteration:	50%
Composite Surfaces:	Disabled
Minimum Elevation:	Not Defined
Minimum Depth:	Not Defined
Minimum Area:	Not Defined
Minimum Weight:	Not Defined

Seismic Loading

Advanced seismic analysis:	No
Staged pseudostatic analysis:	No
Seismic Load Coefficient (Horizontal):	0.25

Loading

1 Distributed Load present

Distributed Load 1	
Distribution:	Constant
Magnitude [kPa]:	50
Orientation:	Vertical

Materials

Material 1	
Color	
Strength Type	Mohr-Coulomb
Unit Weight	20 kN/m3
Cohesion	20 kPa
Phi	20 °
Water Surface	Water Table
Hu Type	Custom
Hu	1
Specify alternate strength type above water surface	No

Global Minimums

Method: bishop simplified

FS	0.907907
Center:	16.692, 25.640
Radius:	17.090
Left Slip Surface Endpoint:	9.802, 10.000
Right Slip Surface Endpoint:	31.719, 17.500
Left Slope Intercept:	9.802 11.000
Right Slope Intercept:	31.719 17.500
Resisting Moment:	17660.8 kN-m
Driving Moment:	19452.3 kN-m
Total Slice Area:	97.5552 m2
Surface Horizontal Width:	21.9167 m
Surface Average Height:	4.45118 m

Method: spencer

FS	0.918623
Center:	16.600, 25.585
Radius:	17.003
Left Slip Surface Endpoint:	9.802, 10.000
Right Slip Surface Endpoint:	31.558, 17.500
Left Slope Intercept:	9.802 11.000
Right Slope Intercept:	31.558 17.500
Resisting Moment:	17534.5 kN-m
Driving Moment:	19087.8 kN-m
Resisting Horizontal Force:	903.92 kN
Driving Horizontal Force:	983.994 kN
Total Slice Area:	95.8568 m2
Surface Horizontal Width:	21.7555 m
Surface Average Height:	4.4061 m

Global Minimum Support Data

No Supports Present

Valid and Invalid Surfaces

Method: bishop simplified

Number of Valid Surfaces:	11347
Number of Invalid Surfaces:	0

Method: spencer

Number of Valid Surfaces:	10753
Number of Invalid Surfaces:	594

Error Codes

Error Code -108 reported for 201 surfaces
Error Code -111 reported for 329 surfaces
Error Code -112 reported for 64 surfaces

Error Code Descriptions

The following errors were encountered during the computation:
-108 = Total driving moment or total driving force < 0.1. This is to limit the calculation of extremely high safety factors if the driving force is very small (0.1 is an arbitrary number).
-111 = Safety factor equation did not converge
-112 = The coefficient M-Alpha = cos(alpha)(1+tan(alpha)tan(phi)/F) < 0.2 for the final iteration of the safety factor calculation. This screens out some slip surfaces which may not be valid in the context of the analysis, in particular, deep seated slip surfaces with many high negative base angle slices in the passive zone.

Slice Data

Global Minimum Query (bishop simplified) - Safety Factor: 0.907907

Slice Number	Width [m]	Weight [kN]	Angle of Slice Base [deg]	Base Material	Base Cohesion [kPa]	Base Friction Angle [deg]	Shear Stress [kPa]	Shear Strength [kPa]	Base Normal Stress [kPa]	Pore Pressure [kPa]	Effective Normal Stress [kPa]	Base Vertical Stress [kPa]	Effective Vertical Stress [kPa]
1	0.440513	5.29392	-22.972	Material 1	20	20	27.1619	24.6605	23.5304	10.7259	12.8045	12.0166	1.29067
2	0.440513	7.76497	-21.3769	Material 1	20	20	28.5722	25.9409	28.81	12.4876	16.3224	17.6259	5.13832
3	0.440513	10.2118	-19.7991	Material 1	20	20	29.9932	27.231	33.9783	14.1112	19.8671	23.1807	9.06945
4	0.440513	12.5385	-18.2368	Material 1	20	20	31.322	28.4375	38.783	15.601	23.182	28.4625	12.8615
5	0.440513	14.7484	-16.6883	Material 1	20	20	32.5644	29.5655	43.2417	16.9607	26.281	33.4791	16.5184
6	0.440513	17.3302	-15.1524	Material 1	20	20	33.9159	30.7925	48.5245	18.8724	29.6521	39.3401	20.4677
7	0.440513	20.2667	-13.6275	Material 1	20	20	35.3658	32.1089	54.5801	21.3111	33.269	46.0062	24.6951
8	0.440513	23.0941	-12.1124	Material 1	20	20	36.7332	33.3503	60.3079	23.6283	36.6796	52.4247	28.7964
9	0.440513	25.8144	-10.6059	Material 1	20	20	38.0215	34.52	65.7196	25.8262	39.8934	58.6	32.7738
10	0.440513	28.4293	-9.10671	Material 1	20	20	39.2342	35.621	70.8252	27.9069	42.9183	64.5362	36.6293
11	0.440513	30.9403	-7.61382	Material 1	20	20	40.3741	36.6559	75.6335	29.8717	45.7618	70.2366	40.3649
12	0.440513	33.3485	-6.12612	Material 1	20	20	41.4435	37.6268	80.1516	31.7221	48.4295	75.7035	43.9814
13	0.440513	35.6549	-4.64256	Material 1	20	20	42.4447	38.5358	84.3858	33.4592	50.9266	80.939	47.4798
14	0.440513	37.8602	-3.16211	Material 1	20	20	43.3793	39.3844	88.3419	35.0837	53.2582	85.9454	50.8617
15	0.440513	39.9649	-1.68377	Material 1	20	20	44.2491	40.1741	92.0243	36.5962	55.4281	90.7235	54.1273
16	0.440513	41.9695	-0.206559	Material 1	20	20	45.0555	40.9062	95.4365	37.9972	57.4393	95.2741	57.2769
17	0.440513	43.874	1.27052	Material 1	20	20	45.7994	41.5816	98.5817	39.2867	59.295	99.5975	60.3108
18	0.440513	45.6783	2.74844	Material 1	20	20	46.4819	42.2012	101.462	40.4648	60.9974	103.694	63.2288
19	0.440513	47.3822	4.2282	Material 1	20	20	47.1036	42.7657	104.079	41.531	62.5483	107.562	66.0307
20	0.440513	48.9852	5.71079	Material 1	20	20	47.6652	43.2756	106.434	42.4848	63.9494	111.201	68.7161
21	0.440513	50.4866	7.19722	Material 1	20	20	48.1672	43.7313	108.527	43.3256	65.2011	114.609	71.2837
22	0.440513	51.8855	8.68855	Material 1	20	20	48.6095	44.1329	110.357	44.0522	66.3045	117.785	73.7328
23	0.440513	53.1808	10.1858	Material 1	20	20	48.9924	44.4805	111.923	44.6634	67.2595	120.726	76.0621
24	0.440513	54.3712	11.6902	Material 1	20	20	49.3156	44.774	113.224	45.1578	68.0662	123.428	78.2701
25	0.440513	55.4549	13.2028	Material 1	20	20	49.5792	45.0133	114.257	45.5335	68.7235	125.888	80.3548
26	0.440513	56.4302	14.7248	Material 1	20	20	49.7825	45.1979	115.019	45.7884	69.2308	128.102	82.3141
27	0.440513	57.2949	16.2575	Material 1	20	20	49.925	45.3273	115.506	45.9201	69.5862	130.065	84.1452
28	0.440513	58.0464	17.8023	Material 1	20	20	50.006	45.4008	115.714	45.9259	69.7883	131.772	85.8457
29	0.440513	58.6819	19.3606	Material 1	20	20	50.0244	45.4175	115.637	45.8025	69.8342	133.214	87.4119
30	0.440513	59.1982	20.934	Material 1	20	20	49.9791	45.3764	115.267	45.5463	69.7211	134.387	88.8403
31	0.440513	59.5917	22.524	Material 1	20	20	49.8688	45.2762	114.599	45.1534	69.4456	135.28	90.1264
32	0.440513	59.8581	24.1326	Material 1	20	20	49.6915	45.1153	113.623	44.619	69.0037	135.885	91.2658
33	0.440513	59.9928	25.7617	Material 1	20	20	49.4457	44.8921	112.329	43.9379	68.3906	136.191	92.2529
34	0.440513	59.9903	27.4135	Material 1	20	20	49.1289	44.6045	110.705	43.1042	67.6003	136.185	93.0811
35	0.440513	59.6027	29.0905	Material 1	20	20	56.7445	51.5187	128.708	42.111	86.5967	160.279	118.168
36	0.440513	57.6096	30.7952	Material 1	20	20	63.4565	57.6126	142.962	39.6218	103.34	180.782	141.16
37	0.440513	55.2153	32.5307	Material 1	20	20	61.7253	56.0408	135.977	36.9558	99.0214	175.347	138.391
38	0.440513	52.6539	34.3005	Material 1	20	20	59.9311	54.4119	128.649	34.1037	94.5457	169.532	135.429
39	0.440513	49.9146	36.1085	Material 1	20	20	58.0696	52.7218	120.956	31.0536	89.9025	163.314	132.261
40	0.440513	46.9853	37.9591	Material 1	20	20	56.1359	50.9662	112.871	27.7918	85.0791	156.665	128.873
41	0.440513	43.8513	39.8577	Material 1	20	20	54.1243	49.1398	104.363	24.3023	80.0609	149.55	125.248
42	0.440513	40.4956	41.8104	Material 1	20	20	52.0279	47.2365	95.3974	20.5657	74.8317	141.933	121.367
43	0.440513	36.8974	43.8247	Material 1	20	20	49.8386	45.2488	85.9298	16.5593	69.3705	133.765	117.205
44	0.440513	33.0318	45.9096	Material 1	20	20	47.5467	43.168	75.9086	12.255	63.6536	124.99	112.735
45	0.440513	28.8677	48.0762	Material 1	20	20	45.1403	40.9832	65.2692	7.61841	57.6508	115.537	107.918
46	0.440513	24.3662	50.3385	Material 1	20	20	42.6043	38.6807	53.9309	2.60611	51.3248	105.318	102.712
47	0.413271	18.4266	52.6372	Material 1	20	20	39.3101	35.6899	43.1076	0	43.1076	94.5923	94.5923
48	0.413271	13.7518	54.9862	Material 1	20	20	35.2459	32	32.9698	0	32.9698	83.2805	83.2805
49	0.413271	8.63482	57.4825	Material 1	20	20	30.9735	28.1211	22.3125	0	22.3125	70.8985	70.8985
50	0.413271	2.97786	60.1639	Material 1	20	20	26.4652	24.0279	11.0666	0	11.0666	57.21	57.21

Global Minimum Query (spencer) - Safety Factor: 0.918623

Slice Number	Width [m]	Weight [kN]	Angle of Slice Base [deg]	Base Material	Base Cohesion [kPa]	Base Friction Angle [deg]	Shear Stress [kPa]	Shear Strength [kPa]	Base Normal Stress [kPa]	Pore Pressure [kPa]	Effective Normal Stress [kPa]	Base Vertical Stress [kPa]	Effective Vertical Stress [kPa]
1	0.437047	5.23474	-22.7675	Material 1	20	20	42.0094	38.5908	61.7875	10.7097	51.0778	44.1564	33.4467
2	0.437047	7.64986	-21.1792	Material 1	20	20	43.3254	39.7997	66.8393	12.44	54.3993	50.0526	37.6126
3	0.437047	10.0436	-19.6077	Material 1	20	20	43.7149	40.1575	69.4166	14.0342	55.3824	53.8438	39.8096
4	0.437047	12.3197	-18.0514	Material 1	20	20	43.9789	40.4	71.5449	15.4965	56.0484	57.2116	41.7151
5	0.437047	14.4816	-16.5088	Material 1	20	20	44.1399	40.5479	73.2855	16.8306	56.4549	60.2032	43.3726
6	0.437047	16.9735	-14.9785	Material 1	20	20	44.6876	41.0511	76.498	18.6607	57.8373	64.542	45.8813
7	0.437047	19.8514	-13.459	Material 1	20	20	45.6173	41.9051	81.2502	21.0665	60.1837	70.333	49.2665
8	0.437047	22.6229	-11.9491	Material 1	20	20	46.3961	42.6205	85.5018	23.3524	62.1494	75.6831	52.3307
9	0.437047	25.2894	-10.4476	Material 1	20	20	47.0429	43.2147	89.3025	25.5206	63.7819	80.6281	55.1075
10	0.437047	27.8526	-8.95326	Material 1	20	20	47.5736	43.7022	92.694	27.5728	65.1212	85.1989	57.6261
11	0.437047	30.3139	-7.46508	Material 1	20	20	48.0013	44.0951	95.7114	29.5107	66.2007	89.4216	59.9109
12	0.437047	32.6745	-5.98196	Material 1	20	20	48.3366	44.4031	98.3824	31.3354	67.047	93.3174	61.982
13	0.437047	34.9352	-4.50285	Material 1	20	20	48.5887	44.6347	100.731	33.0481	67.6833	96.9049	63.8568
14	0.437047	37.0967	-3.02675	Material 1	20	20	48.7652	44.7968	102.778	34.6494	68.1286	100.199	65.5501
15	0.437047	39.1595	-1.55265	Material 1	20	20	48.8723	44.8952	104.539	36.1401	68.3989	103.214	67.0742
16	0.437047	41.1241	-0.0795831	Material 1	20	20	48.9156	44.935	106.029	37.5204	68.5082	105.961	68.4403
17	0.437047	42.9904	1.39343	Material 1	20	20	48.8998	44.9205	107.259	38.7904	68.4685	108.448	69.658
18	0.437047	44.7583	2.86737	Material 1	20	20	48.829	44.8554	108.24	39.9501	68.2899	110.686	70.7355
19	0.437047	46.4277	4.34321	Material 1	20	20	48.7067	44.7431	108.98	40.9991	67.9811	112.679	71.6803
20	0.437047	47.9979	5.82195	Material 1	20	20	48.5359	44.5862	109.487	41.937	67.55	114.436	72.4988
21	0.437047	49.4684	7.30459	Material 1	20	20	48.3194	44.3873	109.766	42.7628	67.0035	115.96	73.1973
22	0.437047	50.8383	8.79216	Material 1	20	20	48.0594	44.1485	109.823	43.4757	66.3476	117.257	73.7808
23	0.437047	52.1063	10.2857	Material 1	20	20	47.7582	43.8718	109.662	44.0743	65.5873	118.328	74.2541
24	0.437047	53.2712	11.7864	Material 1	20	20	47.4176	43.5589	109.285	44.5571	64.7275	119.179	74.6219
25	0.437047	54.3313	13.2954	Material 1	20	20	47.0391	43.2112	108.695	44.9225	63.7721	119.81	74.8876
26	0.437047	55.2849	14.8138	Material 1	20	20	46.6242	42.8301	107.893	45.1682	62.7251	120.224	75.0557
27	0.437047	56.1297	16.3429	Material 1	20	20	46.1742	42.4167	106.881	45.2918	61.5895	120.421	75.1294
28	0.437047	56.8634	17.8841	Material 1	20	20	45.6905	41.9723	105.659	45.2907	60.3682	120.403	75.1119
29	0.437047	57.483	19.4388	Material 1	20	20	45.1737	41.4976	104.226	45.1616	59.0641	120.168	75.0067
30	0.437047	57.9855	21.0086	Material 1	20	20	44.6249	40.9935	102.58	44.901	57.6793	119.718	74.8168
31	0.437047	58.3671	22.595	Material 1	20	20	44.0452	40.4609	100.721	44.5048	56.2158	119.05	74.5456
32	0.437047	58.6239	24.2	Material 1	20	20	43.435	39.9004	98.6444	43.9685	54.6759	118.165	74.1963
33	0.437047	58.7511	25.8255	Material 1	20	20	42.7951	39.3126	96.3476	43.2868	53.0608	117.059	73.7723
34	0.437047	58.7436	27.4736	Material 1	20	20	42.1262	38.6981	93.8264	42.4538	51.3726	115.731	73.2774
35	0.437047	58.5466	29.1468	Material 1	20	20	44.8507	41.2009	99.7118	41.4628	58.249	124.723	83.2606
36	0.437047	56.913	30.8477	Material 1	20	20	55.1277	50.6416	123.536	39.3487	84.187	156.461	117.112
37	0.437047	54.5516	32.5793	Material 1	20	20	53.376	49.0324	116.464	36.6985	79.7658	150.573	113.874
38	0.437047	52.0258	34.3452	Material 1	20	20	51.6447	47.442	109.26	33.8639	75.3962	144.549	110.686
39	0.437047	49.3253	36.1491	Material 1	20	20	49.9338	45.8703	101.911	30.833	71.0781	138.389	107.556
40	0.437047	46.4378	37.9955	Material 1	20	20	48.2431	44.3172	94.4034	27.5924	66.811	132.089	104.497
41	0.437047	43.3492	39.8897	Material 1	20	20	46.573	42.783	86.7219	24.126	62.5959	125.649	101.523
42	0.437047	40.0426	41.8379	Material 1	20	20	44.9242	41.2684	78.8495	20.415	58.4345	119.07	98.6549
43	0.437047	36.4977	43.8475	Material 1	20	20	43.298	39.7745	70.7666	16.4366	54.33	112.357	95.9202
44	0.437047	32.69	45.9273	Material 1	20	20	41.696	38.3029	62.45	12.1632	50.2868	105.518	93.3548
45	0.437047	28.5891	48.0885	Material 1	20	20	40.121	36.8561	53.8724	7.56068	46.3117	98.57	91.0093
46	0.437047	24.1567	50.345	Material 1	20	20	38.5772	35.4379	45.0014	2.58619	42.4152	91.5421	88.9559
47	0.412837	18.409	52.6454	Material 1	20	20	36.2427	33.2934	36.5234	0	36.5234	84.0048	84.0048
48	0.412837	13.7416	55.0049	Material 1	20	20	33.0878	30.3952	28.5607	0	28.5607	75.8235	75.8235
49	0.412837	8.63052	57.513	Material 1	20	20	29.8863	27.4543	20.4805	0	20.4805	67.4162	67.4162
50	0.412837	2.97695	60.2083	Material 1	20	20	26.6332	24.4659	12.2699	0	12.2699	58.7898	58.7898

Interslice Data

Global Minimum Query (bishop simplified) - Safety Factor: 0.907907

Slice Number	X coordinate [m]	Y coordinate - Bottom [m]	Interslice Normal Force [kN]	Interslice Shear Force [kN]	Interslice Force Angle [deg]
1	9.80206	10	4.905	0	0
2	10.2426	9.81327	17.1964	0	0
3	10.6831	9.64084	35.2991	0	0
4	11.1236	9.48225	53.123	0	0
5	11.5641	9.3371	70.4773	0	0
6	12.0046	9.20504	87.1939	0	0
7	12.4451	9.08575	103.589	0	0
8	12.8857	8.97895	119.929	0	0
9	13.3262	8.88442	136.036	0	0
10	13.7667	8.80193	151.751	0	0
11	14.2072	8.73132	166.926	0	0
12	14.6477	8.67243	181.429	0	0
13	15.0882	8.62515	195.136	0	0
14	15.5287	8.58938	207.936	0	0
15	15.9692	8.56504	219.729	0	0
16	16.4098	8.5521	230.419	0	0
17	16.8503	8.55051	239.924	0	0
18	17.2908	8.56028	248.166	0	0
19	17.7313	8.58142	255.075	0	0
20	18.1718	8.61399	260.587	0	0
21	18.6123	8.65804	264.647	0	0
22	19.0528	8.71367	267.205	0	0
23	19.4933	8.78099	268.215	0	0
24	19.9339	8.86014	267.641	0	0
25	20.3744	8.95129	265.451	0	0
26	20.8149	9.05463	261.617	0	0
27	21.2554	9.1704	256.122	0	0
28	21.6959	9.29886	248.951	0	0
29	22.1364	9.44031	240.097	0	0
30	22.5769	9.5951	229.562	0	0
31	23.0175	9.76362	217.352	0	0
32	23.458	9.9463	203.485	0	0
33	23.8985	10.1437	187.984	0	0
34	24.339	10.3562	170.885	0	0
35	24.7795	10.5847	152.235	0	0
36	25.22	10.8298	130.783	0	0
37	25.6605	11.0924	106.797	0	0
38	26.101	11.3733	81.9762	0	0
39	26.5416	11.6738	56.551	0	0
40	26.9821	11.9952	30.7839	0	0
41	27.4226	12.3388	4.97456	0	0
42	27.8631	12.7066	-20.5302	0	0
43	28.3036	13.1006	-45.3246	0	0
44	28.7441	13.5234	-68.9278	0	0
45	29.1846	13.9781	-90.7605	0	0
46	29.6251	14.4687	-110.112	0	0
47	30.0657	15	-126.093	0	0
48	30.4789	15.5413	-137.788	0	0
49	30.8922	16.1312	-146.11	0	0
50	31.3055	16.7794	-149.934	0	0
51	31.7187	17.5	0	0	0

Global Minimum Query (spencer) - Safety Factor: 0.918623

Slice Number	X coordinate [m]	Y coordinate - Bottom [m]	Interslice Normal Force [kN]	Interslice Shear Force [kN]	Interslice Force Angle [deg]
1	9.80206	10	4.905	0	0
2	10.2391	9.81657	30.5396	14.1615	24.8776
3	10.6762	9.64724	61.3762	28.4606	24.8775
4	11.1132	9.49155	90.5712	41.9986	24.8775
5	11.5503	9.34911	117.993	54.7144	24.8776
6	11.9873	9.21958	143.545	66.5628	24.8775
7	12.4243	9.10264	167.793	77.8071	24.8776
8	12.8614	8.99805	191.282	88.6991	24.8776
9	13.2984	8.90556	213.829	99.1541	24.8775
10	13.7355	8.82497	235.28	109.101	24.8775
11	14.1725	8.75611	255.509	118.481	24.8774
12	14.6096	8.69885	274.408	127.245	24.8775
13	15.0466	8.65305	291.887	135.35	24.8775
14	15.4837	8.61863	307.874	142.763	24.8774
15	15.9207	8.59552	322.305	149.455	24.8775
16	16.3578	8.58368	335.131	155.403	24.8775
17	16.7948	8.58307	346.31	160.587	24.8776
18	17.2319	8.5937	355.812	164.993	24.8775
19	17.6689	8.61559	363.611	168.609	24.8775
20	18.1059	8.64878	369.691	171.429	24.8776
21	18.543	8.69335	374.043	173.447	24.8776
22	18.98	8.74937	376.662	174.661	24.8775
23	19.4171	8.81697	377.55	175.073	24.8775
24	19.8541	8.89628	376.716	174.686	24.8775
25	20.2912	8.98748	374.173	173.507	24.8775
26	20.7282	9.09075	369.94	171.544	24.8775
27	21.1653	9.20634	364.041	168.809	24.8776
28	21.6023	9.33449	356.508	165.316	24.8776
29	22.0394	9.47552	347.377	161.082	24.8776
30	22.4764	9.62976	336.69	156.126	24.8776
31	22.9135	9.7976	324.496	150.471	24.8775
32	23.3505	9.97948	310.851	144.144	24.8775
33	23.7876	10.1759	295.818	137.173	24.8775
34	24.2246	10.3874	279.47	129.593	24.8776
35	24.6616	10.6147	261.888	121.44	24.8776
36	25.0987	10.8584	242.567	112.48	24.8775
37	25.5357	11.1194	220.207	102.112	24.8776
38	25.9728	11.3987	197.39	91.5311	24.8775
39	26.4098	11.6973	174.344	80.8446	24.8775
40	26.8469	12.0166	151.316	70.1666	24.8776
41	27.2839	12.358	128.579	59.6233	24.8776
42	27.721	12.7233	106.435	49.3545	24.8774
43	28.158	13.1146	85.2214	39.5179	24.8776
44	28.5951	13.5344	65.3276	30.2929	24.8775
45	29.0321	13.9858	47.2016	21.8878	24.8776
46	29.4692	14.4727	31.3732	14.548	24.8775
47	29.9062	15	18.4803	8.56946	24.8775
48	30.319	15.5409	9.09895	4.21926	24.8776
49	30.7319	16.1306	2.49258	1.15583	24.8775
50	31.1447	16.7789	-0.595111	-0.275958	24.8776
51	31.5576	17.5	0	0	0

Discharge Sections

Entity Information

Group 1

Shared Entities

Type	Coordinates (x,y)
External Boundary	0, 0 35, 0 35, 17.5 25, 17.5 10, 10 0, 10

Scenario-based Entities

Type	Coordinates (x,y)	Master Scenario
Water Table	0, 11 12, 11 25, 15 35, 15	Assigned to: Material 1
Distributed Load	25, 17.5 35, 17.5	Constant DistributionOrientation: VerticalMagnitude: 50 kN/m2Creates Excess Pore Pressure: No